

Package ‘candisc’

November 5, 2025

Type Package

Title Visualizing Generalized Canonical Discriminant and Canonical Correlation Analysis

Version 1.0.0

Date 2025-10-31

Depends R ($\geq 4.1.0$), heplots ($\geq 0.8-6$)

Imports car, graphics, stats, insight, dplyr, ggplot2

Suggests rgl, carData, corrplot, knitr, rmarkdown, MASS, rpart, rpart.plot, klaR, lifecycle

LazyLoad yes

LazyData yes

Maintainer Michael Friendly <friendly@yorku.ca>

Language en-US

Description Functions for computing and visualizing generalized canonical discriminant analyses and canonical correlation analysis for a multivariate linear model. Traditional canonical discriminant analysis is restricted to a one-way 'MANOVA' design and is equivalent to canonical correlation analysis between a set of quantitative response variables and a set of dummy variables coded from the factor variable. The 'candisc' package generalizes this to higher-way 'MANOVA' designs for all factors in a multivariate linear model, computing canonical scores and vectors for each term. The graphic functions provide low-rank (1D, 2D, 3D) visualizations of terms in an 'mlm' via the 'plot.candisc' and 'heplot.candisc' methods. Related plots are now provided for canonical correlation analysis when all predictors are quantitative. Methods for linear discriminant analysis are now included.

License GPL (≥ 2)

Encoding UTF-8

VignetteBuilder knitr

URL <https://github.com/friendly/candisc/>,
<https://friendly.github.io/candisc/>

BugReports <https://github.com/friendly/candisc/issues>

RoxygenNote 7.3.3

NeedsCompilation no

Author Michael Friendly [aut, cre] (ORCID:

[<https://orcid.org/0000-0002-3237-0941>](https://orcid.org/0000-0002-3237-0941)),

John Fox [aut] (ORCID: [<https://orcid.org/0000-0002-1196-8012>](https://orcid.org/0000-0002-1196-8012))

Repository CRAN

Date/Publication 2025-11-05 16:40:15 UTC

Contents

candisc-package	3
cancor	4
candisc	10
candiscList	15
can_lm	17
cereal	18
cor_lda	20
dataIndex	21
Grass	22
heplot.cancor	23
heplot.candisc	26
heplot.candiscList	29
HSB	30
plot.cancor	31
plot_discrim	34
predictor.names	35
predict_discrim	36
PsyAcad	38
redundancy	39
reflect	41
varOrder	42
vecscale	44
vectors	46
Wilks	47
Wine	49
Wolves	50

Index	52
--------------	-----------

candisc-package	<i>Visualizing Generalized Canonical Discriminant and Canonical Correlation Analysis</i>
-----------------	--

Description

This package includes functions for computing and visualizing generalized canonical discriminant analyses and canonical correlation analysis for a multivariate linear model. The goal is to provide ways of visualizing such models in a low-dimensional space corresponding to dimensions (linear combinations of the response variables) of maximal relationship to the predictor variables.

Details

Traditional canonical discriminant analysis is restricted to a one-way MANOVA design and is equivalent to canonical correlation analysis between a set of quantitative response variables and a set of dummy variables coded from the factor variable. The candisc package generalizes this to multi-way MANOVA designs for all terms in a multivariate linear model (i.e., an "mlm" object), computing canonical scores and vectors for each term (giving a "candiscList" object).

The graphic functions are designed to provide low-rank (1D, 2D, 3D) visualizations of terms in a mlm via the `plot.candisc()` method, and the HE plot `heplot.candisc()` and `heplot3d.candisc()` methods. For mlms with more than a few response variables, these methods often provide a much simpler interpretation of the nature of effects in canonical space than heplots for pairs of responses or an HE plot matrix of all responses in variable space.

Analogously, a multivariate linear (regression) model with quantitative predictors can also be represented in a reduced-rank space by means of a canonical correlation transformation of the Y and X variables to uncorrelated canonical variates, Ycan and Xcan. Computation for this analysis is provided by `cancor()` and related methods. Visualization of these results in canonical space are provided by the `plot.cancor()`, `heplot.cancor()` and `heplot3d.cancor()` methods.

These relations among response variables in linear models can also be useful for "effect ordering" (Friendly & Kwan (2003) for *variables* in other multivariate data displays to make the displayed relationships more coherent. The function `varOrder()` implements a collection of these methods.

A new vignette, `vignette("diabetes", package="candisc")`, illustrates some of these methods. A more comprehensive collection of examples is contained in the vignette for the **heplots** package, `vignette("HE-examples", package="heplots")`.

The organization of functions in this package and the **heplots** package may change in a later version.

Author(s)

Michael Friendly and John Fox

Maintainer: Michael Friendly friendly@yorku.ca

References

- Friendly, M. (2007). HE plots for Multivariate General Linear Models. *Journal of Computational and Graphical Statistics*, **16**(2) 421–444. <http://datavis.ca/papers/jcgs-heplots.pdf>, doi:10.1198/106186007X208407.
- Friendly, M. & Kwan, E. (2003). Effect Ordering for Data Displays, *Computational Statistics and Data Analysis*, **43**, 509-539. doi:10.1016/S01679473(02)002906
- Friendly, M. & Sigal, M. (2014). Recent Advances in Visualizing Multivariate Linear Models. *Revista Colombiana de Estadística*, **37**(2), 261-283. doi:10.15446/rce.v37n2spe.47934.
- Friendly, M. & Sigal, M. (2017). Graphical Methods for Multivariate Linear Models in Psychological Research: An R Tutorial, *The Quantitative Methods for Psychology*, 13 (1), 20-45. doi:10.20982/tqmp.13.1.p020.
- Gittins, R. (1985). *Canonical Analysis: A Review with Applications in Ecology*, Berlin: Springer.

See Also

`heplots::heplot()` for details about HE plots.

`candisc()`, `cancor()` for details about canonical discriminant analysis and canonical correlation analysis.

cancor

Canonical Correlation Analysis

Description

The function `cancor` generalizes and regularizes computation for canonical correlation analysis in a way conducive to visualization using methods in the **heplots** package.

The package provides the following display, extractor and plotting methods for "cancor" objects

`print()`, `summary()` Print and summarise the CCA

`coef()` Extract coefficients for X, Y, or both

`scores()` Extract observation scores on the canonical variables

`redundancy()` Redundancy analysis: proportion of variances of the variables in each set (X and Y) accounted for by the variables in the other set through the canonical variates

`plot()` Plot pairs of canonical scores with a data ellipse and regression line

`heplot()` HE plot of the Y canonical variables showing effects of the X variables and projections of the Y variables in this space.

As well, the function provides for observation weights, which may be useful in some situations, as well as providing a basis for robust methods in which potential outliers can be down-weighted.

Usage

```

cancor(x, ...)

## S3 method for class 'formula'
cancor(formula, data, subset, weights, na.rm = TRUE, method = "gensvd", ...)

## Default S3 method:
cancor(
  x,
  y,
  weights,
  X.names = colnames(x),
  Y.names = colnames(y),
  row.names = rownames(x),
  xcenter = TRUE,
  ycenter = TRUE,
  xscale = FALSE,
  yscale = FALSE,
  ndim = min(p, q),
  set.names = c("X", "Y"),
  prefix = c("Xcan", "Ycan"),
  na.rm = TRUE,
  use = if (na.rm) "complete" else "pairwise",
  method = "gensvd",
  ...
)

## S3 method for class 'cancor'
print(x, digits = max(getOption("digits") - 2, 3), ...)

## S3 method for class 'cancor'
summary(object, digits = max(getOption("digits") - 2, 3), ...)

## S3 method for class 'cancor'
scores(x, type = c("x", "y", "both", "list", "data.frame"), ...)

## S3 method for class 'cancor'
coef(object, type = c("x", "y", "both", "list"), standardize = FALSE, ...)

```

Arguments

<code>x</code>	Varies depending on method. For the <code>cancor.default</code> method, this should be a matrix or data.frame whose columns contain the X variables
<code>...</code>	Other arguments, passed to methods
<code>formula</code>	A two-sided formula of the form <code>cbind(y1, y2, y3, \dots) ~ x1 + x2 + x3 + \dots</code>
<code>data</code>	The data.frame within which the formula is evaluated

subset	an optional vector specifying a subset of observations to be used in the calculations.
weights	Observation weights. If supplied, this must be a vector of length equal to the number of observations in X and Y, typically within (0,1). In that case, the variance-covariance matrices are computed using <code>stats::cov.wt</code> , and the number of observations is taken as the number of non-zero weights.
na.rm	logical, determining whether observations with missing cases are excluded in the computation of the variance matrix of (X,Y). See Notes for details on missing data.
method	the method to be used for calculation; currently only <code>method = "gensvd"</code> is supported;
y	For the <code>cancor.default</code> method, a matrix or <code>data.frame</code> whose columns contain the Y variables
X.names, Y.names	Character vectors of names for the X and Y variables.
row.names	Observation names in x, y
xcenter, ycenter	logical. Center the X, Y variables? (not yet implemented)
xscale, yscale	logical. Scale the X, Y variables to unit variance? (not yet implemented)
ndim	Number of canonical dimensions to retain in the result, for scores, coefficients, etc.
set.names	A vector of two character strings, giving names for the collections of the X, Y variables.
prefix	A vector of two character strings, giving prefixes used to name the X and Y canonical variables, respectively.
use	argument passed to <code>var</code> determining how missing data are handled. Only the default, <code>use="complete"</code> is allowed when observation weights are supplied.
digits	Number of digits passed to <code>print</code> and <code>summary</code> methods
object	A <code>cancor</code> object for related methods.
type	For the <code>coef</code> method, the type of coefficients returned, one of "x", "y", "both". For the <code>scores</code> method, the same list, or <code>"data.frame"</code> , which returns a <code>data.frame</code> containing the X and Y canonical scores.
standardize	For the <code>coef</code> method, whether coefficients should be standardized by dividing by the standard deviations of the X and Y variables.

Details

Canonical correlation analysis (CCA), as traditionally presented is used to identify and measure the associations between two sets of quantitative variables, X and Y. It is often used in the same situations for which a multivariate multiple regression analysis (MMRA) would be used.

However, CCA is "symmetric" in that the sets X and Y have equivalent status, and the goal is to find orthogonal linear combinations of each having maximal (canonical) correlations. On the other hand, MMRA is "asymmetric", in that the Y set is considered as responses, *each one* to be explained by *separate* linear combinations of the Xs.

Let $\mathbf{Y}_{n \times p}$ and $\mathbf{X}_{n \times q}$ be two sets of variables over which CCA is computed. We find canonical coefficients $\mathbf{A}_{p \times k}$ and $\mathbf{B}_{q \times k}$, $k = \min(p, q)$ such that the canonical variables

$$\mathbf{U}_{n \times k} = \mathbf{Y}\mathbf{A} \quad \text{and} \quad \mathbf{V}_{n \times k} = \mathbf{X}\mathbf{B}$$

have maximal, diagonal correlation structure. That is, the coefficients $\mathbf{A}$ and $\mathbf{B}$ are chosen such that the (canonical) correlations between each pair $r_i = \text{cor}(\mathbf{u}_i, \mathbf{v}_i)$, $i = 1, 2, \dots, k$ are maximized and all other pairs are uncorrelated, $r_{ij} = \text{cor}(\mathbf{u}_i, \mathbf{v}_j) = 0$, $i \neq j$. Thus, all correlations between the $\mathbf{X}$ and $\mathbf{Y}$ variables are channeled through the correlations between the pairs of canonical variates.

For visualization using HE plots, it is most natural to consider plots representing the relations among the canonical variables for the $\mathbf{Y}$ variables in terms of a multivariate linear model predicting the $\mathbf{Y}$ canonical scores, using either the $\mathbf{X}$ variables or the $\mathbf{X}$ canonical scores as predictors. Such plots, using `heplot.cancor()` provide a low-rank (1D, 2D, 3D) visualization of the relations between the two sets, and so are useful in cases when there are more than 2 or 3 variables in each of $\mathbf{X}$ and $\mathbf{Y}$.

The connection between CCA and HE plots for MMRA models can be developed as follows. CCA can also be viewed as a principal component transformation of the predicted values of one set of variables from a regression on the other set of variables, in the metric of the error covariance matrix.

For example, regress the $\mathbf{Y}$ variables on the $\mathbf{X}$ variables, giving predicted values $\hat{\mathbf{Y}} = \mathbf{X}(\mathbf{X}'\mathbf{X})^{-1}\mathbf{X}'\mathbf{Y}$ and residuals $\mathbf{R} = \mathbf{Y} - \hat{\mathbf{Y}}$. The error covariance matrix is $\mathbf{E} = \mathbf{R}'\mathbf{R}/(n - 1)$. Choose a transformation $\mathbf{Q}$ that orthogonalizes the error covariance matrix to an identity, that is, $(\mathbf{RQ})'(\mathbf{RQ}) = \mathbf{Q}'\mathbf{R}'\mathbf{RQ} = (n - 1)\mathbf{I}$, and apply the same transformation to the predicted values to yield, say, $\mathbf{Z} = \hat{\mathbf{Y}}\mathbf{Q}$. Then, a principal component analysis on the covariance matrix of $\mathbf{Z}$ gives eigenvalues of $\mathbf{E}^{-1}\mathbf{H}$, and so is equivalent to the MMRA analysis of $\text{lm}(\mathbf{Y} \sim \mathbf{X})$ statistically, but visualized here in canonical space.

Value

An object of class `cancorr`, a list with the following components:

<code>cancor</code>	Canonical correlations, i.e., the correlations between each canonical variate for the $\mathbf{Y}$ variables with the corresponding canonical variate for the $\mathbf{X}$ variables.
<code>names</code>	Names for various items, a list of 4 components: <code>X</code> , <code>Y</code> , <code>row.names</code> , <code>set.names</code>
<code>ndim</code>	Number of canonical dimensions extracted, $\leq \min(p, q)$
<code>dim</code>	Problem dimensions, a list of 3 components: <code>p</code> (number of $\mathbf{X}$ variables), <code>q</code> (number of $\mathbf{Y}$ variables), <code>n</code> (sample size)
<code>coef</code>	Canonical coefficients, a list of 2 components: <code>X</code> , <code>Y</code>
<code>scores</code>	Canonical variate scores, a list of 2 components: <code>X</code> , <code>Y</code>
<code>scores</code>	Canonical variate scores, a list of 2 components: <code>X</code> Canonical variate scores for the $\mathbf{X}$ variables <code>Y</code> Canonical variate scores for the $\mathbf{Y}$ variables
<code>X</code>	The matrix $\mathbf{X}$
<code>Y</code>	The matrix $\mathbf{Y}$
<code>weights</code>	Observation weights, if supplied, else <code>NULL</code>
<code>structure</code>	Structure correlations, a list of 4 components: <code>X.xscores</code> , <code>Y.xscores</code> , <code>X.yscores</code> , <code>Y.yscores</code>

structure Structure correlations ("loadings"), a list of 4 components:

- X.xscores** Structure correlations of the X variables with the Xcan canonical scores
- Y.xscores** Structure correlations of the Y variables with the Xcan canonical scores
- X.yscores** Structure correlations of the X variables with the Ycan canonical scores
- Y.yscores** Structure correlations of the Y variables with the Ycan canonical scores

The formula method also returns components call and terms

Methods (by class)

- `cancor(formula)`: "formula" method.
- `cancor(default)`: "default" method.

Methods (by generic)

- `print(cancor)`: `print()` method for "cancor" objects.
- `summary(cancor)`: `summary()` method for "cancor" objects.
- `scores(cancor)`: `scores()` method for "cancor" objects.
- `coef(cancor)`: `coef()` method for "cancor" objects.

Note

Not all features of CCA are presently implemented: standardized vs. raw scores, more flexible handling of missing data, other plot methods, ...

Author(s)

Michael Friendly

References

Gittins, R. (1985). *Canonical Analysis: A Review with Applications in Ecology*, Berlin: Springer.

Mardia, K. V., Kent, J. T. and Bibby, J. M. (1979). *Multivariate Analysis*. London: Academic Press.

See Also

Other implementations of CCA: `stats::cancor()` (very basic), `yacca::cca()` in the **yacca** (fairly complete, but very messy return structure), `CCA::cc()` in **CCA** (fairly complete, very messy return structure, no longer maintained).

`redundancy()`, for redundancy analysis; `plot.cancor()`, for enhanced scatterplots of the canonical variates.

`heplot.cancor()` for CCA HE plots and `heplots::heplot()` for generic heplot methods.

`candisc()` for related methods focused on multivariate linear models with one or more factors among the X variables.

Examples

```

data(Rohwer, package="heplots")
X <- as.matrix(Rohwer[,6:10]) # the PA tests
Y <- as.matrix(Rohwer[,3:5])  # the aptitude/ability variables

# visualize the correlation matrix using corrplot()
if (require(corrplot)) {
  M <- cor(cbind(X,Y))
  corrplot(M, method="ellipse", order="hclust", addrect=2, addCoef.col="black")
}

(cc <- cancort(X, Y, set.names=c("PA", "Ability"))))

## Canonical correlation analysis of:
##      5  PA  variables:  n, s, ns, na, ss
## with      3  Ability variables:  SAT, PPVT, Raven
##
##      CanR  CanRSQ  Eigen percent      cum                      scree
## 1 0.6703 0.44934 0.81599   77.30  77.30 *****
## 2 0.3837 0.14719 0.17260   16.35  93.65 *****
## 3 0.2506 0.06282 0.06704    6.35 100.00 **
##
## Test of H0: The canonical correlations in the
## current row and all that follow are zero
##
##      CanR  WilksL      F df1  df2 p.value
## 1 0.67033 0.44011 3.8961  15 168.8 0.000006
## 2 0.38366 0.79923 1.8379   8 124.0 0.076076
## 3 0.25065 0.93718 1.4078   3  63.0 0.248814

# formula method
cc <- cancort(cbind(SAT, PPVT, Raven) ~ n + s + ns + na + ss, data=Rohwer,
  set.names=c("PA", "Ability"))

# using observation weights
set.seed(12345)
wts <- sample(0:1, size=nrow(Rohwer), replace=TRUE, prob=c(.05, .95))
(ccw <- cancort(X, Y, set.names=c("PA", "Ability"), weights=wts) )

# show correlations of the canonical scores
zapsmall(cor(scores(cc, type="x"), scores(cc, type="y"))))

# standardized coefficients
coef(cc, type="both", standardize=TRUE)

# plot canonical scores
plot(cc,
  smooth=TRUE, pch=16, id.n = 3)
text(-2, 1.5, paste("Can R =", round(cc$cancort[1], 3)), pos = 4)
plot(cc, which = 2,

```

```

    smooth=TRUE, pch=16, id.n = 3)
text(-2.2, 2.5, paste("Can R =", round(cc$cancor[2], 3)), pos = 4)

#####
data(schooldata)
#####

#fit the MMreg model
school.mod <- lm(cbind(reading, mathematics, selfesteem) ~
education + occupation + visit + counseling + teacher, data=schooldata)
car::Anova(school.mod)
pairs(school.mod)

# canonical correlation analysis
school.cc <- cancor(cbind(reading, mathematics, selfesteem) ~
education + occupation + visit + counseling + teacher, data=schooldata)
school.cc
heplot(school.cc, xpd=TRUE, scale=0.3)

```

candisc

Canonical discriminant analysis

Description

candisc performs a generalized canonical discriminant analysis for one term in a multivariate linear model (i.e., an `mlm` object), computing canonical scores and vectors. It represents a transformation of the original variables into a canonical space of maximal differences for the term, controlling for other model terms.

Usage

```

candisc(mod, ...)

## S3 method for class 'mlm'
candisc(mod, term, type = "2", manova, ndim = rank, ...)

## S3 method for class 'candisc'
print(x, digits = max(getOption("digits") - 2, 3), LRtests = TRUE, ...)

## S3 method for class 'candisc'
summary(
  object,
  means = TRUE,
  scores = FALSE,
  coef = c("std"),
  ndim,
  digits = max(getOption("digits") - 2, 4),

```

```

    ...
)

## S3 method for class 'candisc'
coef(object, type = c("std", "raw", "structure"), ...)

## S3 method for class 'candisc'
scores(x, ...)

## S3 method for class 'candisc'
plot(
  x,
  which = 1:2,
  conf = 0.95,
  col,
  pch,
  scale,
  asp = 1,
  var.col = "blue",
  var.lwd = par("lwd"),
  var.labels,
  var.cex = 1,
  var.pos,
  rev.axes = c(FALSE, FALSE),
  ellipse = FALSE,
  ellipse.prob = 0.68,
  fill.alpha = 0.1,
  prefix = "Can",
  suffix = TRUE,
  titles.1d = c("Canonical scores", "Structure"),
  points.1d = FALSE,
  ...
)

```

Arguments

<code>mod</code>	An <code>mlm</code> object, such as computed by <code>lm()</code> with a multivariate response
<code>...</code>	arguments to be passed down. In particular, <code>type="n"</code> can be used with the <code>plot</code> method to suppress the display of canonical scores.
<code>term</code>	the name of one term from <code>mod</code> for which the canonical analysis is performed.
<code>type</code>	type of test for the model term, one of: "II", "III", "2", or "3"
<code>manova</code>	the <code>Anova.mlm</code> object corresponding to <code>mod</code> . Normally, this is computed internally by <code>Anova(mod)</code>
<code>ndim</code>	Number of dimensions to store in (or retrieve from, for the summary method) the means, structure, scores and <code>coeffs.*</code> components. The default is the rank of the H matrix for the hypothesis term.
<code>digits</code>	significant digits to print.

LRtests	logical; should likelihood ratio tests for the canonical dimensions be printed?
object, x	A candisc object
means	Logical value used to determine if canonical means are printed
scores	Logical value used to determine if canonical scores are printed
coef	Type of coefficients printed by the summary method. Any one or more of "std", "raw", or "structure"
which	A vector of one or two integers, selecting the canonical dimension(s) to plot. If the canonical structure for a term has <code>ndim==1</code> , or <code>length(which)==1</code> , a 1D representation of canonical scores and structure coefficients is produced by the <code>plot</code> method. Otherwise, a 2D plot is produced.
conf	Confidence coefficient for the confidence circles around canonical means plotted in the <code>plot</code> method
col	A vector of the unique colors to be used for the levels of the term in the <code>plot</code> method, one for each level of the term. In this version, you should assign colors and point symbols explicitly, rather than relying on the somewhat arbitrary defaults, based on <code>grDevices::palette()</code> .
pch	A vector of the unique point symbols to be used for the levels of the term in the <code>plot</code> method
scale	Scale factor for the variable vectors in canonical space. If not specified, a scale factor is calculated to make the variable vectors approximately fill the plot space.
asp	Aspect ratio for the <code>plot</code> method. The <code>asp=1</code> (the default) assures that the units on the horizontal and vertical axes are the same, so that lengths and angles of the variable vectors are interpretable.
var.col	Color used to plot variable vectors
var.lwd	Line width used to plot variable vectors
var.labels	Optional vector of variable labels to replace variable names in the plots
var.cex	Character expansion size for variable labels in the plots
var.pos	Position(s) of variable vector labels wrt. the end point. If not specified, the labels are out-justified left and right with respect to the end points.
rev.axes	Logical, a vector of <code>length(which)</code> . TRUE causes the orientation of the canonical scores and structure coefficients to be reversed along a given axis.
ellipse	Draw data ellipses for canonical scores?
ellipse.prob	Coverage probability for the data ellipses
fill.alpha	Transparency value for the color used to fill the ellipses. Use <code>fill.alpha</code> to draw the ellipses unfilled.
prefix	Prefix used to label the canonical dimensions plotted
suffix	Suffix for labels of canonical dimensions. If <code>suffix=TRUE</code> the percent of hypothesis (H) variance accounted for by each canonical dimension is added to the axis label.
titles.1d	A character vector of length 2, containing titles for the panels used to plot the canonical scores and structure vectors, for the case in which there is only one canonical dimension.
points.1d	Logical value for <code>plot.candisc</code> when only one canonical dimension.

Details

In typical usage, the term should be a factor or interaction corresponding to a multivariate test with 2 or more degrees of freedom for the null hypothesis.

Canonical discriminant analysis is typically carried out in conjunction with a one-way MANOVA design. It represents a linear transformation of the response variables into a canonical space in which (a) each successive canonical variate produces maximal separation among the groups (e.g., maximum univariate F statistics), and (b) all canonical variates are mutually uncorrelated. For a one-way MANOVA with g groups and p responses, there are $df_h = \min(g-1, p)$ such canonical dimensions, and tests, initially stated by Bartlett (1938) allow one to determine the number of significant canonical dimensions.

Computational details for the one-way case are described in Cooley & Lohnes (1971), and in the *SAS/STAT User's Guide*, "The CANDISC procedure: Computational Details," http://support.sas.com/documentation/cdl/en/statug/63962/HTML/default/viewer.htm#statug_candisc_sect012.htm.

A generalized canonical discriminant analysis extends this idea to a general multivariate linear model. Analysis of each term in the `mlm` produces a rank df_h H matrix sum of squares and crossproducts matrix that is tested against the rank df_e E matrix by the standard multivariate tests (Wilks' Lambda, Hotelling-Lawley trace, Pillai trace, Roy's maximum root test). For any given term in the `mlm`, the generalized canonical discriminant analysis amounts to a standard discriminant analysis based on the H matrix for that term in relation to the full-model E matrix.

The plot method for `candisc` objects is typically a 2D plot, similar to a biplot. It shows the canonical scores for the groups defined by the term as points and the canonical structure coefficients as vectors from the origin.

If the canonical structure for a term has `ndim==1`, or `length(which)==1`, the 1D representation consists of a boxplot of canonical scores and a vector diagram showing the magnitudes of the structure coefficients.

Value

An object of class `candisc` with the following components:

<code>dfh</code>	hypothesis degrees of freedom for term
<code>dfe</code>	error degrees of freedom for the <code>mlm</code>
<code>rank</code>	number of non-zero eigenvalues of HE^{-1}
<code>eigenvalues</code>	eigenvalues of HE^{-1}
<code>canrsq</code>	squared canonical correlations
<code>pct</code>	A vector containing the percentages of the <code>canrsq</code> of their total.
<code>ndim</code>	Number of canonical dimensions stored in the <code>means</code> , <code>structure</code> and <code>coeffs.*</code> components
<code>means</code>	A data.frame containing the class means for the levels of the factor(s) in the term
<code>factors</code>	A data frame containing the levels of the factor(s) in the term
<code>term</code>	name of the term
<code>terms</code>	A character vector containing the names of the terms in the <code>mlm</code> object
<code>coeffs.raw</code>	A matrix containing the raw canonical coefficients

<code>coeffs.std</code>	A matrix containing the standardized canonical coefficients
<code>structure</code>	A matrix containing the canonical structure coefficients on <code>ndim</code> dimensions, i.e., the correlations between the original variates and the canonical scores. These are sometimes referred to as Total Structure Coefficients.
<code>scores</code>	A data frame containing the predictors in the <code>mlm</code> model and the canonical scores on <code>ndim</code> dimensions. These are calculated as $Y \%*\% coeffs.raw$, where Y contains the standardized response variables.

Methods (by class)

- `candisc(mlm)`: "mlm" method.

Methods (by generic)

- `print(candisc)`: `print()` method for "candisc" objects.
- `summary(candisc)`: `summary()` method for "candisc" objects.
- `coef(candisc)`: `coef()` method for "candisc" objects.
- `scores(candisc)`: `scores()` method for "candisc" objects.
- `plot(candisc)`: "plot" method.

Author(s)

Michael Friendly and John Fox

References

- Bartlett, M. S. (1938). Further aspects of the theory of multiple regression. *Proc. Cambridge Philosophical Society* **34**, 33-34.
- Cooley, W.W. & Lohnes, P.R. (1971). *Multivariate Data Analysis*, New York: Wiley.
- Gittins, R. (1985). *Canonical Analysis: A Review with Applications in Ecology*, Berlin: Springer.

See Also

[candiscList\(\)](#), [heplots::heplot\(\)](#), [heplots::heplot3d\(\)](#)

Examples

```
grass.mod <- lm(cbind(N1,N9,N27,N81,N243) ~ Block + Species, data=Grass)
car::Anova(grass.mod, test="Wilks")

grass.can1 <-candisc(grass.mod, term="Species")
print(grass.can1)

plot(grass.can1, var.lwd = 2)

# library(heplots)
heplot(grass.can1, scale=6, fill=TRUE)
```

```
# iris data
iris.mod <- lm(cbind(Petal.Length, Sepal.Length, Petal.Width, Sepal.Width) ~ Species, data=iris)
iris.can <- candisc(iris.mod, data=iris)
#-- assign colors and symbols corresponding to species
col <- c("red", "brown", "green3")
pch <- 1:3
plot(iris.can, col=col, pch=pch)

heplot(iris.can)

# 1-dim plot
iris.can1 <- candisc(iris.mod, data=iris, ndim=1)
plot(iris.can1)
```

candiscList	<i>Canonical discriminant analyses</i>
-------------	--

Description

candiscList performs a generalized canonical discriminant analysis for all terms in a multivariate linear model (i.e., an `mlm` object), computing canonical scores and vectors.

Usage

```
candiscList(mod, ...)

## S3 method for class 'mlm'
candiscList(mod, type = "2", manova, ndim, ...)

## S3 method for class 'candiscList'
print(x, ...)

## S3 method for class 'candiscList'
summary(object, ...)

## S3 method for class 'candiscList'
plot(x, term, ask = interactive(), graphics = TRUE, ...)
```

Arguments

<code>mod</code>	An <code>mlm</code> object, such as computed by <code>lm()</code> with a multivariate response
<code>...</code>	arguments to be passed down.
<code>type</code>	type of test for the model term, one of: "II", "III", "2", or "3"
<code>manova</code>	the <code>Anova.mlm</code> object corresponding to <code>mod</code> . Normally, this is computed internally by <code>Anova(mod)</code>

ndim	Number of dimensions to store in the means, structure, scores and coeffs.* components. The default is the rank of the H matrix for the hypothesis term.
object, x	A candiscList object
term	The name of one term to be plotted for the plot method. If not specified, one candisc plot is produced for each term in the mlm object.
ask	If TRUE (the default, when running interactively), a menu of terms is presented; if ask is FALSE, canonical plots for all terms are produced.
graphics	if TRUE (the default, when running interactively), then the menu of terms to plot is presented in a dialog box rather than as a text menu.

Value

An object of class `candiscList` which is a list of "candisc" objects for the terms in the mlm.

Methods (by class)

- `candiscList(mlm)`: "mlm" method.

Methods (by generic)

- `print(candiscList)`: `print()` method for "candiscList" objects.
- `summary(candiscList)`: `summary()` method for "candiscList" objects.
- `plot(candiscList)`: `plot()` method for "candiscList" objects.

Author(s)

Michael Friendly and John Fox

See Also

[candisc\(\)](#), [heplots::heplot\(\)](#), [heplots::heplot3d\(\)](#)

Examples

```
grass.mod <- lm(cbind(N1,N9,N27,N81,N243) ~ Block + Species, data=Grass)

grass.canL <-candiscList(grass.mod)
names(grass.canL)
names(grass.canL$Species)

## Not run:
print(grass.canL)

## End(Not run)
plot(grass.canL, type="n", ask=FALSE)
heplot(grass.canL$Species, scale=6)
heplot(grass.canL$Block, scale=2)
```

can_lm	<i>Transform a Multivariate Linear model mlm to a Canonical Representation</i>
--------	--

Description

This function uses `candisc()` to transform the responses in a multivariate linear model to scores on canonical variables for a given term and then uses those scores as responses in a linear (lm) or multivariate linear model (mlm).

The function constructs a model formula of the form `Can ~ terms` where `Can` is the canonical score(s) and `terms` are the terms in the original `mlm`, then runs `lm()` with that formula.

Usage

```
can_lm(mod, term, ...)
```

Arguments

<code>mod</code>	A <code>mlm</code> object
<code>term</code>	One term in that model
<code>...</code>	Arguments passed to <code>candisc()</code>

Value

A `lm` object if `term` is a rank 1 hypothesis, otherwise a `mlm` object

Author(s)

Michael Friendly

See Also

`candisc()`, `cancor()`

Examples

```
iris.mod <- lm(cbind(Petal.Length, Sepal.Length, Petal.Width, Sepal.Width) ~ Species, data=iris)
iris.can <- can_lm(iris.mod, "Species")
iris.can
car::Anova(iris.mod)
car::Anova(iris.can)
```

cereal

*Breakfast Cereal Dataset***Description**

A multivariate dataset describing seventy-seven commonly available breakfast cereals, based on the information now available on the FDA food label. The variable `rating` is a likely response variable in statistical models.

Usage

```
data("cereal")
```

Format

A data frame with 77 observations on the following 16 variables.

`name` cereal name, a character vector

`mfr` manufacturer (A G K N P Q R), a character vector

`type` type (cold/hot), a character vector

`calories` calories (number), a numeric vector

`protein` protein(g), a numeric vector

`fat` fat(g), a numeric vector

`sodium` sodium(mg), a numeric vector

`fiber` dietary fiber(g), a numeric vector

`carbo` complex carbohydrates(g), a numeric vector

`sugars` sugars(g), a numeric vector

`potass` potassium(mg), a numeric vector

`vitamins` vitamins & minerals (0, 25, or 100, respectively indicating "none added"; "enriched"; "FDA recommended"), a numeric vector

`shelf` display shelf (1, 2, or 3, counting from the floor), a numeric vector

`weight` weight (in ounces) of one serving (serving size), a numeric vector

`cups` cups per serving, a numeric vector

`rating` health rating of the cereal (unknown calculation method), a numeric vector

Details

This dataset was used in the poster competition for the American Statistical association 1993 Statistical Graphics Exposition, titled *Serial Correlation or Cereal Correlation ??*.

The call for participation reads: "A multivariate dataset describing seventy-seven commonly available breakfast cereals, based on the information now available on the newly-mandated F&DA food label. What are you getting when you eat a bowl of cereal? Can you get a lot of fiber without a lot of

calories? Can you describe what cereals are displayed on high, low, and middle shelves? The good news is that none of the cereals for which we collected data had any cholesterol, and manufacturers rarely use artificial sweeteners and colors, nowadays. However, there is still a lot of data for the consumer to understand while choosing a good breakfast cereal."

Further details on the variables and suggested analyses are available at <https://community.amstat.org/jointscsg-section/dataexpo/dataexpo1993>

The abbreviations for manufacturer, `mfr`, stand for:

A American Home Food Products

G General Mills

K Kellog

N Nabisco

P Post

Q Quaker Oats

R Ralston Purina

Source

From the American Statistical Association 1993 Statistical Graphics Exposition, 'Serial Correlation or Cereal Correlation ??', <https://community.amstat.org/jointscsg-section/dataexpo/dataexpo1993>.

References

Jean Dos Santos, Breakfast Cereals: Data Analysis and Clustering, (Kaggle link doesn't work) Does a bunch of data cleaning and exploratory data analysis in R.

See Also

[MASS::UScereal](#) has a similar dataset with fewer observations and variables, but with the variables normalized to a portion of one US cup.

<https://www.kaggle.com/datasets/crawford/80-cereals> Essentially the same dataset

Examples

```
library(dplyr)
data(cereal)
str(cereal)

# Add explicit name of manufacturer
# names for manufacturers
mfr_names <- c(
  "A" = "American Home Foods",
  "G" = "General Mills",
  "K" = "Kellog",
  "N" = "Nabisco",
  "P" = "Post",
  "Q" = "Quaker Oats",
  "R" = "Ralston Purina"
```

```

)

# recode `mfr` as `mfr_name`
cereal <- cereal |>
  mutate(mfr_name = recode(mfr, !!!mfr_names))

# density plot of ratings
library(ggplot2)
ggplot(data = cereal,
  aes(x = rating, fill = mfr_name, color = mfr_name)) +
  geom_density(alpha = 0.1) +
  theme_classic(base_size = 14) +
  theme(legend.position = "bottom")

```

cor_lda

Calculate Structure Correlations from Discriminant Analysis

Description

`cor_lda()` calculates the "structure" correlations between the observed variables and the discriminant dimension scores from a linear discriminant analysis provided by [MASS::lda\(\)](#). These more directly assess the direction and strength of the relations between the two sets than do the scaling weights returned by `lda()`. They are useful for plotting the discriminant scores, showing the contributions of the variables by vectors.

Usage

```

cor_lda(
  object,
  prior = object$prior,
  dimen,
  method = c("pearson", "kendall", "spearman"),
  ...
)

```

Arguments

<code>object</code>	An object of class "lda" such as results from MASS::lda()
<code>prior</code>	The prior probabilities of the classes. By default, taken to be the proportions in what was set in the call to MASS::lda()
<code>dimen</code>	The dimension of the space to be used. If this is less than the number of available dimensions, $\min(p, ng - 1)$, only the first <code>dimen</code> discriminant components are used.
<code>method</code>	a character string indicating which correlation coefficient is to be computed. One of "pearson" (default), "kendall", or "spearman": can be abbreviated. See stats::cor() for details
<code>...</code>	other arguments (presently ignored)

Value

a numeric matrix of correlations, of size ``nv`` = number of predictor variables * ``dimen``

Author(s)

Michael Friendly

See Also

`predict_discrim()`, `MASS::lda()`, `stats::cor()`

Examples

```
library(candisc)
library(MASS) # for lda()

iris.lda <- lda(Species ~ ., iris)
cor_lda(iris.lda)
```

dataIndex

Indices of observations in a model data frame

Description

Find sequential indices for observations in a data frame corresponding to the unique combinations of the levels of a given model term from a model object or a data frame

Usage

```
dataIndex(x, term)
```

Arguments

x	Either a data frame or a model object
term	The name of one term in the model, consisting only of factors

Value

A vector of indices.

Author(s)

Michael Friendly

Examples

```
factors <- expand.grid(A=factor(1:3),B=factor(1:2),C=factor(1:2))
n <- nrow(factors)
responses <-data.frame(Y1=10+round(10*rnorm(n)),Y2=10+round(10*rnorm(n)))

test <- data.frame(factors, responses)
mod <- lm(cbind(Y1,Y2) ~ A*B, data=test)

dataIndex(mod, "A")
dataIndex(mod, "A:B")
```

Grass

Yields from Nitrogen nutrition of grass species

Description

The data frame Grass gives the yield ($10 * \log_{10}$ dry-weight (g)) of eight grass Species in five replicates (Block) grown in sand culture at five levels of nitrogen.

Format

A data frame with 40 observations on the following 7 variables.

Species a factor with levels B.media D.glomerata F.ovina F.rubra H.pubesens K.cristata
L.perenne P.bertolonii

Block a factor with levels 1 2 3 4 5

N1 species yield at 1 ppm Nitrogen

N9 species yield at 9 ppm Nitrogen

N27 species yield at 27 ppm Nitrogen

N81 species yield at 81 ppm Nitrogen

N243 species yield at 243 ppm Nitrogen

Details

Nitrogen (NaNO_3) levels were chosen to vary from what was expected to be from critically low to almost toxic. The amount of Nitrogen can be considered on a $\log_3$ scale, with levels 0, 2, 3, 4, 5. Gittins (1985, Ch. 11) treats these as equally spaced for the purpose of testing polynomial trends in Nitrogen level.

The data are also not truly multivariate, but rather a split-plot experimental design. For the purpose of exposition, he regards Species as the experimental unit, so that correlations among the responses refer to a composite representative of a species rather than to an individual exemplar.

Source

Gittins, R. (1985), Canonical Analysis: A Review with Applications in Ecology, Berlin: Springer-Verlag, Table A-5.

Examples

```
str(Grass)
grass.mod <- lm(cbind(N1,N9,N27,N81,N243) ~ Block + Species, data=Grass)
car::Anova(grass.mod)

grass.canL <-candisclList(grass.mod)
names(grass.canL)
names(grass.canL$Species)
```

heplot.cancor

Canonical Correlation HE plots

Description

Hypothesis - Error (HE) plots for canonical correlation analysis provide a new graphical method for understanding the relations between two sets of variables, **X** and **Y**. They are similar to HE plots for multivariate multiple regression (MMRA) problems, except that ...

These functions plot ellipses (or ellipsoids in 3D) in canonical space representing the hypothesis and error sums-of-squares-and-products matrices for terms in a multivariate linear model representing the result of a canonical correlation analysis. They provide a low-rank 2D (or 3D) view of the effects in the space of maximum canonical correlations, together with variable vectors representing the correlations of Y variables with the canonical dimensions.

For consistency with [heplot.candisc\(\)](#), the plots show effects in the space of the canonical Y variables selected by which.

Usage

```
## S3 method for class 'cancor'
heplot(
  mod,
  which = 1:2,
  scale,
  asp = 1,
  var.vectors = "Y",
  var.col = c("blue", "darkgreen"),
  var.lwd = par("lwd"),
  var.cex = par("cex"),
  var.xpd = TRUE,
  prefix = "Ycan",
  suffix = TRUE,
```

```

    terms = TRUE,
    ...
)

```

Arguments

<code>mod</code>	A "cancor" object, as computed by <code>cancor()</code>
<code>which</code>	A numeric vector containing the indices of the Y canonical dimensions to plot.
<code>scale</code>	Scale factor for the variable vectors in canonical space. If not specified, the function calculates one to make the variable vectors approximately fill the plot window.
<code>asp</code>	aspect ratio setting. Use <code>asp=1</code> in 2D plots and <code>asp="iso"</code> in 3D plots to ensure equal units on the axes. Use <code>asp=NA</code> in 2D plots and <code>asp=NULL</code> in 3D plots to allow separate scaling for the axes. See Details below.
<code>var.vectors</code>	Which variable vectors to plot? A character vector containing one or more of "X" and "Y".
<code>var.col</code>	Color(s) for variable vectors and labels, a vector of length 1 or 2. The first color is used for Y vectors and the second for X vectors, if these are plotted.
<code>var.lwd</code>	Line width for variable vectors
<code>var.cex</code>	Text size for variable vector labels
<code>var.xpd</code>	logical. Allow variable labels outside the plot box? Does not apply to 3D plots.
<code>prefix</code>	Prefix for labels of the Y canonical dimensions.
<code>suffix</code>	Suffix for labels of canonical dimensions. If <code>suffix=TRUE</code> the percent of hypothesis (H) variance accounted for by each canonical dimension is added to the axis label.
<code>terms</code>	Terms for the X variables to be plotted in canonical space. The default, <code>terms=TRUE</code> or <code>terms="X"</code> plots H ellipses for all of the X variables. <code>terms="Xcan"</code> plots H ellipses for all of the X canonical variables, <code>Xcan1</code> , <code>Xcan2</code> ,
<code>...</code>	Other arguments passed to <code>link[heplots]{heplot}</code> . In particular, you can pass linear hypotheses among the term variables via <code>hypotheses</code> .

Details

The interpretation of variable vectors in these plots is different from that of the terms plotted as H "ellipses," which appear as degenerate lines in the plot (because they correspond to 1 df tests of $\text{rank}(H)=1$).

In canonical space, the interpretation of the H ellipses for the terms is the same as in ordinary HE plots: a term is significant *iff* its H ellipse projects outside the (orthogonalized) E ellipsoid somewhere in the space of the Y canonical dimensions. The orientation of each H ellipse with respect to the Y canonical dimensions indicates which dimensions that X variate contributes to.

On the other hand, the variable vectors shown in these plots are intended only to show the correlations of Y variables with the canonical dimensions. Only their relative lengths and angles with respect to the Y canonical dimensions have meaning. Relative lengths correspond to proportions of variance accounted for in the Y canonical dimensions plotted; angles between the variable vectors and the canonical axes correspond to the structure correlations. The absolute lengths of these

vectors are typically manipulated by the `scale` argument to provide better visual resolution and labeling for the variables.

Setting the aspect ratio of these plots is important for the proper interpretation of angles between the variable vectors and the coordinate axes. However, this then makes it impossible to change the aspect ratio of the plot by re-sizing manually. You can override this using `asp=NA` in 2D plots

Value

Returns invisibly an object of class "heplot", with coordinates for the various hypothesis ellipses and the error ellipse, and the limits of the horizontal and vertical axes.

Author(s)

Michael Friendly

References

Gittins, R. (1985). *Canonical Analysis: A Review with Applications in Ecology*, Berlin: Springer.
Mardia, K. V., Kent, J. T. and Bibby, J. M. (1979). *Multivariate Analysis*. London: Academic Press.

See Also

[`cancor()`] for details on canonical correlation as implemented here;
[`plot.cancor()`] for scatterplots of canonical variable scores.
[`heplot.candisc()`], [`heplots::heplot()`], [`car::linearHypothesis()`]

Examples

```
data(Rohwer, package="heplots")
X <- as.matrix(Rohwer[,6:10])
Y <- as.matrix(Rohwer[,3:5])
cc <- cancor(X, Y, set.names=c("PA", "Ability"))

# basic plot
heplot(cc)

# note relationship of joint hypothesis to individual ones
heplot(cc, scale=1.25, hypotheses=list("na+ns"=c("na", "ns")))

# more options
heplot(cc, hypotheses=list("All X"=colnames(X)),
fill=c(TRUE,FALSE), fill.alpha=0.2,
var.cex=1.5, var.col="red", var.lwd=3,
prefix="Y canonical dimension"
)

# 3D version
## Not run:
heplot3d(cc, var.lwd=3, var.col="red")

## End(Not run)
```

heplot.candisc	<i>Canonical Discriminant HE plots</i>
----------------	--

Description

These functions plot ellipses (or ellipsoids in 3D) in canonical discriminant space representing the hypothesis and error sums-of-squares-and-products matrices for terms in a multivariate linear model. They provide a low-rank 2D (or 3D) view of the effects for that term in the space of maximum discrimination.

Usage

```
## S3 method for class 'candisc'
heplot(
  mod,
  which = 1:2,
  scale,
  asp = 1,
  var.col = "blue",
  var.labels,
  var.lwd = par("lwd"),
  var.cex = par("cex"),
  var.pos,
  rev.axes = c(FALSE, FALSE),
  prefix = "Can",
  suffix = TRUE,
  terms = mod$term,
  ...
)
```

Arguments

<code>mod</code>	A candisc object for one term in a <code>mlm</code>
<code>which</code>	A numeric vector containing the indices of the canonical dimensions to plot.
<code>scale</code>	Scale factor for the variable vectors in canonical space. If not specified, the function calculates one to make the variable vectors approximately fill the plot window.
<code>asp</code>	Aspect ratio for the horizontal and vertical dimensions. The defaults, <code>asp=1</code> for <code>heplot.candisc</code> and <code>asp="iso"</code> for <code>heplot3d.candisc</code> ensure equal units on all axes, so that angles and lengths of variable vectors are interpretable. As well, the standardized canonical scores are uncorrelated, so the Error ellipse (ellipsoid) should plot as a circle (sphere) in canonical space. For <code>heplot3d.candisc</code> , use <code>asp=NULL</code> to suppress this transformation to iso-scaled axes.

<code>var.col</code>	Color for variable vectors and labels
<code>var.labels</code>	Labels for the variable vectors. The default is the rownames of the canonical structure coefficients.
<code>var.lwd</code>	Line width for variable vectors
<code>var.cex</code>	Text size for variable vector labels
<code>var.pos</code>	Position(s) of variable vector labels wrt. the end point. If not specified, the labels are out-justified left and right with respect to the end points.
<code>rev.axes</code>	Logical, a vector of length(which). TRUE causes the orientation of the canonical scores and structure coefficients to be reversed along a given axis.
<code>prefix</code>	Prefix for labels of canonical dimensions.
<code>suffix</code>	Suffix for labels of canonical dimensions. If <code>suffix=TRUE</code> the percent of hypothesis (H) variance accounted for by each canonical dimension is added to the axis label.
<code>terms</code>	Terms from the original <code>mlm</code> whose H ellipses are to be plotted in canonical space. The default is the one term for which the canonical scores were computed. If <code>terms=TRUE</code> , all terms are plotted.
<code>...</code>	Arguments to be passed down to heplot or heplot3d

Details

The generalized canonical discriminant analysis for one term in a `mlm` is based on the eigenvalues, λ_i , and eigenvectors, V , of the H and E matrices for that term. This produces uncorrelated canonical scores which give the maximum univariate F statistics. The canonical HE plot is then just the HE plot of the canonical scores for the given term.

For `heplot3d.candisc`, the default `asp="iso"` now gives a geometrically correct plot, but the third dimension, `CAN3`, is often small. Passing an expanded range in `zlim` to [heplot3d](#) usually helps.

Value

`heplot.candisc` returns invisibly an object of class "heplot", with coordinates for the various hypothesis ellipses and the error ellipse, and the limits of the horizontal and vertical axes.

Similarly, `heplotted.candisc` returns an object of class "heplot3d".

Author(s)

Michael Friendly and John Fox

References

- Friendly, M. (2006). Data Ellipses, HE Plots and Reduced-Rank Displays for Multivariate Linear Models: SAS Software and Examples *Journal of Statistical Software*, 17(6), 1-42. % <https://www.jstatsoft.org/v17/i06/> doi:10.18637/jss.v017.i06
- Friendly, M. (2007). HE plots for Multivariate General Linear Models. *Journal of Computational and Graphical Statistics*, 16(2) 421-444. <http://datavis.ca/papers/jcgs-heplots.pdf>, doi:10.1198/106186007X208407.

See Also

[candisc](#), [candiscList](#), [heplot](#), [heplot3d](#), [aspect3d](#)

Examples

```
## Pottery data, from car package
data(Pottery, package = "carData")
pottery.mod <- lm(cbind(Al, Fe, Mg, Ca, Na) ~ Site, data=Pottery)
pottery.can <- candisc(pottery.mod)

heplot(pottery.can, var.lwd=3)
if(requireNamespace("rgl")){
  heplot3d(pottery.can, var.lwd=3, scale=10, zlim=c(-3,3), wire=FALSE)
}

# reduce example for CRAN checks time

grass.mod <- lm(cbind(N1,N9,N27,N81,N243) ~ Block + Species, data=Grass)

grass.can1 <- candisc(grass.mod,term="Species")
grass.canL <- candiscList(grass.mod)

heplot(grass.can1, scale=6)
heplot(grass.can1, scale=6, terms=TRUE)
heplot(grass.canL, terms=TRUE, ask=FALSE)

heplot3d(grass.can1, wire=FALSE)
# compare with non-iso scaling
rgl::aspect3d(x=1,y=1,z=1)
# or,
# heplot3d(grass.can1, asp=NULL)

## Can't run this in example
# rgl::play3d(rgl::spin3d(axis = c(1, 0, 0), rpm = 5), duration=12)

# reduce example for CRAN checks time

## FootHead data, from heplots package
library(heplots)
data(FootHead)

# use Helmert contrasts for group
contrasts(FootHead$group) <- contr.helmert

foot.mod <- lm(cbind(width, circum,front.back,eye.top,ear.top,jaw)~group, data=FootHead)
foot.can <- candisc(foot.mod)
heplot(foot.can, main="Candisc HE plot",
  hypotheses=list("group.1"="group1","group.2"="group2"),
  col=c("red", "blue", "green3", "green3" ), var.col="red")
```

heplot.candiscList	<i>Canonical Discriminant HE plots</i>
--------------------	--

Description

These functions plot ellipses (or ellipsoids in 3D) in canonical discriminant space representing the hypothesis and error sums-of-squares-and-products matrices for terms in a multivariate linear model. They provide a low-rank 2D (or 3D) view of the effects for that term in the space of maximum discrimination.

Usage

```
## S3 method for class 'candiscList'  
heplot(mod, term, ask = interactive(), graphics = TRUE, ...)
```

Arguments

mod	A candiscList object for terms in a mlm
term	The name of one term to be plotted for the heplot and heplot3d methods. If not specified, one plot is produced for each term in the mlm object.
ask	If TRUE (the default), a menu of terms is presented; if ask is FALSE, canonical HE plots for all terms are produced.
graphics	if TRUE (the default, when running interactively), then the menu of terms to plot is presented in a dialog box rather than as a text menu.
...	Arguments to be passed down

Value

No useful value; used for the side-effect of producing canonical HE plots.

Author(s)

Michael Friendly and John Fox

References

Friendly, M. (2006). Data Ellipses, HE Plots and Reduced-Rank Displays for Multivariate Linear Models: SAS Software and Examples *Journal of Statistical Software*, 17(6), 1-42. <https://www.jstatsoft.org/v17/i06/> doi:10.18637/jss.v017.i06.

Friendly, M. (2007). HE plots for Multivariate General Linear Models. *Journal of Computational and Graphical Statistics*, 16(2) 421–444. <http://datavis.ca/papers/jcgs-heplots.pdf>, doi:10.1198/106186007X208407.

See Also

[candisc](#), [candiscList](#), [heplot](#), [heplot3d](#)

 HSB

High School and Beyond Data

Description

The High School and Beyond Project was a longitudinal study of students in the U.S. carried out in 1980 by the National Center for Education Statistics. Data were collected from 58,270 high school students (28,240 seniors and 30,030 sophomores) and 1,015 secondary schools. The HSB data frame is sample of 600 observations, of unknown characteristics, originally taken from Tatsuoka (1988).

Format

A data frame with 600 observations on the following 15 variables. There is no missing data.

`id` Observation id: a numeric vector

`gender` a factor with levels male female

`race` Race or ethnicity: a factor with levels hispanic asian african-amer white

`ses` Socioeconomic status: a factor with levels low middle high

`sch` School type: a factor with levels public private

`prog` High school program: a factor with levels general academic vocation

`locus` Locus of control: a numeric vector

`concept` Self-concept: a numeric vector

`mot` Motivation: a numeric vector

`career` Career plan: a factor with levels clerical craftsman farmer homemaker laborer manager
military operative prof1 prof2 proprietor protective sales school service technical
not working

`read` Standardized reading score: a numeric vector

`write` Standardized writing score: a numeric vector

`math` Standardized math score: a numeric vector

`sci` Standardized science score: a numeric vector

`ss` Standardized social science (civics) score: a numeric vector

Source

Tatsuoka, M. M. (1988). *Multivariate Analysis: Techniques for Educational and Psychological Research* (2nd ed.). New York: Macmillan, Appendix F, 430-442.

% Originally retrieved from: <http://www.gseis.ucla.edu/courses/data/hbs6.dta>

References

High School and Beyond data files: <http://www.icpsr.umich.edu/icpsrweb/ICPSR/studies/7896>

Examples

```
str(HSB)
# main effects model
hsb.mod <- lm( cbind(read, write, math, sci, ss) ~
gender + race + ses + sch + prog, data=HSB)
car::Anova(hsb.mod)

# Add some interactions
hsb.mod1 <- update(hsb.mod, . ~ . + gender:race + ses:prog)
heplot(hsb.mod1, col=palette()[c(2,1,3:6)], variables=c("read","math"))

hsb.can1 <- candisc(hsb.mod1, term="race")
heplot(hsb.can1, col=c("red", "black"))

# show canonical results for all terms
## Not run:
hsb.can <- candiscList(hsb.mod)
hsb.can

## End(Not run)
```

plot.cancor

Canonical Correlation Plots

Description

This function produces plots to help visualize X, Y data in canonical space.

The present implementation plots the canonical scores for the Y variables against those for the X variables on given dimensions. We treat this as a view of the data in canonical space, and so offer additional annotations to a standard scatterplot.

Canonical correlation analysis assumes that the all correlations between the X and Y variables can be expressed in terms of correlations the canonical variate pairs, (Xcan1, Ycan1), (Xcan2, Ycan2), ..., and that the relations between these pairs are indeed linear.

Data ellipses, and smoothed (loess) curves, together with the linear regression line for each canonical dimension help to assess whether there are peculiarities in the data that might threaten the validity of CCA. Point identification methods can be useful to determine influential cases.

Usage

```
## S3 method for class 'cancor'
plot(
  x,
  which = 1,
  xlim,
  ylim,
  xlab,
  ylab,
  points = TRUE,
  add = FALSE,
  col = palette()[1],
  ellipse = TRUE,
  ellipse.args = list(),
  smooth = FALSE,
  smoother.args = list(),
  col.smooth = palette()[3],
  abline = TRUE,
  col.lines = palette()[2],
  lwd = 2,
  labels = rownames(xy),
  id.method = "mahal",
  id.n = 0,
  id.cex = 1,
  id.col = palette()[1],
  ...
)
```

Arguments

<code>x</code>	A "cancor" object
<code>which</code>	Which dimension to plot? An integer in <code>1:x\$ndim</code> .
<code>xlim, ylim</code>	Limits for x and y axes
<code>xlab, ylab</code>	Labels for x and y axes. If not specified, these are constructed from the <code>set.names</code> component of <code>x</code> .
<code>points</code>	logical. Display the points?
<code>add</code>	logical. Add to an existing plot?
<code>col</code>	Color for points.
<code>ellipse</code>	logical. Draw a data ellipse for the canonical scores?
<code>ellipse.args</code>	A list of arguments passed to dataEllipse . Internally, the function sets the default value for <code>levels</code> to 0.68.
<code>smooth</code>	logical. Draw a (loess) smoothed curve?
<code>smoother.args</code>	Arguments passed to loessLine , which should be consulted for details and defaults.
<code>col.smooth</code>	Color for the smoothed curve.

abline	logical. Draw the linear regression line for Ycan[, which] on Xcan[, which]?
col.lines	Color for the linear regression line
lwd	Line widths
labels	Point labels for point identification via the id.method argument.
id.method	Method used to identify individual points. See showLabels for details. The default, id.method = "mahal" identifies the id.n points furthest from the centroid.
id.n	Number of points to identify
id.cex, id.col	Character size and color for labeled points
...	Other arguments passed down to plot(\dots) and points(\dots)

Value

None. Used for its side effect of producing a plot. %% ~Describe the value returned

Author(s)

Michael Friendly

References

Mardia, K. V., Kent, J. T. and Bibby, J. M. (1979). *Multivariate Analysis*. London: Academic Press.

See Also

[cancor](#),
[dataEllipse](#), [loessLine](#), [showLabels](#)

Examples

```
data(Rohwer, package="heplots")
X <- as.matrix(Rohwer[,6:10]) # the PA tests
Y <- as.matrix(Rohwer[,3:5])  # the aptitude/ability variables

cc <- cancor(X, Y, set.names=c("PA", "Ability"))

plot(cc)
# exercise some options
plot(cc, which=1,
      smooth=TRUE,
      pch = 16,
      id.n=3, ellipse.args=list(fill=TRUE, fill.alpha = 0.2))
plot(cc, which=2, smooth=TRUE)
plot(cc, which=3, smooth=TRUE)

# plot vectors showing structure correlations of Xcan and Ycan with their own variables
plot(cc)
struc <- cc$structure
```

```

Xstruc <- struc$X.scores[,1]
Ystruc <- struc$Y.scores[,1]
scale <- 2

# place vectors in the margins of the plot
usr <- matrix(par("usr"), nrow=2, dimnames=list(c("min", "max"), c("x", "y")))
ypos <- usr[2,2] - (1:5)/10
arrows(0, ypos, scale*Xstruc, ypos, angle=10, len=0.1, col="blue")
text(scale*Xstruc, ypos, names(Xstruc), pos=2, col="blue")

xpos <- usr[2,1] - ( 1 + 1:3)/10
arrows(xpos, 0, xpos, scale*Ystruc, angle=10, len=0.1, col="darkgreen")
text(xpos, scale*Ystruc, names(Ystruc), pos=1, col="darkgreen")

```

plot_discrim

Create a discriminant analysis decision plot using ggplot.

Description

[Experimental]

Discriminant analysis can be more easily understood from plots of the data variables showing how observations are classified. `plot_discrim()` uses the ideas behind effect plots: Visualize predicted values for two focal variables over a grid, with other variables in a model held fixed.

Usage

```

plot_discrim(
  model,
  vars,
  data,
  resolution = 100,
  contour = TRUE,
  contour.color = "black",
  point.size = 3,
  showgrid = c("tile", "point", "none"),
  ...,
  modes.means
)

```

Arguments

<code>model</code>	a discriminant analysis model object from <code>MASS::lda()</code> or <code>MASS::qda()</code>
<code>vars</code>	either a character vector of length 2 of the names of variables, or a formula of form <code>V1 ~ V2</code> specifying y and x axis in the plot respectively.
<code>data</code>	data to use for visualization. Should contain all the data needed to use the model

resolution	number of points in x, y variables to use for visualizing the predicted class boundaries and regions.
contour	logical; should the plot display the boundaries of the classes by contours?
contour.color	color of the lines for the contour boundaries
point.size	size of the plot symbols use to show the data observations
showgrid	a character string; how to display predicted class regions: "tile" for <code>ggplot2::geom_tile()</code> , "point" for <code>ggplot2::geom_point()</code> , or "none" for no grid display.
...	further parameters passed to <code>predict()</code>
modes.means	levels to use for evaluating predictions using the variables <i>not</i> specified in vars. If not specified, the function uses the means for quantitative variables, ...

Details

In setting up this plot for `ggplot2::ggplot()`, this function maps color and shape of class-specific elements of the plot to the value of the class variable in the discriminant analysis. But it simply uses the ggplot defaults...

Author(s)

Original code by Oliver on SO <https://stackoverflow.com/questions/63782598/quadratic-discriminant-analysis>
Generalized by Michael Friendly

See Also

`klaR::partimat()`

Examples

```
library(MASS)
library(ggplot2)
library(dplyr)
library(candisc)

iris.lda <- lda(Species ~ ., iris)
plot_discrim(iris.lda, Petal.Length ~ Petal.Width, data=iris, showgrid = "tile")
```

predictor.names	<i>Get predictor names from a lm-like model</i>
-----------------	---

Description

Get predictor names from a lm-like model

Usage

```
predictor.names(model, ...)

## Default S3 method:
predictor.names(model, ...)
```

Arguments

```
model          Model object
...            other arguments (ignored)
```

Value

A character vector of variable names

Methods (by class)

- `predictor.names(default)`: "default" method.

Examples

```
#none
```

predict_discrim	<i>Predicted values for discriminant analysis</i>
-----------------	---

Description

`predict_discrim` calculates predicted class membership values for a linear or quadratic discriminant analysis, returning a `data.frame` suitable for graphing or other analysis.

Usage

```
predict_discrim(
  object,
  newdata,
  prior = object$prior,
  dimen,
  scores = FALSE,
  posterior = "max",
  ...
)
```

Arguments

object	An object of class "lda" or "qda" such as results from <code>MASS::lda()</code> or <code>MASS::qda()</code>
newdata	A data frame of cases to be classified or, if object has a formula, a data frame with columns of the same names as the variables used. A vector will be interpreted as a row vector. If newdata is missing, an attempt will be made to retrieve the data used to fit the lda object.
prior	The prior probabilities of the classes. By default, taken to be the proportions in what was set in the call to <code>MASS::lda()</code> or <code>MASS::qda()</code>
dimen	The dimension of the space to be used. If this is less than the number of available dimensions, $\min(p, ng - 1)$, only the first dimen discriminant components are used. (This argument is not yet implemented because <code>MASS::qda()</code> does not support this.)
scores	A logical. If TRUE, the discriminant scores of the cases in newdata are appended as additional columns in the the result, with names LD1, LD2, ...
posterior	Either a logical or the character string "max". If TRUE, the posterior probabilities for all classes are included as columns named for the classes. If FALSE, these are omitted. If "max", the maximum value of the probabilities across the classes are included, with the variable name "maxp".
...	arguments based from or to other methods, not yet used here

Details

The `predict()` methods provided for `MASS::lda()` and `MASS::qda()` are a mess, because they return their results as a list, with components `class`, `posterior` and `x`. This function is designed as a wrapper on those to return results in a more consistent and flexible way.

For use in graphs, where you want to show the classification boundaries or regions, you should supply a newdata data frame consisting of two focal variables which are varied over their ranges, with the remaining variables used in the discriminant analysis held fixed at typical values.

Using the `scores` argument, the function also returns the scores on the discriminant functions. This is only available for linear discriminant analysis with `MASS::lda()`.

Value

A data.frame, containing the the predicted class of the observations, values of the newdata variables and the maximum value of the posterior probabilities of the classes. `rownames()` in the result are inherited from those in newdata.

Examples

```
library(candisc)
library(MASS) # for lda()

iris.lda <- lda(Species ~ ., iris)
pred_iris <- predict_discrim(iris.lda)
names(pred_iris)

# include scores, exclude posterior
```

```
pred_iris <- predict_discrim(iris.lda, scores = TRUE, posterior = FALSE)
names(pred_iris)

data(peng, package="heplots")
peng.lda <- lda(species ~ bill_length + bill_depth + flipper_length + body_mass,
               data = peng)
peng_pred <- predict_discrim(peng.lda, scores = TRUE)
str(peng_pred)
```

PsyAcad

Psychological Measures and Academic Achievement

Description

A researcher collected data on three psychological variables, four academic variables (standardized test scores) and gender for 600 college freshman. She is interested in how the set of psychological variables relates to the academic variables and gender. In particular, the researcher is interested in how many dimensions (canonical variables) are necessary to understand the association between the two sets of variables.

Usage

```
data("PsyAcad")
```

Format

A data frame with 600 observations on the following 8 variables.

LocControl locus of control, a numeric vector

SelfConcept self concept, a numeric vector

Motivation motivation, a numeric vector

Read reading score, a numeric vector

Write writing score, a numeric vector

Math mathematics score, a numeric vector

Science science score, a numeric vector

Sex a factor with levels M, F

Source

Taken from <https://stats.oarc.ucla.edu/r/dae/canonical-correlation-analysis/>

Examples

```
data(PsyAcad)
PsyAcad$Sex <- as.numeric(PsyAcad$Sex)
PsyAcad.can <- cancel(cbind(LocControl, SelfConcept, Motivation) ~
  Read + Write + Math + Science + Sex, data = PsyAcad)

PsyAcad.can

# redundancy analysis
redundancy(PsyAcad.can)

# Plots
canR <- PsyAcad.can$cancel
plot(PsyAcad.can, pch=16, id.n = 3)
text(-2, 3, paste("Can R =", round(canR[1], 3)), pos = 3)

plot(PsyAcad.can, which = 2, pch=16, id.n = 3)
text(-2, 3.5, paste("Can R =", round(canR[2], 3)), pos = 3)
```

redundancy	<i>Canonical Redundancy Analysis</i>
------------	--------------------------------------

Description

Calculates indices of redundancy (Stewart & Love, 1968) from a canonical correlation analysis. These give the proportion of variances of the variables in each set (X and Y) which are accounted for by the variables in the other set through the canonical variates.

Usage

```
redundancy(object, ...)

## S3 method for class 'cancel.redundancy'
print(x, digits = max(getOption("digits") - 3, 3), ...)
```

Arguments

object	A "cancel" object
...	Other arguments
x	A "cancel.redundancy" for the print method.
digits	Number of digits to print

Details

The term "redundancy analysis" has a different interpretation and implementation in the environmental ecology literature, such as the **vegan**. In that context, each Y_i variable is regressed separately on the predictors in X , to give fitted values $\hat{Y} = [\hat{Y}_1, \hat{Y}_2, \dots]$. Then a PCA of $\hat{Y}$ is carried out to determine a reduced-rank structure of the predictions.

Value

An object of class "cancor.redundancy", a list with the following 5 components:

Xcan.redun	Canonical redundancies for the X variables, i.e., the total fraction of X variance accounted for by the Y variables through each canonical variate.
Ycan.redun	Canonical redundancies for the Y variables
X.redun	Total canonical redundancy for the X variables, i.e., the sum of Xcan.redun.
Y.redun	Total canonical redundancy for the Y variables
set.names	names for the X and Y sets of variables

Functions

- `print(cancor.redundancy): print()` method for "cancor.redundancy" objects.

Author(s)

Michael Friendly

References

- Muller K. E. (1981). Relationships between redundancy analysis, canonical correlation, and multi-variate regression. *Psychometrika*, **46**(2), 139-42.
- Stewart, D. and Love, W. (1968). A general canonical correlation index. *Psychological Bulletin*, 70, 160-163.
- Brainder, "Redundancy in canonical correlation analysis", <https://brainder.org/2019/12/27/redundancy-in-canonical-correlation-analysis/>

See Also

\ [cancor\(\)](#)

Examples

```
data(Rohwer, package="heplots")
X <- as.matrix(Rohwer[,6:10]) # the PA tests
Y <- as.matrix(Rohwer[,3:5])  # the aptitude/ability variables

cc <- cancor(X, Y, set.names=c("PA", "Ability"))

redundancy(cc)
##
## Redundancies for the PA variables & total X canonical redundancy
##
##      Xcan1      Xcan2      Xcan3 total X|Y
##      0.17342    0.04211    0.00797    0.22350
##
## Redundancies for the Ability variables & total Y canonical redundancy
##
##      Ycan1      Ycan2      Ycan3 total Y|X
```



```
##      0.2249      0.0369      0.0156      0.2774
```

reflect

Reflect Columns in an Object, reversing the sign of all elements

Description

candisc and cancel objects have coefficients for the X and Y and weighted scores for these, whose signs are arbitrary, in the sense that a given column can be reflected (multiplied by -1) without changing the fit. But, often you will want to reverse the direction of one or more dimensions for ease of interpretation.

This function allows you to reflect any columns of the variable coefficients (and corresponding observation scores). This is often useful for interpreting a biplot, for example when a component (often the first) has all negative signs.

Usage

```
reflect(object, columns = 1:2, ...)
```

```
## S3 method for class 'data.frame'
reflect(object, columns = 1:2, ...)
```

```
## S3 method for class 'cancel'
reflect(object, columns = 1:2, ...)
```

```
## S3 method for class 'candisc'
reflect(object, columns = 1:2, ...)
```

Arguments

object	An object whose columns are to be reflected
columns	a vector of indices of the columns to reflect
...	Unused

Details

reflect methods are available for:

- data.frames
- "cancel" objects
- "candisc" objects

Note that `plot.candisc()` and `plot.cancel()` can handle this internally using the argument `rev.axes`.

Value

The object with specified columns of the variable coefficients and observation scores multiplied by -1.

Methods (by class)

- `reflect(data.frame)`: "data.frame" method.
- `reflect(cancor)`: "cancor" method.
- `reflect(candisc)`: "candisc" method.

Author(s)

Michael Friendly

See Also

[ggbiplot::reflect](#) has similar methods for PCA-like objects

varOrder

Order variables according to canonical structure or other criteria

Description

The `varOrder` function implements some features of “effect ordering” (Friendly & Kwan (2003) for *variables* in a multivariate data display to make the displayed relationships more coherent.

This can be used in pairwise HE plots, scatterplot matrices, parallel coordinate plots, plots of multivariate means, and so forth.

For a numeric data frame, the most useful displays often order variables according to the angles of variable vectors in a 2D principal component analysis or biplot. For a multivariate linear model, the analog is to use the angles of the variable vectors in a 2D canonical discriminant biplot.

Usage

```
varOrder(x, ...)

## S3 method for class 'mlm'
varOrder(
  x,
  term,
  variables,
  type = c("can", "pc"),
  method = c("angles", "dim1", "dim2", "alphabet", "data", "colmean"),
  names = FALSE,
  descending = FALSE,
  ...
)
```

```
## S3 method for class 'data.frame'
varOrder(
  x,
  variables,
  method = c("angles", "dim1", "dim2", "alphabet", "data", "colmean"),
  names = FALSE,
  descending = FALSE,
  ...
)

## Default S3 method:
varOrder(x, ...)
```

Arguments

x	A multivariate linear model or a numeric data frame
...	Arguments passed to methods
term	For the <code>mlm</code> method, one term in the model for which the canonical structure coefficients are found.
variables	indices or names of the variables to be ordered; defaults to all response variables an MLM or all numeric variables in a data frame.
type	For an MLM, <code>type="can"</code> uses the canonical structure coefficients for the given term; <code>type="pc"</code> uses the principal component variable eigenvectors.
method	One of <code>c("angles", "dim1", "dim2", "alphabet", "data", "colmean")</code> giving the effect ordering method. "angles" Orders variables according to the angles their vectors make with dimensions 1 and 2, counter-clockwise starting from the lower-left quadrant in a 2D biplot or candisc display. "dim1" Orders variables in increasing order of their coordinates on dimension 1 "dim2" Orders variables in increasing order of their coordinates on dimension 2 "alphabet" Orders variables alphabetically "data" Uses the order of the variables in the data frame or the list of responses in the MLM "colmean" Uses the order of the column means of the variables in the data frame or the list of responses in the MLM
names	logical; if TRUE the effect ordered names of the variables are returned; otherwise, their indices in <code>variables</code> are returned.
descending	If TRUE, the ordered result is reversed to a descending order.

Value

A vector of integer indices of the variables or a character vector of their names.

Methods (by class)

- `varOrder(mlm)`: "mlm" method.
- `varOrder(data.frame)`: "data.frame" method.
- `varOrder(default)`: "default" method.

Author(s)

Michael Friendly

References

Friendly, M. & Kwan, E. (2003). Effect Ordering for Data Displays, *Computational Statistics and Data Analysis*, **43**, 509-539. doi:[10.1016/S01679473\(02\)002906](https://doi.org/10.1016/S01679473(02)002906)

Examples

```
data(Wine, package="candisc")
Wine.mod <- lm(as.matrix(Wine[, -1]) ~ Cultivar, data=Wine)
Wine.can <- candisc(Wine.mod)
plot(Wine.can, ellipse=TRUE)

# pairs.mlm HE plot, variables in given order
pairs(Wine.mod, fill=TRUE, fill.alpha=.1, var.cex=1.5)

order <- varOrder(Wine.mod)
pairs(Wine.mod, variables=order, fill=TRUE, fill.alpha=.1, var.cex=1.5)
```

vecscale

Scale vectors to fill the current plot

Description

Calculates a scale factor so that a collection of vectors nearly fills the current plot, that is, the longest vector does not extend beyond the plot region.

Usage

```
vecscale(
  vectors,
  bbox = matrix(par("usr"), 2, 2),
  origin = c(0, 0),
  factor = 0.95
)
```

Arguments

vectors	a two-column matrix giving the end points of a collection of vectors
bbox	the bounding box of the containing plot region within which the vectors are to be plotted. The default is the bounding box of the current plot window, obtained from <code>par("usr")</code> .
origin	origin of the vectors. Defaults to (0, 0).
factor	maximum length of the rescaled vectors relative to the maximum possible

Details

This function is used in, e.g., `vectors()` to draw labeled vectors in a dimension-reduction plot. The scaling calculated here doesn't directly calculate space for the labels to fit within the plot regions. The `factor` argument can provide for that, shrinking the vectors by that factor.

Value

scale factor, the numeric multiplier of the vectors

Author(s)

Michael Friendly

See Also

`vectors()`, `plot.candisc()`, `heplot.candisc()`

Examples

```
bbox <- matrix(c(-3, 3, -2, 2), 2, 2)
colnames(bbox) <- c("x", "y")
rownames(bbox) <- c("min", "max")
bbox

vecs <- matrix( runif(10, -1, 1), 5, 2)

plot(bbox)
arrows(0, 0, vecs[,1], vecs[,2], angle=10, col="red")
(s <- vecscale(vecs))
arrows(0, 0, s*vecs[,1], s*vecs[,2], angle=10)
```

vectors

*Draw Labeled Vectors in 2D or 3D***Description**

Graphics utility functions to draw vectors from an origin to a collection of points (using `graphics::arrows()` in 2D or `rgl::lines3d()` in 3D) with labels for each (using `graphics::text()` or `rgl::texts3d()`)

Usage

```
vectors(
  x,
  origin = c(0, 0),
  labels = rownames(x),
  scale = 1,
  col = "blue",
  lwd = 1,
  cex = 1,
  length = 0.1,
  angle = 13,
  pos = NULL,
  ...
)
```

Arguments

<code>x</code>	A two-column matrix or a three-column matrix containing the end points of the vectors
<code>origin</code>	Starting point(s) for the vectors
<code>labels</code>	Labels for the vectors
<code>scale</code>	A multiplier for the length of each vector
<code>col</code>	color(s) for the vectors.
<code>lwd</code>	line width(s) for the vectors.
<code>cex</code>	color(s) for the vectors.
<code>length</code>	For vectors, length of the edges of the arrow head (in inches).
<code>angle</code>	For vectors, angle from the shaft of the arrow to the edge of the arrow head.
<code>pos</code>	For vectors, position of the text label relative to the vector head. If <code>pos==NULL</code> (the default), labels are positioned labels outside, relative to arrow ends
<code>...</code>	other graphical parameters, such as <code>lty</code> , <code>xpd</code> , ...

Details

The graphical parameters `col`, `lty` and `lwd` can be vectors of length > 1 and will be recycled if necessary across the rows of `x` which define the vectors.

For use in high-level plots, `vecscale()` can be used to find a value for the `scale` argument to automatically re-scale the vectors to approximately fill the plot region.

The option `xpd = TRUE` can be passed to `vectors()` via the `...` argument to avoid labels being clipped.

Value

None

Author(s)

Michael Friendly

See Also

`graphics::arrows()`, `graphics::text()`, `graphics::segments()`

`[rgl::lines3d()]`, `[rgl::texts3d()]`

Examples

```
set.seed(1234)
plot(c(-3, 3), c(-3,3), type="n",
     xlab = "X", ylab = "Y")
X <- matrix(rnorm(10), ncol=2)
rownames(X) <- LETTERS[1:5]
vectors(X, scale=2, col=palette(), xpd = TRUE)
```

Wilks

Wilks Lambda Tests for Canonical Correlations

Description

Tests the sequential hypotheses that the i th canonical correlation and all that follow it are zero,

$$\rho_i = \rho_{i+1} = \cdots = 0$$

Usage

```
Wilks(object, ...)

## S3 method for class 'cancor'
Wilks(object, ...)

## S3 method for class 'candisc'
Wilks(object, ...)
```

Arguments

<code>object</code>	An object of class "cancor" or "candisc"
<code>...</code>	Other arguments passed to methods (not used)

Details

Wilks' Lambda values are calculated from the eigenvalues and converted to F statistics using Rao's approximation.

Value

A data.frame (of class "anova") containing the test statistics

Methods (by class)

- `Wilks(cancor)`: "cancor" method.
- `Wilks(candisc)`: `print()` method for "candisc" objects.

Author(s)

Michael Friendly

References

Mardia, K. V., Kent, J. T. and Bibby, J. M. (1979). *Multivariate Analysis*. London: Academic Press.

See Also

[cancor\(\)](#)

Examples

```
data(Rohwer, package="heplots")
X <- as.matrix(Rohwer[,6:10]) # the PA tests
Y <- as.matrix(Rohwer[,3:5])  # the aptitude/ability variables

cc <- cancor(X, Y, set.names=c("PA", "Ability"))
Wilks(cc)

iris.mod <- lm(cbind(Petal.Length, Sepal.Length, Petal.Width, Sepal.Width) ~ Species, data=iris)
```



```
iris.can <- candisc(iris.mod, data=iris)
Wilks(iris.can)
```

Wine

Chemical composition of three cultivars of wine

Description

These data are the results of a chemical analysis of wines grown in the same region in Italy but derived from three different cultivars. The analysis determined the quantities of 13 constituents found in each of the three types of wines.

Format

A data frame with 178 observations on the following 14 variables.

Cultivar a factor with levels barolo grignolino barbera

Alcohol a numeric vector

MalicAcid a numeric vector

Ash a numeric vector

AlcAsh a numeric vector, Alkalinity of ash

Mg a numeric vector, Magnesium

Phenols a numeric vector, Total phenols

Flav a numeric vector, Flavanoids

NonFlavPhenols a numeric vector

Proa a numeric vector, Proanthocyanins

Color a numeric vector, color intensity

Hue a numeric vector

OD a numeric vector, OD280/OD315 of diluted wines

Proline a numeric vector

Details

This data set is a classic in the machine learning literature as an easy high-D classification problem, but is also of interest for examples of MANOVA and discriminant analysis.

The precise definitions of these variables is unknown: units, how they were measured, etc.

Source

This data set was obtained from the UCI Machine Learning Repository, <http://archive.ics.uci.edu/ml/datasets/Wine>
This page references a large number of papers that use this data set to compare different methods.

References

In R, a comparable data set is contained in the **ggbiplot** package.

Examples

```
data(Wine)
str(Wine)
#summary(Wine)

Wine.mlm <- lm(as.matrix(Wine[, -1]) ~ Cultivar, data=Wine)
Wine.can <- candisc(Wine.mlm)
Wine.can

plot(Wine.can, ellipse=TRUE)
plot(Wine.can, which=1)
```

Wolves

Wolf skulls

Description

Skull morphometric data on Rocky Mountain and Arctic wolves (*Canis Lupus L.*) taken from Morrison (1990), originally from Jolicoeur (1959).

Format

A data frame with 25 observations on the following 11 variables.

group a factor with levels ar:f ar:m rm:f rm:m, comprising the combinations of location and sex

location a factor with levels ar=Arctic, rm=Rocky Mountain

sex a factor with levels f=female, m=male

x1 palatal length, a numeric vector

x2 postpalatal length, a numeric vector

x3 zygomatic width, a numeric vector

x4 palatal width outside first upper molars, a numeric vector

x5 palatal width inside second upper molars, a numeric vector

x6 postglenoid foramina width, a numeric vector

x7 interorbital width, a numeric vector

x8 braincase width, a numeric vector

x9 crown length, a numeric vector

Details

All variables are expressed in millimeters.

The goal was to determine how geographic and sex differences among the wolf populations are determined by these skull measurements. For MANOVA or (canonical) discriminant analysis, the factors group or location and sex provide alternative parameterizations.

Source

Morrison, D. F. *Multivariate Statistical Methods*, (3rd ed.), 1990. New York: McGraw-Hill, p. 288-289.

% ~~ reference to a publication or URL from which the data were obtained ~~

References

Jolicoeur, P. "Multivariate geographical variation in the wolf *Canis lupis L.*", *Evolution*, XIII, 283–299.

Examples

```
data(Wolves)

# using group
wolf.mod <-lm(cbind(x1,x2,x3,x4,x5,x6,x7,x8,x9) ~ group, data=Wolves)
car::Anova(wolf.mod)

wolf.can <-candisc(wolf.mod)
plot(wolf.can)
heplot(wolf.can)

# using location, sex
wolf.mod2 <-lm(cbind(x1,x2,x3,x4,x5,x6,x7,x8,x9) ~ location*sex, data=Wolves)
car::Anova(wolf.mod2)

wolf.can2 <-candiscList(wolf.mod2)
plot(wolf.can2)
```

Index

- * **MANOVA**
 - Grass, [22](#)
 - Wine, [49](#)
- * **MMRA**
 - cereal, [18](#)
 - HSB, [30](#)
- * **aplot**
 - vectors, [46](#)
- * **cancor**
 - cereal, [18](#)
 - HSB, [30](#)
 - PsyAcad, [38](#)
- * **candisc**
 - Grass, [22](#)
 - Wine, [49](#)
 - Wolves, [50](#)
- * **datasets**
 - cereal, [18](#)
 - Grass, [22](#)
 - HSB, [30](#)
 - PsyAcad, [38](#)
 - Wine, [49](#)
 - Wolves, [50](#)
- * **hplot**
 - candisc, [10](#)
 - candiscList, [15](#)
 - heplot.cancor, [23](#)
 - heplot.candisc, [26](#)
 - heplot.candiscList, [29](#)
 - plot.cancor, [31](#)
- * **htest**
 - Wilks, [47](#)
- * **manip**
 - dataIndex, [21](#)
 - varOrder, [42](#)
 - vecscale, [44](#)
- * **multivariate**
 - cancor, [4](#)
 - candisc, [10](#)
 - candisc-package, [3](#)
 - candiscList, [15](#)
 - heplot.cancor, [23](#)
 - heplot.candisc, [26](#)
 - heplot.candiscList, [29](#)
 - redundancy, [39](#)
 - varOrder, [42](#)
- * **package**
 - candisc-package, [3](#)
- * **utilities**
 - dataIndex, [21](#)
- aspect3d, [28](#)
- can_lm, [17](#)
- cancor, [4](#), [33](#)
- cancor(), [3](#), [4](#), [17](#), [24](#), [40](#), [48](#)
- candisc, [10](#), [28](#), [30](#)
- candisc(), [4](#), [8](#), [16](#), [17](#)
- candisc-package, [3](#)
- candiscList, [15](#), [28](#), [30](#)
- candiscList(), [14](#)
- CCA::cc(), [8](#)
- cereal, [18](#)
- coef.cancor(cancor), [4](#)
- coef.candisc(candisc), [10](#)
- cor_lda, [20](#)
- dataEllipse, [32](#), [33](#)
- dataIndex, [21](#)
- ggbiplot::reflect, [42](#)
- ggplot2::geom_point(), [35](#)
- ggplot2::geom_tile(), [35](#)
- ggplot2::ggplot(), [35](#)
- graphics::arrows(), [46](#), [47](#)
- graphics::segments(), [47](#)
- graphics::text(), [46](#), [47](#)
- Grass, [22](#)
- grDevices::palette(), [12](#)

heplot, 27, 28, 30
heplot.cancor(), 23
heplot.cancor(), 3, 7, 8
heplot.candisc, 26
heplot.candisc(), 3, 23, 45
heplot.candiscList, 29
heplot3d, 27, 28, 30
heplot3d.cancor (heplot.cancor), 23
heplot3d.cancor(), 3
heplot3d.candisc (heplot.candisc), 26
heplot3d.candisc(), 3
heplot3d.candiscList
 (heplot.candiscList), 29
heplots::heplot(), 4, 8, 14, 16
heplots::heplot3d(), 14, 16
HSB, 30

klaR::partimat(), 35

loessLine, 32, 33

MASS::lda(), 20, 21, 37
MASS::qda(), 37
MASS::UScereal, 19

plot.cancor, 31
plot.cancor(), 3, 8
plot.candisc (candisc), 10
plot.candisc(), 3, 41, 45
plot.candiscList (candiscList), 15
plot_discrim, 34
predict_discrim, 36
predict_discrim(), 21
predictor.names, 35
print.cancor (cancor), 4
print.cancor.redundancy (redundancy), 39
print.candisc (candisc), 10
print.candiscList (candiscList), 15
PsyAcad, 38

redundancy, 39
redundancy(), 8
reflect, 41
rgl::lines3d(), 46
rgl::texts3d(), 46

scores (cancor), 4
scores.candisc (candisc), 10
showLabels, 33
stats::cancor(), 8
stats::cor(), 20, 21
stats::cov.wt, 6
summary.cancor (cancor), 4
summary.candisc (candisc), 10
summary.candiscList (candiscList), 15

varOrder, 42
varOrder(), 3
vecscale, 44
vectors, 46
vectors(), 45
vectors3d (vectors), 46

Wilks, 47
Wine, 49
Wolves, 50

yacca::cca(), 8