

Package ‘corrmeta’

October 24, 2025

Title Correlated Meta-Analysis

Version 1.0.1

Maintainer Woo Seok Jung <jungw@wustl.edu>

Description Performs Correlated Meta-Analysis ('corrmeta') across multiple OMIC scans, accounting for hidden non-independencies between elements of the scans due to overlapping samples, related samples, or other information. For more information about the method, refer to the paper Province MA. (2013) <[doi:10.1142/9789814447973_0023](https://doi.org/10.1142/9789814447973_0023)>.

biocViews Genetics, GenomeWideAssociation, SNP, StatisticalMethod, Software

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

VignetteBuilder knitr

LazyData true

Suggests testthat (>= 3.0.0), BiocStyle, knitr, rmarkdown, qpdf

Config/testthat/edition 3

Imports dplyr, polycor, stats, tidyr, magrittr

NeedsCompilation no

Author Woo Seok Jung [aut, cre],
Michael Province [aut, cph]

Depends R (>= 3.5.0)

Repository CRAN

Date/Publication 2025-10-24 21:40:02 UTC

Contents

fishp	2
generate_random_p_values	3
polycorr	3

pvalues_to_zscores	4
snp_example	5
snp_example_missing	5
tetracorr	5
Index	7

fishp	<i>Calculate Fisher's method p-value and meta-analysis statistics</i>
-------	---

Description

Calculate Fisher's method p-value and meta-analysis statistics

Usage

```
fishp(df, vars, df_sigma, sum_sigma)
```

Arguments

- df data frame with "markname" and study names as column names.
- vars character vector of study names to include in the meta-analysis.
- df_sigma data frame of tetrachoric correlations.
- sum_sigma sum of tetrachoric correlations.

Value

A data frame with columns 'markname', 'sum_chisq', 'sum_z', 'sum_sigma_var', 'pvalue', 'meta_z', 'meta_p', 'meta_nlog10p'

Examples

```
data(snp_example)
head(snp_example)
varlist <- c("trt1", "trt2", "trt3")
tc <- tetracorr(snp_example, varlist)
fishp(snp_example, varlist, tc$sigma, tc$sum_sigma)
```

`generate_random_p_values`*Generates a list of random p-values with mixed significant and insignificant values*

Description

Generates a list of random p-values with mixed significant and insignificant values

Usage

```
generate_random_p_values(n, ratio_significant)
```

Arguments

`n` number of samples
`ratio_significant` fraction of p-values to be significant

Value

list of n randomly generated significant and insignificant p-values

`polycorr`*Calculate Polychoric Correlations*

Description

This function calculates the polychoric correlations between pairs of variables in a given data frame. It returns a data frame with the row and column names of the variables, the polychoric correlation coefficient, and its standard error.

Usage

```
polycorr(data, varlist)
```

Arguments

`data` data frame with "markname" and study names as column names.
`varlist` character vector of study names to include in the meta-analysis.

Value

data frame with polychoric correlation coefficients and standard errors

Author(s)

Woo Jung

See Also

[polychor](#)

Examples

```
data(snp_example)
varlist <- c("trt1", "trt2", "trt3")
polycorr(snp_example, varlist)
```

pvalues_to_zscores	<i>Convert P-values to Z-scores</i>
--------------------	-------------------------------------

Description

This function takes a data frame of p-values and converts them to Z-scores using the quantile function for the standard normal distribution.

Usage

```
pvalues_to_zscores(df_pvalues)
```

Arguments

df_pvalues data frame containing p-values

Value

data frame containing Z-scores

Author(s)

Woo Jung

See Also

[qnorm](#)

Examples

```
data(snp_example)
head(snp_example)
pvalues_to_zscores(snp_example)
```

snp_example	<i>Example SNP summary dataset</i>
-------------	------------------------------------

Description

This data set provides 3 simulated 19-sample SNP-trait association p-values

Usage

```
snp_example
```

Format

A dataframe containing 19 observations across 3 SNP scans

snp_example_missing	<i>Example SNP summary dataset with missing values</i>
---------------------	--

Description

This data set provides 3 simulated 19-sample SNP-trait association p-values where some samples are removed to reflect missing values.

Usage

```
snp_example_missing
```

Format

A dataframe containing 19 observations across 3 SNP scans

tetracorr	<i>Calculate Tetrachoric Correlations</i>
-----------	---

Description

This function calculates the tetrachoric correlations between pairs of variables in a given data frame. It returns a list containing a data frame with the tetrachoric correlation coefficients, and the sum of the tetrachoric correlations if the input variable was in p-value form.

Usage

```
tetracorr(data, varlist)
```

Arguments

`data` data frame with "markname" and study names as column names.
`varlist` character vector of study names to include in the meta-analysis.

Value

list containing a data frame with tetrachoric correlation coefficients, and the sum of the tetrachoric correlations if the input variable was in p-value form.

Author(s)

Woo Jung

See Also

[polychor](#)

Examples

```
data(snp_example)
head(snp_example)
varlist <- c("trt1", "trt2", "trt3")
tetracorr(snp_example, varlist)
```

Index

* **datasets**

snp_example, [5](#)

snp_example_missing, [5](#)

fishp, [2](#)

generate_random_p_values, [3](#)

polychor, [4](#), [6](#)

polycorr, [3](#)

pvalues_to_zscores, [4](#)

qnorm, [4](#)

snp_example, [5](#)

snp_example_missing, [5](#)

tetracorr, [5](#)