

# Package ‘emailjsr’

July 22, 2025

**Title** 'emailjs' Support

**Version** 0.0.2

**Maintainer** Changwoo Lim <limcw@zarathu.com>

**Description** Use 'emailjs' API easily in 'R'. This package is not official. <<https://www.emailjs.com/docs/rest-api/send/>>. You can send e-mail with 'emailjs' with function, based on 'httr'. You can also make a 'shiny' ui and server function. It can be used for making feedback form, inquiry, and so on.

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.2.2

**Imports** shiny, shiny.i18n, httr, shinybrowser

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Changwoo Lim [aut, cre] (ORCID:  
<<https://orcid.org/0000-0003-1949-0639>>)

**Repository** CRAN

**Date/Publication** 2022-12-22 20:20:02 UTC

## Contents

send_email . . . . .	2
use_emailjsr_server . . . . .	3
use_emailjsr_ui . . . . .	4
<b>Index</b>	<b>5</b>

---

`send_email`*send\_email*

---

**Description**

Send email using emailjs service.

**Usage**

```
send_email(  
  service_id,  
  user_id,  
  template_id,  
  template_params = list(),  
  access_token = NULL  
)
```

**Arguments**

<code>service_id</code>	emailjs.com Service Id
<code>user_id</code>	emailjs.com User Id or Public Key
<code>template_id</code>	emailjs.com Template Id
<code>template_params</code>	Params passed to emailjs.com. You should set template at emailjs.com in prior.
<code>access_token</code>	emailjs.com Access Token or Private Key. Default is NULL in case of you don't use access token.

**Value**

`response()` Return A `response()` object of `httr`, including response of emailjs server

**Note**

You should allow EmailJS API for non-browser applications.

**Examples**

```
library(emailjsr)  
  
send_email("service_id", "user_id", "template_id", "access_token", list(name = "John Doe"))
```

---

use\_emailjsr\_server    *use\_emailjsr\_server*

---

### Description

emailjs.com R support with preset modal

### Usage

```
use_emailjsr_server(  
  id,  
  service_id,  
  user_id,  
  template_id,  
  access_token,  
  language = "en"  
)
```

### Arguments

id	Should be same to id of use_emailjsr_ui
service_id	emailjs.com Service Id
user_id	emailjs.com User Id
template_id	emailjs.com Template Id
access_token	emailjs.com Access Token
language	Language of modal. "en" for English, and "ko" for Korean.

### Value

No return value, for shiny support

### Examples

```
library(shiny)  
library(emailjsr)  
ui <- fluidPage(  
  use_emailjsr_ui("id")  
)  
  
server <- function(input, output, session) {  
  emailjsr::use_emailjsr_server("id",  
    service_id = "Your_service_id",  
    template_id = "Your_template_id",  
    user_id = "Your_user_id",  
    access_token = "Your_Access-Token",  
    language = "en"  
  )  
}
```

---

use_emailjsr_ui	<i>use_emailjsr_ui</i>
-----------------	------------------------

---

**Description**

emailjs.com R support with preset modal

**Usage**

```
use_emailjsr_ui(id, message = "Show feedback modal")
```

**Arguments**

id	Should be same to id of use_emailjsr_server.
message	Messege on button.

**Value**

No return value, for shiny support

**Examples**

```
library(shiny)
library(emailjsr)
ui <- fluidPage(
  use_emailjsr_ui("id")
)

server <- function(input, output, session) {
  emailjsr::use_emailjsr_server("id",
    service_id = "Your_service_id",
    template_id = "Your_template_id", user_id = "Your_user_id",
    access_token = "Your_Access-Token"
  )
}
```

# Index

`send_email`, 2

`use_emailjsr_server`, 3

`use_emailjsr_ui`, 4