

Package ‘spillR’

July 24, 2025

Type Package

Title Spillover Compensation in Mass Cytometry Data

Version 1.4.0

Description Channel interference in mass cytometry can cause spillover and may result in miscounting of protein markers. We develop a nonparametric finite mixture model and use the mixture components to estimate the probability of spillover. We implement our method using expectation-maximization to fit the mixture model.

biocViews FlowCytometry, ImmunoOncology, MassSpectrometry, Preprocessing, SingleCell, Software, StatisticalMethod, Visualization, Regression

License LGPL-3

Encoding UTF-8

LazyData false

Config/testthat/edition 3

RoxygenNote 7.3.1

Imports dplyr, tibble, tidyselect, stats, ggplot2, tidyr, spatstat.univar, S4Vectors, parallel

Depends R (>= 4.3.0), SummarizedExperiment, CATALYST

Suggests knitr, rmarkdown, cowplot, testthat (>= 3.0.0), BiocStyle, hexbin

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/spillR>

git_branch RELEASE_3_21

git_last_commit b2e6d99

git_last_commit_date 2025-04-15

Repository Bioconductor 3.21

Date/Publication 2025-07-23

Author Marco Guazzini [aut, cre] (ORCID: <https://orcid.org/0009-0007-8111-5772>),
Alexander G. Reisach [aut] (ORCID: <https://orcid.org/0009-0003-5057-6278>),
Sebastian Weichwald [aut] (ORCID: <https://orcid.org/0000-0003-0169-7244>),
Christof Seiler [aut] (ORCID: <https://orcid.org/0000-0001-8802-3642>)
Maintainer Marco Guazzini <m.guazzini@student.maastrichtuniversity.nl>

Contents

compCytot	2
compensate	3
compensate_naive	4
generate_bead	5
generate_real	6
plotDiagnostics	6
tfm	7
Index	8

compCytot	<i>Compute spillover probability and correct for spillover</i>
-----------	--

Description

Compute spillover probability and correct for spillover

Usage

```
compCytot(  
  sce,  
  sce_bead,  
  marker_to_barcode,  
  impute_value,  
  overwrite = FALSE,  
  n_cores = 1,  
  naive = FALSE  
)
```

Arguments

- sce [SingleCellExperiment](#) for the real cells
- sce_bead [SingleCellExperiment](#) for the bead experiment
- marker_to_barcode Table that maps the marker to the barcode in the beads experiment
- impute_value Imputed value for counts that are declared as spillover

overwrite	logical; if TRUE data are overwritten if FALSE data are saved in new columns
n_cores	Number of computing cores
naive	logical; if TRUE use the naive version

Value

A [SingleCellExperiment](#) object

Examples

```
library(CATALYST)
library(dplyr)
bc_key <- c(139, 141:156, 158:176)
sce_bead <- prepData(ss_exp)
sce_bead <- assignPrelim(sce_bead, bc_key, verbose = FALSE)
sce_bead <- applyCutoffs(estCutoffs(sce_bead))
sce_bead <- computeSpillmat(sce_bead)
data(mp_cells, package = "CATALYST")
sce <- prepData(mp_cells)
marker_to_barcode <- rowData(sce_bead)[, c("channel_name", "is_bc")] |>
  as_tibble() |>
  filter(is_bc == TRUE) |>
  mutate(barcode = bc_key) |>
  select(marker = channel_name, barcode)
spillR::compCytof(sce, sce_bead, marker_to_barcode, impute_value = NA)
```

compensate	<i>Compute spillover probability and correct for spillover</i>
------------	--

Description

Compute spillover probability and correct for spillover

Usage

```
compensate(
  tb_real,
  tb_bead,
  target_marker,
  spillover_markers,
  impute_value = NA,
  n_iter = 1000
)
```

Arguments

tb_real	Data frame or tibble with proteins counts of real experiment
tb_bead	Data frame or tibble with proteins counts of bead experiment
target_marker	Marker name in real experiment
spillover_markers	Marker names in bead experiment
impute_value	Value for counts that are declared as spillover
n_iter	Maximum number of EM steps

Value

A list of class <code>spillr</code> containing	
tb_compensate	corrected real cells
tb_spill_prob	probability curve
convergence	covergence table of EM algorithm
tb_real	input real cells
tb_bead	input bead cells
target_marker	input marker in real experiment
spillover_markers	input markers in bead experiment

compensate_naive	<i>Compute spillover probability and correct for spillover from beads only</i>
------------------	--

Description

Compute spillover probability and correct for spillover from beads only

Usage

```
compensate_naive(
  tb_real,
  tb_bead,
  target_marker,
  spillover_markers,
  impute_value = NA
)
```

Arguments

tb_real	Data frame or tibble with proteins counts of real experiment
tb_bead	Data frame or tibble with proteins counts of bead experiment
target_marker	Marker name in real experiment
spillover_markers	Marker names in bead experiment
impute_value	Value for counts that are declared as spillover

Value

A list of class `spillr` containing

tb_compensate	corrected real cells
tb_spill_prob	probability curve
convergence	covergence table of EM algorithm
tb_real	input real cells
tb_bead	input bead cells
target_marker	input marker in real experiment
spillover_markers	input markers in bead experiment

generate_bead	<i>Generate dataset for vignettes and simulation studies</i>
---------------	--

Description

Generate dataset for vignettes and simulation studies

Usage

```
generate_bead()
```

Value

tibble data frame

Examples

```
set.seed(23)
generate_bead()
```

generate_real	<i>Generate dataset for vignettes and simulation studies</i>
---------------	--

Description

Generate dataset for vignettes and simulation studies

Usage

```
generate_real()
```

Value

[tibble](#) data frame

Examples

```
set.seed(23)
generate_real()
```

plotDiagnostics	<i>Compute spillover probability and correct for spillover</i>
-----------------	--

Description

Compute spillover probability and correct for spillover

Usage

```
plotDiagnostics(sce, ch)
```

Arguments

sce	A SingleCellExperiment object
ch	Character string specifying the channel to plot

Value

A list of [ggplot2](#) plots

Examples

```
library(CATALYST)
library(dplyr)
bc_key <- c(139, 141:156, 158:176)
sce_bead <- prepData(ss_exp)
sce_bead <- assignPrelim(sce_bead, bc_key, verbose = FALSE)
sce_bead <- applyCutoffs(estCutoffs(sce_bead))
sce_bead <- computeSpillmat(sce_bead)
data(mp_cells, package = "CATALYST")
sce <- prepData(mp_cells)
marker_to_barcode <- rowData(sce_bead)[, c("channel_name", "is_bc")] |>
  as_tibble() |>
  filter(is_bc == TRUE) |>
  mutate(barcode = bc_key) |>
  select(marker = channel_name, barcode)
sce <- spillR::compCytob(sce, sce_bead, marker_to_barcode, impute_value = NA)
plotDiagnostics(sce, "Yb173Di")
```

tfm	<i>Variance stabilizing transform of counts</i>
-----	---

Description

Variance stabilizing transform of counts

Usage

```
tfm(x)
```

Arguments

x Raw count

Value

A transformed count

Index

compCytotf, [2](#)
compensate, [3](#)
compensate_naive, [4](#)

generate_bead, [5](#)
generate_real, [6](#)
ggplot2, [6](#)

plotDiagnostics, [6](#)

SingleCellExperiment, [2](#), [3](#), [6](#)

tfm, [7](#)
tibble, [5](#), [6](#)