

Package ‘NPARC’

July 23, 2025

Type Package

Title Non-parametric analysis of response curves for thermal proteome profiling experiments

Version 1.21.0

Author Dorothee Childs,
Nils Kurzawa

Maintainer Nils Kurzawa <nilskurzawa@gmail.com>

Description Perform non-parametric analysis of response curves as described by Childs, Bach, Franken et al. (2019): Non-parametric analysis of thermal proteome profiles reveals novel drug-binding proteins.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

Depends R (>= 4.0.0)

Imports dplyr, tidyr, BiocParallel, broom, MASS, rlang, magrittr,
stats, methods

Suggests testthat, devtools, knitr, rprojroot, rmarkdown, ggplot2,
BiocStyle

VignetteBuilder knitr

biocViews Software, Proteomics

git_url <https://git.bioconductor.org/packages/NPARC>

git_branch devel

git_last_commit ca8e4e0

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-07-22

Contents

fitSingleSigmoid	2
getParams	3
NPARC	3

NPARCfit	4
NPARCtest	5
runNPARC	5
stauro_TPP_data_tidy	6
Index	8

fitSingleSigmoid	<i>Fit sigmoid model</i>
------------------	--------------------------

Description

Fit sigmoid model

Usage

```
fitSingleSigmoid(x, y, start = c(Pl = 0, a = 550, b = 10))
```

Arguments

x	numeric vector of the independent variables (typically temperature)
y	numeric vector of the dependent variables (typically relative abundance measurements)
start	numeric vector of start parameters for the melting curve equation

Details

Fits the following function to the data: $y = (1 - Pl)/(1 + \exp((b - a/x))) + Pl$

Value

model summary of type "nls"

Examples

```
data(stauro_TPP_data_tidy)
stk4 <- dplyr::filter(stauro_TPP_data_tidy, grepl("STK4", uniqueID))
fitSingleSigmoid(stk4$temperature, stk4$relAbundance)
```

`getParams`*Control parameters for model fitting*

Description

Control parameters for model fitting

Usage

```
getParams(start = c(P1 = 0, a = 550, b = 10), maxAttempts = 100)
```

Arguments

<code>start</code>	Numeric vector of start parameters for the melting curve equation
<code>maxAttempts</code>	Number of resampling steps in case of unsuccessful model fits

Value

list of two elements: 1) "start" listing the starting parameters for melting curve fitting, 2) "maxAttempts" listing the maximal number of attempts the fit should be allowed

Examples

```
data(stauro_TPP_data_tidy)
df <- dplyr::filter(stauro_TPP_data_tidy, grepl("MAPK|ATP|CDK|GTP|CRK", uniqueID))
testResults <- runNPARC(x = df$temperature,
  y = df$relAbundance,
  id = df$uniqueID,
  groupsAlt = df$compoundConcentration,
  dfType = "empirical",
  control = getParams(maxAttempts = 50))
```

`NPARC`*NPARC package*

Description

Non-parametric analysis of response curves

Details

See the preprint on [Childs, Bach, Franken et al. \(2019\): Non-parametric analysis of thermal proteome profiles reveals novel drug-binding proteins](#)

NPARCtest

*Perform F-test***Description**

Perform F-test

Usage

```
NPARCtest(modelMetrics, dfType = c("empirical", "theoretical"))
```

Arguments

modelMetrics data.frame with results of the model fit in long format.

dfType character value indicating the method for degrees of freedom computation for the F-test. Theoretical yields the text-book solution. Empirical yields estimates derived from the distribution moments of the RSS.

Value

data frame with fitted model parameters and additional columns listing e.g. residuals sum of squares of null and alterantive model and raw and adjusted p values retrieved from testing

Examples

```
data(stauro_TPP_data_tidy)
df <- dplyr::filter(stauro_TPP_data_tidy, grepl("CDK|GTP|CRK", uniqueID))
fits <- NPARCfit(x = df$temperature,
                y = df$relAbundance,
                id = df$uniqueID,
                groupsNull = NULL,
                groupsAlt = df$compoundConcentration,
                returnModels = FALSE)
modelMetrics <- fits$metrics
testRes <- NPARCtest(modelMetrics, dfType = "theoretical")
```

runNPARC

*Non-parametric analysis of response curves***Description**

Wrapper function for melting curve fitting and hypothesis testing.

Usage

```
runNPARC(x, y, id, groupsNull = NULL, groupsAlt,
        BPPARAM = BiocParallel::SerialParam(progressbar = TRUE),
        dfType = c("theoretical", "empirical"), control = getParams())
```

Arguments

<code>x</code>	numeric vector of the independent variables (typically temperature)
<code>y</code>	numeric vector of the dependent variables (typically relative abundance measurements)
<code>id</code>	character vector with the protein ID to which each data point belongs.
<code>groupsNull</code>	one or more vectors with grouping variables for the null models. See details.
<code>groupsAlt</code>	one or more vectors with grouping variables for the alternative models. See details.
<code>BPPARAM</code>	BiocParallel parameter object to invoke curve fitting in parallel. Default: <code>BiocParallel::SerialParam()</code>
<code>dfType</code>	character value indicating the method for degrees of freedom computation for the F-test. Theoretical yields the text-book solution. Empirical yields estimates derived from the distribution moments of the RSS.
<code>control</code>	list of parameters used to control specific parts of the analyse

Details

`groupsNull` or `groupsAlt` can either be a single vector each, or data.frames of the same length as `x` and `y` with one column per factor

Value

data frame with fitted model parameters and additional columns listing e.g. residuals sum of squares of null and alterantive model

Examples

```
data(stauro_TPP_data_tidy)
df <- dplyr::filter(stauro_TPP_data_tidy, grepl("CDK|GTP|CRK", uniqueID))
testResults <- runNPARC(x = df$temperature,
  y = df$relAbundance,
  id = df$uniqueID,
  groupsAlt = df$compoundConcentration,
  dfType = "empirical")
```

`stauro_TPP_data_tidy` *TPP dataset of staurosporine treated cells.*

Description

Data from a thermal proteome profiling (TPP) experiment investigating the ATP-competitive pan-kinase inhibitor staurosporine on K562 cells. The data has been downloaded the data from the supplement of the respective publication and converted into tidy format.

Usage

```
data(stauro_TPP_data_tidy)
```

Format

An object of class "data.frame"

References

Savitski et al. (2014): Tracking cancer drugs in living cells by thermal profiling of the proteome. Science 346, 1255784.

Index

* **datasets**

stauro_TPP_data_tidy, [6](#)

fitSingleSigmoid, [2](#)

getParams, [3](#)

NPARC, [3](#)

NPARC-package (NPARC), [3](#)

NPARCfit, [4](#)

NPARCtest, [5](#)

runNPARC, [5](#)

stauro_TPP_data_tidy, [6](#)