

# Package ‘NetPathMiner’

May 16, 2026

**Version** 1.49.0

**Date** 2014 onwards

**Title** NetPathMiner for Biological Network Construction, Path Mining and Visualization

**Description** NetPathMiner is a general framework for network path mining using genome-scale networks. It constructs networks from KGML, SBML and BioPAX files, providing three network representations, metabolic, reaction and gene representations. NetPathMiner finds active paths and applies machine learning methods to summarize found paths for easy interpretation. It also provides static and interactive visualizations of networks and paths to aid manual investigation.

**Depends** R (>= 3.0.2), igraph (>= 1.0)

**Suggests** rBiopaxParser (>= 2.1), RCurl, graph, knitr, rmarkdown, BiocStyle

**VignetteBuilder** knitr

**License** GPL (>= 2)

**URL** <https://github.com/ahmohamed/NetPathMiner>

**NeedsCompilation** yes

**SystemRequirements** libxml2, libSBML (>= 5.5)

**Biarch** TRUE

**biocViews** GraphAndNetwork, Pathways, Network, Clustering, Classification

**RoxygenNote** 7.2.3

**Encoding** UTF-8

**git\_url** <https://git.bioconductor.org/packages/NetPathMiner>

**git\_branch** devel

**git\_last\_commit** 3bff68e

**git\_last\_commit\_date** 2026-04-28

**Repository** Bioconductor 3.24

**Date/Publication** 2026-05-15

**Author** Ahmed Mohamed [aut, cre] (ORCID:  
 <<https://orcid.org/0000-0001-6507-5300>>),  
 Tim Hancock [aut],  
 Tim Hancock [aut]

**Maintainer** Ahmed Mohamed <mohamed@kuicr.kyoto-u.ac.jp>

## Contents

NetPathMiner-package . . . . .	3
assignEdgeWeights . . . . .	3
biopax2igraph . . . . .	5
colorVertexByAttr . . . . .	6
expandComplexes . . . . .	7
extractPathNetwork . . . . .	8
ex_biopax . . . . .	9
ex_kgml_sig . . . . .	10
ex_microarray . . . . .	10
ex_sbml . . . . .	10
getAttrStatus . . . . .	11
getGeneSetNetworks . . . . .	12
getGeneSets . . . . .	13
getPathsAsEIDs . . . . .	14
KGML2igraph . . . . .	15
layoutVertexByAttr . . . . .	16
makeMetaboliteNetwork . . . . .	17
makeReactionNetwork . . . . .	18
NPMdefaults . . . . .	19
pathClassifier . . . . .	20
pathCluster . . . . .	22
pathRanker . . . . .	23
pathsToBinary . . . . .	25
plotAllNetworks . . . . .	26
plotClassifierROC . . . . .	28
plotClusterMatrix . . . . .	28
plotCytoscapeGML . . . . .	30
plotNetwork . . . . .	32
plotPathClassifier . . . . .	33
plotPathCluster . . . . .	34
plotPaths . . . . .	35
predictPathClassifier . . . . .	37
predictPathCluster . . . . .	38
registerMemoryErr . . . . .	39
reindexNetwork . . . . .	40
rmSmallCompounds . . . . .	41
SBML2igraph . . . . .	42
simplifyReactionNetwork . . . . .	44
stdAttrNames . . . . .	45
toGraphNEL . . . . .	46
vertexDeleteReconnect . . . . .	47

**Index**

**48**

---

NetPathMiner-package    *General framework for network extraction, path mining.*

---

### Description

NetPathMiner implements a flexible module-based process flow for network path mining and visualization, which can be fully inte-grated with user-customized functions. NetPathMiner supports construction of various types of genome scale networks from KGML, SBML and BioPAX formats, enabling its utility to most common pathway databases. NetPathMiner also provides different visualization techniques to facilitate the analysis of even thousands of output paths.

### Author(s)

Ahmed Mohamed <mohamed@kuicr.kyoto-u.ac.jp>

---

assignEdgeWeights    *Assigning weights to network edges*

---

### Description

This function computes edge weights based on a gene expression profile.

### Usage

```
assignEdgeWeights(
  microarray,
  graph,
  use.attr,
  y,
  weight.method = "cor",
  complex.method = "max",
  missing.method = "median",
  same.gene.penalty = "median",
  bootstrap = 100,
  verbose = TRUE
)
```

### Arguments

microarray	Microarray should be a Dataframe or a matrix, with genes as rownames, and samples as columns.
graph	An annotated igraph object.
use.attr	An attribute name to map microarray rows (genes) to graph vertices. The attribute must be annotated in graph, and the values correspond to rownames of microarray. You can check the coverage and if there are complex vertices using <a href="#">getAttrStatus</a> . You can eliminate complexes using <a href="#">expandComplexes</a> .
y	Sample labels, given as a factor or a character vector. This must be the same size as the columns of microarray

<code>weight.method</code>	A function, or a string indicating the name of the function to be used to compute the edge weights. The function is provided with 2 numerical vectors (2 rows from microarray), and it should return a single numerical value (or NA). The default computes Pearson's correlation.
<code>complex.method</code>	A function, or a string indicating the name of the function to be used in weighting edges connecting complexes. If a vertex has >1 attribute value, all possible pairwise weights are first computed, and given to <code>complex.method</code> . The default function is <code>max</code> .
<code>missing.method</code>	A function, or a string indicating the name of the function to be used in weighting edges when one of the vertices lack expression data. The function is passed all edge weights on the graph. Default is <code>median</code> .
<code>same.gene.penalty</code>	A numerical value to be assigned when 2 adjacent vertices have the same attribute value, since correlation and similarity measure will give perfect scores. Alternatively, <code>same.gene.penalty</code> can be a function, computing the penalty from all edge weights on the graph (excluding same-gene and missing values). The default is to take the <code>median</code>
<code>bootstrap</code>	An integer n, where the <code>weight.method</code> is performed on n permutations of the gene profiles, and taking the median value. Set it to NA to disable bootstrapping.
<code>verbose</code>	Print the progress of the function.

**Value**

The input graph with `edge.weight` as an edge attribute. The attribute can be a list of weights if y labels were provided.

**Author(s)**

Ahmed Mohamed

**Examples**

```
## Convert a metabolic network to a reaction network.
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)

## Assign edge weights based on Affymetrix attributes and microarray dataset.
# Calculate Pearson's correlation.
data(ex_microarray) # Part of ALL dataset.
rgraph <- assignEdgeWeights(microarray = ex_microarray, graph = rgraph,
  weight.method = "cor", use.attr="miriam.uniprot",
  y=factor(colnames(ex_microarray)), bootstrap = FALSE)

# Using Spearman correlation, assigning missing edges to -1
## Not run:
  assignEdgeWeights(microarray, graph, use.attr="miriam.affy.probeset",
    y=factor(colnames(microarray)),
    weight.method = function(x1,x2) cor(x1,x2, method="spearman"),
    missing.method = -1)

## End(Not run)
```

---

`biopax2igraph`*Processes BioPAX objects into igraph objects*

---

### Description

This function takes BioPAX objects (level 2 or 3) as input, and returns either a metabolic or a signaling network as output.

### Usage

```
biopax2igraph(  
  biopax,  
  parse.as = c("metabolic", "signaling"),  
  expand.complexes = FALSE,  
  inc.sm.molecules = FALSE,  
  verbose = TRUE  
)
```

### Arguments

<code>biopax</code>	BioPAX object generated by <a href="#">readBiopax</a> .
<code>parse.as</code>	Whether to process file into a metabolic or a signaling network.
<code>expand.complexes</code>	Split protein complexes into individual gene nodes. Ignored if <code>parse.as="metabolic"</code> .
<code>inc.sm.molecules</code>	Include small molecules that are participating in signaling events. Ignored if <code>parse.as="metabolic"</code> .
<code>verbose</code>	Whether to display the progress of the function.

### Details

This function requires `rBiopaxParser` installed.

Users can specify whether files are processes as metabolic or signaling networks.

Metabolic networks are given as bipartite graphs, where metabolites and reactions represent vertex types. Reactions are constructed from `Conversion` classes, connecting them to their corresponding `Lefts` and `Rights`. Each reaction vertex has `genes` attribute, listing all `Catalysis` relationships of this reaction. As a general rule, reactions inherit all annotation attributes of its catalyzing genes.

Signaling network have `genes` as vertices and edges represent interactions, such as activation / inhibition. Genes participating in successive reactions are also connected. Signaling interactions are constructed from `Control` classes, where edges are drawn from controller to controlled.

All annotation attributes are extracted from XRefs associated with the vertices, and are stored according to MIRIAM guidelines (`miraim.db`, where `db` is the database name).

### Value

An igraph object, representing a metabolic or a signaling network.

### Author(s)

Ahmed Mohamed

**See Also**

Other Database extraction methods: [KGML2igraph\(\)](#), [SBML2igraph\(\)](#)

**Examples**

```
if(requireNamespace("rBiopaxParser")){
  data(ex_biopax)
  # Process biopax as a metabolic network
  g <- biopax2igraph(ex_biopax)
  plotNetwork(g)

  # Process SBML file as a signaling network
  g <- biopax2igraph(ex_biopax, parse.as="signaling", expand.complexes=TRUE)
}
```

---

colorVertexByAttr      *Computes colors for vertices according to their attributes.*

---

**Description**

This function returns a list of colors for vertices, assigned similar colors if they share a common attribute (ex: in the same pathway, etc).

**Usage**

```
colorVertexByAttr(graph, attr.name, col.palette = palette())
```

**Arguments**

graph	An annotated igraph object.
attr.name	The attribute name (ex: "pathway") by which vertices will be colored. Complex attributes, where a vertex belongs to more than one group, are supported.
col.palette	A color palette, or a palette generating function (ex: col.palette=rainbow ).

**Value**

A list of colors (in HEX format) for vertices.

**Author(s)**

Ahmed Mohamed

**See Also**

Other Plotting methods: [layoutVertexByAttr\(\)](#), [plotAllNetworks\(\)](#), [plotClassifierROC\(\)](#), [plotClusterMatrix\(\)](#), [plotCytoscapeGML\(\)](#), [plotNetwork\(\)](#), [plotPathClassifier\(\)](#), [plotPaths\(\)](#)

**Examples**

```
data("ex_kgml_sig")
v.colors <- colorVertexByAttr(ex_kgml_sig, "pathway")
plotNetwork(ex_kgml_sig, vertex.color=v.colors)
```

---

expandComplexes

*Expand reactions / complexes into their gene constituents.*


---

**Description**

These are general functions to expand vertices by their attributes, i.e. create a separate vertex for each attribute value.

**Usage**

```
expandComplexes(
  graph,
  v.attr,
  keep.parent.attr = "^pathway",
  expansion.method = c("normal", "duplicate"),
  missing.method = c("keep", "remove", "reconnect")
)

makeGeneNetwork(
  graph,
  v.attr = "genes",
  keep.parent.attr = "^pathway",
  expansion.method = "duplicate",
  missing.method = "remove"
)
```

**Arguments**

graph	An annotated igraph object.
v.attr	Name of the attribute which vertices are expanded to.
keep.parent.attr	A (List of) <a href="#">regex</a> expressions representing attributes to be inherited by daughter vertices. If "all" is passed, all parent attributes are inherited.
expansion.method	If "duplicate", attribute values sharing more than one parent vertex are duplicated for each vertex they participate in. For example, if one gene G1 catalyzes reactions R1, R2; then G1##R1, and G1##R2 vertices are created. If "normal" only one vertex (G1) is created, and inherit all R1 and R2 connections and attributes.
missing.method	How to deal with vertices with no attribute values. "keep" retains the parent node, "remove" simply deletes the vertex, and "reconnect" removes the vertex and connect its neighbours to each other (to prevent graph cuts).

## Details

These functions can be very useful when merging networks constructed from different databases. For example, to match a network created from Reactome to a KEGG network, you can expand metabolite vertices by "miriam.kegg.compound" attribute.

## Value

A new graph with vertices expanded.

makeGeneNetwork returns a graph, where nodes are genes, and edges represent participation in successive reactions.

## Author(s)

Ahmed Mohamed

## See Also

Other Network processing methods: [makeMetaboliteNetwork\(\)](#), [makeReactionNetwork\(\)](#), [reindexNetwork\(\)](#), [rmSmallCompounds\(\)](#), [simplifyReactionNetwork\(\)](#), [vertexDeleteReconnect\(\)](#)

## Examples

```
## Make a gene network from a reaction network.
data(ex_sbml) # A bipartite metabolic network.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)
ggraph <- makeGeneNetwork(rgraph)

## Expand vertices into their constituent genes.
data(ex_kgml_sig) # Ras and chemokine signaling pathways in human
ggraph <- expandComplexes(ex_kgml_sig, v.attr = "miriam.ncbigene",
  keep.parent.attr= c("^pathway", "^compartment"))

## Create a separate vertex for each compartment. This is useful in duplicating
## metabolite vertices in a network.
## Not run:
graph <- expandComplexes(graph, v.attr = "compartment",
  keep.parent.attr = "all",
  expansion.method = "duplicate",
  missing.method = "keep")

## End(Not run)
```

---

extractPathNetwork      *Creates a subnetwork from a ranked path list*

---

## Description

Creates a subnetwork from a ranked path list generated by [pathRanker](#).

## Usage

```
extractPathNetwork(paths, graph)
```

**Arguments**

paths            The paths extracted by [pathRanker](#).  
graph            A annotated igraph object.

**Value**

A subnetwork from all paths provided. If paths are computed for several labels (sample categories), a subnetwork is returned for each label.

**Author(s)**

Ahmed Mohamed

**See Also**

Other Path ranking methods: [getPathsAsEIDs\(\)](#), [pathRanker\(\)](#)

**Examples**

```
## Prepare a weighted reaction network.  
## Conver a metabolic network to a reaction network.  
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.  
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)  
  
## Assign edge weights based on Affymetrix attributes and microarray dataset.  
# Calculate Pearson's correlation.  
data(ex_microarray) # Part of ALL dataset.  
rgraph <- assignEdgeWeights(microarray = ex_microarray, graph = rgraph,  
  weight.method = "cor", use.attr="miriam.uniprot",  
  y=factor(colnames(ex_microarray)), bootstrap = FALSE)  
  
## Get ranked paths using probabilistic shortest paths.  
ranked.p <- pathRanker(rgraph, method="prob.shortest.path",  
  K=20, minPathSize=6)  
  
## Get the subnetwork of paths in reaction graph.  
reaction.sub <- getPathsAsEIDs(ranked.p, rgraph)  
  
## Get the subnetwork of paths in the original metabolic graph.  
metabolic.sub <- getPathsAsEIDs(ranked.p, ex_sbml)
```

---

ex\_biopax

*Biopax example data*

---

**Description**

A dataset containing Porphyrin metabolism pathway in Biopax Level 3 and parsed with [readBiopax](#).

**Examples**

```
data(ex_biopax)  
ex_biopax
```

---

`ex_kgml_sig`*Singaling network from KGML example*

---

**Description**

An example igraph object representing Ras and chemokine signaling pathways in human extracted from KGML files.

**Examples**

```
data(ex_kgml_sig)
plotNetwork(ex_kgml_sig, vertex.color="pathway")
```

---

`ex_microarray`*An microarray data example.*

---

**Description**

An microarray data example. This is part of the ALL dataset, for demonstration purposes.

**Examples**

```
data(ex_microarray)
```

---

`ex_sbml`*Metabolic network from SBML example*

---

**Description**

An example igraph object representing bipartite metabolic network of Carbohydrate metabolism extracted from SBML file from Reactome database.

**Examples**

```
data(ex_sbml)
plotNetwork(ex_sbml, vertex.color="compartment.name")
```

---

getAttrStatus	<i>Get / Set vertex attribute names and coverage</i>
---------------	--

---

### Description

These functions report the annotation status of the vertices of a given network, modify or remove certain annotations.

### Usage

```
getAttrStatus(graph, pattern = "^miriam.")  
  
getAttrNames(graph, pattern = "")  
  
getAttribute(graph, attr.name)  
  
setAttribute(graph, attr.name, attr.value)  
  
rmAttribute(graph, attr.name)
```

### Arguments

graph	An annotated igraph object.
pattern	A <a href="#">regex</a> expression representing attribute name pattern.
attr.name	The attribute name
attr.value	A list of attribute values. This must be the same size as the number of vertices.

### Details

NetPathMiner stores all its vertex annotation attributes in a list, and stores them collectively as a single attr. This is not to interfere with [graph\\_attr\\_names](#) from igraph package. All functions here target NetPathMiner annotations only.

### Value

For `getAttrStatus`, a dataframe summarizing the number of vertices with no (missing), one (single) or more than one (complex) attribute value. The coverage

For `getAttrNames`, a character vector of attribute names matching the pattern.

For `getAttribute`, a list of vertex annotation values for the query attribute.

For `setAttribute`, a graph with the new attribute set.

For `rmAttrNames`, a new igraph object with the attribute removed.

### Author(s)

Ahmed Mohamed

### See Also

Other Attribute handling methods: [stdAttrNames\(\)](#)

**Examples**

```

data(ex_kgml_sig) # Ras and chemokine signaling pathways in human

# Get status of attribute "pathway" only
getAttrStatus(ex_kgml_sig, "^pathway$")

# Get status of all attributes starting with "pathway" and "miriam" keywords
getAttrStatus(ex_kgml_sig, "(^miriam)|(^pathway)")

# Get all attribute names containing "miriam"
getAttrNames(ex_kgml_sig, "miriam")
# Get all attribute names containing "miriam"
getAttribute(ex_kgml_sig, "miriam.ncbigene")

# Remove an attribute from graph
graph <- rmAttribute(ex_kgml_sig, "miriam.ncbigene")

```

---

getGeneSetNetworks      *Generate geneset networks from an annotated network.*

---

**Description**

This function generates geneset networks based on a given network, by grouping vertices sharing common attributes (in the same pathway or compartment).

**Usage**

```

getGeneSetNetworks(
  graph,
  use.attr = "pathway",
  format = c("list", "pathway-class")
)

```

**Arguments**

graph	An annotated igraph object..
use.attr	The attribute by which vertices are grouped (typically pathway, or GO)
format	The output format. If "list" is specified, a list of subgraphs are returned (default). If "pathway-class" is specified, a list of pathway-class objects are returned. Pathway-class is used by graphite package to run several methods of topology-based enrichment analyses.

**Value**

A list of geneset networks as igraph or Pathway-class objects.

**Author(s)**

Ahmed Mohamed

**See Also**

[getGeneSets](#)

**Examples**

```

data(ex_kgml_sig) # Ras and chemokine signaling pathways in human
genesetnets <- getGeneSetNetworks(ex_kgml_sig, use.attr="pathway")

# Integration with graphite package
## Not run:
if(requireNamespace("graphite") & requireNamespace("clipper") & requireNamespace("ALL")){
genesetnets <- getGeneSetNetworks(ex_kgml_sig,
  use.attr="pathway", format="pathway-class")
path <- convertIdentifiers(genesetnets$`Chemokine signaling pathway`,
  "entrez")
genes <- nodes(path)
data(ALL)
all <- as.matrix(exprs(ALL[1:length(genes),1:20]))
classes <- c(rep(1,10), rep(2,10))
rownames(all) <- genes

runClipper(path, all, classes, "mean", pathThr=0.1)
}

## End(Not run)

```

---

getGeneSets

*Generate genesets from an annotated network.*


---

**Description**

This function generates genesets based on a given network, by grouping vertices sharing common attributes (in the same pathway or compartment). Genes associated with each vertex can be specified through `gene.attr` argument.

**Usage**

```
getGeneSets(graph, use.attr = "pathway", gene.attr = "genes", gmt.file)
```

**Arguments**

<code>graph</code>	An annotated igraph object..
<code>use.attr</code>	The attribute by which vertices are grouped (typically pathway, or GO)
<code>gene.attr</code>	The attribute listing genes annotated with each vertex (ex: <code>miriam.ncbigene</code> , <code>miriam.uniprot</code> , ...)
<code>gmt.file</code>	Optinal. If provided, Results are exported to a GMT file. GMT files are readily used by most gene set analysis packages.

**Value**

A list of genesets or written to gmt file if provided.

**Author(s)**

Ahmed Mohamed

**See Also**

[getGeneSetNetworks](#)

**Examples**

```
data(ex_kgml_sig) # Ras and chemokine signaling pathways in human
genesets <- getGeneSets(ex_kgml_sig, use.attr="pathway", gene.attr="miriam.ncbigene")

# Write the genesets in a GMT file, and read it using GSEABase package.
getGeneSets(ex_kgml_sig, use.attr="pathway", gene.attr="miriam.ncbigene", gmt.file="kgml.gmt")
## Not run:
if(requireNamespace("GSEABase"))
  toGmt("kgml.gmt")

## End(Not run)

# Create genesets using compartment information
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
genesets <- getGeneSets(ex_sbml, use.attr="compartment.name", gene.attr="miriam.uniprot")
```

---

getPathsAsEIDs

*Convert a ranked path list to edge ids of a graph*

---

**Description**

Convert a ranked path list to Edge ids of a graph, where paths can come from a different representation (for example matching path from a reaction network to edges on a metabolic network).

**Usage**

```
getPathsAsEIDs(paths, graph)
```

**Arguments**

paths            The paths extracted by [pathRanker](#).

graph            A annotated igraph object.

**Value**

A list of edge ids on the provided graph.

**Author(s)**

Ahmed Mohamed

**See Also**

Other Path ranking methods: [extractPathNetwork\(\)](#), [pathRanker\(\)](#)

**Examples**

```

## Prepare a weighted reaction network.
## Conver a metabolic network to a reaction network.
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)

## Assign edge weights based on Affymetrix attributes and microarray dataset.
# Calculate Pearson's correlation.
data(ex_microarray) # Part of ALL dataset.
rgraph <- assignEdgeWeights(microarray = ex_microarray, graph = rgraph,
  weight.method = "cor", use.attr="miriam.uniprot",
  y=factor(colnames(ex_microarray)), bootstrap = FALSE)

## Get ranked paths using probabilistic shortest paths.
ranked.p <- pathRanker(rgraph, method="prob.shortest.path",
  K=20, minPathSize=6)

## Get the edge ids along paths in the reaction graph.
path.eids <- getPathsAsEIDs(ranked.p, rgraph)

## Get the edge ids along paths in the original metabolic graph.
path.eids <- getPathsAsEIDs(ranked.p, ex_sbml)

```

---

 KGML2igraph

*Processes KGML files into igraph objects*


---

**Description**

This function takes KGML files as input, and returns either a metabolic or a signaling network as output.

**Usage**

```

KGML2igraph(
  filename,
  parse.as = c("metabolic", "signaling"),
  expand.complexes = FALSE,
  verbose = TRUE
)

```

**Arguments**

filename	A character vector containing the KGML files to be processed. If a directory path is provided, all *.xml files in it and its subdirectories are included.
parse.as	Whether to process file into a metabolic or a signaling network.
expand.complexes	Split protein complexes into individual gene nodes. This argument is ignored if parse.as="metabolic"
verbose	Whether to display the progress of the function.

**Details**

Users can specify whether files are processes as metabolic or signaling networks.

Metabolic networks are given as bipartite graphs, where metabolites and reactions represent vertex types. This is constructed from <reaction> xml node in KGML file, connecting them to their corresponding substrates and products. Each reaction vertex has genes attribute, listing all genes associated with the reaction. As a general rule, reactions inherit all annotation attributes of its catalyzing genes.

Signaling network have genes as vertices and edges represent interactions, such as activation / inhibition. Genes participating in successive reactions are also connected. Signaling parsing method processes <ECrel>, <PPrel> and <PCrel> interactions from KGML files.

To generate a genome scale network, simply provide a list of files to be parsed, or put all file in a directory, as pass the directory path as filename

**Value**

An igraph object, representing a metabolic or a signaling network.

**Author(s)**

Ahmed Mohamed

**See Also**

Other Database extraction methods: [SBML2igraph\(\)](#), [biopax2igraph\(\)](#)

**Examples**

```
if(is.loaded("readkgmlfile")){ # This is false if libxml2 wasn't available at installation.
  filename <- system.file("extdata", "hsa00860.xml", package="NetPathMiner")

  # Process KGML file as a metabolic network
  g <- KGML2igraph(filename)
  plotNetwork(g)

  # Process KGML file as a signaling network
  g <- KGML2igraph(filename, parse.as="signaling", expand.complexes=TRUE)
  plotNetwork(g)
}
```

---

layoutVertexByAttr     *A graph layout function, which groups vertices by attribute.*

---

**Description**

This function generates a layout for igraph objects, keeping vertices with the same attribute (ex: in the same pathway, etc) close to each other.

**Usage**

```
layoutVertexByAttr(  
  graph,  
  attr.name,  
  cluster.strength = 1,  
  layout = layout.auto  
)
```

**Arguments**

graph	An annotated igraph object.
attr.name	The attribute name by which vertices are laid out.
cluster.strength	A number indicating tie strengths between vertices with the same attribute. The larger it is, the closer the vertices will be.
layout	A layout function, ideally a force-directed layout function, such as <a href="#">layout_with_fr</a> and <a href="#">layout_with_kk</a> .

**Value**

A two-column matrix indicating the x and y positions of vertices.

**Author(s)**

Ahmed Mohamed

**See Also**

Other Plotting methods: [colorVertexByAttr\(\)](#), [plotAllNetworks\(\)](#), [plotClassifierROC\(\)](#), [plotClusterMatrix\(\)](#), [plotCytoscapeGML\(\)](#), [plotNetwork\(\)](#), [plotPathClassifier\(\)](#), [plotPaths\(\)](#)

**Examples**

```
data("ex_kgml_sig")  
v.layout <- layoutVertexByAttr(ex_kgml_sig, "pathway")  
plotNetwork(ex_kgml_sig, vertex.color="pathway", layout=v.layout)  
  
v.layout <- layoutVertexByAttr(ex_kgml_sig, "pathway", cluster.strength=5)  
plotNetwork(ex_kgml_sig, vertex.color="pathway", layout=v.layout)
```

---

makeMetaboliteNetwork *Convert metabolic network to metabolite network.*

---

**Description**

This function removes reaction nodes keeping them as edge attributes. The resulting network contains metabolite nodes only, where edges indicate that reaction conversions.

**Usage**

```
makeMetaboliteNetwork(graph)
```

**Arguments**

graph            A metabolic network.

**Value**

A reaction network.

**Author(s)**

Ahmed Mohamed

**See Also**

Other Network processing methods: [expandComplexes\(\)](#), [makeReactionNetwork\(\)](#), [reindexNetwork\(\)](#), [rmSmallCompounds\(\)](#), [simplifyReactionNetwork\(\)](#), [vertexDeleteReconnect\(\)](#)

**Examples**

```
## Conver a metabolic network to a metbolite network.
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
mgraph <- makeMetaboliteNetwork(ex_sbml)
```

---

makeReactionNetwork    *Convert metabolic network to reaction network.*

---

**Description**

This function removes metabolite nodes keeping them as edge attributes. The resulting network contains reaction nodes only, where edges indicate that a metabolite produced by one reaction is consumed by the other.

**Usage**

```
makeReactionNetwork(graph, simplify = FALSE)
```

**Arguments**

graph            A metabolic network.

simplify        An option to remove translocation and spontaneous reactions that require no catalyzing genes. Translocation reactions are detected from reaction name (SBML, BioPAX), or by having identical substrates and products.

**Value**

A reaction network.

**Author(s)**

Ahmed Mohamed

**See Also**

Other Network processing methods: [expandComplexes\(\)](#), [makeMetaboliteNetwork\(\)](#), [reindexNetwork\(\)](#), [rmSmallCompounds\(\)](#), [simplifyReactionNetwork\(\)](#), [vertexDeleteReconnect\(\)](#)

**Examples**

```
## Conver a metabolic network to a reaction network.
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)
```

---

NPMdefaults

*Default values for NetPathMiner*

---

**Description**

This function gets a NetPathMiner default value for a variable.

**Usage**

```
NPMdefaults(value)
```

**Arguments**

value            a character string indicating the variable name.

**Details**

NetPathMiner defines the following defaults:

- small.comp.ls Dataframe of ubiquitous metabolites. Used by [rmSmallCompounds](#).
- bridge Dataframe of attributes supported by Brigde Database. Used by [fetchAttribute](#).
- bridge.organisms A list of bridge supported organisms. Used by [fetchAttribute](#).
- bridge.web The base URL for Brigde Database webservices. Used by [fetchAttribute](#).

**Value**

The default value for the given variable.

**Author(s)**

Ahmed Mohamed

**Examples**

```
# Get the default list of small compounds (uniquitous metabolites).
NPMdefaults("small.comp.ls")
```

---

pathClassifier                    *HME3M Markov pathway classifier.*

---

### Description

HME3M Markov pathway classifier.

### Usage

```
pathClassifier(
  paths,
  target.class,
  M,
  alpha = 1,
  lambda = 2,
  hme3miter = 100,
  plriter = 1,
  init = "random"
)
```

### Arguments

paths	The training paths computed by <a href="#">pathsToBinary</a>
target.class	he label of the targe class to be classified. This label must be present as a label within the paths\%\$y object
M	Number of components within the paths to be extracted.
alpha	The PLR learning rate. (between 0 and 1).
lambda	The PLR regularization parameter. (between 0 and 2)
hme3miter	Maximum number of HME3M iterations. It will stop when likelihood change is < 0.001.
plriter	Maximum number of PLR interactions. It will stop when likelihood change is < 0.001.
init	Specify whether to initialize the HME3M responsibilities with the 3M model - random is recommended.

### Details

Take care with selection of lambda and alpha - make sure you check that the likelihood is always increasing.

### Value

A list with the following elements. A list with the following values

h	A dataframe with the EM responsibilities.
theta	A dataframe with the Markov parameters for each component.
beta	A dataframe with the PLR coefficients for each component.
proportions	The probability of each HME3M component.

posterior.probs	The HME3M posterior probability.
likelihood	The likelihood convergence history.
plrplr	The posterior predictions from each components PLR model.
path.probabilities	The 3M probabilities for each path belonging to each component.
params	The parameters used to build the model.
y	The binary response variable used by HME3M. A 1 indicates the location of the target.class labels in paths\\$\$y
perf	The training set ROC curve AUC.
label	The HME3M predicted label for each path.
component	The HME3M component assignment for each path.

**Author(s)**

Timothy Hancock and Ichigaku Takigawa

**References**

Hancock, Timothy, and Mamitsuka, Hiroshi: A Markov Classification Model for Metabolic Pathways, Workshop on Algorithms in Bioinformatics (WABI) , 2009

Hancock, Timothy, and Mamitsuka, Hiroshi: A Markov Classification Model for Metabolic Pathways, Algorithms for Molecular Biology 2010

**See Also**

Other Path clustering & classification methods: [pathCluster\(\)](#), [pathsToBinary\(\)](#), [plotClassifierROC\(\)](#), [plotClusterMatrix\(\)](#), [plotPathClassifier\(\)](#), [plotPathCluster\(\)](#), [predictPathClassifier\(\)](#), [predictPathCluster\(\)](#)

**Examples**

```
## Prepare a weighted reaction network.
## Conver a metabolic network to a reaction network.
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)

## Assign edge weights based on Affymetrix attributes and microarray dataset.
# Calculate Pearson's correlation.
data(ex_microarray) # Part of ALL dataset.
rgraph <- assignEdgeWeights(microarray = ex_microarray, graph = rgraph,
  weight.method = "cor", use.attr="miriam.uniprot",
  y=factor(colnames(ex_microarray)), bootstrap = FALSE)

## Get ranked paths using probabilistic shortest paths.
ranked.p <- pathRanker(rgraph, method="prob.shortest.path",
  K=20, minPathSize=6)

## Convert paths to binary matrix.
ybinpaths <- pathsToBinary(ranked.p)
p.class <- pathClassifier(ybinpaths, target.class = "BCR/ABL", M = 3)

## Contingency table of classification performance
```

```

table(ybinpaths$y,p.class$label)

## Plotting the classifier results.
plotClassifierROC(p.class)
plotClusters(ybinpaths, p.class)

```

---

pathCluster

*3M Markov mixture model for clustering pathways*


---

### Description

3M Markov mixture model for clustering pathways

### Usage

```
pathCluster(ybinpaths, M, iter = 1000)
```

### Arguments

ybinpaths	The training paths computed by <a href="#">pathsToBinary</a> .
M	The number of clusters.
iter	The maximum number of EM iterations.

### Value

A list with the following items:

h	The posterior probabilities that each path belongs to each cluster.
labels	The cluster membership labels.
theta	The probabilities of each gene for each cluster.
proportions	The mixing proportions of each path.
likelihood	The likelihood convergence history.
params	The specific parameters used.

### Author(s)

Ichigaku Takigawa  
Timothy Hancock

### References

Mamitsuka, H., Okuno, Y., and Yamaguchi, A. 2003. Mining biologically active patterns in metabolic pathways using microarray expression profiles. *SIGKDD Explor. News* 1, 5, 2 (Dec. 2003), 113-121.

### See Also

Other Path clustering & classification methods: [pathClassifier\(\)](#), [pathsToBinary\(\)](#), [plotClassifierROC\(\)](#), [plotClusterMatrix\(\)](#), [plotPathClassifier\(\)](#), [plotPathCluster\(\)](#), [predictPathClassifier\(\)](#), [predictPathCluster\(\)](#)

**Examples**

```

## Prepare a weighted reaction network.
## Conver a metabolic network to a reaction network.
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)

## Assign edge weights based on Affymetrix attributes and microarray dataset.
# Calculate Pearson's correlation.
data(ex_microarray) # Part of ALL dataset.
rgraph <- assignEdgeWeights(microarray = ex_microarray, graph = rgraph,
  weight.method = "cor", use.attr="miriam.uniprot", bootstrap = FALSE)

## Get ranked paths using probabilistic shortest paths.
ranked.p <- pathRanker(rgraph, method="prob.shortest.path",
  K=20, minPathSize=8)

## Convert paths to binary matrix.
ybinpaths <- pathsToBinary(ranked.p)
p.cluster <- pathCluster(ybinpaths, M=2)
plotClusters(ybinpaths, p.cluster)

```

pathRanker

*Extracting and ranking paths from a network***Description**

Given a weighted igraph object, path ranking finds a set of node/edge sequences (paths) to maximize the sum of edge weights. `pathRanker(method="prob.shortest.path")` extracts the *K* most probable paths within a weighted network. `pathRanker(method="pvalue")` extracts a list of paths whose sum of edge weights are significantly higher than random paths of the same length.

**Usage**

```

pathRanker(
  graph,
  method = "prob.shortest.path",
  start,
  end,
  verbose = TRUE,
  ...
)

```

**Arguments**

<code>graph</code>	A weighted igraph object. Weights must be in <code>edge.weights</code> or <code>weight edge</code> attributes.
<code>method</code>	Which path ranking method to use.
<code>start</code>	A list of start vertices, given by their vertex id.
<code>end</code>	A list of terminal vertices, given by their vertex id.
<code>verbose</code>	Whether to display the progress of the function.
<code>...</code>	Method-specific parameters. See Details section.

## Details

The input here is graph. A weight must be assigned to each edge. Bootstrapped Pearson correlation edge weights can be assigned to each edge by [assignEdgeWeights](#). However the specification of the edge weight is flexible with the condition that increasing values indicate stronger relationships between vertices.

**Probabilistic Shortest Paths:** `pathRanker(method="prob.shortest.path")` finds the K most probable loopless paths given a weighted network. Before the paths are ranked the edge weights are converted into probabilistic edge weights using the Empirical Cumulative Distribution (ECDF) over all edge weights. This is called ECDF edge weight. The ECDF edge weight serves as a probabilistic rank of the most important gene-gene interactions. The probabilistic nature of the ECDF edge weights allow for a significance test to determine if a path contains any functional structure or is simply a random walk. The probability of a path is simply the product of all ECDF weights along the path. This is computed as a sum of the logs of the ECDF edge weights.

The following arguments can be passed to `pathRanker(method="prob.shortest.path")`:

`K` Maximum number of paths to extract. Defaults to 10.

`minPathSize` The minimum number of edges for each extracted path. Defaults to 1.

`normalize` Specify if you want to normalize the probabilistic edge weights (across different labels) before extracting the paths. Defaults to TRUE.

**P-value method:** `pathRanker(method="pvalue")` is deprecated. Please use `prob.shortest.path` instead.

## Value

A list of paths where each path has the following items:

<code>gene</code>	The ordered sequence of genes visited along the path.
<code>compounds</code>	The ordered sequence of compounds visited along the path.
<code>weights</code>	The ordered sequence of the log(ECDF edge weights) along the path.
<code>distance</code>	The sum of the log(ECDF edge weights) along each path. (a sum of logs is a product)

## Author(s)

Timothy Hancock, Ichigaku Takigawa, Nicolas Wicker and Ahmed Mohamed

## See Also

`getPathAsEIDs`, `extractPathNetwork`

Other Path ranking methods: [extractPathNetwork\(\)](#), [getPathAsEIDs\(\)](#)

## Examples

```
## Prepare a weighted reaction network.
## Conver a metabolic network to a reaction network.
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)

## Assign edge weights based on Affymetrix attributes and microarray dataset.
# Calculate Pearson's correlation.
data(ex_microarray) # Part of ALL dataset.
```

```
rgraph <- assignEdgeWeights(microarray = ex_microarray, graph = rgraph,
  weight.method = "cor", use.attr="miriam.uniprot",
  y=factor(colnames(ex_microarray)), bootstrap = FALSE)

## Get ranked paths using probabilistic shortest paths.
ranked.p <- pathRanker(rgraph, method="prob.shortest.path",
  K=20, minPathSize=6)
```

---

pathsToBinary	<i>Converts the result from pathRanker into something suitable for pathClassifier or pathCluster.</i>
---------------	---

---

### Description

Converts the result from pathRanker into something suitable for pathClassifier or pathCluster.

### Usage

```
pathsToBinary(ypaths)
```

### Arguments

ypaths            The result of [pathRanker](#).

### Details

Converts a set of pathways from [pathRanker](#) into a list of binary pathway matrices. If the pathways are grouped by a response label then the *pathsToBinary* returns a list labeled by response class where each element is the binary pathway matrix for each class. If the pathways are from [pathRanker](#) then a list with a single element containing the binary pathway matrix is returned. To look up the structure of a specific binary path in the corresponding ypaths object simply use matrix index by calling `ypaths[[ybinpaths\$pidx[i, ]]]`, where *i* is the row in the binary paths object you wish to reference.

### Value

A list with the following elements.

paths	All paths within ypaths converted to a binary string and concatenated into the one matrix.
y	The response variable.
pidx	An matrix where each row specifies the location of that path within the ypaths object.

### Author(s)

Timothy Hancock and Ichigaku Takigawa

### See Also

Other Path clustering & classification methods: [pathClassifier\(\)](#), [pathCluster\(\)](#), [plotClassifierROC\(\)](#), [plotClusterMatrix\(\)](#), [plotPathClassifier\(\)](#), [plotPathCluster\(\)](#), [predictPathClassifier\(\)](#), [predictPathCluster\(\)](#)

**Examples**

```

## Prepare a weighted reaction network.
## Conver a metabolic network to a reaction network.
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)

## Assign edge weights based on Affymetrix attributes and microarray dataset.
# Calculate Pearson's correlation.
data(ex_microarray) # Part of ALL dataset.
rgraph <- assignEdgeWeights(microarray = ex_microarray, graph = rgraph,
  weight.method = "cor", use.attr="miriam.uniprot",
  y=factor(colnames(ex_microarray)), bootstrap = FALSE)

## Get ranked paths using probabilistic shortest paths.
ranked.p <- pathRanker(rgraph, method="prob.shortest.path",
  K=20, minPathSize=6)

## Convert paths to binary matrix.
ybinpaths <- pathsToBinary(ranked.p)
p.cluster <- pathCluster(ybinpaths, M=3)
plotClusters(ybinpaths, p.cluster, col=c("red", "green", "blue") )

```

---

plotAllNetworks

*Highlighting ranked paths over multiple network representations.*


---

**Description**

This function highlighting ranked paths over different network representations, metabolic, reaction and gene networks. The functions finds equivalent paths across different networks and marks them.

**Usage**

```

plotAllNetworks(
  paths,
  metabolic.net = NULL,
  reaction.net = NULL,
  gene.net = NULL,
  path.clusters = NULL,
  plot.clusters = TRUE,
  col.palette = palette(),
  layout = layout.auto,
  ...
)

```

**Arguments**

paths	The result of <a href="#">pathRanker</a> .
metabolic.net	A bipartite metabolic network.
reaction.net	A reaction network, resulting from <a href="#">makeReactionNetwork</a> .
gene.net	A gene network, resulting from <a href="#">makeGeneNetwork</a> .

path.clusters	The result from <a href="#">pathCluster</a> or <a href="#">pathClassifier</a> .
plot.clusters	Whether to plot clustering information, as generated by <a href="#">plotClusters</a>
col.palette	A color palette, or a palette generating function (ex:  col.palette=rainbow  ).  ).
layout	Either a graph layout function, or a two-column matrix specifying vertex coordinates.
...	Additional arguments passed to <a href="#">plotNetwork</a> .

**Value**

Highlights the path list over all provided networks.

**Author(s)**

Ahmed Mohamed

**See Also**

Other Plotting methods: [colorVertexByAttr\(\)](#), [layoutVertexByAttr\(\)](#), [plotClassifierROC\(\)](#), [plotClusterMatrix\(\)](#), [plotCytoscapeGML\(\)](#), [plotNetwork\(\)](#), [plotPathClassifier\(\)](#), [plotPaths\(\)](#)

**Examples**

```
## Prepare a weighted reaction network.
## Conver a metabolic network to a reaction network.
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)

## Assign edge weights based on Affymetrix attributes and microarray dataset.
# Calculate Pearson's correlation.
data(ex_microarray) # Part of ALL dataset.
rgraph <- assignEdgeWeights(microarray = ex_microarray, graph = rgraph,
  weight.method = "cor", use.attr="miriam.uniprot",
  y=factor(colnames(ex_microarray)), bootstrap = FALSE)

## Get ranked paths using probabilistic shortest paths.
ranked.p <- pathRanker(rgraph, method="prob.shortest.path",
  K=20, minPathSize=6)

plotAllNetworks(ranked.p, metabolic.net = ex_sbml, reaction.net = rgraph,
  vertex.label = "", vertex.size = 4)
```

---

plotClassifierROC      *Diagnostic plots for pathClassifier.*

---

### Description

Diagnostic plots for [pathClassifier](#).

### Usage

```
plotClassifierROC(mix)
```

### Arguments

`mix`                      The result from [pathClassifier](#).

### Value

Diagnostic plots of the result from [pathClassifier](#). `itemTop` ROC curves for the posterior probabilities (`mix$posterior.probs`) and for each HME3M component (`mix$h`). This gives information about what response label each relates to. A ROC curve with an  $AUC < 0.5$  relates to  $y = 0$ . Conversely ROC curves with  $AUC > 0.5$  relate to  $y = 1$ . `itemBottom` The likelihood convergence history for the HME3M model. If the parameters `alpha` or `lambda` are set too large then the likelihood may decrease.

### Author(s)

Timothy Hancock and Ichigaku Takigawa

### See Also

Other Path clustering & classification methods: [pathClassifier\(\)](#), [pathCluster\(\)](#), [pathsToBinary\(\)](#), [plotClusterMatrix\(\)](#), [plotPathClassifier\(\)](#), [plotPathCluster\(\)](#), [predictPathClassifier\(\)](#), [predictPathCluster\(\)](#)

Other Plotting methods: [colorVertexByAttr\(\)](#), [layoutVertexByAttr\(\)](#), [plotAllNetworks\(\)](#), [plotClusterMatrix\(\)](#), [plotCytoscapeGML\(\)](#), [plotNetwork\(\)](#), [plotPathClassifier\(\)](#), [plotPaths\(\)](#)

---

plotClusterMatrix      *Plots the structure of all path clusters*

---

### Description

Plots the structure of all path clusters

**Usage**

```

plotClusterMatrix(
  ybinpaths,
  clusters,
  col = rainbow(clusters$params$M),
  grid = TRUE
)

plotClusterProbs(clusters, col = rainbow(clusters$params$M))

plotClusters(ybinpaths, clusters, col, ...)

```

**Arguments**

ybinpaths	The training paths computed by <a href="#">pathsToBinary</a> .
clusters	The pathway cluster model trained by <a href="#">pathCluster</a> or <a href="#">pathClassifier</a> .
col	Colors for each path cluster.
grid	A logical, whether to add a <a href="#">grid</a> to the plot
...	Extra paramaters passed to <a href="#">plotClusterMatrix</a>

**Value**

[plotClusterMatrix](#) plots an image of all paths the training dataset. Rows are the paths and columns are the genes (features) included within each path. Paths are colored according to cluster membership.

[plotClusterProbs](#) The training set posterior probabilities for each path belonging to a 3M component.

[plotClusters](#): combines the two plots produced by [plotClusterProbs](#) and [plotClusterMatrix](#).

**Author(s)**

Ahmed Mohamed

**See Also**

Other Path clustering & classification methods: [pathClassifier\(\)](#), [pathCluster\(\)](#), [pathsToBinary\(\)](#), [plotClassifierROC\(\)](#), [plotPathClassifier\(\)](#), [plotPathCluster\(\)](#), [predictPathClassifier\(\)](#), [predictPathCluster\(\)](#)

Other Plotting methods: [colorVertexByAttr\(\)](#), [layoutVertexByAttr\(\)](#), [plotAllNetworks\(\)](#), [plotClassifierROC\(\)](#), [plotCytoscapeGML\(\)](#), [plotNetwork\(\)](#), [plotPathClassifier\(\)](#), [plotPaths\(\)](#)

**Examples**

```

## Prepare a weighted reaction network.
## Conver a metabolic network to a reaction network.
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)

## Assign edge weights based on Affymetrix attributes and microarray dataset.
# Calculate Pearson's correlation.

```

```

data(ex_microarray) # Part of ALL dataset.
rgraph <- assignEdgeWeights(microarray = ex_microarray, graph = rgraph,
  weight.method = "cor", use.attr="miriam.uniprot",
  y=factor(colnames(ex_microarray)), bootstrap = FALSE)

## Get ranked paths using probabilistic shortest paths.
ranked.p <- pathRanker(rgraph, method="prob.shortest.path",
  K=20, minPathSize=8)

## Convert paths to binary matrix.
ybinpaths <- pathsToBinary(ranked.p)
p.cluster <- pathCluster(ybinpaths, M=2)
plotClusters(ybinpaths, p.cluster, col=c("red", "blue") )

```

---

plotCytoscapeGML

*Plots an annotated igraph object in Cytoscape.*


---

### Description

plotCytoscape function has been removed because RCytoscape is no longer present in Bioconductor. Future plans will use RCy3 for Cytoscape plotting, once RCy3 is supported on MacOS and Windows. [plotCytoscapeGML](#) exports the network plot in GML format, that can be later imported into Cytoscape (using "import network from file" option). This function is compatible with all Cytoscape versions.

### Usage

```

plotCytoscapeGML(
  graph,
  file,
  layout = layout.auto,
  vertex.size,
  vertex.label,
  vertex.shape,
  vertex.color,
  edge.color
)

```

### Arguments

graph	An annotated igraph object.
file	Output GML file name to which the network plot is exported.
layout	Either a graph layout function, or a two-column matrix specifying vertex coordinates.
vertex.size	Vertex size. If missing, the vertex attribute "size" ( <code>V(g)\$size</code> ) will be used.
vertex.label	Vertex labels. If missing, the vertex attribute "label" ( <code>V(g)\$label</code> )

	) will be used. If missing, vertices are labeled by their name.
vertex.shape	Vertex shape in one of igraph shapes. If missing, the vertex attribute "shape" ( V(g)\$shape)  ) will be used. Shapes are converted from igraph convention to Cytoscape convention. "square","rectangle" and "vrectangle" are converted to "RECT", "csquare" and "crectangle" are converted to "ROUND_RECT", all other shapes are considered "ELLIPSE"
vertex.color	A color or a list of colors for vertices. Vetices with multiple colors are not supported. If missing, the vertex attribute "color" ( V(g)\$color)  ) will be used.
edge.color	A color or a list of colors for edges. If missing, the edge attribute "color" ( E(g)\$color)  ) will be used.

**Value**

For plotCytoscapeGML, results are written to file.

**Author(s)**

Ahmed Mohamed

**See Also**

Other Plotting methods: [colorVertexByAttr\(\)](#), [layoutVertexByAttr\(\)](#), [plotAllNetworks\(\)](#), [plotClassifierROC\(\)](#), [plotClusterMatrix\(\)](#), [plotNetwork\(\)](#), [plotPathClassifier\(\)](#), [plotPaths\(\)](#)

**Examples**

```
data("ex_sbml")
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)
v.layout <- layoutVertexByAttr(rgraph, "compartment")
v.color <- colorVertexByAttr(rgraph, "compartment")

# Export network plot to GML file
plotCytoscapeGML(rgraph, file="example.gml", layout=v.layout,
  vertex.color=v.color, vertex.size=10)
```

---

plotNetwork

*Plots an annotated igraph object.*


---

### Description

This function is a wrapper function for `plot.igraph`, with 2 main additions. 1. Add the ability to color vertices by their attributes (see examples), accompanied by an informative legend. 2. Resize `vertex.size`, `edge.arrow.size`, `label.cex` according to the plot size and the size of the network.

### Usage

```
plotNetwork(
  graph,
  vertex.color,
  col.palette = palette(),
  layout = layout.auto,
  legend = TRUE,
  ...
)
```

### Arguments

<code>graph</code>	An annotated igraph object.
<code>vertex.color</code>	A list of colors for vertices, or an attribute names (ex: "pathway") by which vertices will be colored. Complex attributes, where a vertex belongs to more than one group, are supported. This can also be the output of <code>colorVertexByAttr</code> .
<code>col.palette</code>	A color palette, or a palette generating function (ex: <code>col.palette=rainbow</code> ).
<code>layout</code>	Either a graph layout function, or a two-column matrix specifying vertex coordinates.
<code>legend</code>	Whether to plot a legend. The legend is only plotted if vertices are colored by attribute values.
<code>...</code>	Additional arguments passed to <code>plot.igraph</code> .

### Value

Produces a plot of the network.

### Author(s)

Ahmed Mohamed

### See Also

Other Plotting methods: `colorVertexByAttr()`, `layoutVertexByAttr()`, `plotAllNetworks()`, `plotClassifierROC()`, `plotClusterMatrix()`, `plotCytoscapeGML()`, `plotPathClassifier()`, `plotPaths()`

**Examples**

```

data("ex_kgml_sig")
plotNetwork(ex_kgml_sig, vertex.color="pathway")
plotNetwork(ex_kgml_sig, vertex.color="pathway", col.palette=heat.colors)
plotNetwork(ex_kgml_sig, vertex.color="pathway",
            col.palette=c("red", "green", "blue", "grey"))

```

---

plotPathClassifier      *Plots the structure of specified path found by pathClassifier.*

---

**Description**

Plots the structure of specified path found by pathClassifier.

**Usage**

```
plotPathClassifier(ybinpaths, obj, m, tol = NULL)
```

**Arguments**

ybinpaths	The training paths computed by <a href="#">pathsToBinary</a>
obj	The pathClassifier <a href="#">pathClassifier</a> .
m	The path component to view.
tol	A tolerance for 3M parameter theta which is the probability for each edge within each cluster. If the tolerance is set all edges with a theta below that tolerance will be removed from the plot.

**Value**

Produces a plot of the paths with the path probabilities and prediction probabilities and ROC curve overlaid.

Center Plot	An image of all paths the training dataset. Rows are the paths and columns are the genes (vertices) included within each pathway. A colour within image indicates if a particular gene (vertex) is included within a specific path. Colours flag whether a path belongs to the current HME3M component ( $P > 0.5$ ).
Center Right	The training set posterior probabilities for each path belonging to the current 3M component.
Center Top	The ROC curve for this HME3M component.
Top Bar Plots	Theta: The 3M component probabilities - indicates the importance of each edge is to a path. Beta: The PLR coefficient - the magnitude indicates the importance of the edge to the classify the response.

**Author(s)**

Timothy Hancock and Ichigaku Takigawa

**See Also**

Other Path clustering & classification methods: [pathClassifier\(\)](#), [pathCluster\(\)](#), [pathsToBinary\(\)](#), [plotClassifierROC\(\)](#), [plotClusterMatrix\(\)](#), [plotPathCluster\(\)](#), [predictPathClassifier\(\)](#), [predictPathCluster\(\)](#)

Other Plotting methods: [colorVertexByAttr\(\)](#), [layoutVertexByAttr\(\)](#), [plotAllNetworks\(\)](#), [plotClassifierROC\(\)](#), [plotClusterMatrix\(\)](#), [plotCytoscapeGML\(\)](#), [plotNetwork\(\)](#), [plotPaths\(\)](#)

**Examples**

```
## Prepare a weighted reaction network.
## Conver a metabolic network to a reaction network.
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)

## Assign edge weights based on Affymetrix attributes and microarray dataset.
# Calculate Pearson's correlation.
data(ex_microarray) # Part of ALL dataset.
rgraph <- assignEdgeWeights(microarray = ex_microarray, graph = rgraph,
  weight.method = "cor", use.attr="miriam.uniprot",
  y=factor(colnames(ex_microarray)), bootstrap = FALSE)

## Get ranked paths using probabilistic shortest paths.
ranked.p <- pathRanker(rgraph, method="prob.shortest.path",
  K=20, minPathSize=6)

## Convert paths to binary matrix.
ybinpaths <- pathsToBinary(ranked.p)
p.class <- pathClassifier(ybinpaths, target.class = "BCR/ABL", M = 3)

## Plotting the classifier results.
plotClassifierROC(p.class)
plotClusters(ybinpaths, p.class)
```

---

plotPathCluster

*Plots the structure of specified path cluster*

---

**Description**

Plots the structure of specified path found by pathCluster.

**Usage**

```
plotPathCluster(ybinpaths, clusters, m, tol = NULL)
```

**Arguments**

ybinpaths	The training paths computed by <a href="#">pathsToBinary</a> .
clusters	The pathway cluster model trained by <a href="#">pathCluster</a> or <a href="#">pathClassifier</a> .
m	The path cluster to view.
tol	A tolerance for 3M parameter theta which is the probability for each edge within each cluster. If the tolerance is set all edges with a theta below that tolerance will be removed from the plot.

**Value**

Produces a plot of the paths with the path probabilities and cluster membership probabilities.

Center Plot	An image of all paths the training dataset. Rows are the paths and columns are the genes (features) included within each path.
Right	The training set posterior probabilities for each path belonging to the current 3M component.
Top Bar Plots	Theta, The 3M component probabilities - indicates the importance of each edge to a pathway.

**Author(s)**

Timothy Hancock and Ichigaku Takigawa

**See Also**

Other Path clustering & classification methods: [pathClassifier\(\)](#), [pathCluster\(\)](#), [pathsToBinary\(\)](#), [plotClassifierROC\(\)](#), [plotClusterMatrix\(\)](#), [plotPathClassifier\(\)](#), [predictPathClassifier\(\)](#), [predictPathCluster\(\)](#)

**Examples**

```
## Prepare a weighted reaction network.
## Conver a metabolic network to a reaction network.
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)

## Assign edge weights based on Affymetrix attributes and microarray dataset.
# Calculate Pearson's correlation.
data(ex_microarray) # Part of ALL dataset.
rgraph <- assignEdgeWeights(microarray = ex_microarray, graph = rgraph,
  weight.method = "cor", use.attr="miriam.uniprot", bootstrap = FALSE)

## Get ranked paths using probabilistic shortest paths.
ranked.p <- pathRanker(rgraph, method="prob.shortest.path",
  K=20, minPathSize=8)

## Convert paths to binary matrix.
ybinpaths <- pathsToBinary(ranked.p)
p.cluster <- pathCluster(ybinpaths, M=2)
plotPathCluster(ybinpaths, p.cluster, m=2, tol=0.05)
```

---

plotPaths

*Plots an annotated igraph object highlighting ranked paths.*

---

**Description**

This function plots a network highlighting ranked paths. If `path.clusters` are provided, paths in the same cluster are assigned similar colors.

**Usage**

```
plotPaths(
  paths,
  graph,
  path.clusters = NULL,
  col.palette = palette(),
  layout = layout.auto,
  ...
)
```

**Arguments**

paths	The result of <a href="#">pathRanker</a> .
graph	An annotated igraph object.
path.clusters	The result from <a href="#">pathCluster</a> or <a href="#">pathClassifier</a> .
col.palette	A color palette, or a palette generating function (ex: col.palette=rainbow ).
layout	Either a graph layout function, or a two-column matrix specifying vertex coordinates.
...	Additional arguments passed to <a href="#">plotNetwork</a> .

**Value**

Produces a plot of the network with paths highlighted. If paths are computed for several labels (sample categories), a plot is created for each label.

**Author(s)**

Ahmed Mohamed

**See Also**

Other Plotting methods: [colorVertexByAttr\(\)](#), [layoutVertexByAttr\(\)](#), [plotAllNetworks\(\)](#), [plotClassifierROC\(\)](#), [plotClusterMatrix\(\)](#), [plotCytoscapeGML\(\)](#), [plotNetwork\(\)](#), [plotPathClassifier\(\)](#)

**Examples**

```
## Prepare a weighted reaction network.
## Conver a metabolic network to a reaction network.
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)

## Assign edge weights based on Affymetrix attributes and microarray dataset.
# Calculate Pearson's correlation.
data(ex_microarray) # Part of ALL dataset.
rgraph <- assignEdgeWeights(microarray = ex_microarray, graph = rgraph,
  weight.method = "cor", use.attr="miriam.uniprot",
  y=factor(colnames(ex_microarray)), bootstrap = FALSE)

## Get ranked paths using probabilistic shortest paths.
ranked.p <- pathRanker(rgraph, method="prob.shortest.path",
```

```

    K=20, minPathSize=6)

## Plot paths.
plotPaths(ranked.p, rgraph)

## Convert paths to binary matrix, build a classifier.
ybinpaths <- pathsToBinary(ranked.p)
p.class <- pathClassifier(ybinpaths, target.class = "BCR/ABL", M = 3)

## Plotting with clusters, on a metabolic graph.
plotPaths(ranked.p, ex_sbml, path.clusters=p.class)

```

---

predictPathClassifier *Predicts new paths given a pathClassifier model.*

---

## Description

Predicts new paths given a pathClassifier model.

## Usage

```
predictPathClassifier(mix, newdata)
```

## Arguments

mix	The result from <a href="#">pathClassifier</a> .
newdata	A data.frame containing the new paths to be classified.

## Value

A list with the following elements.

h	The posterior probabilities for each HME3M component.
posterior.probs	The posterior probabilities for HME3M model to classify the response.
label	A vector indicating the HME3M cluster membership.
component	The HME3M component membership for each pathway.
path.probabilities	The 3M path probabilities.
plr.probabilities	The PLR predictions for each component.

## Author(s)

Timothy Hancock and Ichigaku Takigawa

## See Also

Other Path clustering & classification methods: [pathClassifier\(\)](#), [pathCluster\(\)](#), [pathsToBinary\(\)](#), [plotClassifierROC\(\)](#), [plotClusterMatrix\(\)](#), [plotPathClassifier\(\)](#), [plotPathCluster\(\)](#), [predictPathCluster\(\)](#)

**Examples**

```

## Prepare a weighted reaction network.
## Conver a metabolic network to a reaction network.
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)

## Assign edge weights based on Affymetrix attributes and microarray dataset.
# Calculate Pearson's correlation.
data(ex_microarray) # Part of ALL dataset.
rgraph <- assignEdgeWeights(microarray = ex_microarray, graph = rgraph,
  weight.method = "cor", use.attr="miriam.uniprot",
  y=factor(colnames(ex_microarray)), bootstrap = FALSE)

## Get ranked paths using probabilistic shortest paths.
ranked.p <- pathRanker(rgraph, method="prob.shortest.path",
  K=20, minPathSize=6)

## Convert paths to binary matrix.
ybinpaths <- pathsToBinary(ranked.p)
p.class <- pathClassifier(ybinpaths, target.class = "BCR/ABL", M = 3)

## Just an example of how to predict cluster membership
pclass.pred <- predictPathCluster(p.class, ybinpaths$paths)

```

---

predictPathCluster      *Predicts new paths given a pathCluster model*

---

**Description**

Predicts new paths given a pathCluster model.

**Usage**

```
predictPathCluster(pfit, newdata)
```

**Arguments**

pfit	The pathway cluster model trained by <a href="#">pathCluster</a> or <a href="#">pathClassifier</a> .
newdata	The binary pathway dataset to be assigned a cluster label.

**Value**

A list with the following elements:

labels	a vector indicating the 3M cluster membership.
posterior.probs	a matrix of posterior probabilities for each path belonging to each cluster.

**Author(s)**

Ichigaku Takigawa  
Timothy Hancock

**See Also**

Other Path clustering & classification methods: [pathClassifier\(\)](#), [pathCluster\(\)](#), [pathsToBinary\(\)](#), [plotClassifierROC\(\)](#), [plotClusterMatrix\(\)](#), [plotPathClassifier\(\)](#), [plotPathCluster\(\)](#), [predictPathClassifier\(\)](#)

**Examples**

```
## Prepare a weighted reaction network.
## Conver a metabolic network to a reaction network.
data(ex_sbml) # bipartite metabolic network of Carbohydrate metabolism.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)

## Assign edge weights based on Affymetrix attributes and microarray dataset.
# Calculate Pearson's correlation.
data(ex_microarray) # Part of ALL dataset.
rgraph <- assignEdgeWeights(microarray = ex_microarray, graph = rgraph,
  weight.method = "cor", use.attr="miriam.uniprot", bootstrap = FALSE)

## Get ranked paths using probabilistic shortest paths.
ranked.p <- pathRanker(rgraph, method="prob.shortest.path",
  K=20, minPathSize=8)

## Convert paths to binary matrix.
ybinpaths <- pathsToBinary(ranked.p)
p.cluster <- pathCluster(ybinpaths, M=2)

## just an example of how to predict cluster membership.
pclus.pred <- predictPathCluster(p.cluster, ybinpaths$paths)
```

---

registerMemoryErr      *Internal method to register memory errors.*

---

**Description**

Internal method to register memory errors, caused by compiled code. This method is used only by the package, and should not be invoked by users.

**Usage**

```
registerMemoryErr(method)
```

**Arguments**

method                      The method which generated the error.

**Author(s)**

Ahmed Mohamed

---

reindexNetwork	<i>Replaces current vertex ids with chosen attribute.</i>
----------------	---

---

## Description

This function allows users to replace vertex ids with another attribute, calculating connectivities based on the new attribute.

## Usage

```
reindexNetwork(graph, v.attr)
```

## Arguments

graph	An annotated igraph object.
v.attr	Name of the attribute to use as vertex ids.

## Details

This functions can be very useful when merging networks constructed from different databases. For example, to match a network created from Reactome to a KEGG network, you can reindex the vertices by "miriam.kegg.compound" attribute. Another usage is to remove duplicated vertices (in case of different subcellular compartments, for example). if a network has ATP\_membrane & ATP\_cytoplasm vertices, reindexing by chemical name will collapse them into one 'ATP' vertex.

## Value

A new graph with vertices expanded.

## Author(s)

Ahmed Mohamed

## See Also

Other Network processing methods: [expandComplexes\(\)](#), [makeMetaboliteNetwork\(\)](#), [makeReactionNetwork\(\)](#), [rmSmallCompounds\(\)](#), [simplifyReactionNetwork\(\)](#), [vertexDeleteReconnect\(\)](#)

## Examples

```
## Make a gene network from a reaction network.
data(ex_sbml) # A bipartite metbaolic network.
rgraph <- makeReactionNetwork(ex_sbml, simplify=TRUE)
ggraph <- makeGeneNetwork(rgraph)

## Expand vertices into their contituent genes.
data(ex_kgml_sig) # Ras and chemokine signaling pathways in human
ggraph <- expandComplexes(ex_kgml_sig, v.attr = "miriam.ncbigene",
  keep.parent.attr= c("^pathway", "^compartment"))

## Create a separate vertex for each compartment. This is useful in duplicating
## metabolite vertices in a network.
## Not run:
```

```
graph <- expandComplexes(graph, v.attr = "compartment",
  keep.parent.attr = "all",
  expansion.method = "duplicate",
  missing.method = "keep")

## End(Not run)
```

---

rmSmallCompounds      *Remove ubiquitous compounds from a metabolic network*

---

### Description

This function removes ubiquitous compounds (metabolites connected to numerous reactions) from a metabolic network. These compounds are reaction cofactors and currency compounds, such as ATP, CO<sub>2</sub>, etc. A path through these metabolites may not be biologically meaningful. The default small compound list is derived from Reactome, containing kegg.compound, pubchem.compound, ChEBI and CAS identifiers.

### Usage

```
rmSmallCompounds(
  graph,
  method = c("remove", "duplicate"),
  small.comp.ls = NPMdefaults("small.comp.ls")
)
```

### Arguments

**graph**            A metabolic network.

**method**            How to handle small compounds. Either simply delete these vertices "remove" (default), or make a separate vertex for each reaction they participate in "duplicate".

**small.comp.ls**    A list of small compounds to be used.

### Value

A modified graph, with the small compounds removed or duplicated.

### Author(s)

Ahmed Mohamed

### See Also

Other Network processing methods: [expandComplexes\(\)](#), [makeMetaboliteNetwork\(\)](#), [makeReactionNetwork\(\)](#), [reindexNetwork\(\)](#), [simplifyReactionNetwork\(\)](#), [vertexDeleteReconnect\(\)](#)

**Examples**

```
data(ex_sbml)

sbml.removed <- rmSmallCompounds(ex_sbml, method="remove")
```

---

 SBML2igraph

*Processes SBML files into igraph objects*


---

**Description**

This function takes SBML files as input, and returns either a metabolic or a signaling network as output.

**Usage**

```
SBML2igraph(
  filename,
  parse.as = c("metabolic", "signaling"),
  miriam.attr = "all",
  gene.attr,
  expand.complexes,
  verbose = TRUE
)
```

**Arguments**

filename	A character vector containing the SBML files to be processed. If a directory path is provided, all *.xml and *.sbml files in it and its subdirectories are included.
parse.as	Whether to process file into a metabolic or a signaling network.
miriam.attr	A list of annotation attributes to be extracted. If "all", then all attributes written in MIRIAM guidelines (see Details) are extracted (Default). If "none", then no attributes are extracted. Otherwise, only attributes matching those specified are extracted.
gene.attr	An attribute to distinguish species representing genes from those representing small molecules (see Details). Ignored if parse.as="metabolic".
expand.complexes	Split protein complexes into individual gene nodes. Ignored if parse.as="metabolic", or when gene.attr is not provided.
verbose	Whether to display the progress of the function.

**Details**

Users can specify whether files are processes as metabolic or signaling networks.

Metabolic networks are given as bipartite graphs, where metabolites and reactions represent vertex types. This is constructed from ListOfReactions in SBML file, connecting them to their corresponding substrates and products (ListOfSpecies). Each reaction vertex has genes attribute,

listing all modifiers of this reaction. As a general rule, reactions inherit all annotation attributes of its catalyzing genes.

Signaling network have genes as vertices and edges represent interactions. Since SBML format may represent signaling events as reaction, all species are assumed to be genes (rather than small molecules). For a simple path  $S_0 \rightarrow R_1 \rightarrow S_1$ , in signaling network, the path will be  $S_0 \rightarrow M(R_1) \rightarrow S_1$  where  $M(R_1)$  is  $R_1$  modifier(s). To distinguish gene species from small molecules, user can provide `gene.attr` (for example: `miriam.uniprot` or `miriam.ncbigene`) where only annotated species are considered genes.

All annotation attributes written according to MIRIAM guidelines (either `urn:miriam:xxx:xxx` or `http://identifiers.org/xxx/xxx`) are extracted by default. Non-conforming attributes can be extracted by specifying `miriam.attr`.

To generate a genome scale network, simply provide a list of files to be parsed, or put all file in a directory, as pass the directory path as filename

Note: This function requires libSBML installed (Please see the installation instructions in the Vignette). Some SBML level-3 files may requires additional libraries also (An informative error will be displayed when parsing such files). Please visit [http://sbml.org/Documents/Specifications/SBML\\_Level\\_3/Packages](http://sbml.org/Documents/Specifications/SBML_Level_3/Packages) for more information.

## Value

An igraph object, representing a metabolic or a signaling network.

## Author(s)

Ahmed Mohamed

## See Also

Other Database extraction methods: [KGML2igraph\(\)](#), [biopax2igraph\(\)](#)

## Examples

```
if(is.loaded("readsbmlfile")){ # This is false if libSBML wasn't available at installation.
  filename <- system.file("extdata", "porphyrin.sbml", package="NetPathMiner")

  # Process SBML file as a metabolic network
  g <- SBML2igraph(filename)
  plotNetwork(g)

  # Process SBML file as a signaling network
  g <- SBML2igraph(filename, parse.as="signaling",
                  gene.attr="miriam.uniprot", expand.complexes=TRUE)
  dev.new()
  plotNetwork(g)
}
```

---

`simplifyReactionNetwork`*Removes reactions with no gene annotations*

---

### Description

This function removes reaction vertices with no gene annotations as indicated by the parameter `gene.attr`, and connect their neighbour vertices to preserve graph connectivity. This is particularly meaningful when reactions are translocation or spontaneous reactions, which are not catalysed by genes.

### Usage

```
simplifyReactionNetwork(  
  reaction.graph,  
  gene.attr = "genes",  
  remove.missing.genes = TRUE,  
  reconnect.threshold = vcount(reaction.graph)  
)
```

### Arguments

`reaction.graph` A reaction network.

`gene.attr` The attribute to be considered as "genes". Reactions missing this annotation, will be removed.

`remove.missing.genes`  
If FALSE, only translocation and spontaneous reactions are removed, otherwise all reactions with no gene annotations are removed.

`reconnect.threshold`  
An argument passed to [vertexDeleteReconnect](#)

### Value

A simplified reaction network.

### Author(s)

Ahmed Mohamed

### See Also

Other Network processing methods: [expandComplexes\(\)](#), [makeMetaboliteNetwork\(\)](#), [makeReactionNetwork\(\)](#), [reindexNetwork\(\)](#), [rmSmallCompounds\(\)](#), [vertexDeleteReconnect\(\)](#)

### Examples

```
data(ex_sbml)  
rgraph <- makeReactionNetwork(ex_sbml, simplify=FALSE)  
  
## Removes all reaction nodes with no annotated genes.  
rgraph <- simplifyReactionNetwork(rgraph, remove.missing.genes=TRUE)
```

---

stdAttrNames	<i>MIRIAM annotation attributes</i>
--------------	-------------------------------------

---

## Description

These functions deals with conforming with MIRIAM annotation guidelines, conversion and mapping between MIRIAM identifiers.

## Usage

```
stdAttrNames(graph, return.value = c("matches", "graph"))

fetchAttribute(
  graph,
  organism = "Homo sapiens",
  target.attr,
  source.attr,
  bridge.web = NPMdefaults("bridge.web")
)
```

## Arguments

graph	An annotated igraph object.
return.value	Specify whether to return the names of matched standard annotations, or modify the graph attribute names to match the standards.
organism	The latin name of the organism (Case-sensitive).
target.attr	The target annotation, given as MIRIAM standard in the format <code>miriam.xxx</code>
source.attr	The source annotation attribute from graph
bridge.web	The base URL for Brigde Database webservice.

## Value

For `stdAttrNames`, `matches` gives the original attribute names and their MIRIAM version. Since this is done by simple text matching, mismatches may occur for ambiguous annotations (such as GO, EC number). `graph` returns the input graph with attribute names standardized.

For `fetchAttribute`, the input graph with the fetched attribute mapped to vertices.

## Author(s)

Ahmed Mohamed

## See Also

Other Attribute handling methods: [getAttrStatus\(\)](#)

**Examples**

```

data(ex_kgml_sig) # Ras and chemokine signaling pathways in human
## Modify attribute names to match MIRIAM standard annotations.
graph <- stdAttrNames(ex_kgml_sig, "graph")

# Use Attribute fetcher to get affymetrix probeset IDs for network vertices.
## Not run:
graph <- fetchAttribute(graph, organism="Homo sapiens",
                        target.attr="miriam.affy.probeset")

## End(Not run)

```

---

toGraphNEL

*Converts an annotated igraph object to graphNEL*


---

**Description**

Converts an annotated igraph object to graphNEL

**Usage**

```
toGraphNEL(graph, export.attr = "")
```

**Arguments**

graph	An annotated igraph object..
export.attr	A <a href="#">regex</a> expression representing vertex attributes to be exported to the new graphNEL object. Supplying an empty string "" (default) will export all attributes.

**Value**

A graphNEL object.

**Author(s)**

Ahmed Mohamed

**Examples**

```

data(ex_kgml_sig) # Ras and chemokine signaling pathways in human
graphNEL <- toGraphNEL(ex_kgml_sig, export.attr="^miriam.")

```

---

vertexDeleteReconnect *Network editing: removing vertices and connecting their neighbours*

---

## Description

This function removes vertices given as `vids` and connects their neighbours as long as the shortest path between the neighbours are below the `reconnect.threshold`.

## Usage

```
vertexDeleteReconnect(  
  graph,  
  vids,  
  reconnect.threshold = vcount(graph),  
  copy.attr = NULL  
)
```

## Arguments

<code>graph</code>	A reaction network.
<code>vids</code>	Vertex ids to be removed.
<code>reconnect.threshold</code>	If the shortest path between vertices is larger than this threshold, they are not reconnected.
<code>copy.attr</code>	A function, or a list of functions, combine edge attributes. Edge attributes of new edges (between reconnected neighbours) are obtained by combining original edges attributes along the shortest path between reconnected neighbors.

## Value

A modified graph.

## Author(s)

Ahmed Mohamed

## See Also

Other Network processing methods: [expandComplexes\(\)](#), [makeMetaboliteNetwork\(\)](#), [makeReactionNetwork\(\)](#), [reindexNetwork\(\)](#), [rmSmallCompounds\(\)](#), [simplifyReactionNetwork\(\)](#)

## Examples

```
## Remove all reaction vertices from a bipartite metabolic network  
## keeping only metabolite vertices.  
data(ex_sbml)  
graph <- vertexDeleteReconnect(ex_sbml, vids=which(V(ex_sbml)$reactions))
```

# Index

- \* **Attribute handling methods**
  - getAttrStatus, 11
  - stdAttrNames, 45
- \* **Database extraction methods**
  - biopax2igraph, 5
  - KGML2igraph, 15
  - SBML2igraph, 42
- \* **Network processing methods**
  - expandComplexes, 7
  - makeMetaboliteNetwork, 17
  - makeReactionNetwork, 18
  - reindexNetwork, 40
  - rmSmallCompounds, 41
  - simplifyReactionNetwork, 44
  - vertexDeleteReconnect, 47
- \* **Path clustering & classification methods**
  - pathClassifier, 20
  - pathCluster, 22
  - pathsToBinary, 25
  - plotClassifierROC, 28
  - plotClusterMatrix, 28
  - plotPathClassifier, 33
  - plotPathCluster, 34
  - predictPathClassifier, 37
  - predictPathCluster, 38
- \* **Path ranking methods**
  - extractPathNetwork, 8
  - getPathsAsEIDs, 14
  - pathRanker, 23
- \* **Plotting methods**
  - colorVertexByAttr, 6
  - layoutVertexByAttr, 16
  - plotAllNetworks, 26
  - plotClassifierROC, 28
  - plotClusterMatrix, 28
  - plotCytoscapeGML, 30
  - plotNetwork, 32
  - plotPathClassifier, 33
  - plotPaths, 35
- assignEdgeWeights, 3, 24
- biopax2igraph, 5, 16, 43
- colorVertexByAttr, 6, 17, 27–29, 31, 32, 34, 36
- ex\_biopax, 9
- ex\_kgml\_sig, 10
- ex\_microarray, 10
- ex\_sbml, 10
- expandComplexes, 3, 7, 18, 19, 40, 41, 44, 47
- extractPathNetwork, 8, 14, 24
- fetchAttribute, 19
- fetchAttribute (stdAttrNames), 45
- getAttribute (getAttrStatus), 11
- getAttributeNames (getAttrStatus), 11
- getAttributeStatus, 3, 11, 45
- getGeneSetNetworks, 12, 14
- getGeneSets, 12, 13
- getPathsAsEIDs, 9, 14, 24
- graph\_attr\_names, 11
- grid, 29
- KGML2igraph, 6, 15, 43
- layout\_with\_fr, 17
- layout\_with\_kk, 17
- layoutVertexByAttr, 6, 16, 27–29, 31, 32, 34, 36
- makeGeneNetwork, 26
- makeGeneNetwork (expandComplexes), 7
- makeMetaboliteNetwork, 8, 17, 19, 40, 41, 44, 47
- makeReactionNetwork, 8, 18, 18, 26, 40, 41, 44, 47
- max, 4
- median, 4
- NetPathMiner (NetPathMiner-package), 3
- NetPathMiner-package, 3
- NPM (NetPathMiner-package), 3
- NPMdefaults, 19
- pathClassifier, 20, 22, 25, 27–29, 33–39
- pathCluster, 21, 22, 25, 27–29, 34–39

pathRanker, 8, 9, 14, 23, 25, 26, 36  
pathsToBinary, 20–22, 25, 28, 29, 33–35, 37, 39  
plot.igraph, 32  
plotAllNetworks, 6, 17, 26, 28, 29, 31, 32, 34, 36  
plotClassifierROC, 6, 17, 21, 22, 25, 27, 28, 29, 31, 32, 34–37, 39  
plotClusterMatrix, 6, 17, 21, 22, 25, 27, 28, 28, 31, 32, 34–37, 39  
plotClusterProbs (plotClusterMatrix), 28  
plotClusters, 27  
plotClusters (plotClusterMatrix), 28  
plotCytoscapeGML, 6, 17, 27–30, 30, 32, 34, 36  
plotNetwork, 6, 17, 27–29, 31, 32, 34, 36  
plotPathClassifier, 6, 17, 21, 22, 25, 27–29, 31, 32, 33, 35–37, 39  
plotPathCluster, 21, 22, 25, 28, 29, 34, 34, 37, 39  
plotPaths, 6, 17, 27–29, 31, 32, 34, 35  
predictPathClassifier, 21, 22, 25, 28, 29, 34, 35, 37, 39  
predictPathCluster, 21, 22, 25, 28, 29, 34, 35, 37, 38  
  
readBiopax, 5, 9  
regex, 7, 11, 46  
registerMemoryErr, 39  
reindexNetwork, 8, 18, 19, 40, 41, 44, 47  
rmAttribute (getAttrStatus), 11  
rmSmallCompounds, 8, 18, 19, 40, 41, 44, 47  
  
SBML2igraph, 6, 16, 42  
setAttribute (getAttrStatus), 11  
simplifyReactionNetwork, 8, 18, 19, 40, 41, 44, 47  
stdAttrNames, 11, 45  
  
toGraphNEL, 46  
  
vertexDeleteReconnect, 8, 18, 19, 40, 41, 44, 47