

Package ‘BiocStyle’

October 16, 2019

Title Standard styles for vignettes and other Bioconductor documents

Description Provides standard formatting styles for Bioconductor PDF and HTML documents. Package vignettes illustrate use and functionality.

Version 2.12.0

Author Andrzej Oleś, Martin Morgan, Wolfgang Huber

Maintainer Bioconductor Package Maintainer <maintainer@bioconductor.org>

Imports bookdown, knitr (>= 1.12), rmarkdown (>= 1.2), stats, utils,
yaml, BiocManager

Suggests BiocGenerics, RUnit, htmltools

biocViews Software

License Artistic-2.0

VignetteBuilder knitr

Encoding UTF-8

URL <https://github.com/Bioconductor/BiocStyle>

BugReports <https://github.com/Bioconductor/BiocStyle/issues>

RoxygenNote 6.1.0

git_url <https://git.bioconductor.org/packages/BiocStyle>

git_branch RELEASE_3_9

git_last_commit 0fba3fe

git_last_commit_date 2019-05-02

Date/Publication 2019-10-15

R topics documented:

BiocStyle-defunct	2
helpers	2
html_document	3
latex	4
macros	5
markdown	7
md_document	7
output	8
pdf_document	9

Index**11**

BiocStyle-defunct *Defunct functions in package ‘BiocStyle’*

Description

These functions are defunct and no longer available.

Details

The following functions are no longer available; use the replacement indicated below:

- `latex_old`, `latex2`: [latex](#)
- `pdf_document_old`, `pdf_document2`: [pdf_document](#)
- `html_document_old`, `html_document2`: [html_document](#)

helpers *Specify Rmarkdown document metadata*

Description

Helper functions for including metadata in the document header.

Usage

```
pkg_ver(pkg)
doc_date()
```

Arguments

<code>pkg</code>	character(1), package name
------------------	----------------------------

Details

Use `doc_date` to include document compilation date in the document metadata field ‘date’, and `pkg_ver` for package version specification in the ‘package’ field.

Value

Markdown-formatted character string.

Author(s)

Andrzej Oleś <andrzej.oles@embl.de>, 2014-2015

Examples

```
## current date  
doc_date()  
  
## package name with version  
pkg_ver("BiocStyle")
```

html_document

Use Bioconductor style to format R Markdown HTML output

Description

Format for converting from R Markdown to an Bioconductor HTML document.

Usage

```
html_document(toc = TRUE, number_sections = TRUE, fig_width = NA,  
             fig_height = NA, self_contained = TRUE, css = NULL,  
             pandoc_args = NULL, ..., titlecaps = TRUE)
```

Arguments

<code>toc</code>	logical(1), TRUE to include a table of contents in the output
<code>number_sections</code>	logical(1), TRUE to number section headings
<code>fig_width</code>	numeric(1), default width (in inches) for figures
<code>fig_height</code>	numeric(1), default width (in inches) for figures
<code>self_contained</code>	numeric(1), TRUE to produce a standalone HTML file with no external dependencies, using data: URIs to incorporate the contents of linked scripts, stylesheets, images, and videos. Note that even for self contained documents MathJax is still loaded externally (this is necessary because of it's size).
<code>css</code>	character, one or more css files to include
<code>pandoc_args</code>	character, additional command line options to pass to pandoc
<code>...</code>	Additional arguments passed to html_document
<code>titlecaps</code>	logical(1), TRUE to use the emphasize the first sentence in figure and table captions as title

Details

`BiocStyle::html_document` format extends the [html_document](#) format. See the [online documentation](#) and the package vignette "Authoring R Markdown Vignettes" for additional details on using the format,

Value

R Markdown output format to pass to [render](#)

Author(s)

Andrzej Oleś <andrzej.oles@embl.de>, 2014-2017

See Also

[pdf_document](#), [md_document](#)

Examples

```
## Not run:

# simple invocation
render("input.Rmd", BiocStyle::html_document())

# specify options
render("input.Rmd", BiocStyle::html_document(toc = FALSE))

## End(Not run)
```

latex

Use Bioconductor style to format LaTeX vignettes

Description

This function inserts code into a document preamble to provide a consistent style to Bioconductor vignettes.

Usage

```
latex(..., width, titlecaps = TRUE, short.fignames = FALSE, fig.path,
      use.unsrurl = TRUE, relative.path = FALSE)
```

Arguments

...	Additional arguments, passed to options .
width	integer(1), maximum number of columns on a line used in printing. See options .
titlecaps	logical(1), emphasize the first sentence of float captions
short.fignames	logical(1), indicates whether \incfig figures should be inserted and referred to using short names equal to corresponding code chunk labels without any additional prefix.
fig.path	character(1), custom prefix to be used for figure file names when used with <code>knitr</code> ; has no effect when compiled with Sweave. For details see opts_chunk .
use.unsrurl	logical(1), indicating that the ‘unsrurl’ style will be used (\bibliographystyle command <i>not</i> required).
relative.path	logical(1), copy supporting LaTeX files and use relative paths rather than absolute paths to system files.

Details

Use is described in the ‘Bioconductor LaTeX Style 2.0’ vignette.

By default the ‘unsrturl’ bibliography style is used, which automatically creates links to URL, DOIs, etc. Use a different `bibliographystyle` with `use.unsrturl=FALSE` and standard LaTeX commands for styling bibliographies.

Value

The return value is a character string directing LaTeX to use the Bioconductor style file.

A side effect is setting any options specified as arguments.

Author(s)

Andrzej Oleś, Martin Morgan, Wolfgang Huber

Examples

```
## location of the .sty file
BiocStyle:::bioconductor.sty
```

macros

Link to packages on Bioconductor, CRAN and GitHub

Description

Functions for adding links to Bioconductor, CRAN and GitHub packages into R Markdown documents.

Usage

```
Biocpkg(pkg, vignette = NULL, label = pkg)
Biocannopkg(pkg)
Biocexptpkg(pkg)
CRANpkg(pkg)
Rpackage(pkg)
Githubpkg(repo, pkg)
```

Arguments

<code>pkg</code>	character(1), package name
<code>vignette</code>	character(1), basename of vignette link, including html or pdf extension, e.g., “work-0-intro.html”.
<code>label</code>	character(1) label used to identify the package or vignette.
<code>repo</code>	Repository address in the format username/repo[/subdir]

Details

Use Biocpkg for Bioconductor software, annotation, experiment data, and workflow packages. When vignette=NULL, the function automatically includes a link to the package landing page, the version of which depends on the current Bioconductor version (i.e. if run in a devel environment, it will point towards the devel landing page; otherwise it will point to the release landing page).

Use CRANpkg for R packages available on CRAN. The function automatically includes a link to the master CRAN landing page.

Use Githubpkg for R packages available on GitHub. The repo should include the repository address in the format username/repo[/subdir]. If package is missing, the package name is assumed to be equal the repository name and is extracted from repo.

For R packages which are not available on Bioconductor, CRAN or GitHub, use Rpackage.

Value

Markdown-formatted character vector containing a hyperlinked package name. If vignette != NULL, the address of the specified vignette is returned.

Author(s)

Andrzej Oleś <andrzej.oles@embl.de>, 2014-2015

Examples

```
## link to a Bioconductor software package
Biocpkg("IRanges")

## link to a Bioconductor annotation package
Biocpkg("org.Mm.eg.db")

## link to a Bioconductor experiment data package
Biocpkg("affydata")

## link to a Bioconductor workflow
Biocpkg("simpleSingleCell")
Biocpkg(
  "simpleSingleCell",
  vignette = "work-0-intro.html",
  label = "Episode 1: analyzing scRNA-seq data with R/Bioconductor"
)

## link to a CRAN package
CRANpkg("data.table")

## link to an R package on GitHub
Githubpkg("rstudio/rmarkdown")
```

markdown*Use Bioconductor CSS style to format HTML vignettes*

Description

This function sets the Bioconductor style sheet to provide a consistent style across Bioconductor HTML vignettes.

Usage

```
markdown(css.files, self.contained = TRUE, links.target = TRUE)
```

Arguments

`css.files` character vector containing the location of additional .css files.
`self.contained` logical(1), should the content of the CSS stylesheet files be included into the html file or should they be saved as separate files.
`links.target` logical(1), should external links open in new browser tab/window.

Details

Use is described in the ‘Bioconductor CSS Style’ vignette.

Value

No value is returned. The function is called for its side effect of setting the `markdown` and/or `knitr` specific options controlling the inclusion of the Bioconductor CSS style file in the HTML output.

Author(s)

Andrzej Oleś <andrzej.oles@embl.de>, 2014-2015

Examples

```
## location of the .css file  
BiocStyle:::bioconductor.css
```

md_document*Convert to a BiocStyle markdown document*

Description

Enable BiocStyle macros and author affiliations in markdown documents.

Usage

```
md_document(toc = TRUE, ...)
```

Arguments

- `toc` TRUE to include a table of contents in the output
- `...` Additional function arguments to pass to the base R Markdown [md_document](#) output formatter

Details

The `BiocStyle::md_document` format extends the base [md_document](#) format by means of specifying complex author affiliations. It also loads the `BiocStyle` package namespace to enable the use of helper functions, such as [Biocpkg](#).

Value

R Markdown output format to pass to [render](#)

Author(s)

Andrzej Oleś <andrzej.oles@embl.de>, 2015-2016

See Also

[html_document](#), [pdf_document](#)

Examples

```
## Not run:
rmarkdown::render("input.Rmd", BiocStyle::md_document())
## End(Not run)
```

Description

Helper function to determine the document's current pandoc output format.

Usage

`output()`

Details

The function is useful for defining different behavior depending on the output format, e.g. figure settings.

Value

A character string specifying the pandoc output format.

Author(s)

Andrzej Oleś <andrzej.oles@embl.de>, 2016

Examples

```
## Not run:  
## Switch between SVG and PDF figures depending on document output format  
knitr::opts_chunk$set(  
  dev = switch(output(), html = "svg", latex = "pdf")  
)  
  
## End(Not run)
```

pdf_document

Use Bioconductor style to format R Markdown PDF output

Description

This function sets the Bioconductor style in PDF documents rendered using R Markdown v2.

Usage

```
pdf_document(toc = TRUE, number_sections = TRUE, fig_width = NA,  
            fig_height = NA, includes = NULL, ..., titlecaps = TRUE,  
            toc_newpage = FALSE, use_unsrurl = TRUE, relative_path = FALSE)
```

Arguments

toc	logical(1), TRUE to include a table of contents in the output
number_sections	logical(1), TRUE to number section headings
fig_width	numeric(1), default width (in inches) for figures
fig_height	numeric(1), default width (in inches) for figures
includes	Named list of additional content to include within the document (typically created using the <code>includes</code> function).
...	Additional arguments passed to <code>pdf_document</code> .
titlecaps	logical(1), TRUE to use the emphasize the first sentence in figure and table captions as title
toc_newpage	logical(1), TRUE to start the table of contents on a new page.
use_unsrurl	logical(1), indicating that the ‘unsrurl’ style will be used (\bibliographystyle command <i>not</i> required).
relative_path	logical(1), copy supporting LaTeX files and use relative paths rather than absolute paths to system files.

Value

R Markdown output format to pass to `render`.

Author(s)

Andrzej Oleś <andrzej.oles@embl.de>, 2014-2017

See Also

[html_document](#), [md_document](#)

Examples

```
## Not run:  
  
# simple invocation  
render("input.Rmd", BiocStyle::pdf_document())  
  
# specify an option for latex engine  
render("input.Rmd", BiocStyle::pdf_document(toc = FALSE))  
  
## End(Not run)
```

Index

*Topic **manip**

- helpers, 2
- latex, 4
- markdown, 7
- pdf_document, 9

Biocannopkg (macros), 5

Biocexptpkg (macros), 5

Biocpkg, 8

Biocpkg (macros), 5

BiocStyle-defunct, 2

CRANpkg (macros), 5

doc_date (helpers), 2

Githubpkg (macros), 5

 helpers, 2

 html_document, 2, 3, 3, 8, 10

 includes, 9

 latex, 2, 4

 macros, 5

 markdown, 7

 md_document, 4, 7, 8, 10

 options, 4

 opts_chunk, 4

 output, 8

 pdf_document, 2, 4, 8, 9, 9

 pkg_ver (helpers), 2

 render, 3, 8, 9

 Rpackage (macros), 5