

Package ‘TENxPBMCData’

October 17, 2019

Title PBMC data from 10X Genomics

Version 1.2.0

Description Single-cell RNA-seq data for on PBMC cells, generated by 10X Genomics.

License CC BY 4.0

Depends SingleCellExperiment, HDF5Array

Imports AnnotationHub, ExperimentHub

Suggests knitr, BiocStyle, snow, BiocFileCache, BiocParallel

VignetteBuilder knitr

biocViews SequencingData, RNASeqData, ExpressionData, SingleCellData

NeedsCompilation no

git_url <https://git.bioconductor.org/packages/TENxPBMCData>

git_branch RELEASE_3_9

git_last_commit b35686f

git_last_commit_date 2019-05-02

Date/Publication 2019-10-17

Author Kasper D. Hansen [aut],
Davide Risso [aut],
Stephanie Hicks [aut, cre]

Maintainer Stephanie Hicks <shicks19@jhu.edu>

R topics documented:

TENxPBMCData	2
Index	4

TENxPBMCData

10X PBMC Data

Description

Various single-cell RNA-seq data on PBMC, generated by 10X Genomics.

Usage

```
TENxPBMCData(dataset = c("pbmc4k", "pbmc4k", "pbmc68k",  
                          "frozen_pbmc_donor_a", "frozen_pbmc_donor_b",  
                          "frozen_pbmc_donor_c", "pbmc33k", "pbmc3k",  
                          "pbmc6k", "pbmc4k", "pbmc8k"))
```

Arguments

dataset Which PBMC dataset from 10X Genomics should be retrieved?

Details

Single-cell RNA-seq data were generated by 10X Genomics at various times, using different versions of CellRanger, different chemistries and different genome builds. For details, see the 10X website.

We obtained ‘filtered’ data and generated SingleCellExperiment containers with data stored as an HDF5 Assay.

As rowData we include ENSEMBL and Symbol_TENx which are ENSEMBL gene ID and gene symbol provided by TENx genomics and a remapping of the Ensembl identifier to a Hugo gene symbol as columns Symbol using the org.Hs.eg.db package. The difference between Symbol and Symbol_TENx is that the former has many missing values (for non-protein coding genes) whereas the later is technically not a Hugo gene symbol.

Value

A SingleCellExperiment object with a HDF5Matrix in the counts assay, which contains UMI counts for each gene in each cell. Row- and column-level metadata are also provided.

Author(s)

Kasper D. Hansen, Stephanie Hicks, Davide Risso

References

10X Genomics (2017). 1.3 Million PBMC Cells from E18 Mice. https://support.10xgenomics.com/single-cell-gene-expression/datasets/1.3.0/1M_neurons

See Also

[SingleCellExperiment](#)

Examples

```
sce <- TENxPBMCData()  
sce  
lib.size <- colSums(assay(sce))  
hist(log10(lib.size))
```

Index

SingleCellExperiment, [2](#)

TENxPBMCData, [2](#)