

Package ‘BatchQC’

July 16, 2025

Type Package

Title Batch Effects Quality Control Software

Version 2.5.0

Date 2025-03-06

Description Sequencing and microarray samples often are collected or processed in multiple batches or at different times. This often produces technical biases that can lead to incorrect results in the downstream analysis. BatchQC is a software tool that streamlines batch preprocessing and evaluation by providing interactive diagnostics, visualizations, and statistical analyses to explore the extent to which batch variation impacts the data. BatchQC diagnostics help determine whether batch adjustment needs to be done, and how correction should be applied before proceeding with a downstream analysis. Moreover, BatchQC interactively applies multiple common batch effect approaches to the data and the user can quickly see the benefits of each method. BatchQC is developed as a Shiny App. The output is organized into multiple tabs and each tab features an important part of the batch effect analysis and visualization of the data. The BatchQC interface has the following analysis groups: Summary, Differential Expression, Median Correlations, Heatmaps, Circular Dendrogram, PCA Analysis, Shape, ComBat and SVA.

License MIT + file LICENSE

URL <https://github.com/wejlab/BatchQC>

BugReports <https://github.com/wejlab/BatchQC/issues>

Depends R (>= 4.4.0)

Imports data.table, DESeq2, dplyr, EBSeq, ggdendro, ggnewscale, ggplot2, limma, matrixStats, pheatmap, RColorBrewer, reader, reshape2, scan, shiny, shinyjs, shinythemes, stats, SummarizedExperiment, sva, S4Vectors, tibble, tidyr, tidyverse, umap, utils

Suggests BiocManager, BiocStyle, bladderbatch, devtools, knitr, lintr, plotly, rmarkdown, spelling, testthat (>= 3.0.0)

VignetteBuilder knitr

biocViews BatchEffect, GraphAndNetwork, Microarray, Normalization, PrincipalComponent, Sequencing, Software, Visualization, QualityControl, RNASeq, Preprocessing, DifferentialExpression, ImmunoOncology

Config/testthat/edition 3

Encoding UTF-8

Language en-US

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

git_url <https://git.bioconductor.org/packages/BatchQC>

git_branch devel

git_last_commit 3ab9c73

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-07-16

Author Jessica Anderson [aut, cre] (ORCID:

<<https://orcid.org/0000-0002-0542-9872>>),

W. Evan Johnson [aut] (ORCID: <<https://orcid.org/0000-0002-6247-6595>>),

Solaiappan Manimaran [aut],

Heather Selby [ctb],

Claire Ruberman [ctb],

Kwame Okrah [ctb],

Hector Corrada Bravo [ctb],

Michael Silverstein [ctb],

Regan Conrad [ctb],

Zhaorong Li [ctb],

Evan Holmes [aut],

Solomon Joseph [ctb]

Maintainer Jessica Anderson <anderson.jessica@rutgers.edu>

Contents

BatchQC	3
batchqc_explained_variation	4
batch_correct	5
batch_design	6
batch_indicator	6
bladder_data_upload	7
check_valid_input	7
color_palette	8
ComBat_correction	8
ComBat_seq_correction	9
commentary	10
confound_metrics	10
cor_props	11
counts2pvalue	12
covariates_not_confounded	12
cramers_v	13
dendrogram_alpha_numeric_check	13
dendrogram_color_palette	14
dendrogram_plotter	15
DESeq2_small_size	15

DESeq_large_analysis	16
DE_analyze	17
EV_plotter	18
EV_table	19
get.res	19
goodness_of_fit_DESeq2	20
heatmap_num_to_char_converter	21
heatmap_plotter	21
limma_correction	22
nb_histogram	23
nb_proportion	23
normalize_SE	24
PCA_plotter	25
permuted_DESeq	26
plot_data	26
possible_distances	27
possible_k_neighbors	27
preprocess	28
process_dendrogram	28
protein_data	29
protein_sample_info	29
pval_plotter	30
pval_summary	30
ratio_plotter	31
signature_data	32
std_pearson_corr_coef	32
summarized_experiment	33
sva_correction	33
umap	34
variation_ratios	35
volcano_plot	36

Index	37
--------------	-----------

BatchQC	<i>Run BatchQC shiny app</i>
---------	------------------------------

Description

Run BatchQC shiny app

Usage

BatchQC(dev = FALSE)

Arguments

dev	Run the application in developer mode
-----	---------------------------------------

Value

The shiny app will open

Examples

```
if(interactive()){  
  BatchQC()  
}
```

batchqc_explained_variation

Returns a list of explained variation by batch and condition combinations

Description

Returns a list of explained variation by batch and condition combinations

Usage

```
batchqc_explained_variation(se, batch, condition = NULL, assay_name)
```

Arguments

se	Summarized experiment object
batch	Batch covariate
condition	Condition covariate(s) of interest if desired, default is NULL
assay_name	Assay of choice

Value

List of explained variation by batch and condition

Examples

```
library(scran)  
se <- mockSCE()  
batchqc_explained_variation <- BatchQC::batchqc_explained_variation(se,  
  batch = "Mutation_Status",  
  condition = "Treatment",  
  assay_name = "counts")  
  
batchqc_explained_variation
```

batch_correct	<i>Batch Correct This function allows you to Add batch corrected count matrix to the SE object</i>
---------------	--

batch_design	<i>This function allows you to make a batch design matrix</i>
--------------	---

Description

This function allows you to make a batch design matrix

Usage

```
batch_design(se, batch, covariate)
```

Arguments

se	summarized experiment
batch	batch variable
covariate	biological covariate

Value

design table

Examples

```
library(scran)
se <- mockSCE()
batch_design_tibble <- batch_design(se, batch = "Mutation_Status",
                                     covariate = "Treatment")
batch_design_tibble
```

batch_indicator	<i>Batch and Condition indicator for signature data</i>
-----------------	---

Description

This dataset is from signature data captured when activating different growth pathway genes in human mammary epithelial cells (GEO accession: GSE73628). This data consists of three batches and ten different conditions corresponding to control and nine different pathways.

Usage

```
data(batch_indicator)
```

Format

A data frame with 89 rows and 2 variables:

batch batch
condition condition

bladder_data_upload	<i>Bladder data upload This function uploads the Bladder data set from the bladderbatch package. This dataset is from bladder cancer data with 22,283 different microarray gene expression data. It has 57 bladder samples with 3 metadata variables (batch, outcome and cancer). It contains 5 batches, 3 cancer types (cancer, biopsy, control), and 5 outcomes (Biopsy, mTCC, sTCC-CIS, sTCC+CIS, and Normal). Batch 1 contains only cancer, 2 has cancer and controls, 3 has only controls, 4 contains only biopsy, and 5 contains cancer and biopsy</i>
---------------------	--

Description

Bladder data upload This function uploads the Bladder data set from the bladderbatch package. This dataset is from bladder cancer data with 22,283 different microarray gene expression data. It has 57 bladder samples with 3 metadata variables (batch, outcome and cancer). It contains 5 batches, 3 cancer types (cancer, biopsy, control), and 5 outcomes (Biopsy, mTCC, sTCC-CIS, sTCC+CIS, and Normal). Batch 1 contains only cancer, 2 has cancer and controls, 3 has only controls, 4 contains only biopsy, and 5 contains cancer and biopsy

Usage

```
bladder_data_upload()
```

Value

a SE object with counts data and metadata

Examples

```
library(bladderbatch)
se_object <- bladder_data_upload()
```

check_valid_input	<i>Helper function to save variables as factors if not already factors</i>
-------------------	--

Description

Helper function to save variables as factors if not already factors

Usage

```
check_valid_input(se, batch, condition)
```

Arguments

se	se object
batch	batch
condition	condition

Value

se se object

color_palette	<i>Color palette</i>
---------------	----------------------

Description

This function creates the base color palette used in BatchQC

Usage

```
color_palette(n, first_hue = 25, last_hue = 360)
```

Arguments

- n numeric object representing number of colors to be created
- first_hue numeric object to set the first hue value
- last_hue numeric object to set the final hue value

Value

color_list list of colors generated

Examples

```
library(scran)
n <- 100
color_list <- color_palette(n)
color_list
```

ComBat_correction	<i>ComBat Correction This function applies ComBat correction to your summarized experiment object</i>
-------------------	---

Description

ComBat Correction This function applies ComBat correction to your summarized experiment object

Usage

```
ComBat_correction(se, assay_to_normalize, batch, covar, output_assay_name)
```


Arguments

se	SummarizedExperiment object
assay_to_normalize	Assay that should be corrected
batch	The variable that represents batch
covar	list of covariates
output_assay_name	name of results assay

Value

SE object with an added ComBat corrected array

ComBat_seq_correction	<i>ComBat-Seq Correction This function applies ComBat-seq correction to your summarized experiment object</i>
-----------------------	---

Description

ComBat-Seq Correction This function applies ComBat-seq correction to your summarized experiment object

Usage

```
ComBat_seq_correction(se, assay_to_normalize, batch, group, covar,
output_assay_name)
```

Arguments

se	SummarizedExperiment object
assay_to_normalize	Assay that should be corrected
batch	The variable that represents batch
group	The group variable
covar	list of covariates
output_assay_name	name of results assay

Value

SE object with an added ComBat-seq corrected array

commentary	<i>This function creates the commentary recommendation when there are more than 20 samples.</i>
------------	---

Description

This function creates the commentary recommendation when there are more than 20 samples.

Usage

```
commentary(
  nb_fit,
  nb_fit_pval,
  count_below_value,
  count_below_value_pval,
  low_pval
)
```

Arguments

nb_fit	Boolean representing if the count is below the threshold
nb_fit_pval	Boolean representing if the p-val count is below threshold
count_below_value	number of features below threshold
count_below_value_pval	number of features below p-val threshold
low_pval	pval threshold

Value

a commentary string statement

confound_metrics	<i>Combine std. Pearson correlation coefficient and Cramer's V</i>
------------------	--

Description

Combine std. Pearson correlation coefficient and Cramer's V

Usage

```
confound_metrics(se, batch)
```

Arguments

se	summarized experiment
batch	batch variable

Value

metrics of confounding

Examples

```
library(scran)
se <- mockSCE()
confound_table <- BatchQC::confound_metrics(se, batch = "Mutation_Status")
confound_table
```

cor_props

This function allows you to calculate correlation properties

Description

This function allows you to calculate correlation properties

Usage

```
cor_props(bd)
```

Arguments

bd batch design

Value

correlation properties

Examples

```
library(scran)
se <- mockSCE()
batch_design_tibble <- batch_design(se, batch = "Mutation_Status",
                                     covariate = "Treatment")
correlation_property <- BatchQC::cor_props(batch_design_tibble)
correlation_property
```

counts2pvalue	<i>This function calculates p-values for each gene given counts, estimated NB size, and estimated NB mean</i>
---------------	---

Description

This function calculates p-values for each gene given counts, estimated NB size, and estimated NB mean

Usage

```
counts2pvalue(counts, size, mu)
```

Arguments

counts	a vector of gene expression values (in counts)
size	an estimated size parameter of the NB distributions for the gene
mu	a vector of estimated mu parameter of the NB distributions for different samples of the gene

Value

a p-value based on estimated NB size and mean

covariates_not_confounded	<i>Returns list of covariates not confounded by batch; helper function for explained variation and for populating shiny app condition options</i>
---------------------------	---

Description

Returns list of covariates not confounded by batch; helper function for explained variation and for populating shiny app condition options

Usage

```
covariates_not_confounded(se, batch)
```

Arguments

se	Summarized experiment object
batch	Batch variable

Value

List of explained variation by batch and condition

Examples

```
library(scran)
se <- mockSCE()
covariates_not_confounded <- BatchQC::covariates_not_confounded(se,
                                                                batch = "Mutation_Status")
covariates_not_confounded
```

cramers_v

*This function allows you to calculate Cramer's V***Description**

This function allows you to calculate Cramer's V

Usage

```
cramers_v(bd)
```

Arguments

bd batch design

Value

Cramer's V

Examples

```
library(scran)
se <- mockSCE()
batch_design_tibble <- batch_design(se, batch = "Mutation_Status",
                                   covariate = "Treatment")
cramers_v_result <- BatchQC::cramers_v(batch_design_tibble)
cramers_v_result
```

dendrogram_alpha_numeric_check

*Dendrogram alpha or numeric checker***Description**

This function checks if there is any numeric or strings for plotting legend

Usage

```
dendrogram_alpha_numeric_check(dendro_var)
```

Arguments

dendro_var column from dendrogram object representing category

Value

geom_label label for the legend of category variable

Examples

```
library(scran)
se <- mockSCE()
dendro_alpha_numeric_check <- dendrogram_alpha_numeric_check(
  dendro_var = "Treatment")
dendro_alpha_numeric_check
```

dendrogram_color_palette

Dendrogram color palette

Description

This function creates the color palette used in the dendrogram plotter

Usage

```
dendrogram_color_palette(col, dendrogram_info)
```

Arguments

col string object representing color of the label
dendrogram_info dendrogram_ends object

Value

annotation_color vector of colors corresponding to col variable

Examples

```
library(scran)
se <- mockSCE()
process_dendro <- BatchQC::process_dendrogram(se, "counts")
dendrogram_ends <- process_dendro$dendrogram_ends
col <- process_dendro$condition_var
dendro_colors <- dendrogram_color_palette(col = "Treatment",
  dendrogram_info = dendrogram_ends)
dendro_colors
```

dendrogram_plotter	<i>Dendrogram Plot</i>
--------------------	------------------------

Description

This function creates a dendrogram plot

Usage

```
dendrogram_plotter(se, assay, batch_var, category_var)
```

Arguments

se	SummarizedExperiment object
assay	assay to plot
batch_var	sample metadata column representing batch
category_var	sample metadata column representing category of interest

Value

named list of dendrogram plots
 dendrogram is a dendrogram ggplot
 circular_dendrogram is a circular dendrogram ggplot

Examples

```
library(scran)
se <- mockSCE()
dendrogram_plot <- BatchQC::dendrogram_plotter(se,
                                                "counts",
                                                "Mutation_Status",
                                                "Treatment")

dendrogram_plot$dendrogram
dendrogram_plot$circular_dendrogram
```

DESeq2_small_size	<i>This function calculated the goodness of fit of DESeq2 for small sample sizes (intended for less than 20 samples).</i>
-------------------	---

Description

This function calculated the goodness of fit of DESeq2 for small sample sizes (intended for less than 20 samples).

Usage

```
DESeq2_small_size(
  count_matrix,
  condition,
  other_variables,
  conditions_df,
  formula_for_DESeq,
  num_samples
)
```

Arguments

count_matrix	matrix containing the data to be analyzed
condition	a vector containing a factor of the condition of interest (typically batch)
other_variables	a vector of strings of other variables of interest
conditions_df	data frame containing information for the other variables of interest (columns in order of the other_variables vector)
formula_for_DESeq	the stat formula to be used in the DESeq analysis
num_samples	total number of samples to analyze

Value

a list containing the string recommendation, the histogram and a reference for the original source of the test

DESeq_large_analysis	<i>This function calculated the goodness of fit of DESeq2 for larger sample sizes (intended for more than 20 samples).</i>
----------------------	--

Description

This function calculated the goodness of fit of DESeq2 for larger sample sizes (intended for more than 20 samples).

Usage

```
DESeq_large_analysis(
  count_matrix,
  condition,
  other_variables,
  conditions_df,
  formula_for_DESeq,
  num_samples,
  sampled
)
```


Arguments

count_matrix	matrix containing the data to be analyzed
condition	a vector containing a factor of the condition of interest (typically batch)
other_variables	a vector of strings of other variables of interest
conditions_df	data frame containing information for the other variables of interest (columns in order of the other_variables vector)
formula_for_DESeq	the stat formula to be used in the DESeq analysis
num_samples	total number of samples to analyze
sampled	the down sampled matrix

Value

a list containing the string recommendation

DE_analyze	<i>Differential Expression Analysis</i>
------------	---

Description

This function runs DE analysis on a count matrix (DESeq) or a normalized log or log-CPM matrix (limma) contained in the se object

Usage

```
DE_analyze(se, method, batch, conditions, assay_to_analyze)
```

Arguments

se	SummarizedExperiment object
method	DE analysis method option (either 'DESeq2' or 'limma')
batch	metadata column in the se object representing batch
conditions	metadata columns in the se object representing additional analysis covariates
assay_to_analyze	Assay in the se object (either counts for DESeq2 or normalized data for limma) for DE analysis

Value

A named list containing the log2FoldChange, pvalue and adjusted pvalue (padj) for each analysis returned by DESeq2 or limma

Examples

```
library(scran)
se <- mockSCE()
differential_expression <- BatchQC::DE_analyze(se = se,
                                              method = "DESeq2",
                                              batch = "Treatment",
                                              conditions = c(
                                                "Mutation_Status"),
                                              assay_to_analyze = "counts")

pval_summary(differential_expression)
pval_plotter(differential_expression)
```

EV_plotter

This function allows you to plot explained variation

Description

This function allows you to plot explained variation

Usage

```
EV_plotter(batchqc_ev)
```

Arguments

batchqc_ev table of explained variation from batchqc_explained_variation

Value

boxplot of explained variation

Examples

```
library(scran)
se <- mockSCE()
se$Mutation_Status <- as.factor(se$Mutation_Status)
se$Treatment <- as.factor(se$Treatment)
expl_var_result <- batchqc_explained_variation(se, batch = "Mutation_Status",
                                              condition = "Treatment", assay_name = "counts")
EV_boxplot <- BatchQC::EV_plotter(expl_var_result[[1]])
EV_boxplot
```

EV_table	<i>EV Table Returns table with percent variation explained for specified number of genes</i>
----------	--

Description

EV Table Returns table with percent variation explained for specified number of genes

Usage

```
EV_table(batchqc_ev)
```

Arguments

batchqc_ev explained variation results from batchqc_explained_variation

Value

List of explained variation by batch and condition

Examples

```
library(scran)
se <- mockSCE()
se$Mutation_Status <- as.factor(se$Mutation_Status)
se$Treatment <- as.factor(se$Treatment)
exp_var_result <- BatchQC::batchqc_explained_variation(se,
  batch = "Mutation_Status",
  condition = "Treatment",
  assay_name = "counts")
EV_table <- BatchQC::EV_table(exp_var_result[[1]])

EV_table
```

get.res	<i>Helper function to get residuals</i>
---------	---

Description

Helper function to get residuals

Usage

```
get.res(y, X)
```

Arguments

y assay
X model matrix design

Value

residuals

goodness_of_fit_DESeq2

This function calculates goodness-of-fit pvalues for all genes by looking at how the NB model by DESeq2 fit the data

Description

This function calculates goodness-of-fit pvalues for all genes by looking at how the NB model by DESeq2 fit the data

Usage

```
goodness_of_fit_DESeq2(
  se,
  count_matrix,
  condition,
  other_variables = NULL,
  num_genes = 500
)
```

Arguments

se	the se object where all the data is contained
count_matrix	name of the assay with gene expression matrix (in counts)
condition	name of the se colData with the condition status
other_variables	name of the se colData containing other variables of interest that should be considered in the DESeq2 model
num_genes	downsample value, default is 500 (or all genes if less)

Value

a matrix of pvalues where each row is a gene and each column is a level within the condition of interest

Examples

```
# example code
library(scran)
se <- mockSCE(ncells = 20)
se$Treatment <- as.factor(se$Treatment)
se$Mutation_Status <- as.factor(se$Mutation_Status)
nb_results <- goodness_of_fit_DESeq2(se = se, count_matrix = "counts",
  condition = "Treatment", other_variables = "Mutation_Status")
nb_results[1]
nb_results[2]
nb_results[3]
```

```
heatmap_num_to_char_converter
```

Heatmap numeric to character converter

Description

This function converts any found numerics to characters

Usage

```
heatmap_num_to_char_converter(ann_col)
```

Arguments

ann_col column data of heatmap

Value

ann_col modified column data of heatmap

Examples

```
library(scran)
se <- mockSCE()
col_info <- colData(se)
ann_col <- heatmap_num_to_char_converter(ann_col = col_info)
ann_col
```

```
heatmap_plotter              Heatmap Plotter
```

Description

This function allows you to plot a heatmap

Usage

```
heatmap_plotter(se, assay, nfeature, annotation_column, log_option)
```

Arguments

se	SummarizedExperiment
assay	normalized or corrected assay
nfeature	number of features to display
annotation_column	choose column
log_option	TRUE if data should be logged before plotting (recommended for sequencing counts), FALSE if data should not be logged (for instance, data is already logged)

Value

heatmap plot

Examples

```
library(scran)
se <- mockSCE()
heatmaps <- BatchQC::heatmap_plotter(se,
                                     assay = "counts",
                                     nfeature = 15,
                                     annotation_column = c("Mutation_Status",
                                                            "Treatment"), log_option = FALSE)
correlation_heatmap <- heatmaps$correlation_heatmap
correlation_heatmap

heatmap <- heatmaps$topn_heatmap
heatmap
```

limma_correction	<i>Limma Correction This function applies limma batch correction to your provided assay</i>
------------------	---

Description

Limma Correction This function applies limma batch correction to your provided assay

Usage

```
limma_correction(se, assay_to_normalize, batch, covar, output_assay_name)
```

Arguments

se	SummarizedExperiment object
assay_to_normalize	Log assay that should be corrected
batch	Factor containing batch information
covar	list of covariates
output_assay_name	name of results assay

Value

SE object with an added limma corrected array

nb_histogram	<i>This function creates a histogram from the negative binomial goodness-of-fit adjusted pvalues.</i>
--------------	---

Description

This function creates a histogram from the negative binomial goodness-of-fit adjusted pvalues.

Usage

```
nb_histogram(adj_p_val_table)
```

Arguments

adj_p_val_table
table of adjusted p-values from the nb test

Value

a histogram of the number of genes within a p-value range

nb_proportion	<i>This function determines the proportion of p-values below a specific value and compares to the previously determined threshold of 0.42 for extreme low values.</i>
---------------	---

Description

This function determines the proportion of p-values below a specific value and compares to the previously determined threshold of 0.42 for extreme low values.

Usage

```
nb_proportion(
  adj_p_val_table,
  p_val_table,
  low_pval = 0.01,
  threshold = 0.42,
  num_samples
)
```

Arguments

adj_p_val_table
table of adjusted p-values from the nb test

p_val_table
table of p-values from the nb test

low_pval
value of the p-value cut off to use in proportion

threshold
the value to compare the proportion of p-values to for data sets less than 20, default is 0.42

num_samples
the number of samples in the analysis

Value

a statement about whether DESeq2 is appropriate to use for analysis

normalize_SE	<i>This function allows you to add normalized count matrix to the SE object</i>
--------------	---

Description

This function allows you to add normalized count matrix to the SE object

Usage

```
normalize_SE(se, method, log_bool, assay_to_normalize, output_assay_name)
```

Arguments

se	SummarizedExperiment Object
method	Normalization Method, either 'CPM' or 'DESeq' or 'none' for log only
log_bool	True or False; True to log normalize the data set after normalization method
assay_to_normalize	Which SE assay to do normalization on
output_assay_name	name for the resulting normalized assay

Value

the original SE object with normalized assay appended

Examples

```
library(scran)
se <- mockSCE()
se_CPM_normalized <- BatchQC::normalize_SE(se, method = "CPM",
                                           log_bool = FALSE,
                                           assay_to_normalize = "counts",
                                           output_assay_name =
                                             "CPM_normalized_counts")
se_DESeq_normalized <- BatchQC::normalize_SE(se, method = "DESeq",
                                           log_bool = FALSE,
                                           assay_to_normalize = "counts",
                                           output_assay_name =
                                             "DESeq_normalized_counts")

se_CPM_normalized
se_DESeq_normalized
```


PCA_plotter

*This function allows you to plot PCA***Description**

This function allows you to plot PCA

Usage

```
PCA_plotter(se, nfeature, color, shape, batch, assays, xaxisPC,
            yaxisPC, log_option = FALSE)
```

Arguments

se	SummarizedExperiment object
nfeature	number of features
color	choose a color
shape	choose a shape
batch	variable representing batch (for ellipses)
assays	array of assay names from se
xaxisPC	the PC to plot as the x axis
yaxisPC	the PC to plot as the y axis
log_option	TRUE if data should be logged before plotting (recommended for sequencing counts), FALSE if data should not be logged (for instance, data is already logged); FALSE by default

Value

List containing PCA info, PCA variance and PCA plot

Examples

```
library(scran)
se <- mockSCE()
se_object_ComBat_Seq <- BatchQC::batch_correct(se, method = "ComBat-Seq",
                                              assay_to_normalize = "counts",
                                              batch = "Mutation_Status",
                                              covar = "Treatment",
                                              output_assay_name =
                                                "ComBat_Seq_Corrected")
pca_plot <- BatchQC::PCA_plotter(se = se_object_ComBat_Seq,
                                nfeature = 2, color = "Mutation_Status",
                                shape = "Treatment", batch = "batch",
                                assays = c("counts", "ComBat_Seq_Corrected"),
                                xaxisPC = 1, yaxisPC = 2, log_option = FALSE)

pca_plot$plot
pca_plot$var_explained
```

permuted_DESeq	<i>This function performs DESeq on the permuted dataset adjusted p-values.</i>
----------------	--

Description

This function performs DESeq on the permuted dataset adjusted pvalues.

Usage

```
permuted_DESeq(
  count_matrix,
  condition,
  other_variables,
  conditions_df,
  formula_for_DESeq
)
```

Arguments

count_matrix	matrix containing the data to be analyzed
condition	a vector containing a factor of the condition of interest (typically batch)
other_variables	a vector of strings of other variables of interest
conditions_df	data frame containing information for the other variables of interest (columns in order of the other_variables vector)
formula_for_DESeq	the stat formula to be used in the DESeq analysis

Value

a DESeq2 object

plot_data	<i>This function formats the PCA plot using ggplot</i>
-----------	--

Description

This function formats the PCA plot using ggplot

Usage

```
plot_data(pca_plot_data, color, shape, batch, xaxisPC, yaxisPC)
```

Arguments

pca_plot_data	Data for all assays to plot
color	variable that will be plotted as color
shape	variable that will be plotted as shape
batch	variable representing batch for the ellipses
xaxisPC	the PC to plot as the x axis
yaxisPC	the PC to plot as the y axis

Value

PCA plot

possible_distances	<i>Create pottential min_distance values for exploratory analysis based on the value of spread</i>
--------------------	--

Description

Create pottential min_distance values for exploratory analysis based on the value of spread

Usage

```
possible_distances(spread)
```

Arguments

spread	numeric; the value of spread used in the exploratory analysis
--------	---

Value

vector of min_distance values to use in exploratory analysis

possible_k_neighbors	<i>Create a vector of possible nearest neighbor values from 5, 15, 25, 50, and 100</i>
----------------------	--

Description

Create a vector of possible nearest neighbor values from 5, 15, 25, 50, and 100

Usage

```
possible_k_neighbors(data_size)
```

Arguments

data_size	size of the data set used to create umaps
-----------	---

Value

k nearest neighbor list

preprocess	<i>Preprocess assay data</i>
------------	------------------------------

Description

Preprocess assay data

Usage

```
preprocess(se, assay, nfeature, log_option)
```

Arguments

se	Summarized Experiment object
assay	Assay from SummarizedExperiment object
nfeature	Number of variable features to use
log_option	"True" if data should be logged, "False" otherwise

Value

Returns processed data

process_dendrogram	<i>Process Dendrogram</i>
--------------------	---------------------------

Description

This function processes count data for dendrogram plotting

Usage

```
process_dendrogram(se, assay)
```

Arguments

se	SummarizedExperiment object
assay	assay to plot

Value

named list of dendrogram data
dendrogram_segments is data representing segments of the dendrogram
dendrogram_ends is data representing ends of the dendrogram

Examples

```
library(scran)
se <- mockSCE()
process_dendro <- BatchQC::process_dendrogram(se, "counts")
process_dendro
```

protein_data	<i>Protein data with 39 protein expression levels</i>
--------------	---

Description

This data consists of two batches and two conditions corresponding to case and control. The columns are case/control samples, and the rows represent 39 different proteins.

Usage

```
data(protein_data)
```

Format

A data frame with 39 rows and 24 variables

protein_sample_info	<i>Batch and Condition indicator for protein expression data</i>
---------------------	--

Description

This data consists of two batches and two conditions corresponding to case and control for the protein expression data

Usage

```
data(protein_sample_info)
```

Format

A data frame with 24 rows and 2 variables:

batch Batch Indicator

category Condition (Case vs Control) Indicator

pval_plotter	<i>P-value Plotter This function allows you to plot p-values of explained variation</i>
--------------	---

Description

P-value Plotter This function allows you to plot p-values of explained variation

Usage

```
pval_plotter(DE_results)
```

Arguments

DE_results Differential Expression analysis result (a named list of dataframes corresponding to each analysis completed with a "pvalue" column)

Value

boxplots of pvalues for each condition

Examples

```
library(scran)
se <- mockSCE()
differential_expression <- BatchQC::DE_analyze(se = se,
                                              method = "DESeq2",
                                              batch = "Treatment",
                                              conditions = c(
                                                "Mutation_Status"),
                                              assay_to_analyze = "counts")

pval_summary(differential_expression)
pval_plotter(differential_expression)
```

pval_summary	<i>Returns summary table for p-values of explained variation</i>
--------------	--

Description

Returns summary table for p-values of explained variation

Usage

```
pval_summary(res_list)
```

Arguments

res_list Differential Expression analysis result (a named list of dataframes corresponding to each analysis completed with a "pvalue" column)

Value

summary table for p-values of explained variation for each analysis

Examples

```
library(scran)
se <- mockSCE()
differential_expression <- BatchQC::DE_analyze(se = se,
                                              method = "DESeq2",
                                              batch = "Treatment",
                                              conditions = c(
                                                "Mutation_Status"),
                                              assay_to_analyze = "counts")

pval_summary(differential_expression)
```

ratio_plotter

This function allows you to plot ratios of explained variation

Description

This function allows you to plot ratios of explained variation

Usage

```
ratio_plotter(ev_ratio)
```

Arguments

ev_ratio table of ratios from variation_ratios()

Value

boxplot of ratios

Examples

```
library(scran)
se <- mockSCE()
se$Mutation_Status <- as.factor(se$Mutation_Status)
se$Treatment <- as.factor(se$Treatment)
expl_var_result <- batchqc_explained_variation(se, batch = "Mutation_Status",
                                              condition = "Treatment", assay_name = "counts")
ratios_results <- variation_ratios(expl_var_result[[1]],
                                  batch = "Mutation_Status")
ratio_boxplot <- BatchQC::ratio_plotter(ratios_results)
ratio_boxplot
```

signature_data

*Signature data with 1600 gene expression levels***Description**

This data consists of three batches and ten conditions. The columns are samples, and the rows represent 1600 different genes.

Usage

```
data(signature_data)
```

Format

A data frame with 1600 rows and 89 variables

std_pearson_corr_coef *Calculate a standardized Pearson correlation coefficient***Description**

Calculate a standardized Pearson correlation coefficient

Usage

```
std_pearson_corr_coef(bd)
```

Arguments

bd batch design

Value

standardized Pearson correlation coefficient

Examples

```
library(scran)
se <- mockSCE()
batch_design_tibble <- batch_design(se, batch = "Mutation_Status",
                                   covariate = "Treatment")
pearson_cor_result <- BatchQC::std_pearson_corr_coef(batch_design_tibble)
pearson_cor_result
```

summarized_experiment	<i>This function creates a summarized experiment object from count and metadata files uploaded by the user</i>
-----------------------	--

Description

This function creates a summarized experiment object from count and metadata files uploaded by the user

Usage

```
summarized_experiment(counts, columndata)
```

Arguments

counts	counts dataframe
columndata	metadata dataframe

Value

a summarized experiment object

Examples

```
data(protein_data)
data(protein_sample_info)
se_object <- summarized_experiment(protein_data, protein_sample_info)
```

sva_correction	<i>sva Correction This function applies sva correction to a summarized experiment object (implementation adapted from sva::psva)</i>
----------------	--

Description

sva Correction This function applies sva correction to a summarized experiment object (implementation adapted from sva::psva)

Usage

```
sva_correction(
  se,
  assay_to_normalize,
  var_of_interest,
  covar,
  output_assay_name
)
```

Arguments

se	SummarizedExperiment object
assay_to_normalize	Assay that should be corrected
var_of_interest	The experimental variable of interest
covar	list of covariates to include in sva analysis
output_assay_name	name of results assay

Value

SE object with an added sva corrected array

umap	<i>Create a umap plot; wrapper function for umap package pplus custom plotting</i>
------	--

Description

Create a umap plot; wrapper function for umap package pplus custom plotting

Usage

```
umap(
  se_object,
  assay_of_interest,
  batch,
  neighbors = 15,
  min_distance = 0.1,
  spread = 1,
  exploratory = FALSE
)
```

Arguments

se_object	se_object; containing data of interest
assay_of_interest	string; the assay in the se_object to plot
batch	string; representing batch
neighbors	integer; number of nearest neighbors, default 15 per umap; lower values prioritize local structure, higher values will represent bigger picture but lose finer details
min_distance	numeric; how close points appear in final layout; higher values puts less emphasis on global structure; must be less than spread
spread	numeric; dispersion of points in umap
exploratory	Boolean; default is FALSE, if True, a 5x5 grid with k = 15, 25, 50, 100 and min_distance = 0.1, .2, .5, .75, .99 will be plotted

Value

umap plot

Examples

```
library(scran)
se <- mockSCE()
se$Treatment <- as.factor(se$Treatment)
se$Mutation_Status <- as.factor(se$Mutation_Status)
umap_plot <- BatchQC::umap(se_object = se, assay_of_interest = "counts",
batch = "Treatment")
umap_plot
```

variation_ratios	<i>Creates Ratios of batch to variable variation statistic</i>
------------------	--

Description

Creates Ratios of batch to variable variation statistic

Usage

```
variation_ratios(ex_variation_table, batch)
```

Arguments

ex_variation_table	table of explained variation results from batchqc_explained_variation
batch	batch

Value

dataframe with condition/batch ratios

Examples

```
library(scran)
se <- mockSCE()
se$Mutation_Status <- as.factor(se$Mutation_Status)
se$Treatment <- as.factor(se$Treatment)
expl_var_result <- batchqc_explained_variation(se, batch = "Mutation_Status",
condition = "Treatment", assay_name = "counts")
ratios_results <- variation_ratios(expl_var_result[[1]],
batch = "Mutation_Status")
ratios_results
```

volcano_plot

*Volcano plot***Description**

This function allows you to plot DE analysis results as a volcano plot

Usage

```
volcano_plot(DE_results, pslider = 0.05, fcslider)
```

Arguments

DE_results	a dataframe with the results of one of the DE Analysis; must include "log2FoldChange" and "pvalue" columns
pslider	Magnitude of significance value threshold, default is 0.05
fcslider	Magnitude of expression change value threshold

Value

A volcano plot of expression change and significance value data

Examples

```
library(scran)
se <- mockSCE()
differential_expression <- BatchQC::DE_analyze(se = se,
                                              method = "DESeq2",
                                              batch = "Treatment",
                                              conditions = c(
                                                "Mutation_Status",
                                                "Cell_Cycle"),
                                              assay_to_analyze = "counts")

value <- round((max(abs(
  differential_expression[[length(differential_expression)]][, 1]))
+ min(abs(
  differential_expression[[length(differential_expression)]][, 1])) / 2)

volcano_plot(differential_expression[[1]], pslider = 0.05, fcslider = value)
```

Index

- * **Internal**
 - check_valid_input, [7](#)
- * **datasets**
 - batch_indicator, [6](#)
 - protein_data, [29](#)
 - protein_sample_info, [29](#)
 - signature_data, [32](#)
- * **internal**
 - counts2pvalue, [12](#)
- batch_correct, [5](#)
- batch_design, [6](#)
- batch_indicator, [6](#)
- BatchQC, [3](#)
- batchqc_explained_variation, [4](#)
- bladder_data_upload, [7](#)
- check_valid_input, [7](#)
- color_palette, [8](#)
- ComBat_correction, [8](#)
- ComBat_seq_correction, [9](#)
- commentary, [10](#)
- confound_metrics, [10](#)
- cor_props, [11](#)
- counts2pvalue, [12](#)
- covariates_not_confounded, [12](#)
- cramers_v, [13](#)
- DE_analyze, [17](#)
- dendrogram_alpha_numeric_check, [13](#)
- dendrogram_color_palette, [14](#)
- dendrogram_plotter, [15](#)
- DESeq2_small_size, [15](#)
- DESeq_large_analysis, [16](#)
- EV_plotter, [18](#)
- EV_table, [19](#)
- get.res, [19](#)
- goodness_of_fit_DESeq2, [20](#)
- heatmap_num_to_char_converter, [21](#)
- heatmap_plotter, [21](#)
- limma_correction, [22](#)
- nb_histogram, [23](#)
- nb_proportion, [23](#)
- normalize_SE, [24](#)
- PCA_plotter, [25](#)
- permuted_DESeq, [26](#)
- plot_data, [26](#)
- possible_distances, [27](#)
- possible_k_neighbors, [27](#)
- preprocess, [28](#)
- process_dendrogram, [28](#)
- protein_data, [29](#)
- protein_sample_info, [29](#)
- pval_plotter, [30](#)
- pval_summary, [30](#)
- ratio_plotter, [31](#)
- signature_data, [32](#)
- std_pearson_corr_coef, [32](#)
- summarized_experiment, [33](#)
- sva_correction, [33](#)
- umap, [34](#)
- variation_ratios, [35](#)
- volcano_plot, [36](#)