

Package ‘RiboCrypt’

July 18, 2025

Type Package

Title Interactive visualization in genomics

Version 1.15.2

License MIT + file LICENSE

Description R Package for interactive visualization and browsing NGS data.

It contains a browser for both transcript and genomic coordinate view.

In addition a QC and general metaplots are included, among others differential translation plots and gene expression plots. The package is still under development.

biocViews Software, Sequencing, RiboSeq, RNASeq,

Encoding UTF-8

LazyData true

BugReports <https://github.com/m-swirski/RiboCrypt/issues>

URL <https://github.com/m-swirski/RiboCrypt>

Depends R (>= 3.6.0), ORFik (>= 1.13.12)

Imports bslib, BiocGenerics, BiocParallel, Biostrings, ComplexHeatmap, cowplot, crosstalk, data.table, dplyr, DT, fst, GenomeInfoDb, GenomicFeatures, GenomicRanges, ggplot2, grid, htmlwidgets, httr, IRanges, jsonlite, knitr, markdown, NGLViewR, plotly, rlang, rclipboard, RCurl, rtracklayer, shiny, shinycssloaders, shinyhelper, shinyjs, shinyjqui, shinyWidgets, stringr, writexl

Suggests testthat, rmarkdown, BiocStyle, BSgenome, BSgenome.Hsapiens.UCSC.hg19

RoxygenNote 7.3.1

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/RiboCrypt>

git_branch devel

git_last_commit 5432893

git_last_commit_date 2025-07-14

Repository Bioconductor 3.22

Date/Publication 2025-07-17

Author Michal Swirski [aut, cre, cph],
Haakon Tjeldnes [aut, ctb],
Kornel Labun [ctb]

Maintainer Michal Swirski <michal.swirski@uw.edu.pl>

Contents

antisense	2
browseRC	3
collection_dir_from_exp	4
collection_path_from_exp	5
collection_to_wide	5
compute_collection_table	6
createSeqPanelPattern	7
DEG_plot	8
fetch_JS_seq	9
fetch_summary	10
geneTrackLayer	10
getCoverageProfile	11
getIndexes	11
get_meta_browser_plot_full	12
ggplotlyHover	13
load_collection	13
make_rc_url	14
matchMultiplePatterns	15
matchToGRanges	15
multiOmicsPlot_animate	16
multiOmicsPlot_list	18
multiOmicsPlot_ORFikExp	21
normalize_collection	24
organism_input_select	25
RiboCrypt_app	25
trimOverlaps	27
Index	28

antisense

Get antisense

Description

Get antisense

Usage

```
antisense(grl)
```

Value

a GRangesList

browseRC

*Browse a gene on Ribocrypt webpage***Description**

Can also display local RiboCrypt app if specified in the 'host' argument.

Usage

```

browseRC(
  symbol = NULL,
  gene_id = NULL,
  tx_id = NULL,
  exp = "all_merged-Homo_sapiens_modalities",
  libraries = NULL,
  leader_extension = 0,
  trailer_extension = 0,
  viewMode = FALSE,
  other_tx = FALSE,
  plot_on_start = TRUE,
  frames_type = "columns",
  kmer = 1,
  add_translons = FALSE,
  zoom_range = NULL,
  host = "https://ribocrypt.org",
  browser = getOption("browser")
)

```

Arguments

symbol	gene symbol, default NULL
gene_id	gene symbol, default NULL
tx_id	gene symbol, default NULL
exp	experiment name, default "all_merged-Homo_sapiens_modalities"
libraries	NULL, default to first in experiment, c("RFP","RNA") would add RNA to default.
leader_extension	integer, default 0. (How much to extend view upstream)
trailer_extension	integer, default 0. (How much to extend view downstream)
viewMode	FALSE (transcript view), TRUE gives genomic.
other_tx	FALSE, show all other annotation in region (isoforms etc.)
plot_on_start	logical, default TRUE. Plot gene when opening browser.
frames_type	"columns"
kmer	integer, default 1 (no binning), binning size of windows, to smear out the signal.
add_translons	logical, default FALSE. If TRUE, add translons predicted sequences in annotation.

zoom_range	character, zoom values.
host	url, default "https://ribocrypt.org". Set to localhost for local version.
browser	getOption("browser")

Value

browseURL, opens browse with page

Examples

```
browseRC("ATF4", "ENSG00000128272")
```

collection_dir_from_exp	<i>Get collection directory</i>
-------------------------	---------------------------------

Description

Get collection directory

Usage

```
collection_dir_from_exp(df, must_exists = FALSE, new_format = TRUE)
```

Arguments

df	ORFik experiment
must_exists	logical, stop if dir does not exists
new_format	logical, TRUE is new or old fst format (FALSE)

Value

file.path(resFolder(df), "collection_tables")

Examples

```
df <- ORFik.template.experiment()
collection_dir_from_exp(df)
```

```
collection_path_from_exp
```

Get collection path

Description

For directory and id, must be fst format file

Usage

```
collection_path_from_exp(
  df,
  id,
  gene_name_list = NULL,
  must_exists = TRUE,
  collection_dir = collection_dir_from_exp(df, must_exists),
  grl_all = loadRegion(df)
)
```

Arguments

df ORFik experiment

id character, transcript ids

gene_name_list a data.table, default NULL, with gene ids

must_exists logical, stop if dir does not exists

collection_dir = collection_dir_from_exp(df, must_exists)

grl_all a GRangesList for new format, what genomic range to get.

Value

file.path(resFolder(df), "collection_tables")

Examples

```
df <- ORFik.template.experiment()
tx_id <- "ENST0000012312"
collection_path_from_exp(df, id = tx_id, must_exists = FALSE)
```

```
collection_to_wide      Cast a collection table to wide format
```

Description

Cast a collection table to wide format

Usage

```
collection_to_wide(table, value.var = "logscore")
```

Arguments

table	a data.table in long format
value.var	which column to use as scores, default "logscore"

Value

a table in wide format

compute_collection_table

Get collection table normalized in wide format

Description

Get collection table normalized in wide format

Usage

```
compute_collection_table(
  path,
  lib_sizes,
  df,
  metadata_field,
  normalization,
  kmer,
  metadata,
  min_count = 0,
  format = "wide",
  value.var = "logscore",
  as_list = FALSE,
  subset = NULL,
  group_on_tx_tpm = NULL,
  split_by_frame = FALSE,
  ratio_interval = NULL,
  decreasing_order = FALSE
)
```

Arguments

path	the path to gene counts
lib_sizes	named integer vector, default NULL. If given will do a pre tpm normalization for full library sizes
df	the ORFik experiment to load the precomputed collection from. It must also have defined runIDs() for all samples.
metadata_field	the column name in metadata, to select to group on.
normalization	a character string, which mode, for options see RiboCrypt::normalizations
kmer	integer, default 1L (off), if > 1 will smooth out signal with sliding window size kmer.
metadata	a data.table of metadata, must contain the Run column to select libraries.

min_count	integer, default 0. Minimum counts of coverage over transcript to be included.
format	character, default "wide", alternative "long". The format of the table output.
value.var	which column to use as scores, default "logscore"
as_list	logical, default FALSE. Return as list of size 2, count data.table and metadata data.table Set to TRUE if you need metadata subset (needed if you subset the table, to get correct matching)
subset	numeric vector, positional interval to subset, must be <= size of whole region.
group_on_tx_tpm	numeric vector, default NULL. tpm values per libraries. Either for that gene or some other gene.
split_by_frame	logical, default FALSE For kmer sliding window, should it split by frame
ratio_interval	numeric vector of size 2 or 4, default NULL. If 2, means you should sort libraries on coverage in that region. If 4, means to sort on ratio of that region in this gene vs the other region in another gene.
decreasing_order	logical, default FALSE. Sort you ordering vector from lowest (default). If TRUE, sort from highest downwards.

Value

a data.table in long or wide (default) format, if as list, it is a list of size 2 (see argument as_list)

createSeqPanelPattern *Create sequence panel for RiboCrypt*

Description

Create sequence panel for RiboCrypt

Usage

```
createSeqPanelPattern(
  sequence,
  start_codons = "ATG",
  stop_codons = c("TAA", "TAG", "TGA"),
  frame = 1,
  custom_motif = NULL
)
```

Arguments

sequence	the DNAStrngSet
start_codons	character vector, default "ATG"
stop_codons	character vector, default c("TAA", "TAG", "TGA")
frame	frame not used
custom_motif	character vector, default NULL.

Value

a ggplot object

DEG_plot

*Differential expression plots (1D or 2D)***Description**

Gives you interactive 1D or 2D DE plots

Usage

```
DEG_plot(
  dt,
  draw_non_regulated = TRUE,
  add_search_bar = TRUE,
  xlim = ifelse(two_dimensions, "bidir.max", "auto"),
  ylim = "bidir.max",
  xlab = ifelse(two_dimensions, "RNA fold change (log2)", "Mean counts (log2)"),
  ylab = ifelse(two_dimensions, "RFP fold change (log2)", "Fold change (log2)"),
  two_dimensions = ifelse("LFC" %in% colnames(dt), FALSE, TRUE),
  color.values = c(`No change` = "black", Significant = "red", Buffering = "purple",
    `mRNA abundance` = "darkgreen", Expression = "blue", Forwarded = "yellow", Inverse =
    "aquamarine", Translation = "orange4"),
  format = "png"
)
```

Arguments

dt	a data.table with results from a differential expression run. Normally from: ORFik::DTEG.analysis(df1, df2)
draw_non_regulated	logical, default TRUE Should non-regulated rows be included in the plot? Will make the plot faster to render if skipped (FALSE)
add_search_bar	logical, default TRUE. Add a crosstalk search bar to search for genes in the plot
xlim	numeric vector or character preset, default: ifelse(two_dimensions, "bidir.max", "auto") (Equal in both + / - direction, using max value + 0.5 of meanCounts(in 1d) / rna(in 2d) column of dt). If you want ggplot to decide limit, set to "auto". For numeric vector, specify min and max x limit: like c(-5, 5)
ylim	numeric vector or character preset, default: "bidir.max" (Equal in both + / - direction, using max value + 0.5 of LFC(in 1d) / rfp(in 2d) column of dt). If you want ggplot to decide limit, set to "auto". For numeric vector, specify min and max x limit: like c(-5, 5)
xlab	character, default: ifelse(two_dimensions, "RNA fold change (log2)", "Mean counts (log2)")
ylab	character, default: ifelse(two_dimensions, "RFP fold change (log2)", "Fold change (log2)")
two_dimensions	logical, default: ifelse("LFC" %in% colnames(dt), FALSE, TRUE) Is this two dimensional, like: Ribo-seq vs RNA-seq. Alternative, FALSE: Then Log fold change vs mean counts

color.values	named character vector, default: c("No change" = "black", "Significant" = "red", "Buffering" = "purple", "mRNA abundance" = "darkgreen", "Expression" = "blue", "Forwarded" = "yellow", "Inverse" = "aquamarine", "Translation" = "orange4")
format	character, default "png". Format for plotly bar.

Value

plotly object or crosstalk bscols if add_search_bar is TRUE.

Examples

```
# Load experiment
df <- ORFik.template.experiment()
df_rna <- df[df$libtype == "RNA",]
# 1 Dimensional analysis
dt <- DEG.analysis(df_rna)
dt$Regulation[1] <- "Significant" # Fake sig level
DEG_plot(dt, draw_non_regulated = TRUE)
# 2 Dimensional analysis
df_rfp <- df[df$libtype == "RFP",]
dt_2d <- DTEG.analysis(df_rfp, df_rna, output.dir = NULL)
dt_2d$Regulation[4] <- "Translation" # Fake sig level
dt_2d$rfp.lfc[4] <- -0.3 # Fake sig level
dt_2d$Regulation[5] <- "Buffering" # Fake sig level
dt_2d$rna.lfc[5] <- -0.3 # Fake sig level
DEG_plot(dt_2d, draw_non_regulated = TRUE)
```

fetch_JS_seq

Fetch Javascript sequence

Description

Fetch Javascript sequence

Usage

```
fetch_JS_seq(
  target_seq,
  nplots,
  distance = 50,
  display_dist,
  aa_letter_code = "one_letter",
  input_id
)
```

Arguments

target_seq	the target sequence
nplots	number of plots
distance	numeric, default 50.
display_dist	display distance

aa_letter_code "one_letter"
input_id shiny id of the object

Value

a list of 2 lists, the nt list (per frame, total 3) and AA list (per frame, total 3)

fetch_summary	<i>Fetch summary of uniprot id</i>
---------------	------------------------------------

Description

Fetch summary of uniprot id

Usage

fetch_summary(qualifier, provider = "alphafold")

Arguments

qualifier uniprot ids
provider "pdbe", alternatives: "alphafold", "all"

Value

a character of json

geneTrackLayer	<i>How many rows does the gene track need</i>
----------------	---

Description

How many rows does the gene track need

Usage

geneTrackLayer(gr1)

Arguments

gr1 a GRangesList

Value

numeric, the track row index

getCoverageProfile	<i>Get coverage profile</i>
--------------------	-----------------------------

Description

Get coverage profile

Usage

```
getCoverageProfile(grl, reads, kmers = 1, kmers_type = "mean")
```

Arguments

grl	a GRangesList
reads	GRanges
kmers	1
kmers_type	"mean"

Value

data.table of coverage

getIndexes	<i>Get index</i>
------------	------------------

Description

Get index

Usage

```
getIndexes(ref_granges)
```

Arguments

ref_granges	a GRanges object
-------------	------------------

Value

integer vector, indices

```
get_meta_browser_plot_full
```

Full plot for allsamples browser

Description

Full plot for allsamples browser

Usage

```
get_meta_browser_plot_full(
  m,
  heatmap,
  id,
  df,
  summary = TRUE,
  annotation = TRUE,
  region_type,
  plotType = "plotly",
  tx_annotation,
  display_region,
  cds_annotation,
  viewMode,
  collapse_intron_flank,
  rel_heights = c(0.2, 0.75, 0.05)
)
```

Arguments

<code>m</code>	data.table of coverage per sample (wide format)
<code>heatmap</code>	ComplexHeatmap object of plot from 'm'
<code>id</code>	id of transcript
<code>df</code>	ORFik experiment
<code>summary</code>	logical, default TRUE (add top plot)
<code>annotation</code>	logical, default TRUE (add bottom annotation track)
<code>region_type</code>	character, "what is the coverage region?" Usually full mrna: "mrna" or "leader+cds".
<code>plotType</code>	= "plotly",
<code>tx_annotation</code>	a GRangesList of tx annotation
<code>display_region</code>	a GRangesList of display region
<code>cds_annotation</code>	a GRangesList of cds annotation
<code>viewMode</code>	character, "tx" or "genomic"
<code>collapse_intron_flank</code>	integer, if TRUE and viewMode genomic, collapse introns to this max size.
<code>rel_heights</code>	numeric < 1, default: c(0.2, 0.75, 0.05). Relative heights, sum to 1 and must be length 3.

Value

a cowplot grub

ggplotlyHover	<i>Call ggplotly with hoveron defined</i>
---------------	---

Description

Call ggplotly with hoveron defined

Usage

```
ggplotlyHover(x, ...)
```

Arguments

x	a a ggplot argument
...	additional arguments for ggplotly

Value

a ggplotly object

load_collection	<i>Load a ORFik collection table</i>
-----------------	--------------------------------------

Description

Load a ORFik collection table

Usage

```
load_collection(path, grl = attr(path, "range"))
```

Arguments

path	the path to gene counts
grl	a GRangesList, default attr(path, "range"), for new fst format, which range to get.

Value

a data.table in long format

make_rc_url

*Create URL to browse a gene on Ribocrypt webpage***Description**

Can also make url for local RiboCrypt app' On the actual app, the function make_url_from_inputs is used on the shiny reactive input object. This one is for manual use.

Usage

```
make_rc_url(
  symbol = NULL,
  gene_id = NULL,
  tx_id = NULL,
  exp = "all_merged-Homo_sapiens_modalities",
  libraries = NULL,
  leader_extension = 0,
  trailer_extension = 0,
  viewMode = FALSE,
  other_tx = FALSE,
  plot_on_start = TRUE,
  frames_type = "columns",
  kmer = 1,
  add_translons = FALSE,
  zoom_range = NULL,
  host = "https://ribocrypt.org"
)
```

Arguments

symbol	gene symbol, default NULL
gene_id	gene symbol, default NULL
tx_id	gene symbol, default NULL
exp	experiment name, default "all_merged-Homo_sapiens_modalities"
libraries	NULL, default to first in experiment, c("RFP","RNA") would add RNA to default.
leader_extension	integer, default 0. (How much to extend view upstream)
trailer_extension	integer, default 0. (How much to extend view downstream)
viewMode	FALSE (transcript view), TRUE gives genomic.
other_tx	FALSE, show all other annotation in region (isoforms etc.)
plot_on_start	logical, default TRUE. Plot gene when opening browser.
frames_type	"columns"
kmer	integer, default 1 (no binning), binning size of windows, to smear out the signal.
add_translons	logical, default FALSE. If TRUE, add translons predicted sequences in annotation.
zoom_range	character, zoom values.
host	url, default "https://ribocrypt.org". Set to localhost for local version.

Value

character, URL.

Examples

```
make_rc_url("ATF4", "ENSG00000128272")
```

matchMultiplePatterns	<i>Match multiple patterns</i>
-----------------------	--------------------------------

Description

Match multiple patterns

Usage

```
matchMultiplePatterns(patterns, Seq)
```

Arguments

patterns	character
Seq	a DNASTringSet

Value

integer vector, indices (named with pattern hit)

matchToGRanges	<i>Match to GRanges</i>
----------------	-------------------------

Description

Match to GRanges

Usage

```
matchToGRanges(matches, ref_granges)
```

Arguments

matches	integer vector, indices
ref_granges	GRanges

Value

GRanges object

multiOmicsPlot_animate

Multi-omics animation using list input

Description

The animation will move with a play button, there is 1 transition per library given.

Usage

```
multiOmicsPlot_animate(
  display_range,
  annotation = display_range,
  reference_sequence,
  reads,
  viewMode = c("tx", "genomic")[1],
  custom_regions = NULL,
  leader_extension = 0,
  trailer_extension = 0,
  withFrames = NULL,
  frames_type = "lines",
  colors = NULL,
  kmers = NULL,
  kmers_type = c("mean", "sum")[1],
  ylabels = NULL,
  lib_to_annotation_proportions = c(0.8, 0.2),
  lib_proportions = NULL,
  annotation_proportions = NULL,
  width = NULL,
  height = NULL,
  plot_name = "default",
  plot_title = NULL,
  display_sequence = c("both", "nt", "aa", "none")[1],
  seq_render_dist = 100,
  aa_letter_code = c("one_letter", "three_letters")[1],
  annotation_names = NULL,
  start_codons = "ATG",
  stop_codons = c("TAA", "TAG", "TGA"),
  custom_motif = NULL,
  AA_code = Biostrings::GENETIC_CODE,
  log_scale = FALSE,
  BPPARAM = BiocParallel::SerialParam(),
  summary_track = FALSE,
  summary_track_type = frames_type,
  export.format = "svg",
  frames_subset = "all"
)
```

Arguments

`display_range` the whole region to visualize, a [GRangesList](#) or [GRanges](#) object

annotation	the whole annotation which your target region is a subset, a GRangesList or GRanges object
reference_sequence	the genome reference, a FaFile or FaFile convertible object
reads	the NGS libraries, as a list of GRanges with or without score column for replicates.
viewMode	character, default "tx" (transcript coordinates, first position is 1, exons are merged into a single sequence) Alternative: "genomic" (genomic coordinates, first position is first position in display_range argument. Introns are displayed).
custom_regions	a GRangesList or NULL, default: NULL. The alternative annotation, like self defined uORFs etc. The vertical annotation bars will have a different color.
leader_extension	integer, default 0. (How much to extend view upstream)
trailer_extension	integer, default 0. (How much to extend view downstream)
withFrames	a logical vector, default NULL. Alternative: a length 1 or same length as list length of "reads" argument.
frames_type	character, default "lines". Alternative: - columns - stacks - area
colors	character, default NULL (automatic colouring). If "withFrames" argument is TRUE, colors are set to c("red", "green", "blue") for the 3 frames. Alternative: Character vector of length 1 or length of "reads" list argument.
kmers	numeric (integer), bin positions into kmers. Default NULL, which is equal to 1, i.e. no binning.
kmers_type	character, function used for kmers sliding window. default: "mean", alternative: "sum"
ylabels	character, default NULL. Name of libraries in "reads" list argument.
lib_to_annotation_proportions	numeric vector of length 2. relative sizes of profiles and annotation.
lib_proportions	numeric vector of length equal to displayed libs. Relative sizes of profiles displayed
annotation_proportions	numeric vector of length 3 (seq displayed), or 2 (seq not displayed). Relative sizes of annotation tracks.
width	numeric, default NULL. Width of plot.
height	numeric, default NULL. Height of plot.
plot_name	= character, default "default" (will create name from display_range name). Alternative: custom name for region.
plot_title	character, default NULL. A title for plot.
display_sequence	character/logical, default c("both", "nt", "aa", "none")[1]. If TRUE or "both", display nucleotide and aa sequence in plot.

seq_render_dist	integer, default 100. The sequences will appear after zooming below this threshold.
aa_letter_code	character, when set to "three_letters", three letter amino acid code is used. One letter by default.
annotation_names	character, default NULL. Alternative naming for annotation.
start_codons	character vector, default "ATG"
stop_codons	character vector, default c("TAA", "TAG", "TGA")
custom_motif	character vector, default NULL.
AA_code	Genetic code for amino acid display. Default is SGC0 (standard: Vertebrate). See Biostrings::GENETIC_CODE_TABLE for options. To change to bacterial, do: Biostrings::getGeneticCode("11")
log_scale	logical, default FALSE. Log2 scale the count values, for easier visualization of shapes.
BPPARAM	how many cores/threads to use? default: BiocParallel::SerialParam(). To see number of threads used for multicores, do BiocParallel::bpparam()\$workers. You can also add a time remaining bar, for a more detailed pipeline.
summary_track	logical, default FALSE. Display a top track, that is the sum of all tracks.
summary_track_type	character, default is same as 'frames_type' argument
export.format	character, default: "svg". alternative: "png". when you click the top right image button export, what should it export as?
frames_subset	character, default "all". Alternatives: "red", "green", "blue".

Value

the plot object

Examples

```
library(RiboCrypt)
df <- ORFik.template.experiment()[9:10,]
cds <- loadRegion(df, "cds")
mrna <- loadRegion(df, "mrna")
multiOmicsPlot_animate(mrna[1], annotation = cds[1], reference_sequence = findFa(df),
  frames_type = "columns", leader_extension = 30, trailer_extension = 30,
  withFrames = c(TRUE, TRUE),
  reads = outputLibs(df, type = "pshifted", output.mode = "envirlist",
    naming = "full", BPPARAM = BiocParallel::SerialParam()))
```

multiOmicsPlot_list	<i>Multi-omics plot using list input</i>
---------------------	--

Description

Customizable html plots for visualizing genomic data.

Usage

```

multiOmicsPlot_list(
  display_range,
  annotation = display_range,
  reference_sequence,
  reads,
  viewMode = c("tx", "genomic")[1],
  custom_regions = NULL,
  leader_extension = 0,
  trailer_extension = 0,
  withFrames = NULL,
  frames_type = "lines",
  colors = NULL,
  kmers = NULL,
  kmers_type = c("mean", "sum")[1],
  ylabels = NULL,
  lib_to_annotation_proportions = c(0.8, 0.2),
  lib_proportions = NULL,
  annotation_proportions = NULL,
  width = NULL,
  height = NULL,
  plot_name = "default",
  plot_title = NULL,
  display_sequence = c("both", "nt", "aa", "none")[1],
  seq_render_dist = 100,
  aa_letter_code = c("one_letter", "three_letters")[1],
  annotation_names = NULL,
  start_codons = "ATG",
  stop_codons = c("TAA", "TAG", "TGA"),
  custom_motif = NULL,
  AA_code = Biostrings::GENETIC_CODE,
  log_scale = FALSE,
  BPPARAM = BiocParallel::SerialParam(),
  summary_track = FALSE,
  summary_track_type = frames_type,
  export.format = "svg",
  frames_subset = "all"
)

```

Arguments

<code>display_range</code>	the whole region to visualize, a GRangesList or GRanges object
<code>annotation</code>	the whole annotation which your target region is a subset, a GRangesList or GRanges object
<code>reference_sequence</code>	the genome reference, a FaFile or FaFile convertible object
<code>reads</code>	the NGS libraries, as a list of GRanges with or without score column for replicates.
<code>viewMode</code>	character, default "tx" (transcript coordinates, first position is 1, exons are merged into a single sequence)

	Alternative: "genomic" (genomic coordinates, first position is first position in display_range argument. Introns are displayed).
custom_regions	a GRangesList or NULL, default: NULL. The alternative annotation, like self defined uORFs etc. The vertical annotation bars will have a different color.
leader_extension	integer, default 0. (How much to extend view upstream)
trailer_extension	integer, default 0. (How much to extend view downstream)
withFrames	a logical vector, default NULL. Alternative: a length 1 or same length as list length of "reads" argument.
frames_type	character, default "lines". Alternative: - columns - stacks - area
colors	character, default NULL (automatic colouring). If "withFrames" argument is TRUE, colors are set to c("red", "green", "blue") for the 3 frames. Alternative: Character vector of length 1 or length of "reads" list argument.
kmers	numeric (integer), bin positions into kmers. Default NULL, which is equal to 1, i.e. no binning.
kmers_type	character, function used for kmers sliding window. default: "mean", alternative: "sum"
ylabels	character, default NULL. Name of libraries in "reads" list argument.
lib_to_annotation_proportions	numeric vector of length 2. relative sizes of profiles and annotation.
lib_proportions	numeric vector of length equal to displayed libs. Relative sizes of profiles displayed
annotation_proportions	numeric vector of length 3 (seq displayed), or 2 (seq not displayed). Relative sizes of annotation tracks.
width	numeric, default NULL. Width of plot.
height	numeric, default NULL. Height of plot.
plot_name	= character, default "default" (will create name from display_range name). Alternative: custom name for region.
plot_title	character, default NULL. A title for plot.
display_sequence	character/logical, default c("both", "nt", "aa", "none")[1]. If TRUE or "both", display nucleotide and aa sequence in plot.
seq_render_dist	integer, default 100. The sequences will appear after zooming below this threshold.
aa_letter_code	character, when set to "three_letters", three letter amino acid code is used. One letter by default.
annotation_names	character, default NULL. Alternative naming for annotation.
start_codons	character vector, default "ATG"
stop_codons	character vector, default c("TAA", "TAG", "TGA")

custom_motif	character vector, default NULL.
AA_code	Genetic code for amino acid display. Default is SGC0 (standard: Vertebrate). See Biostrings::GENETIC_CODE_TABLE for options. To change to bacterial, do: Biostrings::getGeneticCode("11")
log_scale	logical, default FALSE. Log2 scale the count values, for easier visualization of shapes.
BPPARAM	how many cores/threads to use? default: BiocParallel::SerialParam(). To see number of threads used for multicores, do BiocParallel::bpparam()\$workers. You can also add a time remaining bar, for a more detailed pipeline.
summary_track	logical, default FALSE. Display a top track, that is the sum of all tracks.
summary_track_type	character, default is same as 'frames_type' argument
export.format	character, default: "svg". alternative: "png". when you click the top right image button export, what should it export as?
frames_subset	character, default "all". Alternatives: "red", "green", "blue".

Value

the plot object

Examples

```
library(RiboCrypt)
df <- ORFik.template.experiment()[9:10,]
cds <- loadRegion(df, "cds")
mrna <- loadRegion(df, "mrna")
multiOmicsPlot_list(mrna[1], annotation = cds[1], reference_sequence = findFa(df),
                    frames_type = "columns", leader_extension = 30, trailer_extension = 30,
                    reads = outputLibs(df, type = "pshifted", output.mode = "envirlist",
                                       naming = "full", BPPARAM = BiocParallel::SerialParam()))
```

multiOmicsPlot_ORFikExp

Multi-omics plot using ORFik experiment input

Description

Customizable html plots for visualizing genomic data.

Usage

```
multiOmicsPlot_ORFikExp(
  display_range,
  df,
  annotation = "cds",
  reference_sequence = findFa(df),
  reads = outputLibs(df, type = "pshifted", output.mode = "envirlist", naming = "full",
                    BPPARAM = BiocParallel::SerialParam()),
  viewMode = c("tx", "genomic")[1],
  custom_regions = NULL,
```

```

leader_extension = 0,
trailer_extension = 0,
withFrames = libraryTypes(df, uniqueTypes = FALSE) %in% c("RFP", "RPF", "LSU", "TI"),
frames_type = "lines",
colors = NULL,
kmers = NULL,
kmers_type = c("mean", "sum")[1],
ylab = bamVarName(df),
lib_to_annotation_proportions = c(0.8, 0.2),
lib_proportions = NULL,
annotation_proportions = NULL,
width = NULL,
height = NULL,
plot_name = "default",
plot_title = NULL,
display_sequence = c("both", "nt", "aa", "none")[1],
seq_render_dist = 100,
aa_letter_code = c("one_letter", "three_letters")[1],
annotation_names = NULL,
start_codons = "ATG",
stop_codons = c("TAA", "TAG", "TGA"),
custom_motif = NULL,
log_scale = FALSE,
BPPARAM = BiocParallel::SerialParam(),
input_id = "",
summary_track = FALSE,
summary_track_type = frames_type,
export.format = "svg",
frames_subset = "all"
)

```

Arguments

display_range	the whole region to visualize, a GRangesList or GRanges object
df	an ORFik experiment or a list containing ORFik experiments. Usually a list when you have split Ribo-seq and RNA-seq etc.
annotation	the whole annotation which your target region is a subset, a GRangesList or GRanges object
reference_sequence	the genome reference, default <code>ORFik::findFa(df)</code>
reads	the NGS libraries, as a list of GRanges with or without 'score' column for replicates. Can also be a <code>covRle</code> object of precomputed coverage. Default: <code>outputLibs(df, type = "pshifted", output.mode = "envirlist", naming = "full", BPPARAM = BiocParallel::SerialParam())</code>
viewMode	character, default "tx" (transcript coordinates, first position is 1, exons are merged into a single sequence) Alternative: "genomic" (genomic coordinates, first position is first position in display_range argument. Introns are displayed).
custom_regions	a GRangesList or <code>NULL</code> , default: <code>NULL</code> . The alternative annotation, like self defined uORFs etc. The vertical annotation bars will have a different color.

leader_extension	integer, default 0. (How much to extend view upstream)
trailer_extension	integer, default 0. (How much to extend view downstream)
withFrames	a logical vector, default libraryTypes(df, uniqueTypes = FALSE) %in% c("RFP", "RPF", "LSU", "TI") Alternative: a length 1 or same length as list length of "reads" argument.
frames_type	character, default "lines". Alternative: - columns - stacks - area
colors	character, default NULL (automatic colouring). If "withFrames" argument is TRUE, colors are set to c("red", "green", "blue") for the 3 frames. Alternative: Character vector of length 1 or length of "reads" list argument.
kmers	numeric (integer), bin positions into kmers. Default NULL, which is equal to 1, i.e. no binning.
kmers_type	character, function used for kmers sliding window. default: "mean", alternative: "sum"
ylabels	character, default bamVarName(df). Name of libraries in "reads" list argument.
lib_to_annotation_proportions	numeric vector of length 2. relative sizes of profiles and annotation.
lib_proportions	numeric vector of length equal to displayed libs. Relative sizes of profiles displayed
annotation_proportions	numeric vector of length 3 (seq displayed), or 2 (seq not displayed). Relative sizes of annotation tracks.
width	numeric, default NULL. Width of plot.
height	numeric, default NULL. Height of plot.
plot_name	character, default "default" (will create name from display_range name).
plot_title	character, default NULL. A title for plot.
display_sequence	character/logical, default c("both", "nt", "aa", "none")[1]. If TRUE or "both", display nucleotide and aa sequence in plot.
seq_render_dist	integer, default 100. The sequences will appear after zooming below this threshold.
aa_letter_code	character, when set to "three_letters", three letter amino acid code is used. One letter by default.
annotation_names	character, default NULL. Alternative naming for annotation.
start_codons	character vector, default "ATG"
stop_codons	character vector, default c("TAA", "TAG", "TGA")
custom_motif	character vector, default NULL.
log_scale	logical, default FALSE. Log2 scale the count values, for easier visualization of shapes.

BPPARAM	how many cores/threads to use? default: BiocParallel::SerialParam(). To see number of threads used for multicores, do BiocParallel::bpparam()\$workers. You can also add a time remaining bar, for a more detailed pipeline.
input_id	character path, default: "", id for shiny to display structures, should be "" for local users.
summary_track	logical, default FALSE. Display a top track, that is the sum of all tracks.
summary_track_type	character, default is same as 'frames_type' argument
export.format	character, default: "svg". alternative: "png". when you click the top right image button export, what should it export as?
frames_subset	character, default "all". Alternatives: "red", "green", "blue".

Value

the plot object

Examples

```
library(RiboCrypt)
df <- ORFik.template.experiment()[9,] #Use third library in experiment only
cds <- loadRegion(df, "cds")
multiOmicsPlot_ORFikExp(extendLeaders(extendTrailers(cds[1], 30), 30), df,
                        frames_type = "columns")
```

normalize_collection	<i>Normalize collection table</i>
----------------------	-----------------------------------

Description

Normalize collection table

Usage

```
normalize_collection(
  table,
  normalization,
  lib_sizes = NULL,
  kmer = 1L,
  add_logscore = TRUE,
  split_by_frame = FALSE
)
```

Arguments

table	a data.table in long format
normalization	a character string, which mode, for options see RiboCrypt::normalizations
lib_sizes	named integer vector, default NULL. If given will do a pre tpm normalization for full library sizes
kmer	integer, default 1L (off), if > 1 will smooth out signal with sliding window size kmer.
add_logscore	logical, default TRUE, adds a log(score + 1) to table
split_by_frame	logical, default FALSE For kmer sliding window, should it split by frame

Value

a data.table of normalized results

organism_input_select *Select box for organism*

Description

Select box for organism

Usage

```
organism_input_select(genomes, ns)
```

Arguments

genomes	name of genomes, returned from list.experiments()
ns	the ID, for shiny session

Value

selectizeInput object

RiboCrypt_app *Create RiboCrypt app*

Description

Create RiboCrypt app

Usage

```
RiboCrypt_app(
  validate.experiments = TRUE,
  options = list(launch.browser = ifelse(interactive(), TRUE, FALSE)),
  all_exp = list.experiments(validate = validate.experiments),
  browser_options = c(),
  init_tab_focus = "browser",
  metadata = NULL,
  all_exp_meta = all_exp[grepl("all_samples-", name), ]
)
```



```
#           default_view_mode = "genomic"))
#RiboCrypt_app(validate.experiments = FALSE,
#  browser_options = c(plot_on_start = "TRUE",
#           default_experiment = "all_merged-Saccharomyces_cerevisiae",
#           default_gene = "EFM5-YGR001",
#           default_view_mode = "genomic"))
```

trimOverlaps	<i>Trim overlaps</i>
--------------	----------------------

Description

Trim overlaps

Usage

```
trimOverlaps(overlaps, display_range)
```

Arguments

overlaps	GRanges
display_range	GRanges

Value

GRanges

Index

* internal

- [antisense](#), [2](#)
- [createSeqPanelPattern](#), [7](#)
- [geneTrackLayer](#), [10](#)
- [getCoverageProfile](#), [11](#)
- [getIndexes](#), [11](#)
- [ggplotlyHover](#), [13](#)
- [matchMultiplePatterns](#), [15](#)
- [matchToGRanges](#), [15](#)
- [trimOverlaps](#), [27](#)

[antisense](#), [2](#)

[browseRC](#), [3](#)

[collection_dir_from_exp](#), [4](#)
[collection_path_from_exp](#), [5](#)
[collection_to_wide](#), [5](#)
[compute_collection_table](#), [6](#)
[createSeqPanelPattern](#), [7](#)

[DEG_plot](#), [8](#)

[experiment](#), [22](#)

[FaFile](#), [17](#), [19](#)

[fetch_JS_seq](#), [9](#)

[fetch_summary](#), [10](#)

[geneTrackLayer](#), [10](#)
[get_meta_browser_plot_full](#), [12](#)
[getCoverageProfile](#), [11](#)
[getIndexes](#), [11](#)
[ggplotlyHover](#), [13](#)
[GRanges](#), [16](#), [17](#), [19](#), [22](#)
[GRangesList](#), [16](#), [17](#), [19](#), [22](#)

[load_collection](#), [13](#)

[make_rc_url](#), [14](#)
[matchMultiplePatterns](#), [15](#)
[matchToGRanges](#), [15](#)
[multiOmicsPlot_animate](#), [16](#)
[multiOmicsPlot_list](#), [18](#)
[multiOmicsPlot_ORFikExp](#), [21](#)

[normalize_collection](#), [24](#)

[organism_input_select](#), [25](#)

[RiboCrypt_app](#), [25](#)

[trimOverlaps](#), [27](#)