# SNPlocs.Hsapiens.dbSNP155.GRCh37

July 16, 2025

SNPlocs.Hsapiens.dbSNP155.GRCh37 The SNPlocs.Hsapiens.dbSNP155.GRCh37 package

### Description

Human SNP locations and alleles extracted from dbSNP Build 155 and placed on the GRCh37/hg19 assembly

# Details

The 929,496,192 SNPs in this package were extracted from the RefSNP JSON files for chromosomes 1-22, X, Y, and MT, located at https://ftp.ncbi.nih.gov/snp/archive/b155/JSON/ (these files were created by NCBI in May 2021).

These SNPs are compatible with package **BSgenome.Hsapiens.UCSC.hg19**, that is, they can be "injected" in the **BSgenome** object contained in this package.

SNP positions and alleles are reported with respect to the *plus* strand.

Only SNPs of type *snv* (*single-nucleotide* variant a.k.a. *single-base substitution*) were kept. Other variant types supported by dbSNP are: *delins* (indel), *ins* (insertion), *del* (deletion), and *mnv* (multiple nucleotide variation). These other variants are NOT included in SNPlocs.Hsapiens.dbSNP155.GRCh37 but are available in the XtraSNPlocs.Hsapiens.dbSNP155.GRCh37 package.

#### Note

The SNPs in this package can be "injected" in BSgenome.Hsapiens.UCSC.hg19 and will land at the correct positions.

See ?injectSNPs in the **BSgenome** software package for more information about the SNP injection mechanism.

# Author(s)

H. Pagès

#### References

SNP Home at NCBI: https://www.ncbi.nlm.nih.gov/snp

dbSNP Human Build 155 Release announcement (June 22, 2021): https://www.ncbi.nlm.nih. gov/mailman/pipermail/dbsnp-announce/2021q2/000229.html

The GRCh37.p13 assembly: https://www.ncbi.nlm.nih.gov/assembly/GCF\_000001405.25/

The hg19 genome at UCSC (based on GRCh37.p13): http://genome.ucsc.edu/cgi-bin/hgGateway? db=hg19

#### See Also

- The XtraSNPlocs.Hsapiens.dbSNP155.GRCh37 package for SNPs of type other than snv.
- snpcount in the **BSgenome** software package for how to access the data stored in this package.
- IUPAC\_CODE\_MAP in the **Biostrings** package.
- The GPos class in the GenomicRanges package.
- injectSNPs in the BSgenome software package for SNP injection.
- The VariantAnnotation software package to annotate variants with respect to location and amino acid coding.

## Examples

```
## ------
## A. BASIC USAGE
## -----
snps <- SNPlocs.Hsapiens.dbSNP155.GRCh37</pre>
snpcount(snps)
seqinfo(snps)
## Get the positions and alleles of all SNPs on chromosomes 22 and MT:
snpsBySeqname(snps, seqnames=c("22", "MT"))
## Get the positions and alleles of all SNPs within some regions:
snpsByOverlaps(snps, GRanges(c("Y:230001-232000", "19:88501-89000")))
## B. EXTRACT SNP INFORMATION FOR A SET OF RS IDS
## _____
"rs3734153", "rs79381275", "rs1516535", "rs74342513")
## Note that the first call to snpsById() takes a long time but
## subsequent calls are faster.
my_snps <- snpsById(snps, my_rsids)</pre>
my_snps
## Translate the IUPAC ambiguity codes used to represent the alleles
## into nucleotides:
IUPAC_CODE_MAP[mcols(my_snps)$alleles_as_ambig]
## _____
```

2

## C. INJECTION IN THE REFERENCE GENOME
## -----library(BSgenome.Hsapiens.UCSC.hg19)
ref\_genome <- BSgenome.Hsapiens.UCSC.hg19
ref\_genome
alt\_genome <- injectSNPs(ref\_genome, "SNPlocs.Hsapiens.dbSNP155.GRCh37")
alt\_genome # note the additional line "with SNPs injected from..."
alphabetFrequency(ref\_genome\$chr22)
alphabetFrequency(alt\_genome\$chr22)</pre>

## Get the number of nucleotides that were modified by this injection: neditAt(ref\_genome\$chr22, alt\_genome\$chr22) # 11798497

# Index

\* package SNPlocs.Hsapiens.dbSNP155.GRCh37, 1 .loadAlleles (SNPlocs.Hsapiens.dbSNP155.GRCh37), 1 .loadLoc (SNPlocs.Hsapiens.dbSNP155.GRCh37), 1 BSgenome, 1 COMPATIBLE\_BSGENOMES (SNPlocs.Hsapiens.dbSNP155.GRCh37), 1 GPos, 2 injectSNPs, 1, 2 IUPAC\_CODE\_MAP, 2 snpcount, 2  ${\tt SNPlocs.Hsapiens.dbSNP155.GRCh37,1}$ SNPlocs.Hsapiens.dbSNP155.GRCh37-package (SNPlocs.Hsapiens.dbSNP155.GRCh37), 1