

Package ‘ternarynet’

July 17, 2025

Version 1.52.0

Date 2024-02-19

Title Ternary Network Estimation

Description Gene-regulatory network (GRN) modeling seeks to infer dependencies between genes and thereby provide insight into the regulatory relationships that exist within a cell. This package provides a computational Bayesian approach to GRN estimation from perturbation experiments using a ternary network model, in which gene expression is discretized into one of 3 states: up, unchanged, or down). The ternarynet package includes a parallel implementation of the replica exchange Monte Carlo algorithm for fitting network models, using MPI.

Author Matthew N. McCall <mccallm@gmail.com>, Anthony Almudevar <Anthony_Alumudevar@urmc.rochester.edu>, David Burton <David_Burton@urmc.rochester.edu>, Harry Stern <harry.stern@rochester.edu>

Depends R (>= 4.0)

Imports utils, igraph, methods, graphics, stats, BiocParallel

Suggests testthat

Enhances Rmpi, snow

License GPL (>= 2)

biocViews Software, CellBiology, GraphAndNetwork, Network, Bayesian

NeedsCompilation yes

Maintainer McCall N. Matthew <mccallm@gmail.com>

git_url <https://git.bioconductor.org/packages/ternarynet>

git_branch RELEASE_3_21

git_last_commit dc372ee

git_last_commit_date 2025-04-15

Repository Bioconductor 3.21

Date/Publication 2025-07-16

Contents

attractorSummary	2
graphPosterior	3
parallelFit	4
plotFit	6
plotPost	7
plotTraces	8
predictAttractor	9
simulateSteadyState	10
ternaryFit-class	11
ternaryFitParameters-class	12
ternaryPost-class	14
tnetfit	15
tnetpost	16
Index	18

attractorSummary	<i>Summarize Attractors</i>
------------------	-----------------------------

Description

This function summarizes the posterior probability of possible attractors.

Usage

```
attractorSummary(tpost, post.prob.limit = 0.01, wildtype = TRUE)
```

Arguments

- tpost a ternaryPost object
- post.prob.limit the minimum posterior probability for an attractor to be listed
- wildtype if TRUE, the wildtype attractors are summarized; if FALSE, the perturbed at-
tractors are summarized.

Value

The function returns a matrix of attractors and posterior probabilities for each perturbation.

Author(s)

Matthew N. McCall and Anthony Almudevar

See Also

Almudevar A, McCall MN, McMurray H, Land H (2011). Fitting Boolean Networks from Steady State Perturbation Data, *Statistical Applications in Genetics and Molecular Biology*, 10(1): Article 47.

Examples

```
ssObj <- matrix(c(1,1,1,0,1,1,0,0,1),nrow=3)
pObj <- matrix(c(1,0,0,0,1,0,0,0,1),nrow=3)
rownames(ssObj) <- rownames(pObj) <- colnames(ssObj) <- colnames(pObj) <- c("Gene1", "Gene2", "Gene3")
tnfitObj <- tnetfit(ssObj, pObj)
tnpostObj <- tnetpost(tnfitObj, mdelta=10, msample=10)
attractorSummary(tnpostObj)
```

graphPosterior

Network Topology

Description

This function summarizes the topology of the ternary network using marginal edge probabilities.

Usage

```
graphPosterior(tpost)
```

Arguments

tpost a ternaryPost object

Value

The function returns a matrix of marginal posterior probabilities of each possible network edge – rows are children and columns are parents. The first column represents no parents.

Author(s)

Matthew N. McCall and Anthony Almudevar

See Also

Almudevar A, McCall MN, McMurray H, Land H (2011). Fitting Boolean Networks from Steady State Perturbation Data, *Statistical Applications in Genetics and Molecular Biology*, 10(1): Article 47.

Examples

```

ssObj <- matrix(c(1,1,1,0,1,1,0,0,1),nrow=3)
pObj <- matrix(c(1,0,0,0,1,0,0,0,1),nrow=3)
rownames(ssObj) <- rownames(pObj) <- colnames(ssObj) <- colnames(pObj) <- c("Gene1","Gene2","Gene3")
tnfitObj <- tnetfit(ssObj, pObj)
tnpostObj <- tnetpost(tnfitObj, mdelta=10, msample=10)
graphPosterior(tnpostObj)

```

parallelFit

*Fit ternary network models using parallel tempering***Description**

Fit ternary network models using parallel tempering

Usage

```

parallelFit(experiment_set,
            max_parents,
            n_cycles,
            n_write,
            T_lo,
            T_hi,
            target_score,
            n_proc,
            logfile,
            n_thread,
            init_parents,
            init_outcomes,
            exchange_interval,
            adjust_move_size_interval,
            max_states,
            callback)

```

Arguments

experiment_set	data frame containing five columns: i_exp (experiment index), i_node (node index), outcome (-1/0/1), value (cost for that outcome), is_perturbation (0 or 1)
max_parents	maximum number of parents allowed for each node
n_cycles	maximum number of Monte Carlo cycles
n_write	number of times to write output during the run
T_lo	T for lowest-temperature replica
T_hi	T for highest-temperature replica
target_score	target_score - run will terminate if this is reached
n_proc	number of replicas

logfile	filename for log file
n_thread	number of openMP threads to run per process; default=1
init_parents	initial parents; randomized if null
init_outcomes	initial outcomes; set to '.' if null
exchange_interval	steps between exchanges; default=1000
adjust_move_size_interval	steps between move size adjustment; default=7001
max_states	max states to propagate when testing for repetition; default=10
callback	callback function, should take one integer argument (the replica number), used to call set.seed with different seed for each replica

Value

The return value is a list with an element for each replica. Each element is itself a list of the best unnormalized score, normalized score (unnormalized score divided by product of number of nodes and number of experiments), list of parents for each node, and array describing the transition rule, giving the outcome of a node for each possible configuration of parent nodes.

Author(s)

Harry A. Stern and Matthew N. McCall

Examples

```
i_exp <- as.integer(c(0,0,0, 0,0,0, 0,0,0, 0,0,0,
                    1,1,1, 1,1,1, 1,1,1, 1,1,1,
                    2,2,2, 2,2,2, 2,2,2, 2,2,2,
                    3,3,3, 3,3,3, 3,3,3, 3,3,3,
                    4,4,4, 4,4,4, 4,4,4, 4,4,4,
                    5,5,5, 5,5,5, 5,5,5, 5,5,5,
                    6,6,6, 6,6,6, 6,6,6, 6,6,6,
                    7,7,7, 7,7,7, 7,7,7, 7,7,7))

i_node <- as.integer(c(0,0,0, 1,1,1, 2,2,2, 3,3,3,
                    0,0,0, 1,1,1, 2,2,2, 3,3,3,
                    0,0,0, 1,1,1, 2,2,2, 3,3,3,
                    0,0,0, 1,1,1, 2,2,2, 3,3,3,
                    0,0,0, 1,1,1, 2,2,2, 3,3,3,
                    0,0,0, 1,1,1, 2,2,2, 3,3,3,
                    0,0,0, 1,1,1, 2,2,2, 3,3,3,
                    0,0,0, 1,1,1, 2,2,2, 3,3,3))

outcome <- as.integer(c(-1,0,1, -1,0,1, -1,0,1, -1,0,1,
                    -1,0,1, -1,0,1, -1,0,1, -1,0,1,
                    -1,0,1, -1,0,1, -1,0,1, -1,0,1,
                    -1,0,1, -1,0,1, -1,0,1, -1,0,1,
                    -1,0,1, -1,0,1, -1,0,1, -1,0,1,
                    -1,0,1, -1,0,1, -1,0,1, -1,0,1,
```

```

-1,0,1, -1,0,1, -1,0,1, -1,0,1,
-1,0,1, -1,0,1, -1,0,1, -1,0,1))

value <- c(0,1,2, 0,1,2, 0,1,2, 0,1,2,
          2,1,0, 0,1,2, 0,1,2, 0,1,2,
          2,1,0, 2,1,0, 0,1,2, 0,1,2,
          2,1,0, 2,1,0, 2,1,0, 0,1,2,
          2,1,0, 2,1,0, 2,1,0, 2,1,0,
          0,1,2, 2,1,0, 2,1,0, 2,1,0,
          0,1,2, 0,1,2, 2,1,0, 2,1,0,
          0,1,2, 0,1,2, 0,1,2, 2,1,0)

is_perturbation <-
c(TRUE,TRUE,TRUE, FALSE,FALSE,FALSE, FALSE,FALSE,FALSE, FALSE,FALSE,FALSE,
  FALSE,FALSE,FALSE, TRUE,TRUE,TRUE, FALSE,FALSE,FALSE, FALSE,FALSE,FALSE,
  FALSE,FALSE,FALSE, FALSE,FALSE,FALSE, TRUE,TRUE,TRUE, FALSE,FALSE,FALSE,
  FALSE,FALSE,FALSE, FALSE,FALSE,FALSE, FALSE,FALSE,FALSE, TRUE,TRUE,TRUE,
  TRUE,TRUE,TRUE, FALSE,FALSE,FALSE, FALSE,FALSE,FALSE, FALSE,FALSE,FALSE,
  FALSE,FALSE,FALSE, TRUE,TRUE,TRUE, FALSE,FALSE,FALSE, FALSE,FALSE,FALSE,
  FALSE,FALSE,FALSE, FALSE,FALSE,FALSE, TRUE,TRUE,TRUE, FALSE,FALSE,FALSE,
  FALSE,FALSE,FALSE, FALSE,FALSE,FALSE, FALSE,FALSE,FALSE, TRUE,TRUE,TRUE)

indata <- data.frame(i_exp,i_node,outcome,value,is_perturbation)

results <- parallelFit(indata,
                       max_parents=1,
                       n_cycles=100000,
                       n_write=10,
                       T_lo=0.001,
                       T_hi=2.0,
                       target_score=0,
                       n_proc=1,
                       logfile='try.log')

lowest_temp_results <- results[[1]]

print('Unnormalized score:')
print(lowest_temp_results$unnormalized_score)

print('Normalized score:')
print(lowest_temp_results$normalized_score)

print('Parents:')
print(lowest_temp_results$parents)

print('Outcomes:')
print(lowest_temp_results$outcomes)

```

Description

This function plots the graph corresponding to the minimum scoring network.

Usage

```
plotFit(ternaryFit, type="interactive", ...)
```

Arguments

<code>ternaryFit</code>	a ternaryFit object
<code>type</code>	the type of plot to produce. "interactive" produces a plot that can be altered in the plotting window using the <code>tkplot</code> function from the <code>igraph</code> package. "static" produces a standard plot in any R graphics device.
<code>...</code>	additional parameters passed to the plotting function

Value

A plot of the network corresponding to the minimum score (stored in the `graphObjMin` slot) is plotted.

Author(s)

Matthew N. McCall and Anthony Almudevar

See Also

Almudevar A, McCall MN, McMurray H, Land H (2011). Fitting Boolean Networks from Steady State Perturbation Data, *Statistical Applications in Genetics and Molecular Biology*, 10(1): Article 47.

Examples

```
ssObj <- matrix(c(1,1,1,0,1,1,0,0,1),nrow=3)
pObj <- matrix(c(1,0,0,0,1,0,0,0,1),nrow=3)
tnfitObj <- tnetfit(ssObj, pObj)
plotFit(tnfitObj, type="static")
```

plotPost

Network Posterior Plot

Description

This function plots the graph consisting of all edges with a marginal posterior probability greater than the selected threshold.

Usage

```
plotPost(ternaryPost, threshold=0.5, type="interactive", ...)
```

Arguments

ternaryPost	a ternaryPost object
type	the type of plot to produce. "interactive" produces a plot that can be altered in the plotting window using the tkplot function from the igraph package. "static" produces a standard plot in any R graphics device.
threshold	the marginal posterior probability required for an edge to be included in the plot.
...	additional parameters passed to the plotting function

Value

A plot of the network consisting of all edges with a marginal posterior probability greater than the selected threshold.

Author(s)

Matthew N. McCall and Anthony Almudevar

See Also

Almudevar A, McCall MN, McMurray H, Land H (2011). Fitting Boolean Networks from Steady State Perturbation Data, *Statistical Applications in Genetics and Molecular Biology*, 10(1): Article 47.

Examples

```
ssObj <- matrix(c(1,1,1,0,1,1,0,0,1),nrow=3)
pObj <- matrix(c(1,0,0,0,1,0,0,0,1),nrow=3)
tnfitObj <- tnetfit(ssObj, pObj)
tnpostObj <- tnetpost(tnfitObj, mdelta=10, msample=10)
plotPost(tnpostObj, type="static")
```

plotTraces

Network Fit Traces

Description

This function plots the trace of four model parameters.

Usage

```
plotTraces(tfit)
```

Arguments

tfit	a ternaryFit object
------	---------------------

Value

The function creates a 2x2 grid of the four trace plots.

Author(s)

Matthew N. McCall and Anthony Almudevar

See Also

Almudevar A, McCall MN, McMurray H, Land H (2011). Fitting Boolean Networks from Steady State Perturbation Data, Statistical Applications in Genetics and Molecular Biology, 10(1): Article 47.

Examples

```
ssObj <- matrix(c(1,1,1,0,1,1,0,0,1),nrow=3)
pObj <- matrix(c(1,0,0,0,1,0,0,0,1),nrow=3)
tnfitObj <- tnetfit(ssObj, pObj)
plotTraces(tnfitObj)
```

predictAttractor

Predict the attractor(s) resulting from a given perturbation

Description

This function computes the posterior probabilities of attractors reached for a given perturbation using the networks from a ternaryPost object.

Usage

```
predictAttractor(tpost, perturbations, wildtype = TRUE, verbose = FALSE)
```

Arguments

tpost	a ternaryPost object
perturbations	a list with two elements: perturbed.genes and forced.states
wildtype	if TRUE, the wildtype attractors are summarized; if FALSE, the perturbed attractors are summarized.
verbose	if TRUE, periodic reports on progress are printed.

Value

The function returns a list with two elements: \post.prob: the posterior probability of each attractor
 \ attractor.summary: a single vector of steady states based on the resulting attractor

Author(s)

Matthew N. McCall and Anthony Almudevar

See Also

Almudevar A, McCall MN, McMurray H, Land H (2011). Fitting Boolean Networks from Steady State Perturbation Data, Statistical Applications in Genetics and Molecular Biology, 10(1): Article 47.

Examples

```
ssObj <- matrix(c(1,1,1,0,1,1,0,0,1),nrow=3)
pObj <- matrix(c(1,0,0,0,1,0,0,0,1),nrow=3)
rownames(ssObj) <- rownames(pObj) <- colnames(ssObj) <- colnames(pObj) <- c("Gene1", "Gene2", "Gene3")
tnfitObj <- tnetfit(ssObj, pObj)
tnpostObj <- tnetpost(tnfitObj, mdelta=10, msample=10)
predictAttractor(tnpostObj, list(perturbed.genes=c(1,2),forced.states=c(1,1)))
```

simulateSteadyState	<i>Simulate Steady State Data</i>
---------------------	-----------------------------------

Description

This function generates simulated steady state data from a given network.

Usage

```
simulateSteadyState(perturbationObj, tableObj, graphObj, degreeObj, wildtype=FALSE)
```

Arguments

perturbationObj	a matrix of perturbation experiments. Rows are genes and columns are experiments.
tableObj	a matrix containing the transition function tables
graphObj	a matrix containing the parents of each node
degreeObj	a vector containing the in-degree of each node
wildtype	if TRUE, the perturbations are assumed to be transient; if FALSE, the perturbations are assumed to be persistent.

Value

The function creates a steadyStateObj.

Author(s)

Matthew N. McCall and Anthony Almudevar

See Also

Almudevar A, McCall MN, McMurray H, Land H (2011). Fitting Boolean Networks from Steady State Perturbation Data, Statistical Applications in Genetics and Molecular Biology, 10(1): Article 47.

Examples

```
pObj <- matrix(c(1,0,0,0,1,0,0,0,1),nrow=3)
degreeObj <- c(0,1,1)
graphObj <- matrix(nrow=1,ncol=3)
graphObj[1,1] <- 0
graphObj[1,2] <- 1
graphObj[1,3] <- 2
tableObj <- matrix(nrow=3,ncol=3)
tableObj[,1] <- rep(0,3)
tableObj[,2] <- c(-1,0,1)
tableObj[,3] <- c(-1,0,1)
ssObj <- simulateSteadyState(pObj, tableObj, graphObj, degreeObj)
```

ternaryFit-class

Ternary Network Fit

Description

This is a class representation of the output of the ternary network fitting algorithm implemented in the function `tnetfit`.

Creating Objects

While one can create their own objects using the function `ternaryFit()`, this is highly discouraged. Typically this class is created by running the `tnetfit` function.

Slots

perturbationObj: a matrix of perturbation experiments. Rows are genes and columns are experiments.

steadyStateObj: a matrix of steady gene expression observations from a perturbation experiment. Rows are genes and columns are experiments.

geneNames: a vector of gene names corresponding to the rows of the `perturbationObj` and `steadyStateObj`.

experimentNames: a vector of experiment names corresponding to the columns of the `perturbationObj` and `steadyStateObj`.

degreeObjMin: a vector containing the in-degree of each node in the fit achieving the minimum score

graphObjMin: a matrix containing the parents of each node in the fit achieving the minimum score

tableObjMin: a matrix containing the table in the fit achieving the minimum score

newScore: the most recent score
minScore: the minimum score
finalTemperature: the final value of the temperature parameter
traces: a dataframe contain the traces for 4 parameters
stageCount: the number of stages
xSeed: the random seed.
inputParams: the ternaryFitParameters object used.

Methods

All named elements can be accessed and set in the standard way (e.g. `xSeed(object)` and `xSeed(object)<-`).

Author(s)

Matthew N. McCall and Anthony Almudevar

See Also

`tnetpost`, `ternaryFitParameters-class`, `ternaryPost-class`. Almudevar A, McCall MN, McMurray H, Land H (2011). Fitting Boolean Networks from Steady State Perturbation Data, Statistical Applications in Genetics and Molecular Biology, 10(1): Article 47.

Examples

```

ssObj <- matrix(c(1,1,1,0,1,1,0,0,1),nrow=3)
pObj <- matrix(c(1,0,0,0,1,0,0,0,1),nrow=3)
tnfitObj <- tnetfit(ssObj, pObj)
class(tnfitObj)

```

`ternaryFitParameters-class`

Ternary Network Fitting Parameters

Description

This is a class representation of the input parameters for the ternary network fitting algorithm implemented in the function `tnetfit`.

Creating Objects

```
ternaryFitParameters()
```

This creates a `ternaryFitParameters` object with the default fitting parameters.

Slots

- perturbationType:** this parameter currently can only be set to 1
- scoreType:** the method to score networks. Can be set to either 1 or 2, corresponding the the score types in Almudevar et al. (2011).
- backupStage:** current fit is output periodically according to this parameter
- maxStage:** the maximum number of stages permitted. Ideally, the actual number of stages required until convergence should be much less than this value.
- maxTransition:** This parameter provides an adaptive truncation of the stage sample size. The stage terminates before the specified fixed sample size if the number of transitions resulting in a strict increase of the score reaches this value. If the sampler is in steady state, then this count should be approximately half the number of transitions in which the score changes value.
- epsilon:** Convergence tolerance.
- beta0:** Algorithm terminates when this number of consecutive convergence events have occurred.
- chi0:** The target initial acceptance rate. This should be close to 1, although setting it too close will increase computation time.
- delta:** The increment change in steady state distribution between stages (as variational distance). Larger values tend to decrease computation time, but too large a value will result in spurious convergence.
- ne:** The fixed sample size (number of MCMC transitions) per stage.
- m0:** The sample size (number of transitions) used to determine the initial temperature.
- maxDegree:** Maximum number of parents per node permitted in model topology.
- pAddParent:** This is the probability of adding a parent to a randomly selected node in the proposal function.
- pExchangeParent:** This parameter gives the probability of a parent exchange in the proposal function. The AddParent operation takes precedence, so this probability should be interpreted as being conditional on the rejection of the AddParent operation.
- neighborDegree:** Number of applications of the proposal function.
- pNeighborhood:** Vector of probabilities denoted, which generates the random number of proposal function iterations. The length is one less than neighborDegree. If neighborDegree equals 1 then no iteration is performed, and this vector is ignored.
- rho:** Weight parameter for the exponential smoothing of the variance estimate. For no smoothing set to 1.
- edgePenalty:** This parameter provides a complexity penalty. This number times the number of edges is added to the score. To apply no penalty set this parameter to 0.

Methods

All named elements can be accessed and set in the standard way (e.g. `scoreType(object)` and `scoreType(object)<-`).

Author(s)

Matthew N. McCall and Anthony Almudevar

See Also

tnetfit, ternaryFit-class, ternaryPost-class. Almudevar A, McCall MN, McMurray H, Land H (2011). Fitting Boolean Networks from Steady State Perturbation Data, Statistical Applications in Genetics and Molecular Biology, 10(1): Article 47.

Examples

```
# create an instance
ternaryFitParameters()
```

ternaryPost-class	<i>Ternary Network Posterior</i>
-------------------	----------------------------------

Description

This is a class representation of the output of the ternary network posterior sampling algorithm implemented in the function tnetpost.

Creating Objects

While one can create their own objects using the function ternaryPost(), this is highly discouraged. Typically this class is created by running the tnetpost function.

Slots

perturbationObj: a matrix of perturbation experiments. Rows are genes and columns are experiments.

steadyStateObj: a matrix of steady gene expression observations from a perturbation experiment. Rows are genes and columns are experiments.

geneNames: a vector of gene names corresponding to the rows of the perturbationObj and steadyStateObj.

experimentNames: a vector of experiment names corresponding to the columns of the perturbationObj and steadyStateObj.

scores: the score of each sample

degreeObjs: the in-degree vector for each sample

graphObjs: the graph matrix for each sample

tableObjs: the table matrix for each sample

inputParams: the ternaryFitParameters object used

Methods

All named elements can be accessed and set in the standard way (e.g. scores(object) and scores(object)<-).

Author(s)

Matthew N. McCall and Anthony Almudevar

See Also

tnetfit, ternaryFitParameters-class, ternaryFit-class. Almudevar A, McCall MN, McMurray H, Land H (2011). Fitting Boolean Networks from Steady State Perturbation Data, Statistical Applications in Genetics and Molecular Biology, 10(1): Article 47.

Examples

```
ssObj <- matrix(c(1,1,1,0,1,1,0,0,1),nrow=3)
pObj <- matrix(c(1,0,0,0,1,0,0,0,1),nrow=3)
tnfitObj <- tnetfit(ssObj, pObj)
tnpostObj <- tnetpost(tnfitObj, mdelta=10, msample=10)
class(tnpostObj)
```

tnetfit	<i>Ternary Network Fitting</i>
---------	--------------------------------

Description

This function fits a ternary network based on perturbation experiments.

Usage

```
tnetfit(steadyStateObj, perturbationObj, params=ternaryFitParameters(),
xSeed=NA)
```

Arguments

steadyStateObj	a matrix of steady gene expression observations from a perturbation experiment. Rows are genes and columns are experiments.
perturbationObj	a matrix of perturbation experiments. Rows are genes and columns are experiments.
params	a ternaryFitParameters object
xSeed	an integer random seed. If NA, a random seed is generated.

Value

The function returns a ternaryFit object.

Author(s)

Matthew N. McCall and Anthony Almudevar

See Also

Almudevar A, McCall MN, McMurray H, Land H (2011). Fitting Boolean Networks from Steady State Perturbation Data, *Statistical Applications in Genetics and Molecular Biology*, 10(1): Article 47.

Examples

```
ssObj <- matrix(c(1,1,1,0,1,1,0,0,1),nrow=3)
pObj <- matrix(c(1,0,0,0,1,0,0,0,1),nrow=3)
rownames(ssObj) <- rownames(pObj) <- colnames(ssObj) <- colnames(pObj) <- c("Gene1","Gene2","Gene3")
tnfitObj <- tnetfit(ssObj, pObj)
```

tnetpost

*Ternary Network Posterior Sampling***Description**

This function samples from the posterior density of a ternary network based on perturbation experiments.

Usage

```
tnetpost(tfit, mdelta=as.integer(10000), msample=as.integer(2000), temperatureScale=1.0, xSeed=NA)
```

Arguments

tfit	a ternaryFit object
mdelta	number of transitions between samples
msample	number of samples
temperatureScale	the final temperature is multiplied by this value for sampling
xSeed	an integer random seed. If NA, a random seed is generated.

Value

The function returns a ternaryPost object.

Author(s)

Matthew N. McCall and Anthony Almudevar

See Also

Almudevar A, McCall MN, McMurray H, Land H (2011). Fitting Boolean Networks from Steady State Perturbation Data, *Statistical Applications in Genetics and Molecular Biology*, 10(1): Article 47.

Examples

```
ssObj <- matrix(c(1,1,1,0,1,1,0,0,1),nrow=3)
pObj <- matrix(c(1,0,0,0,1,0,0,0,1),nrow=3)
rownames(ssObj) <- rownames(pObj) <- colnames(ssObj) <- colnames(pObj) <- c("Gene1","Gene2","Gene3")
tnfitObj <- tnetfit(ssObj, pObj)
tnpostObj <- tnetpost(tnfitObj, mdelta=10, msample=10)
```

Index

- * **classes**
 - ternaryFit-class, [11](#)
 - ternaryFitParameters-class, [12](#)
 - ternaryPost-class, [14](#)
- * **manip**
 - attractorSummary, [2](#)
 - graphPosterior, [3](#)
 - plotFit, [6](#)
 - plotPost, [7](#)
 - plotTraces, [8](#)
 - predictAttractor, [9](#)
 - simulateSteadyState, [10](#)
 - tnetfit, [15](#)
 - tnetpost, [16](#)
- attractorSummary, [2](#)
- backupStage
 - (ternaryFitParameters-class), [12](#)
- backupStage, ternaryFitParameters-method
 - (ternaryFitParameters-class), [12](#)
- backupStage<-
 - (ternaryFitParameters-class), [12](#)
- backupStage<-, ternaryFitParameters-method
 - (ternaryFitParameters-class), [12](#)
- beta0 (ternaryFitParameters-class), [12](#)
- beta0, ternaryFitParameters-method
 - (ternaryFitParameters-class), [12](#)
- beta0<- (ternaryFitParameters-class), [12](#)
- beta0<-, ternaryFitParameters-method
 - (ternaryFitParameters-class), [12](#)
- chi0 (ternaryFitParameters-class), [12](#)
- chi0, ternaryFitParameters-method
 - (ternaryFitParameters-class), [12](#)
- chi0<- (ternaryFitParameters-class), [12](#)
- chi0<-, ternaryFitParameters-method
 - (ternaryFitParameters-class), [12](#)
- class:ternaryFit (ternaryFit-class), [11](#)
- class:ternaryFitParameters
 - (ternaryFitParameters-class), [12](#)
- class:ternaryPost (ternaryPost-class), [14](#)
- degreeObjMin (ternaryFit-class), [11](#)
- degreeObjMin, ternaryFit-method
 - (ternaryFit-class), [11](#)
- degreeObjMin<- (ternaryFit-class), [11](#)
- degreeObjMin<-, ternaryFit-method
 - (ternaryFit-class), [11](#)
- degreeObjs (ternaryPost-class), [14](#)
- degreeObjs, ternaryPost-method
 - (ternaryPost-class), [14](#)
- degreeObjs<- (ternaryPost-class), [14](#)
- degreeObjs<-, ternaryPost-method
 - (ternaryPost-class), [14](#)
- delta (ternaryFitParameters-class), [12](#)
- delta, ternaryFitParameters-method
 - (ternaryFitParameters-class), [12](#)
- delta<- (ternaryFitParameters-class), [12](#)
- delta<-, ternaryFitParameters-method
 - (ternaryFitParameters-class), [12](#)
- dim, ternaryFit-method
 - (ternaryFit-class), [11](#)
- dim, ternaryPost-method
 - (ternaryPost-class), [14](#)
- edgePenalty

(ternaryFitParameters-class),
 12
 edgePenalty, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 edgePenalty<-
 (ternaryFitParameters-class),
 12
 edgePenalty<- , ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 epsilon (ternaryFitParameters-class), 12
 epsilon, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 epsilon<- (ternaryFitParameters-class),
 12
 epsilon<- , ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 experimentNames (ternaryFit-class), 11
 experimentNames, ternaryFit-method
 (ternaryFit-class), 11
 experimentNames, ternaryPost-method
 (ternaryPost-class), 14
 experimentNames<- (ternaryFit-class), 11
 experimentNames<- , ternaryFit-method
 (ternaryFit-class), 11
 experimentNames<- , ternaryPost-method
 (ternaryPost-class), 14

 finalTemperature (ternaryFit-class), 11
 finalTemperature, ternaryFit-method
 (ternaryFit-class), 11
 finalTemperature<- (ternaryFit-class),
 11
 finalTemperature<- , ternaryFit-method
 (ternaryFit-class), 11

 geneNames (ternaryFit-class), 11
 geneNames, ternaryFit-method
 (ternaryFit-class), 11
 geneNames, ternaryPost-method
 (ternaryPost-class), 14
 geneNames<- (ternaryFit-class), 11
 geneNames<- , ternaryFit-method
 (ternaryFit-class), 11
 geneNames<- , ternaryPost-method
 (ternaryPost-class), 14

 graphObjMin (ternaryFit-class), 11
 graphObjMin, ternaryFit-method
 (ternaryFit-class), 11
 graphObjMin<- (ternaryFit-class), 11
 graphObjMin<- , ternaryFit-method
 (ternaryFit-class), 11
 graphObjs (ternaryPost-class), 14
 graphObjs, ternaryPost-method
 (ternaryPost-class), 14
 graphObjs<- (ternaryPost-class), 14
 graphObjs<- , ternaryPost-method
 (ternaryPost-class), 14
 graphPosterior, 3

 initialize, ternaryFit-method
 (ternaryFit-class), 11
 initialize, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 initialize, ternaryPost-method
 (ternaryPost-class), 14
 inputParams (ternaryFit-class), 11
 inputParams, ternaryFit-method
 (ternaryFit-class), 11
 inputParams, ternaryPost-method
 (ternaryPost-class), 14
 inputParams<- (ternaryFit-class), 11
 inputParams<- , ternaryFit-method
 (ternaryFit-class), 11
 inputParams<- , ternaryPost-method
 (ternaryPost-class), 14

 m0 (ternaryFitParameters-class), 12
 m0, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 m0<- (ternaryFitParameters-class), 12
 m0<- , ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 maxDegree (ternaryFitParameters-class),
 12
 maxDegree, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 maxDegree<-
 (ternaryFitParameters-class),
 12

maxDegree<- ,ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 maxStage (ternaryFitParameters-class),
 12
 maxStage, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 maxStage<-
 (ternaryFitParameters-class),
 12
 maxStage<- ,ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 maxTransition
 (ternaryFitParameters-class),
 12
 maxTransition, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 maxTransition<-
 (ternaryFitParameters-class),
 12
 maxTransition<- ,ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 minScore (ternaryFit-class), 11
 minScore, ternaryFit-method
 (ternaryFit-class), 11
 minScore<- (ternaryFit-class), 11
 minScore<- ,ternaryFit-method
 (ternaryFit-class), 11

 ne (ternaryFitParameters-class), 12
 ne, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 ne<- (ternaryFitParameters-class), 12
 ne<- ,ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 neighborDegree
 (ternaryFitParameters-class),
 12
 neighborDegree, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 neighborDegree<-
 (ternaryFitParameters-class),
 12

 neighborDegree<- ,ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 newScore (ternaryFit-class), 11
 newScore, ternaryFit-method
 (ternaryFit-class), 11
 newScore<- (ternaryFit-class), 11
 newScore<- ,ternaryFit-method
 (ternaryFit-class), 11

 pAddParent
 (ternaryFitParameters-class),
 12
 pAddParent, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 pAddParent<-
 (ternaryFitParameters-class),
 12
 pAddParent<- ,ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 parallelFit, 4
 perturbationObj (ternaryFit-class), 11
 perturbationObj, ternaryFit-method
 (ternaryFit-class), 11
 perturbationObj, ternaryPost-method
 (ternaryPost-class), 14
 perturbationObj<- (ternaryFit-class), 11
 perturbationObj<- ,ternaryFit-method
 (ternaryFit-class), 11
 perturbationObj<- ,ternaryPost-method
 (ternaryPost-class), 14
 perturbationType
 (ternaryFitParameters-class),
 12
 perturbationType, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 perturbationType<-
 (ternaryFitParameters-class),
 12
 perturbationType<- ,ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 pExchangeParent
 (ternaryFitParameters-class),
 12

pExchangeParent, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 pExchangeParent<-
 (ternaryFitParameters-class),
 12
 pExchangeParent<-, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 plotFit, 6
 plotPost, 7
 plotTraces, 8
 pNeighborhood
 (ternaryFitParameters-class),
 12
 pNeighborhood, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 pNeighborhood<-
 (ternaryFitParameters-class),
 12
 pNeighborhood<-, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 predictAttractor, 9

 rho (ternaryFitParameters-class), 12
 rho, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 rho<- (ternaryFitParameters-class), 12
 rho<-, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12

 scores (ternaryPost-class), 14
 scores, ternaryPost-method
 (ternaryPost-class), 14
 scores<- (ternaryPost-class), 14
 scores<-, ternaryPost-method
 (ternaryPost-class), 14
 scoreType (ternaryFitParameters-class),
 12
 scoreType, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 scoreType<-
 (ternaryFitParameters-class),
 12

 scoreType<-, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 show, ternaryFit-method
 (ternaryFit-class), 11
 show, ternaryFitParameters-method
 (ternaryFitParameters-class),
 12
 show, ternaryPost-method
 (ternaryPost-class), 14
 simulateSteadyState, 10
 stageCount (ternaryFit-class), 11
 stageCount, ternaryFit-method
 (ternaryFit-class), 11
 stageCount<- (ternaryFit-class), 11
 stageCount<-, ternaryFit-method
 (ternaryFit-class), 11
 steadyStateObj (ternaryFit-class), 11
 steadyStateObj, ternaryFit-method
 (ternaryFit-class), 11
 steadyStateObj, ternaryPost-method
 (ternaryPost-class), 14
 steadyStateObj<- (ternaryFit-class), 11
 steadyStateObj<-, ternaryFit-method
 (ternaryFit-class), 11
 steadyStateObj<-, ternaryPost-method
 (ternaryPost-class), 14

 tableObjMin (ternaryFit-class), 11
 tableObjMin, ternaryFit-method
 (ternaryFit-class), 11
 tableObjMin<- (ternaryFit-class), 11
 tableObjMin<-, ternaryFit-method
 (ternaryFit-class), 11
 tableObjs (ternaryPost-class), 14
 tableObjs, ternaryPost-method
 (ternaryPost-class), 14
 tableObjs<- (ternaryPost-class), 14
 tableObjs<-, ternaryPost-method
 (ternaryPost-class), 14
 ternaryFit (ternaryFit-class), 11
 ternaryFit-class, 11
 ternaryFit-methods (ternaryFit-class),
 11
 ternaryFitParameters
 (ternaryFitParameters-class),
 12
 ternaryFitParameters-class, 12

ternaryFitParameters-methods
 (ternaryFitParameters-class),
 12

ternaryPost (ternaryPost-class), 14

ternaryPost-class, 14

ternaryPost-methods
 (ternaryPost-class), 14

tnetfit, 15

tnetpost, 16

traces (ternaryFit-class), 11

traces, ternaryFit-method
 (ternaryFit-class), 11

traces<- (ternaryFit-class), 11

traces<- , ternaryFit-method
 (ternaryFit-class), 11

xSeed (ternaryFit-class), 11

xSeed, ternaryFit-method
 (ternaryFit-class), 11

xSeed<- (ternaryFit-class), 11

xSeed<- , ternaryFit-method
 (ternaryFit-class), 11