

Package ‘clusterProfiler’

April 12, 2022

Type Package

Title A universal enrichment tool for interpreting omics data

Version 4.2.2

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Description This package supports functional characteristics of both coding and non-coding genomics data for thousands of species with up-to-date gene annotation. It provides a universal interface for gene functional annotation from a variety of sources and thus can be applied in diverse scenarios. It provides a tidy interface to access, manipulate, and visualize enrichment results to help users achieve efficient data interpretation. Datasets obtained from multiple treatments and time points can be analyzed and compared in a single run, easily revealing functional consensus and differences among distinct conditions.

Depends R (>= 3.5.0)

Imports AnnotationDbi, downloader, DOSE (>= 3.13.1), dplyr, enrichplot (>= 1.9.3), GO.db, GOSemSim, magrittr, methods, plyr, qvalue, rlang, stats, tidyverse, utils, yulab.utils

Suggests AnnotationHub, knitr, rmarkdown, org.Hs.eg.db, prettydoc, ReactomePA, testthat

VignetteBuilder knitr

ByteCompile true

License Artistic-2.0

URL <https://yulab-smu.top/biomedical-knowledge-mining-book/> (docs),
<https://doi.org/10.1016/j.xinn.2021.100141> (paper)

BugReports <https://github.com/GuangchuangYu/clusterProfiler/issues>

biocViews Annotation, Clustering, GeneSetEnrichment, GO, KEGG, MultipleComparison, Pathways, Reactome, Visualization

RoxygenNote 7.1.2

git_url <https://git.bioconductor.org/packages/clusterProfiler>

git_branch RELEASE_3_14

git_last_commit 4ebb9de

git_last_commit_date 2022-01-12

Date/Publication 2022-04-12

Author Guangchuang Yu [aut, cre, cph]
 (<<https://orcid.org/0000-0002-6485-8781>>),
 Li-Gen Wang [ctb],
 Erqiang Hu [ctb],
 Meijun Chen [ctb],
 Giovanni Dall'Olio [ctb]

R topics documented:

clusterProfiler-package	3
bitr	3
bitr_kegg	4
browseKEGG	4
buildGOmap	5
compareCluster	6
DataSet	7
download_KEGG	7
dropGO	8
enrichDAVID	8
enricher	9
enrichGO	10
enrichKEGG	12
enrichMKEGG	13
enrichWP	14
get_wp_organisms	15
Gff2GeneTable	15
go2ont	16
go2term	16
gofilter	17
groupGO	17
groupGOResult-class	18
GSEA	19
gseGO	20
gseKEGG	21
gseMKEGG	22
gseWP	23
idType	24
ko2name	25
merge_result	25
plotGOgraph	26
read.gmt	27
search_kegg_organism	27
simplify	28
uniprot_get	29

clusterProfiler-package

*statistical analysis and visualization of functional profiles for genes
and gene clusters*

Description

The package implements methods to analyze and visualize functional profiles of gene and gene clusters.

bitr

*bitr***Description**

Biological Id TRanslator

Usage

```
bitr(geneID, fromType, toType, OrgDb, drop = TRUE)
```

Arguments

geneID	input gene id
fromType	input id type
toType	output id type
OrgDb	annotation db
drop	drop NA or not

Value

data.frame

Author(s)

Guangchuang Yu

bitr_kegg*bitr_kegg*

Description

convert biological ID using KEGG API

Usage

```
bitr_kegg(geneID, fromType, toType, organism, drop = TRUE)
```

Arguments

geneID	input gene id
fromType	input id type
toType	output id type
organism	supported organism, can be search using search_kegg_organism function
drop	drop NA or not

Value

data.frame

Author(s)

Guangchuang Yu

browseKEGG*browseKEGG*

Description

open KEGG pathway with web browser

Usage

```
browseKEGG(x, pathID)
```

Arguments

x	an instance of enrichResult or gseaResult
pathID	pathway ID

Value

url

Author(s)

Guangchuang Yu

*buildGOMap**buildGOMap*

Description

building GO mapping files

Usage`buildGOMap(gomap)`**Arguments**

gomap data.frame with two columns of GO and gene ID

Details

provided by a data.frame of GO (column 1) and gene (column 2) direct annotation this function will building gene to GO and GO to gene mapping, with directly and indirectly (ancestor GO term) annotation.

Value

data.frame, GO annotation with indirect annotation

Author(s)

Yu Guangchuang

<code>compareCluster</code>	<i>Compare gene clusters functional profile</i>
-----------------------------	---

Description

Given a list of gene set, this function will compute profiles of each gene cluster.

Usage

```
compareCluster(geneClusters, fun = "enrichGO", data = "", ...)
```

Arguments

- geneClusters a list of entrez gene id. Alternatively, a formula of type Entrez~group
- fun One of "groupGO", "enrichGO", "enrichKEGG", "enrichDO" or "enrichPathway" .
- data if geneClusters is a formula, the data from which the clusters must be extracted.
- ... Other arguments.

Value

A `clusterProfResult` instance.

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

See Also

[compareClusterResult-class](#), [groupGO](#) [enrichGO](#)

Examples

```
## Not run:
data(gcSample)
xx <- compareCluster(gcSample, fun="enrichKEGG",
                      organism="hsa", pvalueCutoff=0.05)
as.data.frame(xx)
# plot(xx, type="dot", caption="KEGG Enrichment Comparison")

## formula interface
mydf <- data.frame(Entrez=c('1', '100', '1000', '100101467',
                           '100127206', '100128071'),
                     group = c('A', 'A', 'A', 'B', 'B', 'B'),
                     othergroup = c('good', 'good', 'bad', 'bad', 'good', 'bad'))
xx.formula <- compareCluster(Entrez~group, data=mydf,
                             fun='groupGO', OrgDb='org.Hs.eg.db')
as.data.frame(xx.formula)
```

```
## formula interface with more than one grouping variable
xx.formula.twogroups <- compareCluster(Entrez~group+othergroup, data=mydf,
                                         fun='groupGO', OrgDb='org.Hs.eg.db')
as.data.frame(xx.formula.twogroups)

## End(Not run)
```

DataSet

Datasets gcSample contains a sample of gene clusters.

Description

Datasets gcSample contains a sample of gene clusters.

Datasets kegg_species contains kegg species information

Datasets DE_GSE8057 contains differential expressed genes obtained from GSE8057 dataset

download_KEGG

download_KEGG

Description

download the latest version of KEGG pathway/module

Usage

```
download_KEGG(species, keggType = "KEGG", keyType = "kegg")
```

Arguments

species	species
keggType	one of 'KEGG' or 'MKEGG'
keyType	supported keyType, see bitr_kegg

Value

list

Author(s)

Guangchuang Yu

`dropGO`*dropGO***Description**

drop GO term of specific level or specific terms (mostly too general).

Usage

```
dropGO(x, level = NULL, term = NULL)
```

Arguments

<code>x</code>	an instance of 'enrichResult' or 'compareClusterResult'
<code>level</code>	GO level
<code>term</code>	GO term

Value

modified version of `x`

Author(s)

Guangchuang Yu

`enrichDAVID`*enrichDAVID***Description**

enrichment analysis by DAVID

Usage

```
enrichDAVID(
  gene,
  idType = "ENTREZ_GENE_ID",
  universe,
  minGSSize = 10,
  maxGSSize = 500,
  annotation = "GOTERM_BP_FAT",
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  qvalueCutoff = 0.2,
  species = NA,
  david.user
)
```

Arguments

gene	input gene
idType	id type
universe	background genes. If missing, the all genes listed in the database (eg TERM2GENE table) will be used as background.
minGSSize	minimal size of genes annotated for testing
maxGSSize	maximal size of genes annotated for testing
annotation	david annotation
pvalueCutoff	adjusted pvalue cutoff on enrichment tests to report
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
qvalueCutoff	qvalue cutoff on enrichment tests to report as significant. Tests must pass i) pvalueCutoff on unadjusted pvalues, ii) pvalueCutoff on adjusted pvalues and iii) qvalueCutoff on qvalues to be reported.
species	species
david.user	david user

Value

A `enrichResult` instance

Author(s)

Guangchuang Yu

enricher

enricher

Description

A universal enrichment analyzer

Usage

```
enricher(
  gene,
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  universe,
  minGSSize = 10,
  maxGSSize = 500,
  qvalueCutoff = 0.2,
  TERM2GENE,
  TERM2NAME = NA
)
```

Arguments

gene	a vector of gene id
pvalueCutoff	adjusted pvalue cutoff on enrichment tests to report
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes. If missing, the all genes listed in the database (eg TERM2GENE table) will be used as background.
minGSSize	minimal size of genes annotated for testing
maxGSSize	maximal size of genes annotated for testing
qvalueCutoff	qvalue cutoff on enrichment tests to report as significant. Tests must pass i) pvalueCutoff on unadjusted pvalues, ii) pvalueCutoff on adjusted pvalues and iii) qvalueCutoff on qvalues to be reported.
TERM2GENE	user input annotation of TERM TO GENE mapping, a data.frame of 2 column with term and gene
TERM2NAME	user input of TERM TO NAME mapping, a data.frame of 2 column with term and name

Value

A `enrichResult` instance

Author(s)

Guangchuang Yu

`enrichGO`

GO Enrichment Analysis of a gene set. Given a vector of genes, this function will return the enrichment GO categories after FDR control.

Description

GO Enrichment Analysis of a gene set. Given a vector of genes, this function will return the enrichment GO categories after FDR control.

Usage

```
enrichGO(
  gene,
  OrgDb,
  keyType = "ENTREZID",
  ont = "MF",
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  universe,
  qvalueCutoff = 0.2,
```

```

minGSSize = 10,
maxGSSize = 500,
readable = FALSE,
pool = FALSE
)

```

Arguments

gene	a vector of entrez gene id.
OrgDb	OrgDb
keyType	keytype of input gene
ont	One of "BP", "MF", and "CC" subontologies, or "ALL" for all three.
pvalueCutoff	adjusted pvalue cutoff on enrichment tests to report
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes. If missing, the all genes listed in the database (eg TERM2GENE table) will be used as background.
qvalueCutoff	qvalue cutoff on enrichment tests to report as significant. Tests must pass i) pvalueCutoff on unadjusted pvalues, ii) pvalueCutoff on adjusted pvalues and iii) qvalueCutoff on qvalues to be reported.
minGSSize	minimal size of genes annotated by Ontology term for testing.
maxGSSize	maximal size of genes annotated for testing
readable	whether mapping gene ID to gene Name
pool	If ont='ALL', whether pool 3 GO sub-ontologies

Value

An `enrichResult` instance.

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

See Also

[enrichResult-class](#), [compareCluster](#)

Examples

```

## Not run:
data(geneList, package = "DOSE")
de <- names(geneList)[1:100]
yy <- enrichGO(de, 'org.Hs.eg.db', ont="BP", pvalueCutoff=0.01)
head(yy)

## End(Not run)

```

enrichKEGG	<i>KEGG Enrichment Analysis of a gene set. Given a vector of genes, this function will return the enrichment KEGG categories with FDR control.</i>
------------	--

Description

KEGG Enrichment Analysis of a gene set. Given a vector of genes, this function will return the enrichment KEGG categories with FDR control.

Usage

```
enrichKEGG(
  gene,
  organism = "hsa",
  keyType = "kegg",
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  universe,
  minGSSize = 10,
  maxGSSize = 500,
  qvalueCutoff = 0.2,
  use_internal_data = FALSE
)
```

Arguments

gene	a vector of entrez gene id.
organism	supported organism listed in ' http://www.genome.jp/kegg/catalog/org_list.html '
keyType	one of "kegg", 'ncbi-geneid', 'ncib-proteinid' and 'uniprot'
pvalueCutoff	adjusted pvalue cutoff on enrichment tests to report
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes. If missing, the all genes listed in the database (eg TERM2GENE table) will be used as background.
minGSSize	minimal size of genes annotated by Ontology term for testing.
maxGSSize	maximal size of genes annotated for testing
qvalueCutoff	qvalue cutoff on enrichment tests to report as significant. Tests must pass i) pvalueCutoff on unadjusted pvalues, ii) pvalueCutoff on adjusted pvalues and iii) qvalueCutoff on qvalues to be reported.
use_internal_data	logical, use KEGG.db or latest online KEGG data

Value

A `enrichResult` instance.

Author(s)

Guangchuang Yu <http://guangchuangyu.github.io>

See Also

[enrichResult-class](#), [compareCluster](#)

Examples

```
## Not run:
data(geneList, package='DOSE')
de <- names(geneList)[1:100]
yy <- enrichMKEGG(de, pvalueCutoff=0.01)
head(yy)

## End(Not run)
```

enrichMKEGG

KEGG Module Enrichment Analysis of a gene set. Given a vector of genes, this function will return the enrichment KEGG Module categories with FDR control.

Description

KEGG Module Enrichment Analysis of a gene set. Given a vector of genes, this function will return the enrichment KEGG Module categories with FDR control.

Usage

```
enrichMKEGG(
  gene,
  organism = "hsa",
  keyType = "kegg",
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  universe,
  minGSSize = 10,
  maxGSSize = 500,
  qvalueCutoff = 0.2
)
```

Arguments

gene	a vector of entrez gene id.
organism	supported organism listed in ' http://www.genome.jp/kegg/catalog/org_list.html '
keyType	one of "kegg", 'ncbi-geneid', 'ncib-proteinid' and 'uniprot'
pvalueCutoff	adjusted pvalue cutoff on enrichment tests to report

pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes. If missing, the all genes listed in the database (eg TERM2GENE table) will be used as background.
minGSSize	minimal size of genes annotated by Ontology term for testing.
maxGSSize	maximal size of genes annotated for testing
qvalueCutoff	qvalue cutoff on enrichment tests to report as significant. Tests must pass i) pvalueCutoff on unadjusted pvalues, ii) pvalueCutoff on adjusted pvalues and iii) qvalueCutoff on qvalues to be reported.

Value

A `enrichResult` instance.

`enrichWP`

enrichWP

Description

ORA analysis for WikiPathways

Usage

```
enrichWP(gene, organism, ...)
```

Arguments

gene	a vector of entrez gene id
organism	supported organisms, which can be accessed via the <code>get_wp_organisms()</code> function
...	additional parameters, see also the parameters supported by the <code>enricher()</code> function

Details

This function performs over-representation analysis using WikiPathways

Value

A `enrichResult` instance

Author(s)

Guangchuang Yu

get_wp_organisms	<i>get_wp_organism</i>
------------------	------------------------

Description

list supported organism of WikiPathways

Usage

```
get_wp_organisms()
```

Details

This function extracts information from '<https://data.wikipathways.org/current/gmt/>' and lists all supported organisms

Value

supported organism list

Author(s)

Guangchuang Yu

Gff2GeneTable	<i>Gff2GeneTable</i>
---------------	----------------------

Description

read GFF file and build gene information table

Usage

```
Gff2GeneTable(gffFile, compress = TRUE)
```

Arguments

gffFile	GFF file
compress	compress file or not

Details

given a GFF file, this function extracts information from it and save it in working directory

Value

file save.

Author(s)

Yu Guangchuang

go2ont

go2ont

Description

convert goid to ontology (BP, CC, MF)

Usage

`go2ont(goid)`

Arguments

`goid` a vector of GO IDs

Value

`data.frame`

Author(s)

Guangchuang Yu

go2term

go2term

Description

convert goid to descriptive term

Usage

`go2term(goid)`

Arguments

`goid` a vector of GO IDs

Value

`data.frame`

Author(s)

Guangchuang Yu

`gofilter``gofilter`

Description

filter GO enriched result at specific level

Usage

```
gofilter(x, level = 4)
```

Arguments

x	output from enrichGO or compareCluster
level	GO level

Value

updated object

Author(s)

Guangchuang Yu

`groupGO`

Functional Profile of a gene set at specific GO level. Given a vector of genes, this function will return the GO profile at a specific level.

Description

Functional Profile of a gene set at specific GO level. Given a vector of genes, this function will return the GO profile at a specific level.

Usage

```
groupGO(  
  gene,  
  OrgDb,  
  keyType = "ENTREZID",  
  ont = "CC",  
  level = 2,  
  readable = FALSE  
)
```

Arguments

gene	a vector of entrez gene id.
OrgDb	OrgDb
keyType	key type of input gene
ont	One of "MF", "BP", and "CC" subontologies.
level	Specific GO Level.
readable	if readable is TRUE, the gene IDs will mapping to gene symbols.

Value

A groupGOResult instance.

Author(s)

Guangchuang Yu <http://guangchuangyu.github.io>

See Also

[groupGOResult-class](#), [compareCluster](#)

Examples

```
data(gcSample)
yy <- groupGO(gcSample[[1]], 'org.Hs.eg.db', ont="BP", level=2)
head(summary(yy))
#plot(yy)
```

groupGOResult-class *Class "groupGOResult" This class represents the result of functional Profiles of a set of gene at specific GO level.*

Description

Class "groupGOResult" This class represents the result of functional Profiles of a set of gene at specific GO level.

Slots

- result GO classification result
- ontology Ontology
- level GO level
- organism one of "human", "mouse" and "yeast"
- gene Gene IDs
- readable logical flag of gene ID in symbol or not.

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

See Also

[compareClusterResult](#) [compareCluster](#) [groupGO](#)

GSEA

GSEA

Description

a universal gene set enrichment analysis tools

Usage

```
GSEA(  
  geneList,  
  exponent = 1,  
  minGSSize = 10,  
  maxGSSize = 500,  
  eps = 1e-10,  
  pvalueCutoff = 0.05,  
  pAdjustMethod = "BH",  
  TERM2GENE,  
  TERM2NAME = NA,  
  verbose = TRUE,  
  seed = FALSE,  
  by = "fgsea",  
  ...  
)
```

Arguments

geneList	order ranked geneList
exponent	weight of each step
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of genes annotated for testing
eps	This parameter sets the boundary for calculating the p value.
pvalueCutoff	adjusted pvalue cutoff
pAdjustMethod	p value adjustment method
TERM2GENE	user input annotation of TERM TO GENE mapping, a data.frame of 2 column with term and gene
TERM2NAME	user input of TERM TO NAME mapping, a data.frame of 2 column with term and name

verbose	logical
seed	logical
by	one of 'fgsea' or 'DOSE'
...	other parameter

Value

`gseaResult` object

Author(s)

Guangchuang Yu

`gseGO`

gseGO

Description

Gene Set Enrichment Analysis of Gene Ontology

Usage

```
gseGO(
  geneList,
  ont = "BP",
  OrgDb,
  keyType = "ENTREZID",
  exponent = 1,
  minGSSize = 10,
  maxGSSize = 500,
  eps = 1e-10,
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  verbose = TRUE,
  seed = FALSE,
  by = "fgsea",
  ...
)
```

Arguments

geneList	order ranked geneList
ont	one of "BP", "MF", and "CC" subontologies, or "ALL" for all three.
OrgDb	OrgDb
keyType	keytype of gene

exponent	weight of each step
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of genes annotated for testing
eps	This parameter sets the boundary for calculating the p value.
pvalueCutoff	pvalue Cutoff
pAdjustMethod	pvalue adjustment method
verbose	print message or not
seed	logical
by	one of 'fgsea' or 'DOSE'
...	other parameter

Value

gseaResult object

Author(s)

Yu Guangchuang

gseKEGGgseKEGG

Description

Gene Set Enrichment Analysis of KEGG

Usage

```
gseKEGG(  
  geneList,  
  organism = "hsa",  
  keyType = "kegg",  
  exponent = 1,  
  minGSSize = 10,  
  maxGSSize = 500,  
  eps = 1e-10,  
  pvalueCutoff = 0.05,  
  pAdjustMethod = "BH",  
  verbose = TRUE,  
  use_internal_data = FALSE,  
  seed = FALSE,  
  by = "fgsea",  
  ...  
)
```

Arguments

geneList	order ranked geneList
organism	supported organism listed in ' http://www.genome.jp/kegg/catalog/org_list.html '
keyType	one of "kegg", 'ncbi-geneid', 'ncib-proteinid' and 'uniprot'
exponent	weight of each step
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of genes annotated for testing
eps	This parameter sets the boundary for calculating the p value.
pvalueCutoff	pvalue Cutoff
pAdjustMethod	pvalue adjustment method
verbose	print message or not
use_internal_data	logical, use KEGG.db or latest online KEGG data
seed	logical
by	one of 'fgsea' or 'DOSE'
...	other parameter

Value

gseaResult object

Author(s)

Yu Guangchuang

gseMKEGG

gseMKEGG

Description

Gene Set Enrichment Analysis of KEGG Module

Usage

```
gseMKEGG(
  geneList,
  organism = "hsa",
  keyType = "kegg",
  exponent = 1,
  minGSSize = 10,
  maxGSSize = 500,
  eps = 1e-10,
  pvalueCutoff = 0.05,
```

```

pAdjustMethod = "BH",
verbose = TRUE,
seed = FALSE,
by = "fgsea",
...
)

```

Arguments

geneList	order ranked geneList
organism	supported organism listed in 'http://www.genome.jp/kegg/catalog/org_list.html'
keyType	one of "kegg", 'ncbi-geneid', 'ncib-proteinid' and 'uniprot'
exponent	weight of each step
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of genes annotated for testing
eps	This parameter sets the boundary for calculating the p value.
pvalueCutoff	pvalue Cutoff
pAdjustMethod	pvalue adjustment method
verbose	print message or not
seed	logical
by	one of 'fgsea' or 'DOSE'
...	other parameter

Value

gseaResult object

Author(s)

Yu Guangchuang

gseWP

gseWP

Description

GSEA analysis for WikiPathways

Usage

`gseWP(geneList, organism, ...)`

Arguments

<code>geneList</code>	ranked gene list
<code>organism</code>	supported organisms, which can be accessed via the <code>get_wp_organisms()</code> function
<code>...</code>	additional parameters, see also the parameters supported by the <code>enricher()</code> function

Details

This function performs GSEA using WikiPathways

Value

A `gseaResult` instance

Author(s)

Guangchuang Yu

`idType` *idType*

Description

list ID types supported by annoDb

Usage

```
idType(OrgDb = "org.Hs.eg.db")
```

Arguments

<code>OrgDb</code>	annotation db
--------------------	---------------

Value

character vector

Author(s)

Guangchuang Yu

ko2name

ko2name

Description

convert ko ID to descriptive name

Usage

`ko2name(ko)`

Arguments

ko ko ID

Value

`data.frame`

Author(s)

guangchuang yu

merge_result

merge_result

Description

merge a list of enrichResult objects to compareClusterResult

Usage

`merge_result(enrichResultList)`

Arguments

enrichResultList
 a list of enrichResult objects

Value

a compareClusterResult instance

Author(s)

Guangchuang Yu

`plotGOgraph`*plotGOgraph***Description**

plot GO graph

Usage

```
plotGOgraph(
  x,
  firstSigNodes = 10,
  useInfo = "all",
  sigForAll = TRUE,
  useFullNames = TRUE,
  ...
)
```

Arguments

<code>x</code>	output of enrichGO or gseGO
<code>firstSigNodes</code>	number of significant nodes (retangle nodes in the graph)
<code>useInfo</code>	additional info
<code>sigForAll</code>	if TRUE the score/p-value of all nodes in the DAG is shown, otherwise only score will be shown
<code>useFullNames</code>	logical
<code>...</code>	additional parameter of showSigOfNodes, please refer to topGO

Value

GO DAG graph

Author(s)

Guangchuang Yu

read.gmt	<i>read.gmt</i>
----------	-----------------

Description

parse gmt file to a data.frame

Usage

```
read.gmt(gmtfile)
```

```
read.gmt.wp(gmtfile)
```

Arguments

gmtfile gmt file

Value

data.frame

Author(s)

Guangchuang Yu

search_kegg_organism	<i>search_kegg_organism</i>
----------------------	-----------------------------

Description

search kegg organism, listed in http://www.genome.jp/kegg/catalog/org_list.html

Usage

```
search_kegg_organism(  
  str,  
  by = "scientific_name",  
  ignore.case = FALSE,  
  use_internal_data = TRUE  
)
```

Arguments

str string
by one of 'kegg.code', 'scientific_name' and 'common_name'
ignore.case TRUE or FALSE
use_internal_data logical, use kegg_species.rda or latest online KEGG data

Value

```
data.frame
```

Author(s)

Guangchuang Yu

simplify

simplify method

Description

simplify output from enrichGO and gseGO by removing redundancy of enriched GO terms
 simplify output from compareCluster by removing redundancy of enriched GO terms

Usage

```
## S4 method for signature 'enrichResult'
simplify(
  x,
  cutoff = 0.7,
  by = "p.adjust",
  select_fun = min,
  measure = "Wang",
  semData = NULL
)

## S4 method for signature 'gseaResult'
simplify(
  x,
  cutoff = 0.7,
  by = "p.adjust",
  select_fun = min,
  measure = "Wang",
  semData = NULL
)

## S4 method for signature 'compareClusterResult'
simplify(
  x,
  cutoff = 0.7,
  by = "p.adjust",
  select_fun = min,
  measure = "Wang",
  semData = NULL
)
```

Arguments

x	output of enrichGO
cutoff	similarity cutoff
by	feature to select representative term, selected by 'select_fun' function
select_fun	function to select feature passed by 'by' parameter
measure	method to measure similarity
semData	GOSemSimDATA object

Value

updated enrichResult object
updated compareClusterResult object

Author(s)

Guangchuang Yu
Gwang-Jin Kim and Guangchuang Yu
Guangchuang Yu

References

issue #28 <https://github.com/GuangchuangYu/clusterProfiler/issues/28>
issue #162 <https://github.com/GuangchuangYu/clusterProfiler/issues/162>

uniprot_get

uniprot_get

Description

retreve annotation data from uniprot

Usage

`uniprot_get(taxID)`

Arguments

`taxID` taxonomy ID

Value

gene table data frame

Author(s)

guangchuang yu

Index

- * **classes**
 - groupGOResult-class, 18
- * **datasets**
 - DataSet, 7
- * **manip**
 - compareCluster, 6
 - enrichGO, 10
 - enrichKEGG, 12
 - groupGO, 17
- bitr, 3
- bitr_kegg, 4
- browseKEGG, 4
- buildGOmap, 5
- clusterProfiler
 - (clusterProfiler-package), 3
- clusterProfiler-package, 3
- compareCluster, 6, 11, 13, 18, 19
- compareClusterResult, 19
- DataSet, 7
- DE_GSE8057 (DataSet), 7
- download_KEGG, 7
- dropGO, 8
- enrichDAVID, 8
- enricher, 9
- enrichGO, 6, 10
- enrichKEGG, 12
- enrichMKEGG, 13
- enrichWP, 14
- gcSample (DataSet), 7
- get_wp_organisms, 15
- Gff2GeneTable, 15
- go2ont, 16
- go2term, 16
- gofilter, 17
- groupGO, 6, 17, 19
- groupGOResult-class, 18
- GSEA, 19
- gseGO, 20
- gseKEGG, 21
- gseMKEGG, 22
- gseWP, 23
- idType, 24
- kegg_species (DataSet), 7
- ko2name, 25
- merge_result, 25
- plotGOgraph, 26
- read.gmt, 27
- search_kegg_organism, 27
- show, groupGOResult-method
 - (groupGOResult-class), 18
- simplify, 28
- simplify, compareClusterResult-method
 - (simplify), 28
- simplify, enrichResult-method
 - (simplify), 28
- simplify, gseaResult-method (simplify), 28
- uniprot_get, 29