

Package ‘PREDA’

July 4, 2025

Version 1.55.0

Title Position Related Data Analysis

Author Francesco Ferrari <francesco.ferrari@ifom.eu>

Maintainer Francesco Ferrari <francesco.ferrari@ifom.eu>

License GPL-2

Depends R (>= 2.9.0), Biobase, lokern (>= 1.0.9), multtest, stats,
methods, annotate

Suggests quantsmooth, qvalue, limma, caTools, affy, PREDAsampledata

Enhances Rmpi, rsprng

Description Package for the position related analysis of quantitative
functional genomics data.

Collate AllClasses.R AllGenerics.R analysesNames.R
CleanNAAnnotationDataframe.R
compareFunctionFromStatisticsForPREDA.R
computeDatasetSignature.R DataForPREDA2dataframe.R
DataForPREDA2GenomicAnnotationsForPREDA.R
DataForPREDA2StatisticsForPREDA.R datasetSignatureFromFlags.R
eset2GenomicAnnotations.R GE_computeStatistic.R
GEhighWeakExpressionWorkflow.R genomePlot_improved.R
genomePlot.R GenomicAnnotations2dataframe.R
GenomicAnnotations2GenomicAnnotationsForPREDA.R
GenomicAnnotations2reference_positions.R
GenomicAnnotationsExtract.R GenomicAnnotationsFilter_neg.R
GenomicAnnotationsFilter_pos.R
GenomicAnnotationsForPREDA2dataframe.R
GenomicAnnotationsForPREDA2GenomicAnnotations.R
GenomicAnnotationsForPREDA2PREDAResults.R
GenomicAnnotationsForPREDAFromfile.R
GenomicAnnotationsForPREDAGetExpectedFlags.R
GenomicAnnotationsFromdataframe.R GenomicAnnotationsFromfile.R
GenomicAnnotationsFromLibrary.R
GenomicAnnotationsSortAndCleanNA.R GenomicRegions2dataframe.R
GenomicRegionsAnnotate.R GenomicRegionsChrNumber.R
GenomicRegionsComparison.R GenomicRegionsCreateRegionsIds.R
GenomicRegionsFilter_neg.R GenomicRegionsFilter_pos.R
GenomicRegionsFindOverlap.R GenomicRegionsFromdataframe.R
GenomicRegionsFromfile.R GenomicRegionsNumber.R

GenomicRegionsSpan.R GenomicRegionsTotalSpan.R
 GESimulationsWorkflow.R getExpectedSmoothFunction.R
 getExpectedSmoothFunction_runmean.R getObservedSmoothFunction.R
 getObservedSmoothFunction_runmean.R getStatisticByName.R
 initialize-methods.R MergeStatisticAnnotations2DataForPREDA.R
 PREDADataAndResults2dataframe.R PREDA_main_permRows.R
 PREDA_main_permSamples.R PREDA_main.R
 PREDA_multTestCorrection.R PREDA_quantsmoothStatPerm.R
 PREDA_quantsmoothStat.R PREDAResults2dataframe.R
 PREDAResults2GenomicRegions.R
 PREDAResults2GenomicRegionsSingle.R
 PREDAResults2PREDADataAndResults.R
 PREDAResultsGetObservedFlags.R PREDA_smoothStatPerm.R
 PREDA_smoothStat.R PREDA_splineStatPerm.R PREDA_splineStat.R
 preprocessingGE.R RMAwithCDFfilter.R simulations.R
 SODEGIR_GEstatistics.R SODEGIRpreprocessingGE.R
 SortAnnotationDataframe.R StatisticsForPREDA2dataframe.R
 StatisticsForPREDAFilterColumns_neg.R
 StatisticsForPREDAFilterColumns_pos.R
 StatisticsForPREDAFromdataframe.R statisticsForPREDAfromEset.R
 StatisticsForPREDAFromfile.R

biocViews Software, CopyNumberVariation, GeneExpression, Genetics

git_url <https://git.bioconductor.org/packages/PREDA>

git_branch devel

git_last_commit f486caa

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-07-03

Contents

analysesNames	3
computeDatasetSignature	4
DataForPREDA-class	6
DataForPREDA2dataframe	8
DataForPREDA2GenomicAnnotationsForPREDA	8
DataForPREDA2StatisticsForPREDA	9
DataForPREDA2MedianCenter	9
eset2GenomicAnnotations	10
genomePlot	11
GenomicAnnotations-class	12
GenomicAnnotations2dataframe	14
GenomicAnnotations2GenomicAnnotationsForPREDA	14
GenomicAnnotations2reference_positions	15
GenomicAnnotationsExtract	16
GenomicAnnotationsFilter_neg	17
GenomicAnnotationsFilter_pos	17
GenomicAnnotationsForPREDA-class	18
GenomicAnnotationsForPREDA2dataframe	20
GenomicAnnotationsForPREDA2GenomicAnnotations	21

GenomicAnnotationsForPREDA2PREDAResults	21
GenomicAnnotationsForPREDAFromfile	22
GenomicAnnotationsFromdataframe	24
GenomicAnnotationsFromfile	25
GenomicAnnotationsFromLibrary	27
GenomicAnnotationsSortAndCleanNA	28
GenomicRegions-class	28
GenomicRegions2dataframe	30
GenomicRegionsAnnotate	31
GenomicRegionsChrNumber	32
GenomicRegionsComparison	33
GenomicRegionsCreateRegionsIds	34
GenomicRegionsFilter_neg	34
GenomicRegionsFilter_pos	35
GenomicRegionsFindOverlap	35
GenomicRegionsFromdataframe	36
GenomicRegionsFromfile	38
GenomicRegionsNumber	39
GenomicRegionsSpan	39
GenomicRegionsTotalSpan	40
getStatisticByName	40
MergeStatisticAnnotations2DataForPREDA	41
PREDADDataAndResults-class	41
PREDADDataAndResults2dataframe	44
PREDAResults-class	44
PREDAResults2dataframe	46
PREDAResults2GenomicRegions	47
PREDAResults2GenomicRegionsSingle	48
PREDAResults2PREDADataAndResults	49
PREDAResultsGetObservedFlags	49
PREDA_main	50
preprocessingGE	51
SODEGIRpreprocessingGE	53
SODEGIR_GEstatistics	56
StatisticsForPREDA-class	57
StatisticsForPREDA2dataframe	59
StatisticsForPREDAFilterColumns_neg	59
StatisticsForPREDAFilterColumns_pos	60
StatisticsForPREDAFromdataframe	60
statisticsForPREDAfromEset	61
StatisticsForPREDAFromfile	63
Index	65

analysesNames

Get the names of the analyses in the from PREDA objects

Description

Get the names of the analyses in the from StatisticsForPREDA objects, PREDAResults objects and objects from classes extending these classes.

Usage

```
analysesNames(.Object)
```

Arguments

.Object an object of class `StatisticsForPREDA`, `PREDAResults` or any other class extending these classes

Value

Character vector of `analysesNames`

Author(s)

Francesco Ferrari

See Also

["StatisticsForPREDA"](#), ["PREDAResults"](#)

Examples

```
require(PREDAsampledata)
data(SODEGIRGEanalysisResults)
analysesNames(SODEGIRGEanalysisResults)
```

```
computeDatasetSignature
```

Function to compute dataset signature for recurrent significant genomic regions

Description

Function to compute dataset signature for recurrent significant genomic regions

Usage

```
# computeDatasetSignature(.Object, genomicRegionsList=genomicRegionsList,
# multTestCorrection="fdr", signature_qval_threshold=0.05,
# returnRegions=TRUE, use.referencePositions=TRUE)

computeDatasetSignature(.Object, ...)
```

Arguments

.Object Object of class `GenomicAnnotationsForPREDA`

... See below

genomicRegionsList: List of `genomicRegions` objects for which the recurrent overlapping regions will be evaluated

multTestCorrection: Multiple testing correction that will be adopted to correct the statistic p-values. Possible values are "fdr", for benjamini and Hochberg multiple testing correction and "qvalue" for p-values correction performed with qvalue package.

signature_qual_threshold: Threshold used to select significant regions resulting from the dataset signature statistic

returnRegions: Logical, if TRUE (default) the genomic regions constituting the dataset signature are returned, otherwise a PREDAResults object containing dataset signature statistics is returned.

use.referencePositions: Logical, if TRUE the input reference positions used for PREDA analysis will be used to identify significant genomic regions boundaries as well.

Details

The function adopts a binomial test to identify significant recurrence of genomic regions across multiple dataset samples.

Value

A GenomicRegions object (if returnRegions = TRUE) or a PREDAResults object containing dataset signature statistics (if returnRegions = FALSE)

Author(s)

Francesco Ferrari

See Also

[GenomicRegions](#), [PREDAResults](#)

Examples

```
## Not run:

require(PREDAsampledData)
data(SODEGIRCNanalysisResults)
data(GEDDataForPREDA)

SODEGIR_CN_GAIN<-PREDAResults2GenomicRegions(
  SODEGIRCNanalysisResults, qual.threshold=0.01,
  smoothStatistic.tail="upper", smoothStatistic.threshold=0.1)

CNgain_signature<-computeDatasetSignature(GEDDataForPREDA,
  genomicRegionsList=SODEGIR_CN_GAIN)

## End(Not run)
```

DataForPREDA-class	<i>Class "DataForPREDA" is used to manage all of the data required as input for PREDA analysis</i>
--------------------	--

Description

This class is used to manage all of the data required as input for PREDA analysis: it is usually created by merging a GenomicAnnotationsForPREDA and a StatisticsForPREDA classes

Objects from the Class

Objects can be created by calls of the form `new("DataForPREDA", ids, chr, start, end, strand, chromosomesNumbers, chromosomesLabels, position, optionalAnnotations, optionalAnnotationsHeaders, statistic, analysesNames, testedTail)`.

Slots

position: Object of class "integer" ~~

ids: Object of class "character" a character vector of unique identifiers for the genomic features under investigation

chr: Object of class "integer" a numeric vector representing the chromosome where each ids is mapped. Please note that chromosome usually not represented with a number must will be converted to a number as well. e.g. for Human, chromsosomees X and Y will be converted to chromosomes 23 and 24 respectively. User defined options will allow this conversion during GenomicAnnotations objects initialization.

start: Object of class "integer" a numeric vector of start genomic position for each genomic feature under investigation (i.e. gene, transcript, SNP or other elements).

end: Object of class "integer" a numeric vector of end genomic position for each genomic feature under investigation (i.e. gene, transcript, SNP or other elements).

strand: Object of class "numeric" a numeric vector of strand genomic position for each genomic feature under investigation: value 1 is used for "plus" (forward) strand and value -1 for "minus" (reverse) strand. User defined options will allow the conversion to this format during GenomicAnnotations objects initialization.

chromosomesNumbers: Object of class "numeric" a numeric vector containing the list of chromosomes for which genomic annotations are provided in the GenomicAnnotations object. Each chromosome is represented just once in increasing order. Please note that chromosome usually not represented with a number must will be converted to a number as well. e.g. for Human, chromsosomees X and Y will be converted to chromosomes 23 and 24 respectively.

chromosomesLabels: Object of class "character" a character vector containing the list of chromosomes for which genomic annotations are provided in the GenomicAnnotations object. Each chromosome is represented just once in the same order as reported in chromosomesNumbers slot. This slot is actually used just to provide a label for each associated chromosome number, in case that some non numeric chromosome is used (e.g. to preserve the correspondence between chr 23 and the actual chr X in Human)

optionalAnnotations: Object of class "matrix" optional annotations associated to the genomic features can be managed along with genomic positions annotations. E.g. GeneSymbol or EntrezGene ids can be associated to gene related GenomicAnnotaitons objects. These additional annotations are not mandatory (the default value for this slot is NULL) The additional annotations must be provided as a matrix of character, with a number of rows equal to the length of "ids" slot and a number of columns equal to the length of "optionalAnnotationsHeaders" slot.

optionalAnnotationsHeaders: Object of class "character" character vector containing the names associated to optional annotations. Please avoid using spaces in annotations names.

statistic: Object of class "matrix" a numeric matrix containing gene-centered statistics (or statistics on genomic data centered on other genomic features under investigation). The statistics must be provided as a matrix of numeric values, with a number of rows equal to the length of "ids" slot and a number of columns equal to the length of "analysesNames" slot.

analysesNames: Object of class "character" a character vector of unique names associated to each column of statistic matrix. This is just a name that will be used to identify each analysis.

testedTail: Object of class "character" a character describing what tail of the statistic distribution will be analyzed during PREDA analysis. Possible values are "upper", "lower" or "both". Anyway we strongly recommend using PREDA analysis only for statistics on genomic data with a symmetric distribution around zero.

Extends

Class "[GenomicAnnotationsForPREDA](#)", directly. Class "[StatisticsForPREDA](#)", directly. Class "[GenomicAnnotations](#)", by class "GenomicAnnotationsForPREDA", distance 2.

Methods

DataForPREDA2dataframe signature(.Object = "DataForPREDA"): extract data and annotations as a dataframe with probeids as rownames

DataForPREDA2GenomicAnnotationsForPREDA signature(.Object = "DataForPREDA"): extract a GenomicAnnotationsForPREDA object from a data DataForPREDA object

DataForPREDA2StatisticsForPREDA signature(.Object = "DataForPREDA"): extract a StatisticsForPREDA object from a data DataForPREDA object

GenomicAnnotationsFilter_neg signature(.Object = "DataForPREDA"): filter annotations to remove selected chromosomes

GenomicAnnotationsFilter_pos signature(.Object = "DataForPREDA"): filter annotations to keep selected chromosomes

GenomicAnnotationsSortAndCleanNA signature(.Object = "DataForPREDA"): sort annotations according to selected chromosomes and to remove genes containing any NA annotation field

initialize signature(.Object = "DataForPREDA"): initialize method for DataForPREDA objects

StatisticsForPREDAFilterColumns_neg signature(.Object = "DataForPREDA"): filter statistics to remove selected analyses

StatisticsForPREDAFilterColumns_pos signature(.Object = "DataForPREDA"): filter statistics to keep selected analyses

Note

This class is better described in the package vignette

Author(s)

Francesco Ferrari

See Also

["GenomicAnnotations"](#), ["GenomicAnnotationsForPREDA"](#), ["StatisticsForPREDA"](#), [DataForPREDA2dataframe](#), [DataForPREDA2GenomicAnnotationsForPREDA](#), [GenomicAnnotationsFilter_neg](#), [GenomicAnnotationsFilter_pos](#), [GenomicAnnotationsSortAndCleanNA](#), [StatisticsForPREDAFilterColumns_neg](#), [StatisticsForPREDAFilterColumns_pos](#)

Examples

```
showClass("DataForPREDA")
```

```
DataForPREDA2dataframe
```

extract data and annotations as a dataframe

Description

extract data and annotations as a dataframe with probeids as rownames

Usage

```
DataForPREDA2dataframe(.Object)
```

Arguments

`.Object` An object of class DataForPREDA

Details

extract data and annotations as a dataframe with probeids as rownames

Value

a dataframe with probeids as rownames

```
DataForPREDA2GenomicAnnotationsForPREDA
```

extract a GenomicAnnotationsForPREDA object from a data DataForPREDA object

Description

extract a GenomicAnnotationsForPREDA object from a data DataForPREDA object

Usage

```
DataForPREDA2GenomicAnnotationsForPREDA(.Object)
```

Arguments

`.Object` an object of class DataForPREDA

Details

extract a GenomicAnnotationsForPREDA object from a data DataForPREDA object

Value

a GenomicAnnotationsForPREDA object

DataForPREDA2StatisticsForPREDA

extract a StatisticsForPREDA object from a data DataForPREDA object

Description

extract a StatisticsForPREDA object from a data DataForPREDA object

Usage

```
DataForPREDA2StatisticsForPREDA(.Object)
```

Arguments

.Object a data DataForPREDA object

Details

extract a StatisticsForPREDA object from a data DataForPREDA object

Value

a StatisticsForPREDA object

DataForPREDAMedianCenter

Function to scale median value of DataForPREDA statistics to zero

Description

Function to scale median value of DataForPREDA statistics to zero

Usage

```
DataForPREDAMedianCenter(.Object, ...)
```

Arguments

.Object a DataForPREDA object
...

Details

Scale median value of DataForPREDA statistics to zero

Value

a DataForPREDA object

`eset2GenomicAnnotations`*Function building a GenomicAnnotations object on an ExpressionSet object*

Description

Function building a GenomicAnnotations object on an ExpressionSet object

Usage

```
# eset2GenomicAnnotations(.Object, retain.chrs,  
# optionalAnnotations)
```

```
eset2GenomicAnnotations(.Object, ...)
```

Arguments

<code>.Object</code>	ExpressionSet object. The associated annotation library will be used to build a GenomicAnnotations object.
<code>...</code>	See below
	retain.chrs: Numeric vector, containing the list of chromosomes selected for the output GenomicAnnotations object. E.g. set <code>retain.chrs=1:22</code> to limit the GenomicAnnotations object to chromosomes from 1 to 22. This might be useful to limit GenomicAnnotations objects to autosomic chromosomes.
	optionalAnnotations: Character vector to select additional annotations fields to be included into the GenomicAnnotations object.

Value

An object of class "[GenomicAnnotations](#)"

Author(s)

Francesco Ferrari

See Also

["GenomicAnnotations"](#)

Examples

```
## Not run:  
require("PREDAsampledData")  
data(ExpressionSetRCC)  
  
GEGenomicAnnotations<-eset2GenomicAnnotations(ExpressionSetRCC,  
retain.chrs=1:22)  
  
## End(Not run)
```

genomePlot

*draw a genome plot***Description**

draw a genome plot with user defined genomic regions

Usage

```
# genomePlot(.Object, genomicRegions=NULL, draw.blocks=TRUE,
# parallel.plot=TRUE, grouping=NULL, custom.labels=NULL,
# scale.positions=NULL, qval.threshold=0.05,
# use.referencePositions=FALSE, smoothStatistic.tail=NULL,
# smoothStatistic.threshold=NULL, region.colors=NULL,
# limitChrs=NULL)

genomePlot(.Object, ...)
```

Arguments

- | | |
|---------|--|
| .Object | Object of class GenomicAnnotationsForPREDA, or any other class extending this one. |
| ... | See below |
- genomicRegions:** A list of GenomicRegions object containing the genomic regions to be highlighted in the plot.
- draw.blocks:** If TRUE genomic regions are plotted as blocks. Otherwise they are plotted as coloured ticks. Currently only draw.blocks=TRUE is implemented.
- parallel.plot:** Logical, if TRUE multiple copies of each chromosome are drawn.
In particular a number of copies equal to length(grouping), if grouping is not null, or a number of copies equal to the number of GenomicRegions objects provided as input.
- grouping:** Vector specifying how input GenomicRegions objects will be grouped on chromosomes.
- custom.labels:** A character to specify user defined labels for vertical axis
- scale.positions:** Parameter to set the scale for chromosomal positions (horizontal axis). Possible values are "Mb" or "Kb"
- qval.threshold:** If genomicRegions is NULL, and a PREDAResults or PREDADataAndResults is provided as input, the function PREDAResults2GenomicRegions is applied with this parameter to extract significant GenomicRegions.
- use.referencePositions:** If genomicRegions is NULL, and a PREDAResults or PREDADataAndResults is provided as input, the function PREDAResults2GenomicRegions is applied with this parameter to extract significant GenomicRegions.
- smoothStatistic.tail:** If genomicRegions is NULL, and a PREDAResults or PREDADataAndResults is provided as input, the function PREDAResults2GenomicRegions is applied with this parameter to extract significant GenomicRegions.

smoothStatistic.threshold: If genomicRegions is NULL, and a PREDAResults or PREDADataAndResults is provided as input, the function PREDAResults2GenomicRegions is applied with this parameter to extract significant GenomicRegions.

region.colors: Character vector specifying the list of colors to be used for drawing each set of GenomicRegions. Must be of length equal to the number of GenomicRegions objects provided as input.

limitChrs: Numeric vector, that can be used to limit the plot to a subset of chromosomes.

Details

See also the PREDA tutorial vignette for more details and sample usage

Value

A plot of the genome with significant GenomicRegions

Author(s)

Francesco Ferrari

See Also

[PREDAResults2GenomicRegions](#), [PREDAResults](#), [PREDADataAndResults](#), [GenomicAnnotationsForPREDA](#)

Examples

```
## See PREDA tutorial vignette for some examples
```

GenomicAnnotations-class

Class "GenomicAnnotations" to manage information about genomic features

Description

This class is used to manage information about genomic features under investigation: i.e. genomic genes, SNP or others, with particular focus on the genomic coordinates of each of them. Other additional annotations associated to each element can be stored in a GenomicAnnotations object in the optionalAnnotations slots

Objects from the Class

Objects can be created by calls of the form `new("GenomicAnnotations",ids, chr, start, end, strand, chromosomesNumbers, chromosomesLabels,optionalAnnotations, optionalAnnotationsHeaders)`.

Slots

ids: Object of class "character" ~~
 chr: Object of class "integer" ~~
 start: Object of class "integer" ~~
 end: Object of class "integer" ~~
 strand: Object of class "numeric" ~~
 chromosomesNumbers: Object of class "numeric" ~~
 chromosomesLabels: Object of class "character" ~~
 optionalAnnotations: Object of class "matrix" ~~
 optionalAnnotationsHeaders: Object of class "character" ~~

Methods

GenomicAnnotations2dataframe signature(.Object = "GenomicAnnotations"): extracts annotations as a dataframe with probeids as rownames

GenomicAnnotations2GenomicAnnotationsForPREDA signature(.Object = "GenomicAnnotations"): generate a new GenomicAnnotationsForPREDA object from a GenomicAnnotations object

GenomicAnnotations2reference_positions signature(.Object = "GenomicAnnotations"): extract from the GenomicAnnotations object a vector containing a vector with reference positions

GenomicAnnotationsExtract signature(.Object = "GenomicAnnotations"): extract optional annotations for a specific region

GenomicAnnotationsFilter_neg signature(.Object = "GenomicAnnotations"): filter annotations to remove selected chromosomes

GenomicAnnotationsFilter_pos signature(.Object = "GenomicAnnotations"): filter annotations to keep selected chromosomes

GenomicAnnotationsSortAndCleanNA signature(.Object = "GenomicAnnotations"): sort annotations according to selected chromosomes and to remove genes containing any NA annotation field

GenomicRegionsAnnotate signature(.Object1 = "GenomicRegions", .Object2 = "GenomicAnnotations"): extract annotations from a GenomicAnnotations object for a set of regions specified as a GenomicRegions object

initialize signature(.Object = "GenomicAnnotations"): initialize method for GenomicAnnotations objects

Note

This class is better described in the package vignette

Author(s)

Francesco Ferrari

See Also

[GenomicAnnotations2dataframe](#), [GenomicAnnotations2GenomicAnnotationsForPREDA](#), [GenomicAnnotations2reference_positions](#), [GenomicAnnotationsFilter_neg](#), [GenomicAnnotationsFilter_pos](#), [GenomicAnnotationsSortAndCleanNA](#), [GenomicRegionsAnnotate](#)

Examples

```
showClass("GenomicAnnotations")
```

```
GenomicAnnotations2dataframe
```

extracts annotations as a dataframe

Description

extracts annotations as a dataframe with probeids as rownames

Usage

```
GenomicAnnotations2dataframe(.Object)
```

Arguments

.Object A GenomicAnnotations object

Details

extract annotations as a dataframe with probeids as rownames

Value

a dataframe with probeids as rownames

```
GenomicAnnotations2GenomicAnnotationsForPREDA
```

generate a GenomicAnnotationsForPREDA object from a GenomicAnnotations object

Description

generate a new GenomicAnnotationsForPREDA object from a GenomicAnnotations object

Usage

```
# GenomicAnnotations2GenomicAnnotationsForPREDA(.Object,  
# positions=NULL, reference_position_type=NULL)
```

```
GenomicAnnotations2GenomicAnnotationsForPREDA(.Object,  
... )
```

Arguments

.Object An object of class GenomicAnnotations
 ... See below
positions: Vector to specify reference positions for GenomicAnnotationsForPREDA object if not specified with reference_position_type parameter
reference_position_type: Specify which genomic coordinate must be used as reference position for PREDA analysis. Possible values are "start", "end", "median", "strand.start" or "strand.end".
 "strand.start" is strand specific start: i.e. start on positive strand but end on negative strand. "strand.end" is strand specific end.

Value

A GenomicAnnotationsForPREDA object

Author(s)

Francesco Ferrari

See Also

[GenomicAnnotationsForPREDA](#)

Examples

```
## Not run:

GEGenomicAnnotations<-GenomicAnnotationsFromLibrary(annotLibrary
= "org.Hs.eg.db", retain.chrs=1:22)

GEGenomicAnnotationsForPREDA<-
  GenomicAnnotations2GenomicAnnotationsForPREDA(
    GEGenomicAnnotations, reference_position_type="median")

## End(Not run)
```

GenomicAnnotations2reference_positions

extract reference positions from the GenomicAnnotations

Description

extract from the GenomicAnnotations object a vector containing a vector with reference positions

Usage

```
# GenomicAnnotations2reference_positions(.Object,
# reference_position_type=c("start", "end", "median", "strand.start", "strand.end"),
# withnames=TRUE)

GenomicAnnotations2reference_positions(.Object, ...)
```

Arguments

.Object Object of class GenomicAnnotations
 ... See below

reference_position_type: Specify which genomic coordinate must be used as reference position for PREDA analysis. Possible values are "start", "end", "median", "strand.start" or "strand.end".
 "strand.start" is strand specific start: i.e. start on positive strand but end on negative strand. "strand.end" is strand specific end.

withnames: Logical, if TRUE the "ids" slot content is used as names for the output vector

Value

A numeric vector with the selected reference positions.

GenomicAnnotationsExtract

extract optional annotations for a specific region

Description

extract optional annotations for a specific region

Usage

```
# GenomicAnnotationsExtract(.Object, chr, start, end,
# AnnotationsHeader=NULL, sep.character="; ",
# complete.inclusion=FALSE, skipSorting=FALSE,
# annotationAsRange=FALSE, getJustFeaturesNumber=FALSE)

GenomicAnnotationsExtract(.Object, ...)
```

Arguments

.Object An object of class GenomicAnnotations
 ... See below

chr: Coordinate for the selected genomic region
start: Coordinate for the selected genomic region
end: Coordinate for the selected genomic region
AnnotationsHeader: Character or numeric vector to select the annotations columns to be considered
sep.character: Character used to separate annotated features in the output
complete.inclusion: Logical, if TRUE only annotated features completely included in the region are reported. If FALSE (default), every overlapping the feature is considered.
skipSorting: Logical, if TRUE, annotation sorting is skipped before processing output (to save computational time, e.g. in a long loop)
annotationAsRange: If TRUE, then only the first and last annotated element in the region are reported
getJustFeaturesNumber: Logical: if TRUE, just the number of annotated features in the region is returned

Details

Extract annotations associated to a specific genomic region from a GenomicAnnotations object. Only annotations from the specified columns are returned.

Value

A character vector is returned

See Also

["GenomicAnnotations"](#)

GenomicAnnotationsFilter_neg

filter annotations to remove selected chromosomes

Description

filter annotations to remove selected chromosomes

Usage

```
# GenomicAnnotationsFilter_neg(.Object, chrToRemove, chrAsLabels=FALSE)
```

```
GenomicAnnotationsFilter_neg(.Object, ...)
```

Arguments

.Object An object of class GenomicAnnotations or classes inheriting from GenomicAnnotations

... See below

chrToRemove: List of chromosomes to be removed from the annotations object.

chrAsLabels: Logical, TRUE if chromosomes are listed as their character labels, instead of using the numeric indexes

GenomicAnnotationsFilter_pos

filter annotations to keep selected chromosomes

Description

filter annotations to keep selected chromosomes

Usage

```
# GenomicAnnotationsFilter_pos(.Object, chrToRetain, chrAsLabels=FALSE)
```

```
GenomicAnnotationsFilter_pos(.Object, ...)
```

Arguments

.Object	An object of class GenomicAnnotations or classes inheriting from GenomicAnnotations
...	See below
	chrToRetain: List of chromosomes to be maintained after removing the annotations for all the other chromosomes.
	chrAsLabels: Logical, TRUE if chromosomes are listed as their character labels, instead of using the numeric indexes

GenomicAnnotationsForPREDA-class

Class "GenomicAnnotationsForPREDA" GenomicAnnotations class with additional slot specifying the reference position for PREDA analysis

Description

This class is equivalent to the GenomicAnnotations class but includes an additional slot specifying the reference position that will be used for PREDA smoothing of data: this is included in the "position" slot. A unique reference position is required for PREDA analysis because this position is used for smoothing data along chromosomal coordinates. This reference position usually is the start, the end, or the median position of each considered genomic feature, nevertheless other user defined positions could be used as well.

Objects from the Class

Objects can be created by calls of the form `new("GenomicAnnotationsForPREDA", ids, chr, start, end, strand, chromosomesNumbers, chromosomesLabels, position, optionalAnnotations, optionalAnnotationsHeaders)`.

Slots

- position:** Object of class "integer" a numeric vector of reference genomic positions that will be associated and used for each genomic feature under investigation for smoothing data during PREDA analysis.
- ids:** Object of class "character" a character vector of unique identifiers for the genomic features under investigation
- chr:** Object of class "integer" a numeric vector representing the chromosome where each ids is mapped. Please note that chromosome usually not represented with a number must will be converted to a number as well. e.g. for Human, chromosomes X and Y will be converted to chromosomes 23 and 24 respectively. User defined options will allow this conversion during GenomicAnnotations objects initialization.
- start:** Object of class "integer" a numeric vector of start genomic position for each genomic feature under investigation (i.e. gene, transcript, SNP or other elements).
- end:** Object of class "integer" a numeric vector of end genomic position for each genomic feature under investigation (i.e. gene, transcript, SNP or other elements).

- strand:** Object of class "numeric" a numeric vector of strand genomic position for each genomic feature under investigation: value 1 is used for "plus" (forward) strand and value -1 for "minus" (reverse) strand. User defined options will allow the conversion to this format during GenomicAnnotations objects initialization.
- chromosomesNumbers:** Object of class "numeric" a numeric vector containing the list of chromosomes for which genomic annotations are provided in the GenomicAnnotations object. Each chromosome is represented just once in increasing order. Please note that chromosome usually not represented with a number must will be converted to a number as well. e.g. for Human, chromosomes X and Y will be converted to chromosomes 23 and 24 respectively.
- chromosomesLabels:** Object of class "character" a character vector containing the list of chromosomes for which genomic annotations are provided in the GenomicAnnotations object. Each chromosome is represented just once in the same order as reported in chromosomesNumbers slot. This slot is actually used just to provide a label for each associated chromosome number, in case that some non numeric chromosome is used (e.g. to preserve the correspondence between chr 23 and the actual chr X in Human)
- optionalAnnotations:** Object of class "matrix" optional annotations associated to the genomic features can be managed along with genomic positions annotations. E.g. GeneSymbol or EntrezGene ids can be associated to gene related GenomicAnnotations objects. These additional annotations are not mandatory (the default value for this slot is NULL) The additional annotations must be provided as a matrix of character, with a number of rows equal to the length of "ids" slot and a number of columns equal to the length of "optionalAnnotationsHeaders" slot.
- optionalAnnotationsHeaders:** Object of class "character" character vector containing the names associated to optional annotations. Please avoid using spaces in annotations names.

Extends

Class "[GenomicAnnotations](#)", directly.

Methods

- genomePlot** signature(.Object = "GenomicAnnotationsForPREDA"): draw a genome plot
- GenomicAnnotations2dataframe** signature(.Object = "GenomicAnnotationsForPREDA"): extract annotations as a dataframe with probeids as rownames
- GenomicAnnotationsFilter_neg** signature(.Object = "GenomicAnnotationsForPREDA"): filter annotations to remove selected chromosomes
- GenomicAnnotationsFilter_pos** signature(.Object = "GenomicAnnotationsForPREDA"): filter annotations to keep selected chromosomes
- GenomicAnnotationsForPREDA2dataframe** signature(.Object = "GenomicAnnotationsForPREDA"): extract annotations as a dataframe with probeids as rownames
- GenomicAnnotationsForPREDA2GenomicAnnotations** signature(.Object = "GenomicAnnotationsForPREDA"): extract the GenomicAnnotations object from the GenomicAnnotationsForPREDA object
- GenomicAnnotationsForPREDA2PREDAResults** signature(.Object = "GenomicAnnotationsForPREDA"): add PREDA results information to genomic annotations creating a PREDAResults object
- GenomicAnnotationsSortAndCleanNA** signature(.Object = "GenomicAnnotationsForPREDA"): sort annotations according to selected chromosomes and to remove genes containing any NA annotation field
- initialize** signature(.Object = "GenomicAnnotationsForPREDA"): initialize method for GenomicAnnotationsForPREDA objects

Note

This class is better described in the package vignette

Author(s)

Francesco Ferrari

See Also

["GenomicAnnotations"](#), [GenomicAnnotationsSortAndCleanNA](#), [GenomicAnnotationsForPREDA2PREDAResults](#), [GenomicAnnotationsForPREDA2dataframe](#), [GenomicAnnotationsFilter_pos](#), [GenomicAnnotationsFilter_neg](#), [GenomicAnnotationsFilter_pos_neg](#)

Examples

```
showClass("GenomicAnnotationsForPREDA")
```

GenomicAnnotationsForPREDA2dataframe
extract annotations as a dataframe

Description

extract annotations as a dataframe with probeids as rownames

Usage

```
GenomicAnnotationsForPREDA2dataframe(.Object)
```

Arguments

.Object an object of class GenomicAnnotationsForPREDA

Details

extract annotations from an object of class GenomicAnnotationsForPREDA as a dataframe with probeids as rownames

Value

a dataframe with probeids as rownames

GenomicAnnotationsForPREDA2GenomicAnnotations

extract the GenomicAnnotations object from the GenomicAnnotations-ForPREDA object

Description

extract the GenomicAnnotations object from the GenomicAnnotationsForPREDA object

Usage

```
GenomicAnnotationsForPREDA2GenomicAnnotations(.Object)
```

Arguments

.Object an object of class GenomicAnnotationsForPREDA

GenomicAnnotationsForPREDA2PREDAResults

add PREDA results information to genomic annotations creating a PREDAResults object

Description

add PREDA results information to genomic annotations creating a PREDAResults object

Usage

```
# GenomicAnnotationsForPREDA2PREDAResults(.Object, analysesNames, testedTail, smoothStatistic, pvalue)
```

```
GenomicAnnotationsForPREDA2PREDAResults(.Object, ...)
```

Arguments

.Object An object of class GenomicAnnotationsForPREDA

... See below

analysesNames: analysesNames as in PREDAResults object

testedTail: testedTail as in PREDAResults object

smoothStatistic: smoothStatistic as in PREDAResults object

pvalue: pvalue as in PREDAResults object

qvalue: qvalue as in PREDAResults object

GenomicAnnotationsForPREDAFromfile

Function to create a GenomicAnnotationsForPREDA object from a txt file

Description

Function to create a GenomicAnnotationsForPREDA object from a txt file

Usage

```
GenomicAnnotationsForPREDAFromfile(file, ids_column, chr_column,
start_column, end_column, strand_column, chromosomesNumbers =
NULL, chromosomesLabels = NULL, chromosomesLabelsInput = NULL,
MinusStrandString = "-", PlusStrandString = "+",
optionalAnnotationsColumns = NULL, reference_position_type =
"median", ...)
```

Arguments

file	Path to the input txt file containing genomic annotations
ids_column	Specify the column from the input txt file with gene (or other genomic features) ids. Can be specified using column index (numeric) or column name (character).
chr_column	Specify the column from the input txt file with chromosome annotations fields for each ids. Can be specified using column index (numeric) or column name (character).
start_column	Specify the column from the input txt file with genomic start position for each genomic element. Can be specified using column index (numeric) or column name (character).
end_column	Specify the column from the input txt file with genomic end position for each genomic element. Can be specified using column index (numeric) or column name (character).
strand_column	Specify the column from the input txt file with genomic strand mapping for each genomic element. Can be specified using column index (numeric) or column name (character).
chromosomesNumbers	Numeric vector to specify the list of numeric values to be associated to each chromosome (especially useful for chromosomes not associated to a number such as chr X or Y)
chromosomesLabels	Character vector to specify the list of character labels to be associated to each chromosome (especially useful for chromosomes not associated to a number such as chr X or Y)
chromosomesLabelsInput	Character vector to specify the list of character labels associated to each chromosome in the input file. Particularly useful when non numeric character strings are associated to each chromosome in the input file: e.g. "chr3" for chromosome "3".

MinusStrandString	Character string used to identify minus strand in the input text file
PlusStrandString	Character string used to identify plus strand in the input text file
optionalAnnotationsColumns	Character vector of columns headers or numeric vector of columns indices to specify columns of the input file containing additional annotation fields
reference_position_type	Character string to specify which genomic coordinate must be used as reference position for PREDA analysis. See also " GenomicAnnotations2GenomicAnnotationsForPREDA "
...	any other parameter for read.table function that could be useful for parsing the input file, such as "sep", "quote", "header", "na.strings" and other parameters.

Value

An object of class "[GenomicAnnotationsForPREDA](#)"

Author(s)

Francesco Ferrari

See Also

["GenomicAnnotationsForPREDA"](#)

Examples

```
## Not run:

data(PREDAsampledata)
CNdataPath <- system.file("sampledata", "CopyNumber", package =
"PREDAsampledata")
CNannotationFile <- file.path(CNdataPath , "SNPAnnot100k.csv")

CNGenomicsAnnotations<-GenomicAnnotationsForPREDAFromfile(
  file=CNannotationFile,
  ids_column=1,
  chr_column="Chromosome",
  start_column=4,
  end_column=4,
  strand_column="Strand",
  chromosomesLabelsInput=1:22,
  MinusStrandString="-", PlusStrandString="+",
  optionalAnnotationsColumns=c("Cytoband", "Entrez_gene"),
  header=TRUE, sep=",", quote="\"", na.strings = c("NA", "",
  "---"))

## End(Not run)
```

GenomicAnnotationsFromdataframe

Function to create a GenomiAnnotations object from a dataframe

Description

Function to create a GenomiAnnotations object from a dataframe

Usage

```
GenomicAnnotationsFromdataframe(GenomicAnnotations_dataframe, ids_column, chr_column,
start_column, end_column, strand_column, chromosomesNumbers =
NULL, chromosomesLabels = NULL, chromosomesLabelsInput = NULL,
MinusStrandString = "-", PlusStrandString =
"+", optionalAnnotationsColumns = NULL)
```

Arguments

GenomicAnnotations_dataframe	Dataframe object containing genomic annotations.
ids_column	Specify the column from the input txt file with gene (or other genomic features) ids. Can be specified using column index (numeric) or column name (character).
chr_column	Specify the column from the input txt file with chromosome annotations fields for each ids. Can be specified using column index (numeric) or column name (character).
start_column	Specify the column from the input txt file with genomic start position for each genomic element. Can be specified using column index (numeric) or column name (character).
end_column	Specify the column from the input txt file with genomic end position for each genomic element. Can be specified using column index (numeric) or column name (character).
strand_column	Specify the column from the input txt file with genomic strand mapping for each genomic element. Can be specified using column index (numeric) or column name (character).
chromosomesNumbers	Numeric vector to specify the list of numeric values to be associated to each chromosome (especially useful for chromosomes not associated to a number such as chr X or Y)
chromosomesLabels	Character vector to specify the list of character labels to be associated to each chromosome (especially useful for chromosomes not associated to a number such as chr X or Y)
chromosomesLabelsInput	Character vector to specify the list of character labels associated to each chromosome in the input file. Particularly useful when non numeric character strings are associated to each chromosome in the input file: e.g. "chr3" for chromosome "3".
MinusStrandString	Character string used to identify minus strand in the input text file

PlusStrandString

Character string used to identify plus strand in the input text file

optionalAnnotationsColumns

Character vector of columns headers or numeric vector of columns indices to specify columns of the input file containing additional annotation fields

Value

An object of class `"GenomicAnnotations"`

Author(s)

Francesco Ferrari

See Also

`"GenomicAnnotations"`

GenomicAnnotationsFromFile

Function to create a GenomicAnnotations object from a text file

Description

Function to create a GenomicAnnotations object from a text file

Usage

```
GenomicAnnotationsFromFile(file, ids_column, chr_column,
  start_column, end_column, strand_column, chromosomesNumbers =
  NULL, chromosomesLabels = NULL, chromosomesLabelsInput = NULL,
  MinusStrandString = "-", PlusStrandString =
  "+", optionalAnnotationsColumns = NULL, ...)
```

Arguments

<code>file</code>	Path to the input txt file containing genomic annotations
<code>ids_column</code>	Specify the column from the input txt file with gene (or other genomic features) ids. Can be specified using column index (numeric) or column name (character).
<code>chr_column</code>	Specify the column from the input txt file with chromosome annotations fields for each ids. Can be specified using column index (numeric) or column name (character).
<code>start_column</code>	Specify the column from the input txt file with genomic start position for each genomic element. Can be specified using column index (numeric) or column name (character).
<code>end_column</code>	Specify the column from the input txt file with genomic end position for each genomic element. Can be specified using column index (numeric) or column name (character).
<code>strand_column</code>	Specify the column from the input txt file with genomic strand mapping for each genomic element. Can be specified using column index (numeric) or column name (character).

chromosomesNumbers	Numeric vector to specify the list of numeric values to be associated to each chromosome (especially useful for chromosomes not associated to a number such as chr X or Y)
chromosomesLabels	Character vector to specify the list of character labels to be associated to each chromosome (especially useful for chromosomes not associated to a number such as chr X or Y)
chromosomesLabelsInput	Character vector to specify the list of character labels associated to each chromosome in the input file. Particularly useful when non numeric character strings are associated to each chromosome in the input file: e.g. "chr3" for chromosome "3".
MinusStrandString	Character string used to identify minus strand in the input text file
PlusStrandString	Character string used to identify plus strand in the input text file
optionalAnnotationsColumns	Character vector of columns headers or numeric vector of columns indices to specify columns of the input file containing additional annotation fields
...	any other parameter for read.table function that could be useful for parsing the input file, such as "sep", "quote", "header", "na.strings" and other parameters.

Value

An object of class "[GenomicAnnotations](#)"

Author(s)

Francesco Ferrari

See Also

["GenomicAnnotations"](#)

Examples

```
## Not run:

data(PREDAsampledata)
CNdataPath <- system.file("sampledata", "CopyNumber", package =
"PREDAsampledata")
CNannotationFile <- file.path(CNdataPath , "SNPAnnot100k.csv")

CNGenomicsAnnotations<-GenomicAnnotationsForPREDAFromFile(
  file=CNannotationFile,
  ids_column=1,
  chr_column="Chromosome",
  start_column=4,
  end_column=4,
  strand_column="Strand",
  chromosomesLabelsInput=1:22,
  MinusStrandString="-", PlusStrandString="+",
  optionalAnnotationsColumns=c("Cytoband", "Entrez_gene"),
```

```
header=TRUE, sep=",", quote="\"", na.strings = c("NA", "",
"---"))
```

```
## End(Not run)
```

GenomicAnnotationsFromLibrary

Function extracting a GenomicAnnotations object from a Bioconductor annotation library

Description

Function extracting a GenomicAnnotations object from a Bioconductor annotation library

Usage

```
GenomicAnnotationsFromLibrary(annotLibrary, probeIDs = NULL,
retain.chrs = NULL, optionalAnnotations = NULL)
```

Arguments

annotLibrary	Character string containing the name of the annotations library to be used for building the GenomicAnnotations object
probeIDs	Optional: list of reference id from the selected annotLibrary to be used for building the GenomicAnnotations object
retain.chrs	Numeric vector, containing the list of chromosomes selected for the output GenomicAnnotations object. E.g. set retain.chrs=1:22 to limit the GenomicAnnotations object to chromosomes from 1 to 22. This might be useful to limit GenomicAnnotations objects to autosomic chromosomes.
optionalAnnotations	Character vector to select additional annotations fields to be included into the GenomicAnnotations object.

Value

An object of class "[GenomicAnnotations](#)"

Author(s)

Francesco Ferrari

See Also

["GenomicAnnotations"](#)

Examples

```
## Not run:

GEGenomicAnnotations<-GenomicAnnotationsFromLibrary(annotLibrary=
"org.Hs.eg.db", retain.chrs=1:22)

# with optional annotations Genesymbols and EntrezGeneIDs
GEGenomicAnnotations<-GenomicAnnotationsFromLibrary(annotLibrary=
"hgu133plus2.db", retain.chrs=1:22,
optionalAnnotations=c("SYMBOL", "ENTREZID"))

## End(Not run)
```

GenomicAnnotationsSortAndCleanNA

sort annotations according to selected chromosomes and to remove genes containing any NA annotation field

Description

sort annotations according to selected chromosomes and to remove genes containing any NA annotation field

Usage

```
# GenomicAnnotationsSortAndCleanNA(.Object, sorting_position_column="start")

GenomicAnnotationsSortAndCleanNA(.Object, ...)
```

Arguments

.Object	An object of class GenomicAnnotations or any object inheriting from GenomicAnnotations
...	See below
	sorting_position_column: Annotations slot used to sort data within each chromosome. Possible values include "start", "end" or "position" (the last one for GenomicAnnotationsForPREDA objects)

GenomicRegions-class	<i>Class "GenomicRegions" is used to manage information about genomic regions</i>
----------------------	---

Description

This class is used to manage genomic regions information that can be derived from PREDA analysis results or from other sources: e.g. relevant genomic regions from literature reports can be imported into a GenomicRegions object and compared with PREDA analysis results

Objects from the Class

Objects can be created by calls of the form `new("GenomicRegions", chr, start, end, chromosomesNumbers, chromosomesLabels, optionalAnnotations, optionalAnnotationsHeaders, ids)`.

Slots

chr: Object of class "integer" a numeric vector representing the chromosome where each genomic region is located. Please note that chromosome usually not represented with a number must will be converted to a number as well. e.g. for Human, chromosomes X and Y will be converted to chromosomes 23 and 24 respectively. User defined options will allow this conversion during GenomicAnnotations objects initialization.

start: Object of class "integer" a numeric vector of start genomic position for each genomic region. This vector must have the same length of "chr" slot.

end: Object of class "integer" a numeric vector of end genomic position for each genomic region. This vector must have the same length of "chr" slot.

chromosomesNumbers: Object of class "numeric" a numeric vector containing the list of chromosomes associated to genomic regions in the GenomicRegions object. Each chromosome is represented just once in increasing order. Please note that chromosomes usually not represented with a number will be converted to a number as well. e.g. for Human, chromosomes X and Y will be converted to chromosomes 23 and 24 respectively.

chromosomesLabels: Object of class "character" a character vector containing the list of chromosomes associated to genomic regions in the GenomicRegions object. Each chromosome is represented just once in the same order as reported in chromosomesNumbers slot. This slot is actually used just to provide a label for each associated chromosome number, in case that some non numeric chromosome is used (e.g. to preserve the correspondence between chr 23 and the actual chr X in Human)

optionalAnnotations: Object of class "matrix" optional annotations associated to the genomic regions can be managed along with GenomicRegions objects. E.g. the list of GeneSymbol or EntrezGene ids associated to each genomic region can be provided as optional annotation. These additional annotations are not mandatory (the default value for this slot is NULL) The additional annotations must be provided as a matrix of character, with a number of rows equal to the length of "chr", "start" and "end" slots and a number of columns equal to the length of "optionalAnnotationsHeaders" slot.

optionalAnnotationsHeaders: Object of class "character" the list of names associated to optional annotations. Please avoid using spaces in annotations names.

ids: Object of class "character" a character vector of unique identifiers associated to each genomic regions. This is just an optional element of GenomicRegions objects: the default value is NULL.

Methods

GenomicRegions2dataframe signature(.Object = "GenomicRegions"): extract genomic regions information as a dataframe object

GenomicRegionsAnnotate signature(.Object1 = "GenomicRegions", .Object2 = "GenomicAnnotations"): extract annotations from a GenomicAnnotations object for a set of regions specified as a GenomicRegions object

GenomicRegionsChrNumber signature(.Object = "GenomicRegions"): determine the number of chromosomes with genomic regions

GenomicRegionsComparison signature(.Object1 = "GenomicRegions", .Object2 = "GenomicRegions"): compare GenomicRegions objects to identify overlaps

GenomicRegionsCreateRegionsIds signature(.Object = "GenomicRegions"): generate unique ids for GenomicRegions objects

GenomicRegionsFilter_neg signature(.Object = "GenomicRegions"): filter genomic regions to remove selected chromosomes

GenomicRegionsFilter_pos signature(.Object = "GenomicRegions"): filter genomic regions to keep selected chromosomes

GenomicRegionsNumber signature(.Object = "GenomicRegions"): determine the number of genomic regions

GenomicRegionsSpan signature(.Object = "GenomicRegions"): determine the span of each genomic region

GenomicRegionsTotalSpan signature(.Object = "GenomicRegions"): determine the total span of genomic regions

initialize signature(.Object = "GenomicRegions"): initialize method for GenomicRegions objects

Note

This class is better described in the package vignette

Author(s)

Francesco Ferrari

See Also

[GenomicAnnotationsSortAndCleanNA,PREDADDataAndResults2dataframe](#)

Examples

```
showClass("GenomicRegions")
```

GenomicRegions2dataframe

extract genomic regions information as a dataframe object

Description

extract genomic regions information as a dataframe object

Usage

```
GenomicRegions2dataframe(GenomicRegionsObject)
```

Arguments

GenomicRegionsObject
Object of class genomic regions

Details

Extract genomic regions information as a dataframe object

Value

A dataframe object

Author(s)

Francesco Ferrari

Examples

```
## Not run:
require(PREDAsampledData)

data(GEanalysisResults)

genomic_regions_UP<-PREDAResults2GenomicRegions(GEanalysisResults
, qval.threshold=0.05, smoothStatistic.tail="upper",
smoothStatistic.threshold=0.5)

dataframe_UPregions<-GenomicRegions2dataframe(
genomic_regions_UP[[1]])

## End(Not run)
```

GenomicRegionsAnnotate

extract annotations from a GenomicAnnotations object for a set of regions specified as a GenomicRegions object

Description

extract annotations from a GenomicAnnotations object for a set of regions specified as a GenomicRegions object

Usage

```
# GenomicRegionsAnnotate(.Object1, .Object2,
# AnnotationsHeaders=NULL, sep.character="; ",
# complete.inclusion=FALSE, annotationAsRange=FALSE,
# getJustFeaturesNumber=FALSE)

GenomicRegionsAnnotate(.Object1, .Object2, ...)
```

Arguments

.Object1	An object of class GenomicRegions
.Object2	An object of class GenomicAnnotations
...	See below

- AnnotationsHeaders:** Names of optional annotations fields from GenomicAnnotations object that are used to annotate the GenomicRegions object. Multiple annotation fields can be used
- sep.character:** Character sequence used to separate annotation features
- complete.inclusion:** Logical, if TRUE only annotations features entirely covered by one of the genomic regions are considered. (e.g. a gene completely included in the genomic regions from start to end) If FALSE also partial overlapping annotation features are used
- annotationAsRange:** Logical, if TRUE only the first and last annotation features associated to each the genomic region are returned
- getJustFeaturesNumber:** Logical, if TRUE only the numbers of annotation features overlapping the genomic regions are returned. If TRUE, only the first element specified with AnnotationsHeaders parameter is considered.

Details

The annotation features overlapping the input genomic regions are used to add optional annotations field to the GenomicRegions object.

If previous optional annotations fields are present, they are preserved as well in the output object

Value

A GenomicRegions object with optionalAnnotations

GenomicRegionsChrNumber
<i>determine the number of chromosomes with genomic regions</i>

Description

determine the number of chromosomes with genomic regions

Usage

GenomicRegionsChrNumber(.Object)

Arguments

.Object An object of class GenomicRegions

GenomicRegionsComparison

compare GenomicRegions objects to identify overlaps and differences

Description

compare GenomicRegions objects to identify overlaps and differences

Usage

```
GenomicRegionsComparison(.Object1, .Object2)
```

Arguments

.Object1	An object of Class GenomicRegions
.Object2	An object of Class GenomicRegions

Details

Compare GenomicRegions objects to identify overlaps and differences

Value

A list containing:

overlapping.regions

GenomicRegions object describing the overlapping regions between input object1 and object2

difference.1.2 GenomicRegions object describing the regions from input object1 not overlapping regions from object2

difference.2.1 GenomicRegions object describing the regions from input object2 not overlapping regions from object1

GenomicRegions1.number

Number of genomic regions in input object1

GenomicRegions2.number

Number of genomic regions in input object2

overlapping.number

Number of overlapping genomic regions between input object1 and object2

GenomicRegions1.totalspan

Total span of genomic regions in input object1

GenomicRegions2.totalspan

Total span of genomic regions in input object2

overlapping.totalspan

Total span of overlapping genomic regions between input object1 and object2

overlap.VS.GenomicRegions1.ratio

Ratio between overlapping regions and regions from input object1

overlap.VS.GenomicRegions2.ratio

Ratio between overlapping regions and regions from input object2

Author(s)

Francesco Ferrari

See Also

[GenomicRegionsFindOverlap](#), [GenomicRegions](#)

GenomicRegionsCreateRegionsIds

generate unique ids for GenomicRegions objects

Description

generate unique ids for GenomicRegions objects

Usage

```
GenomicRegionsCreateRegionsIds(.Object, ...)
```

Arguments

.Object An object of class GenomicRegions
...

GenomicRegionsFilter_neg

filter genomic regions to remove selected chromosomes

Description

filter genomic regions to remove selected chromosomes

Usage

```
# GenomicRegionsFilter_neg(.Object, chrToRemove, chrAsLabels=FALSE, quiet=FALSE)
```

```
GenomicRegionsFilter_neg(.Object, ...)
```

Arguments

.Object An object of class GenomicRegions
... See below

chrToRemove: List of chromosomes to be removed from the genomic regions object.

chrAsLabels: Logical, TRUE if chromosomes are listed as their character labels, instead of using the numeric indexes

quiet: Logical, if FALSE a message is printed to warn of empty (NULL) result of the filtering selection.

GenomicRegionsFilter_pos

filter genomic regions to keep selected chromosomes

Description

filter genomic regions to keep selected chromosomes

Usage

```
# GenomicRegionsFilter_pos(.Object, chrToRetain, chrAsLabels=FALSE, quiet=FALSE)
```

```
GenomicRegionsFilter_pos(.Object, ...)
```

Arguments

`.Object` An object of class `GenomicRegions`

`...` See below

chrToRetain: List of chromosomes to be maintained after removing the genomic regions for all the other chromosomes.

chrAsLabels: Logical, TRUE if chromosomes are listed as their character labels, instead of using the numeric indexes

quiet: Logical, if FALSE a message is printed to warn of empty (NULL) result of the filtering selection.

GenomicRegionsFindOverlap

Function to find overlap between GenomicRegions objects

Description

Function to find overlap between `GenomicRegions` objects

Usage

```
GenomicRegionsFindOverlap(GenomicRegions1, GenomicRegions2 = NULL)
```

Arguments

`GenomicRegions1`

Either a `GenomicRegions` object or a list of `GenomicRegions` objects

`GenomicRegions2`

Optional with default value NULL. Either a `GenomicRegions` object or a list of `GenomicRegions` objects.

Details

Input genomic regions object are compared to select overlapping genomic regions that are returned as GenomicRegions objects.

If two single GenomicRegions object are provided, just one comparison is performed and one single GenomicRegions object is returned.

If one single list of GenomicRegions objects is provided as input, then the included GenomicRegions objects are compared to select overlapping GenomicRegions across all of the elements.

If two lists of GenomicRegions objects are provided as input, they must have the same number of elements, because element by element comparison will be performed to identify overlapping GenomicRegions across all of the elements.

Value

Either a single GenomicRegions object or a list of GenomicRegions objects.

Author(s)

Francesco Ferrari

See Also

[GenomicRegionsComparison](#), [GenomicRegions](#)

Examples

```
## Not run:
require(PREDASampledData)
data(SODEGIRCNanalysisResults)
data(SODEGIRGEanalysisResults)

SODEGIR_GE_UP<-PREDAResults2GenomicRegions(
  SODEGIRGEanalysisResults, qual.threshold=0.05,
  smoothStatistic.tail="upper", smoothStatistic.threshold=0.5)

SODEGIR_CN_GAIN<-PREDAResults2GenomicRegions(
  SODEGIRCNanalysisResults, qual.threshold=0.01,
  smoothStatistic.tail="upper", smoothStatistic.threshold=0.1)

SODEGIR_AMPLIFIED<-GenomicRegionsFindOverlap(SODEGIR_GE_UP,
  SODEGIR_CN_GAIN)

## End(Not run)
```

GenomicRegionsFromdataframe

Function to create a GenomicRegions object from a dataframe

Description

Function to create a GenomicRegions object from a dataframe

Usage

```
GenomicRegionsFromdataframe(GenomicRegions_dataframe, ids_column=NULL, chr_column,
start_column, end_column, chromosomesNumbers=NULL,
chromosomesLabels=NULL, chromosomesLabelsInput=NULL)
```

Arguments

GenomicRegions_dataframe	Dataframe object containing the annotations for genomic regions
ids_column	Specify the column from the input dataframe with (optional) ids for genomic regions. Can be specified using column index (numeric) or column name (character).
chr_column	Specify the column from the input dataframe with chromosome annotations fields. Can be specified using column index (numeric) or column name (character).
start_column	Specify the column from the input dataframe with genomic start position for each genomic region. Can be specified using column index (numeric) or column name (character).
end_column	Specify the column from the input dataframe with genomic end position for each genomic region. Can be specified using column index (numeric) or column name (character).
chromosomesNumbers	Numeric vector to specify the list of numeric values to be associated to each chromosome (especially useful for chromosomes not associated to a number such as chr X or Y)
chromosomesLabels	Character vector to specify the list of character labels to be associated to each chromosome (especially useful for chromosomes not associated to a number such as chr X or Y)
chromosomesLabelsInput	Character vector to specify the list of character labels associated to each chromosome in the input. Particularly useful when non numeric character strings are associated to each chromosome in the input file: e.g. "chr3" for chromosome "3".

Value

An object of class "[GenomicRegions](#)"

Author(s)

Francesco Ferrari

See Also

["GenomicRegions"](#)

GenomicRegionsFromFile

Function to create a GenomicRegions object from a text file

Description

Function to create a GenomicRegions object from a text file

Usage

```
GenomicRegionsFromFile(file, ids_column=NULL, chr_column,
start_column, end_column, chromosomesNumbers=NULL,
chromosomesLabels=NULL, chromosomesLabelsInput=NULL, ...)
```

Arguments

file	Path to the input txt file containing genomic regions annotations
ids_column	Specify the column from the input txt file with (optional) ids for genomic regions. Can be specified using column index (numeric) or column name (character).
chr_column	Specify the column from the input txt file with chromosome annotations fields. Can be specified using column index (numeric) or column name (character).
start_column	Specify the column from the input txt file with genomic start position for each genomic region. Can be specified using column index (numeric) or column name (character).
end_column	Specify the column from the input txt file with genomic end position for each genomic region. Can be specified using column index (numeric) or column name (character).
chromosomesNumbers	Numeric vector to specify the list of numeric values to be associated to each chromosome (especially useful for chromosomes not associated to a number such as chr X or Y)
chromosomesLabels	Character vector to specify the list of character labels to be associated to each chromosome (especially useful for chromosomes not associated to a number such as chr X or Y)
chromosomesLabelsInput	Character vector to specify the list of character labels associated to each chromosome in the input file. Particularly useful when non numeric character strings are associated to each chromosome in the input file: e.g. "chr3" for chromosome "3".
...	any other parameter for read.table function that could be useful for parsing the input file, such as "sep", "quote", "header", "na.strings" and other parameters.

Value

An object of class "[GenomicRegions](#)"

Author(s)

Francesco Ferrari

See Also

["GenomicRegions"](#)

GenomicRegionsNumber *determine the number of genomic regions*

Description

determine the number of genomic regions

Usage

```
GenomicRegionsNumber(.Object)
```

Arguments

.Object An object of class GenomicRegions

GenomicRegionsSpan *determine the span of each genomic region*

Description

determine the span of each genomic region

Usage

```
GenomicRegionsSpan(.Object, ...)
```

Arguments

.Object An object of class GenomicRegions

...

GenomicRegionsTotalSpan

determine the total span of genomic regions

Description

determine the total span of genomic regions

Usage

```
GenomicRegionsTotalSpan(.Object, ...)
```

Arguments

.Object Object of Class GenomicRegions

...

getStatisticByName

extract data for individual analyses using the analysis name

Description

extract data for individual analyses using the analysis name

Usage

```
# getStatisticByName(.Object, analysisName)
```

```
getStatisticByName(.Object, ...)
```

Arguments

.Object An object of class StatisticsForPREDA

... See below

analysisName: Character name of the analysis to be returned

MergeStatisticAnnotations2DataForPREDA

Merge a StatisticsForPREDA and a GenomicAnnotationsForPREDA object into a DataForPREDA object.

Description

This function merges a StatisticsForPREDA and a GenomicAnnotationsForPREDA object into a DataForPREDA object

Usage

```
MergeStatisticAnnotations2DataForPREDA(StatisticsForPREDAObject,
GenomicAnnotationsForPREDAObject, sortAndCleanNA = FALSE, quiet =
FALSE, MedianCenter = FALSE)
```

Arguments

StatisticsForPREDAObject	An object of class StatisticsForPREDA
GenomicAnnotationsForPREDAObject	An object of class GenomicAnnotationsForPREDA
sortAndCleanNA	Logical, if TRUE, genomic annotations are sorted for chromosome and genomic position then ids with NA positional annotations are removed
quiet	Logical, if TRUE messages reporting the number of unmatched ids are suppressed.
MedianCenter	Logical, if TRUE data are normalized per median sample.

Value

An object of class DataForPREDA

Author(s)

Francesco Ferrari

PREDADataAndResults-class

Class "PREDADataAndResults" is used to manage the PREDA analysis output

Description

This class is used to manage the PREDA analysis output along with corresponding input data

Objects from the Class

Objects can be created by calls of the form `new("PREDADataAndResults", ids, chr, start, end, strand, chromosomesNumbers, chromosomesLabels, position, optionalAnnotations, optionalAnnotationsHeaders, analysesNames, testedTail, smoothStatistic, pvalue, qvalue, statistic)`.

Slots

analysesNames: Object of class "character" a character vector of unique names associated to each column of smoothStatistic, pvalue and qvalue matrices. This is just a name that is used to identify each analysis.

testedTail: Object of class "character" a character describing what tail of the statistic distribution will be analyzed during PREDA analysis. Possible values are "upper", "lower" or "both". Anyway we strongly recommend using PREDA analysis only

smoothStatistic: Object of class "matrix" a numeric matrix containing smoothed observed statistics as obtained from PREDA analysis. The smoothed statistics must be provided as a matrix of numeric values, with a number of rows equal to the length of "ids" slot and a number of columns equal to the length of "analysesNames" slot.

pvalue: Object of class "matrix" a numeric matrix containing unadjusted gene-centered pvalues as obtained from PREDA analysis. The pvalue matrix must be provided as a matrix of numeric values, with a number of rows equal to the length of "ids" slot and a number of columns equal to the length of "analysesNames" slot.

qvalue: Object of class "matrix" a numeric matrix containing adjusted gene-centered pvalues as obtained from PREDA analysis: i.e. usually FDR adjusted pvalues, but other multiple testing methods could be adopted as well. The qvalue matrix must be provided as a matrix of numeric values, with a number of rows equal to the length of "ids" slot and a number of columns equal to the length of "analysesNames" slot.

position: Object of class "integer" a numeric vector of reference genomic positions that will be associated and used for each genomic feature under investigation for smoothing data during PREDA analysis.

ids: Object of class "character" a character vector of unique identifiers for the genomic features under investigation

chr: Object of class "integer" a numeric vector representing the chromosome where each ids is mapped. Please note that chromosome usually not represented with a number must will be converted to a number as well. e.g. for Human, chromosomes X and Y will be converted to chromosomes 23 and 24 respectively. User defined options will allow this conversion during GenomicAnnotations objects initialization.

start: Object of class "integer" a numeric vector of start genomic position for each genomic feature under investigation (i.e. gene, transcript, SNP or other elements).

end: Object of class "integer" a numeric vector of end genomic position for each genomic feature under investigation (i.e. gene, transcript, SNP or other elements).

strand: Object of class "numeric" a numeric vector of strand genomic position for each genomic feature under investigation: value 1 is used for "plus" (forward) strand and value -1 for "minus" (reverse) strand. User defined options will allow the conversion to this format during GenomicAnnotations objects initialization.

chromosomesNumbers: Object of class "numeric" a numeric vector containing the list of chromosomes for which genomic annotations are provided in the GenomicAnnotations object. Each chromosome is represented just once in increasing order. Please note that chromosome usually not represented with a number must will be converted to a number as well. e.g. for Human, chromosomes X and Y will be converted to chromosomes 23 and 24 respectively.

chromosomesLabels: Object of class "character" a character vector containing the list of chromosomes for which genomic annotations are provided in the GenomicAnnotations object. Each chromosome is represented just once in the same order as reported in chromosomes-Numbers slot. This slot is actually used just to provide a label for each associated chromosome number, in case that some non numeric chromosome is used (e.g. to preserve the correspondence between chr 23 and the actual chr X in Human)

optionalAnnotations: Object of class "matrix" optional annotations associated to the genomic features can be managed along with genomic positions annotations. E.g. GeneSymbol or EntrezGene ids can be associated to gene related GenomicAnnotations objects. These additional annotations are not mandatory (the default value for this slot is NULL) The additional annotations must be provided as a matrix of character, with a number of rows equal to the length of "ids" slot and a number of columns equal to the length of "optionalAnnotationsHeaders" slot.

optionalAnnotationsHeaders: Object of class "character" character vector containing the names associated to optional annotations. Please avoid using spaces in annotations names.

statistic: Object of class "matrix" a numeric matrix containing gene-centered statistics (or statistics on genomic data centered on other genomic features under investigation). The statistics must be provided as a matrix of numeric values, with a number of rows equal to the length of "ids" slot and a number of columns equal to the length of "analysesNames" slot.

Extends

Class "PREDAResults", directly. Class "DataForPREDA", directly. Class "GenomicAnnotationsForPREDA", by class "PREDAResults", distance 2. Class "StatisticsForPREDA", by class "DataForPREDA", distance 2. Class "GenomicAnnotations", by class "PREDAResults", distance 3.

Methods

GenomicAnnotationsSortAndCleanNA signature(.Object = "PREADDataAndResults"): sort annotations according to selected chromosomes and to remove genes containing any NA annotation field

initialize signature(.Object = "PREADDataAndResults"): initialize method for PREADDataAndResults objects

PREDADDataAndResults2dataframe signature(.Object = "PREADDataAndResults"): extract data and annotations as a dataframe with probeids as rownames

Note

This class is better described in the package vignette

Author(s)

Francesco Ferrari

See Also

"GenomicAnnotations", "GenomicAnnotationsForPREDA", "StatisticsForPREDA", "DataForPREDA", "PREDAResults", GenomicAnnotationsSortAndCleanNA,PREADDataAndResults2dataframe

Examples

```
showClass("PREADDataAndResults")
```

```
PREDADDataAndResults2dataframe
```

extract data and annotations as a dataframe with probeids as rownames

Description

extract data and annotations as a dataframe with probeids as rownames

Usage

```
PREDADDataAndResults2dataframe(.Object)
```

Arguments

.Object An object of class PREDADDataAndResults

```
PREDAResults-class
```

Class "PREDAResults" ~is used to manage the PREDA analysis output

Description

this class is used to manage the basic PREDA analysis output including smoothened statistic, pvalues and qvalues.

Objects from the Class

Objects can be created by calls of the form `new("PREDAResults", ids, chr, start, end, strand, chromosomesNumbers, chromosomesLabels, position, optionalAnnotations, optionalAnnotationsHeaders, analysesNames, testedTail, smoothStatistic, pvalue, qvalue)`.

Slots

analysesNames: Object of class "character" a character vector of unique names associated to each column of smoothStatistic, pvalue and qvalue matrices. This is just a name that is used to identify each analysis.

testedTail: Object of class "character" a character describing what tail of the statistic distribution will be analyzed during PREDA analysis. Possible values are "upper", "lower" or "both". Anyway we strongly recommend using PREDA analysis only

smoothStatistic: Object of class "matrix" a numeric matrix containing smoothed observed statistics as obtained from PREDA analysis. The smoothed statistics must be provided as a matrix of numeric values, with a number of rows equal to the length of "ids" slot and a number of columns equal to the length of "analysesNames" slot.

pvalue: Object of class "matrix" a numeric matrix containing unadjusted gene-centered pvalues as obtained from PREDA analysis. The pvalue matrix must be provided as a matrix of numeric values, with a number of rows equal to the length of "ids" slot and a number of columns equal to the length of "analysesNames" slot.

- qvalue:** Object of class "matrix" a numeric matrix containing adjusted gene-centered pvalues as obtained from PREDA analysis: i.e. usually FDR adjusted pvalues, but other multiple testing methods could be adopted as well. The qvalue matrix must be provided as a matrix of numeric values, with a number of rows equal to the length of "ids" slot and a number of columns equal to the length of "analysesNames" slot.
- position:** Object of class "integer" a numeric vector of reference genomic positions that will be associated and used for each genomic feature under investigation for smoothing data during PREDA analysis.
- ids:** Object of class "character" a character vector of unique identifiers for the genomic features under investigation
- chr:** Object of class "integer" a numeric vector representing the chromosome where each ids is mapped. Please note that chromosome usually not represented with a number must will be converted to a number as well. e.g. for Human, chromosomes X and Y will be converted to chromosomes 23 and 24 respectively. User defined options will allow this conversion during GenomicAnnotations objects initialization.
- start:** Object of class "integer" a numeric vector of start genomic position for each genomic feature under investigation (i.e. gene, transcript, SNP or other elements).
- end:** Object of class "integer" a numeric vector of end genomic position for each genomic feature under investigation (i.e. gene, transcript, SNP or other elements).
- strand:** Object of class "numeric" a numeric vector of strand genomic position for each genomic feature under investigation: value 1 is used for "plus" (forward) strand and value -1 for "minus" (reverse) strand. User defined options will allow the conversion to this format during GenomicAnnotations objects initialization.
- chromosomesNumbers:** Object of class "numeric" a numeric vector containing the list of chromosomes for which genomic annotations are provided in the GenomicAnnotations object. Each chromosome is represented just once in increasing order. Please note that chromosome usually not represented with a number must will be converted to a number as well. e.g. for Human, chromosomes X and Y will be converted to chromosomes 23 and 24 respectively.
- chromosomesLabels:** Object of class "character" a character vector containing the list of chromosomes for which genomic annotations are provided in the GenomicAnnotations object. Each chromosome is represented just once in the same order as reported in chromosomesNumbers slot. This slot is actually used just to provide a label for each associated chromosome number, in case that some non numeric chromosome is used (e.g. to preserve the correspondence between chr 23 and the actual chr X in Human)
- optionalAnnotations:** Object of class "matrix" optional annotations associated to the genomic features can be managed along with genomic positions annotations. E.g. GeneSymbol or EntrezGene ids can be associated to gene related GenomicAnnotations objects. These additional annotations are not mandatory (the default value for this slot is NULL) The additional annotations must be provided as a matrix of character, with a number of rows equal to the length of "ids" slot and a number of columns equal to the length of "optionalAnnotationsHeaders" slot.
- optionalAnnotationsHeaders:** Object of class "character" character vector containing the names associated to optional annotations. Please avoid using spaces in annotations names.

Extends

Class "[GenomicAnnotationsForPREDA](#)", directly. Class "[GenomicAnnotations](#)", by class "GenomicAnnotationsForPREDA", distance 2.

Methods

GenomicAnnotationsSortAndCleanNA signature(.Object = "PREDAResults"): sort annotations according to selected chromosomes and to remove genes containing any NA annotation field

initialize signature(.Object = "PREDAResults"): initialize method for PREDAResults objects

PREDAResults2dataframe signature(.Object = "PREDAResults"): extact preda results statistics as a data frame object

PREDAResults2GenomicRegions signature(.Object = "PREDAResults"): identify significant genomic regions from a PREDAResults object

PREDAResults2GenomicRegionsSingle signature(.Object = "PREDAResults"): identify significant genomic regions from a single analysis in a PREDAResults object

PREDAResults2PREDADDataAndResults signature(.Object = "PREDAResults"): merge PREDAResults and input statistics to create a PREDADDataAndResults object

PREDAResultsGetObservedFlags signature(.Object = "PREDAResults"): extract genomic positions with significant alterations as a matrix of flags from a PREDAResults object

Note

This class is better described in the package vignette

Author(s)

Francesco Ferrari

See Also

["GenomicAnnotations"](#), ["GenomicAnnotationsForPREDA"](#), [GenomicAnnotationsSortAndCleanNA](#), [PREDAResults2dataframe](#), [PREDAResults2GenomicRegions](#), [PREDAResults2GenomicRegionsSingle](#), [PREDAResults2PREDADDataAndResults](#), [PREDAResultsGetObservedFlags](#)

Examples

```
showClass("PREDAResults")
```

```
PREDAResults2dataframe
```

extact preda results statistics as a data frame object

Description

extact preda results statistics as a data frame object

Usage

```
PREDAResults2dataframe(.Object)
```

Arguments

.Object An object of class PREDAResults

PREDAResults2GenomicRegions

identify significant genomic regions from a PREDAResults object

Description

identify significant genomic regions from a PREDAResults object

Usage

```
# PREDAResults2GenomicRegions(.Object, qval.threshold=0.05,
# use.referencePositions=TRUE, smoothStatistic.tail=NULL,
# smoothStatistic.threshold=NULL)
```

```
PREDAResults2GenomicRegions(.Object, ...)
```

Arguments

.Object Object of class PREDAResults or PREDADataAndResults

... See below

qval.threshold: q-value threshold used to identify significant genomic regions

use.referencePositions: Logical, if TRUE the input reference positions used for PREDA analysis will be used to identify significant genomic regions boundaries as well.

smoothStatistic.tail: Possible values are "upper" or "lower". This parameter specify if only one tail of the smoothed statistic distribution must be considered. If it is NULL, both tails are used and smoothStatistic.threshold is ignored.

smoothStatistic.threshold: Threshold on smoothStatistic values to select significant genomic regions.

Details

A list of genomic regions objects is returned: one GenomicRegions object for each analysis in the input PREDAResults.

A NULL element is included in the output list whenever no significant regions are identified.

Value

A list of genomic regions objects

Author(s)

Francesco Ferrari

Examples

```
## Not run:
require(PREDAsampledData)

data(GEanalysisResults)

genomic_regions_UP<-PREDAResults2GenomicRegions(GEanalysisResults
, qval.threshold=0.05, smoothStatistic.tail="upper",
smoothStatistic.threshold=0.5)

## End(Not run)
```

PREDAResults2GenomicRegionsSingle

*identify significant genomic regions from a single analysis in a
PREDAResults object*

Description

identify significant genomic regions from a single analysis in a PREDAResults object

Usage

```
# PREDAResults2GenomicRegionsSingle(.Object,
# qval.threshold=0.05, analysisName=NULL,
# use.referencePositions=TRUE, smoothStatistic.tail=NULL,
# smoothStatistic.threshold=NULL)

PREDAResults2GenomicRegionsSingle(.Object, ...)
```

Arguments

.Object	Object of class PREDAResults or PREDADDataAndResults
...	See below

qval.threshold: q-value threshold used to identify significant genomic regions

analysisName: name of the analysis to be considered

use.referencePositions: Logical, if TRUE the input reference positions used for PREDA analysis will be used to identify significant genomic regions boundaries as well.

smoothStatistic.tail: Possible values are "upper" or "lower". This parameter specify if only one tail of the smoothed statistic distribution must be considered. If it is NULL, both tails are used and smoothStatistic.threshold is ignored.

smoothStatistic.threshold: Threshold on smoothStatistic values to select significant genomic regions.

PREDAResults2PREDADDataAndResults

merge PREDAResults and input statistics to create a PREDADDataAndResults object

Description

merge PREDAResults and input statistics to create a PREDADDataAndResults object

Usage

```
# PREDAResults2PREDADDataAndResults(.Object, statistic)
```

```
PREDAResults2PREDADDataAndResults(.Object, ...)
```

Arguments

.Object	An object of class PREDAResults
...	See below
	statistic: A matrix containing input statistics

PREDAResultsGetObservedFlags

extract genomic positions with significant alterations as a matrix of flags from a PREDAResults object

Description

extract genomic positions with significant alterations as a matrix of flags from a PREDAResults object

Usage

```
# PREDAResultsGetObservedFlags(.Object, qval.threshold=0.05,  
# smoothStatistic.tail=NULL, smoothStatistic.threshold=NULL,  
# null.value=0, significant.value=1)
```

```
PREDAResultsGetObservedFlags(.Object, ...)
```

Arguments

.Object	An object of class PREDAResults or PREDADDataAndResults
...	See below
	qval.threshold: q-value threshold used to identify significant genomic positions
	smoothStatistic.tail: Possible values are "upper" or "lower". This parameter specify if only one tail of the smoothed statistic distribution must be considered. If it is NULL, both tails are used and smoothStatistic.threshold is ignored.

smoothStatistic.threshold: Threshold on smoothStatistic values to select significant genomic regions.

null.value: Value (flag) assigned to not significant positions

significant.value: Value (flag) assigned to significant positions

PREDA_main

function performing the core of PREDA analysis

Description

function performing the core of PREDA analysis

Usage

```
PREDA_main(inputDataForPREDA, outputGenomicAnnotationsForPREDA
=NULL, nperms = 10000, verbose = TRUE, parallelComputations =
FALSE, multTestCorrection = "fdr", permutePerChromosome = FALSE,
blocksize = 10, permuteStatisticSign = FALSE, smoothMethod =
"lokern_scaledBandwidth_repeated", force = FALSE,
lokern_scaledBandwidthFactor = 2, limit.analysis = NULL)
```

Arguments

inputDataForPREDA

A Data for PREDA object

outputGenomicAnnotationsForPREDA

A GenomicAnnotationsForPREDA object.

If NULL, GenomicsAnnotations for output data are obtained from inputDataForPREDA

nperms

Number of permutations performed in PREDA analysis.

verbose

Logical, if TRUE some messages are printed concerning the advancement of the analysis.

parallelComputations

Logical, if TRUE Rmpi is used to spawn slave processes, thus using parallel computing to speedup the analysis.

multTestCorrection

Multiple testing correction that will be adopted to correct the statistic p-values. Possible values are "fdr", for benjamini and Hochberg multiple testing correction and "qvalue" for p-values correction performed with qvalue package.

permutePerChromosome

Logical, if TRUE data permutations are perfored separately for each chromosome. In most cases the default value (FALSE) is preferable to avoid biases related to specific chromosomes extreme alterations.

blocksize

A parameter used to tune parallel computations if parallelComputations is TRUE. This is actually the number of permutations performed on each slave process before every communication with master process.

This is useful to reduce the numebr of network communications when slow communicatinos are established among slave processes.

permuteStatisticSign	Logical, if TRUE statistics signs are permuted instead of permuting data along chromosomal position.
smoothMethod	The default smoothing method used in the PREDA_main function is lokern smoothing with scaled bandwidth, using a scaling factor equal to 2. Possible values are "lokern", for standard lokern smoothing, "quantsmooth", "spline" and "runningmean.x", where x is a user defined value for the number of adjacent data points using for running mean smoothing.
force	Logical, if TRUE force skipping quantsmooth control on number of data points. Since quantsmooth is very slow with a high number of input data, a check stopping computation with more than 2000 data points in one or more chromosome was introduced. This parameter allows skipping this security check.
lokern_scaledBandwidthFactor	Factor of scaling for lokern estimated bandwidths
limit.analysis	Vector (numeric or character representing analyses names) to limit the output of preda analysis to a subset of input analyses.

Details

See supplementary material about PREDA method

Value

If outputGenomicAnnotationsForPREDA is NULL, a PREDADataAndResults object is returned. Otherwise a PREDAResults object is returned instead

Author(s)

Francesco Ferrari

See Also

Supplementary information about PREDA method

Examples

```
#See examples in PREDA tutorial
```

```
preprocessingGE
```

Wrapper function for gene expression data preprocessing for differential expression analysis with PREDA

Description

Wrapper function for gene expression data preprocessing for differential expression analysis with PREDA

Usage

```
preprocessingGE(SampleInfoFile = NULL, CELfiles_dir = NULL,
AffyBatchInput = NULL, custom_cdfname, arrayNameColumn = NULL,
sampleNameColumn = NULL, classColumn,
referenceGroupLabel, statisticType, optionalAnnotations = NULL,
retain.chrs = NULL, reference_position_type = "median",
testedTail = "both")
```

Arguments

<code>SampleInfoFile</code>	Path to sample info file
<code>CELfiles_dir</code>	Path to directory containing raw CEL data files for Affymetrix arrays
<code>AffyBatchInput</code>	Alternatively input raw data can be provided as an <code>AffyBatch</code> object. In this case sample classes will be inferred from phenodata contained in <code>AffyBatch</code> object. In particular <code>classColumn</code> parameter will refer to the column in <code>pData(AffyBatchInput)</code> object.
<code>custom_cdfname</code>	Specify the cdf library to be used for data preprocessing
<code>arrayNameColumn</code>	Column of sampleinfo file containing the name of raw data (CEL) files
<code>sampleNameColumn</code>	Column of sampleinfo file containing the name to be used for samples labels
<code>classColumn</code>	Column of sampleinfo file containing the label of sample classes. If input raw data are provided as an <code>AffyBatch</code> object, this parameter refers instead to the column in <code>pData(AffyBatchInput)</code> object.
<code>referenceGroupLabel</code>	Specify which class label is used for the reference sample used in computing statistics for differential expression.
<code>statisticType</code>	Statistic for differential expression that is computed on input data. Possible values are "tstatistic", "FC" (Fold Change), "FCmedian" (fold change computed on medians)
<code>optionalAnnotations</code>	Character vector to select additional annotations fields to be included into the <code>GenomicAnnotations</code> object.
<code>retain.chrs</code>	Numeric vector, containing the list of chromosomes selected for the output <code>GenomicAnnotations</code> object. E.g. set <code>retain.chrs=1:22</code> to limit the <code>GenomicAnnotations</code> object to chromosomes from 1 to 22. This might be useful to limit <code>GenomicAnnotations</code> objects to autosomic chromosomes.
<code>reference_position_type</code>	Specify which genomic coordinate must be used as reference position for PREDA analysis. Possible values are "start", "end", "median", "strand.start" or "strand.end".
<code>testedTail</code>	Specify what tail of the distribution will be tested for significantly extreme values in PREDA analysis. Possible values are "both", "upper" or "lower".

Details

Preprocess raw (CEL) files for Affymetrix gene expression arrays using user defined CDF libraries and RMA normalization. Then statistics for differential expression are computed. Then annotations are retrieved from the corresponding annotation library.

Please note this function is a user-friendly preprocessing function for Affy gene expression microarrays. Step by step preprocessing functions can be used with any other platform.

Value

A DataForPREDA object is returned.

Author(s)

Francesco Ferrari

See Also

[DataForPREDA](#)

Examples

```
## Not run:

require("PREDAsampledata")
CELfilesPath <- system.file("sampledata", "GeneExpression",
package = "PREDAsampledata")
infofile <- file.path(CELfilesPath , "sampleinfoGE_PREDA.txt")
sampleinfo<-read.table(infofile, sep="\t", header=TRUE)

GEDataForPREDA<-preprocessingGE(SampleInfoFile=infofile,
CELfiles_dir=CELfilesPath,
custom_cdfname="hgu133plus2",
arrayNameColumn=1,
sampleNameColumn=2,
classColumn="Class",
referenceGroupLabel="normal",
statisticType="tstatistic",
optionalAnnotations=c("SYMBOL", "ENTREZID"),
retain.chrs=1:22
)

## End(Not run)
```

SODEGIRpreprocessingGE

Wrapper function for gene expression data preprocessing for SODEGIR analysis

Description

Wrapper function for gene expression data preprocessing for SODEGIR analysis

Usage

```
SODEGIRpreprocessingGE(SampleInfoFile = NULL, CELfiles_dir = NULL,
AffyBatchInput = NULL, custom_cdfname, arrayNameColumn = NULL,
sampleNameColumn = NULL, classColumn,
referenceGroupLabel, statisticType, optionalAnnotations = NULL,
retain.chrs = NULL, reference_position_type = "median",
```

```
testedTail = "both", singleSampleOutput = TRUE,
varianceAll=FALSE)
```

Arguments

SampleInfoFile	Path to sample info file
CELfiles_dir	Path to directory containing raw CEL data files for Affymetrix arrays
AffyBatchInput	Alternatively input raw data can be provided as an AffyBatch object. In this case sample classes will be inferred from phenodata contained in AffyBatch object. In particular classColumn parameter will refer to the column in pData(AffyBatchInput) object.
custom_cdfname	Specify the cdf library to be used for data preprocessing
arrayNameColumn	Column of sampleinfo file containing the name of raw data (CEL) files
sampleNameColumn	Column of sampleinfo file containing the name to be used for samples labels
classColumn	Column of sampleinfo file containing the label of sample classes. If input raw data are provided as an AffyBatch object, this parameter refers instead to the column in pData(AffyBatchInput) object.
referenceGroupLabel	Specify which class label is used for the reference sample used in computing statistics for differential expression.
statisticType	Statistic for differential expression that is computed on input data. Possible values are "tstatistic", "FC" (Fold Change), "FCmedian" (fold change computed on medians)
optionalAnnotations	Character vector to select additional annotations fields to be included into the GenomicAnnotations object.
retain.chrs	Numeric vector, containing the list of chromosomes selected for the output GenomicAnnotations object. E.g. set retain.chrs=1:22 to limit the GenomicAnnotations object to chromosomes from 1 to 22. This might be useful to limit GenomicAnnotations objects to autosomic chromosomes.
reference_position_type	Specify which genomic coordinate must be used as reference position for PREDA analysis. Possible values are "start", "end", "median", "strand.start" or "strand.end". "strand.start" is strand specific start: i.e. start on positive strand but end on negative strand. "strand.end" is strand specific end.
testedTail	Specify what tail of the distribution will be tested for significantly extreme values in PREDA analysis. Possible values are "both", "upper" or "lower".
singleSampleOutput	Logical, if TRUE a statistic comparing each sample with the reference group is computed.
varianceAll	This parameter affects the computation only when singleSampleOutput is TRUE. varianceAll is itself a logical parameter. If TRUE, all pathological (e.g. tumor) samples and all normal (reference) samples are used to estimate variance in the comparison of individual pathological samples to the normal reference, as described in the original SODEGIR paper by Bicciato et al. (Nucleic Acids Res. 2009).

The original SODEGIR statistic for Gene Expression was based on the SAM score. However, since July 2018 the original samr package is no more available in CRAN. Therefore in the current PREDA version the `varianceAll=TRUE` and `singleSampleOutput=TREU` can't be used with SAM. When `singleSampleOutput` is `TRUE` and a different `statisticType` is used, the variance is actually computed using only the normal (reference) samples.

If `FALSE` (default value), the computation of statistics for single sample VS reference comparisons only take into account the variance in the reference group of samples.

Details

Preprocess raw (CEL) files for Affymetrix gene expression arrays using user defined CDF libraries and RMA normalization.

Then statistics for differential expression are computed comparing each sample with the reference group.

Then annotations are retrieved from the corresponding annotation library.

Please note this function is a user-friendly preprocessing function for Affy gene expression microarrays. Step by step preprocessing functions can be used with any other platform.

Value

A `DataForPREDA` object is returned.

Author(s)

Francesco Ferrari

References

Silvio Biccato, Roberta Spinelli, Mattia Zampieri, Eleonora Mangano, Francesco Ferrari, Luca Beltrame, Ingrid Cifola, Clelia Peano, Aldo Solari, and Cristina Battaglia. A computational procedure to identify significant overlap of differentially expressed and genomic imbalanced regions in cancer datasets. *Nucleic Acids Res*, 37(15):5057-70, August 2009.

See Also

[preprocessingGE](#), [DataForPREDA](#)

Examples

```
## Not run:
require(PREDAsampledata)

CELfilesPath <- system.file("sampledata", "GeneExpression",
package = "PREDAsampledata")

infofile <- file.path(CELfilesPath , "sampleinfoGE_PREDA.txt")

SODEGIRGEDataForPREDA<-SODEGIRpreprocessingGE(SampleInfoFile=
infofile,
CELfiles_dir=CELfilesPath,
custom_cdfname="hgu133plus2",
arrayNameColumn=1,
```

```

sampleNameColumn=2,
classColumn="Class",
referenceGroupLabel="normal",
statisticType="tstatistic",
optionalAnnotations=c("SYMBOL", "ENTREZID"),
retain.chrs=1:22
)

## End(Not run)

```

SODEGIR_GEstatistics	<i>Wrapper function for gene expression statistics preprocessing for SODEGIR analysis</i>
----------------------	---

Description

Wrapper function for gene expression statistics preprocessing for SODEGIR analysis.

Usage

```

# SODEGIR_GEstatistics(.Object, pData_classColumn=NULL,
# referenceGroupLabel=NULL,
# statisticType=c("tstatistic", "FC", "FCmedian", "eBayes"),
# singleSampleOutput=TRUE, varianceAll=FALSE)

SODEGIR_GEstatistics(.Object, ...)

```

Arguments

<code>.Object</code>	An object of class <code>ExpressionSet</code> containing gene expression input data
<code>...</code>	See below

pData_classColumn: Column of `phenoData` slot from the `ExpressionSet` object, containing the label of sample classes

referenceGroupLabel: Specify which class label is used for the reference sample used in computing statistics for differential expression.

statisticType: Statistic for differential expression that is computed on input data. Possible values are "tstatistic", "FC" (Fold Change), "FCmedian" (fold change computed on medians)

singleSampleOutput: Logical, if TRUE a statistic comparing each sample with the reference group is computed.

varianceAll: This parameter affect the computation only when `singleSampleOutput` is TRUE.
`varianceAll` is itself a logical parameter. If TRUE, all pathological (e.g. tumor) samples and all normal (reference) samples are used to estimate variance in the comparison of individual pathological samples to the normal reference, as described in the original SODEGIR apper by Bicciato et al. (Nucleic Acids Res. 2009).

The original SODEGIR statistic for Gene Expression was based on the SAM score. However, since July 2018 the samr package is no more available in CRAN. Therefore in the current PREDA version the varianceAll=TRUE parameter can't be used as SAM is not available. When singleSampleOutput is TRUE and a different statisticType is used, the variance is actually computed using only the normal (reference) samples. If FALSE (default value), the computation of statistics for single sample VS reference comparisons only take into account the variance in the reference group of samples.

Details

Using an ExpressionSet object as input, statistics for differential expression are computed comparing each sample with the reference group.

Value

The output is returned as a matrix.

Author(s)

Francesco Ferrari

References

Silvio Bicciato, Roberta Spinelli, Mattia Zampieri, Eleonora Mangano, Francesco Ferrari, Luca Beltrame, Ingrid Cifola, Clelia Peano, Aldo Solari, and Cristina Battaglia. A computational procedure to identify significant overlap of differentially expressed and genomic imbalanced regions in cancer datasets. Nucleic Acids Res, 37(15):5057-70, August 2009.

See Also

[preprocessingGE](#), [SODEGIRpreprocessingGE](#), [ExpressionSet](#)

StatisticsForPREDA-class

Class "StatisticsForPREDA" is used to manage the datamatrix containing statistics for PREDA analyses

Description

This class is used to manage the datamatrix containing statistics for PREDA analyses: i.e. the gene (or other genomic feature) centered statistics accounting for differential expression (or for the other type of variation under investigation)

Objects from the Class

Objects can be created by calls of the form `new("StatisticsForPREDA", ids, statistic, analysesNames, testedTail)`.

Slots

- ids:** Object of class "character" a character vector of unique identifiers for the genomic features under investigation
- statistic:** Object of class "matrix" a numeric matrix containing gene-centered statistics (or statistics on genomic data centered on other genomic features under investigation). The statistics must be provided as a matrix of numeric values, with a number of rows equal to the length of "ids" slot and a number of columns equal to the length of "analysesNames" slot.
- analysesNames:** Object of class "character" a character vector of unique names associated to each column of statistic matrix. This is just a name that will be used to identify each analysis.
- testedTail:** Object of class "character" a character describing what tail of the statistic distribution will be analyzed during PREDA analysis. Possible values are "upper", "lower" or "both". Anyway we strongly recommend using PREDA analysis only for statistics on genomic data with a symmetric distribution around zero.

Methods

- analysesNames** signature(.Object = "StatisticsForPREDA"): get the names of the analyses in the StatisticsForPREDA object
- getStatisticByName** signature(.Object = "StatisticsForPREDA"): extract data for individual analyses using the analysis name
- initialize** signature(.Object = "StatisticsForPREDA"): initialize method for StatisticsForPREDA objects
- StatisticsForPREDA2dataframe** signature(.Object = "StatisticsForPREDA"): extract data as a dataframe with probeids as rownames
- StatisticsForPREDAFilterColumns_neg** signature(.Object = "StatisticsForPREDA"): filter statistics to remove selected analyses
- StatisticsForPREDAFilterColumns_pos** signature(.Object = "StatisticsForPREDA"): filter statistics to keep selected analyses

Note

This class is better described in the package vignette

Author(s)

Francesco Ferrari

See Also

["DataForPREDA"](#), [analysesNames](#), [getStatisticByName](#), [StatisticsForPREDA2dataframe](#), [StatisticsForPREDAFilterColumns_neg](#), [StatisticsForPREDAFilterColumns_pos](#)

Examples

```
showClass("StatisticsForPREDA")
```

StatisticsForPREDA2dataframe

extract data as a dataframe with probeids as rownames

Description

extract data as a dataframe with probeids as rownames

Usage

```
StatisticsForPREDA2dataframe(.Object)
```

Arguments

.Object An object of class StatisticsForPREDA

StatisticsForPREDAFilterColumns_neg

filter statistics to remove selected analyses

Description

filter statistics to remove selected analyses

Usage

```
# StatisticsForPREDAFilterColumns_neg(.Object, analysesToRemove,
# analysesAsNames=FALSE)
```

```
StatisticsForPREDAFilterColumns_neg(.Object, ...)
```

Arguments

.Object An object of class StatisticsForPREDA

... See below

analysesToRemove: Analysis statistics columns to be removed after filtering

analysesAsNames: Logical, if TRUE analyses are listed as their character names.
If FALSE they can be listed as numeric indexes.

```
StatisticsForPREDAFilterColumns_pos
    filter statistics to keep selected analyses
```

Description

filter statistics to keep selected analyses

Usage

```
# StatisticsForPREDAFilterColumns_pos(.Object, analysesToRetain,
# analysesAsNames=FALSE)

StatisticsForPREDAFilterColumns_pos(.Object, ...)
```

Arguments

.Object	An object of class StatisticsForPREDA
...	See below
analysesToRetain:	Analysis statistics columns to be retained after filtering
analysesAsNames:	Logical, if TRUE analyses are listed as their character names. If FALSE they can be listed as numeric indexes.

```
StatisticsForPREDAFromdataframe
    Function to create a StatisticsForPREDA objet from a dataframe
```

Description

Function to create a StatisticsForPREDA objet from a dataframe

Usage

```
StatisticsForPREDAFromdataframe(StatisticsForPREDA_dataframe, ids_column = NULL,
statistic_columns = NULL, analysesNames = NULL, testedTail =
c("upper", "lower", "both"))
```

Arguments

StatisticsForPREDA_dataframe	Input dataframe containing statistics on genomics data.
ids_column	Specify the column from the input dataframe with gene (or other genomic features) ids. Can be specified using column index (numeric) or column name (character).
statistic_columns	Specify the column (or columns) from the input dataframe with gsta.enomic data statistics that will be included in the statisticsForPREDA object. Can be specified using column index (numeric) or column name (character). If NULL (default), all columns excluding ids_column will be considered as input statistics

analysesNames	Names (labels) to be associated to each input statistic. If NULL the column names for statistics_columns will be used.
testedTail	Specify what tail of the distribution will be tested for significantly extreme values in PREDA analysis. Possible values are "both", "upper" or "lower".
...	any other parameter for read.table function that could be useful for parsing the input file, such as "sep", "quote", "header", "na.strings" and other parameters.

Details

A dataframe is parsed and a statisticsForPREDA object is built using contained data.

Value

A statisticsForPREDA object

Author(s)

Francesco Ferrari

See Also

[StatisticsForPREDA](#)

Examples

```
## Not run:
require(PREDAsampledata)

CNdataPath <- system.file("sampledata", "CopyNumber", package =
"PREDAsampledata")

CNdataFile <- file.path(CNdataPath , "CNAG_data-PREDA.txt")

CNannotationFile <- file.path(CNdataPath , "SNPAnnot100k.csv")

CNStatisticsForPREDA<-StatisticsForPREDAFromdataframe(file=CNdataFile,
ids_column="AffymetrixSNPsID", testedTail="both", sep="\t",
header=TRUE)

## End(Not run)
```

```
statisticsForPREDAfromEset
```

function to compute a statisticsForPREDA object from an Expression-Set object

Description

function to compute a statisticsForPREDA object from an ExpressionSet object

Usage

```
# statisticsForPREDAfromEset(.Object, pData_classColumn=NULL,
# statisticType=NULL, logged=TRUE, referenceGroupLabel=NULL,
# classVector=NULL, testedTail="both")

statisticsForPREDAfromEset(.Object, ...)
```

Arguments

.Object	Object of class ExpressionSet
...	See below

pData_classColumn: Column from pData(.Object) containing the labels for different samples classes.

statisticType: Statistic for differential expression that is computed on input data. Possible values are "tstatistic", "FC" (Fold Change), "FCmedian" (fold change computed on medians)

logged: Logical value (default TRUE) to specify if the input data are logged (Log2). This parameter will influence the computation of statistics.

referenceGroupLabel: Specify which class label is used for the reference sample used in computing statistics for differential expression.

classVector: If pData_classColumn is NULL then a vector specifying the sample classes is required and can be provided with classVector parameter

testedTail: Specify what tail of the distribution will be tested for significantly extreme values in PREDA analysis. Possible values are "both", "upper" or "lower". Default value is "both".

Details

An object of class ExpressionSet is used as input and gene centered statistics for differential expression are computed on the contained data. The computed statistics are used to build a StatisticsForPREDA object

Value

An object of class StatisticsForPREDA

Author(s)

Francesco Ferrari

See Also

["StatisticsForPREDA"](#)

Examples

```
## Not run:

require(PREDAsampledata)

data(ExpressionSetRCC)
```

```
GStatisticsForPREDA<-statisticsForPREDAfromEset(
ExpressionSetRCC, statisticType="tstatistic",
referenceGroupLabel="normal", classVector=sampleinfo[, "Class"])

## End(Not run)
```

StatisticsForPREDAFromfile

Function to create a StatisticsForPREDA objet from a txt file

Description

Function to create a StatisticsForPREDA objet from a txt file

Usage

```
StatisticsForPREDAFromfile(file, ids_column = NULL,
statistic_columns = NULL, analysesNames = NULL, testedTail =
c("upper", "lower", "both"), ...)
```

Arguments

<code>file</code>	Path to the input txt file containing statistics on genomics data
<code>ids_column</code>	Specify the column from the input txt file with gene (or other genomic features) ids. Can be specified using column index (numeric) or column name (character).
<code>statistic_columns</code>	Specify the column (or columns) from the input txt file with gsta.enomic data statistics that will be included in the statisticsForPREDA object. Can be specified using column index (numeric) or column name (character). If NULL (default), all columns excluding <code>ids_column</code> will be considered as input statistics
<code>analysesNames</code>	Names (labels) to be associated to each input statistic. If NULL the column names for <code>statistic_columns</code> will be used.
<code>testedTail</code>	Specify what tail of the distribution will be tested for significantly extreme values in PREDA analysis. Possible values are "both", "upper" or "lower".
<code>...</code>	any other parameter for read.table function that could be useful for parsing the input file, such as "sep", "quote", "header", "na.strings" and other parameters.

Details

A txt file is parsed and a statisticsForPREDA object is built using contained data.

Value

A statisticsForPREDA object

Author(s)

Francesco Ferrari

See Also[StatisticsForPREDA](#)**Examples**

```
## Not run:
require(PREDAsampledata)

CNdataPath <- system.file("sampledata", "CopyNumber", package =
"PREDAsampledata")

CNdataFile <- file.path(CNdataPath , "CNAG_data_PREDA.txt")

CNannotationFile <- file.path(CNdataPath , "SNPAnnot100k.csv")

CNStatisticsForPREDA<-StatisticsForPREDAFromfile(file=CNdataFile,
ids_column="AffymetrixSNPsID", testedTail="both", sep="\t",
header=TRUE)

## End(Not run)
```

Index

* classes

- DataForPREDA-class, [6](#)
- GenomicAnnotations-class, [12](#)
- GenomicAnnotationsForPREDA-class, [18](#)
- GenomicRegions-class, [28](#)
- PREDADatAndResults-class, [41](#)
- PREDAResults-class, [44](#)
- StatisticsForPREDA-class, [57](#)

- analysesNames, [3](#), [58](#)
- analysesNames, PREDAResults-method (analysesNames), [3](#)
- analysesNames, StatisticsForPREDA-method (analysesNames), [3](#)

- computeDatasetSignature, [4](#)
- computeDatasetSignature, GenomicAnnotationsForPREDA-method (computeDatasetSignature), [4](#)

- DataForPREDA, [43](#), [53](#), [55](#), [58](#)
- DataForPREDA-class, [6](#)
- DataForPREDA2dataframe, [7](#), [8](#)
- DataForPREDA2dataframe, DataForPREDA-method (DataForPREDA2dataframe), [8](#)
- DataForPREDA2GenomicAnnotationsForPREDA, [7](#), [8](#)
- DataForPREDA2GenomicAnnotationsForPREDA, DataForPREDA-method (DataForPREDA2GenomicAnnotationsForPREDA), [8](#)
- DataForPREDA2StatisticsForPREDA, [7](#), [9](#)
- DataForPREDA2StatisticsForPREDA, DataForPREDA-method (DataForPREDA2StatisticsForPREDA), [9](#)
- DataForPREDAMedianCenter, [9](#)
- DataForPREDAMedianCenter, DataForPREDA-method (DataForPREDAMedianCenter), [9](#)

- eset2GenomicAnnotations, [10](#)
- eset2GenomicAnnotations, ExpressionSet-method (eset2GenomicAnnotations), [10](#)
- ExpressionSet, [57](#)

- genomePlot, [11](#), [20](#)
- genomePlot, GenomicAnnotationsForPREDA-method (genomePlot), [11](#)
- GenomicAnnotations, [7](#), [10](#), [17](#), [19](#), [20](#), [25–27](#), [43](#), [45](#), [46](#)
- GenomicAnnotations-class, [12](#)
- GenomicAnnotations2dataframe, [13](#), [14](#), [20](#)
- GenomicAnnotations2dataframe, GenomicAnnotations-method (GenomicAnnotations2dataframe), [14](#)
- GenomicAnnotations2dataframe, GenomicAnnotationsForPREDA-method (GenomicAnnotations2dataframe), [14](#)
- GenomicAnnotations2GenomicAnnotationsForPREDA, [13](#), [14](#), [23](#)
- GenomicAnnotations2GenomicAnnotationsForPREDA, GenomicAnnotationsForPREDA-method (GenomicAnnotations2GenomicAnnotationsForPREDA), [14](#)
- GenomicAnnotations2reference_positions, [13](#), [15](#)
- GenomicAnnotations2reference_positions, GenomicAnnotationsForPREDA-method (GenomicAnnotations2reference_positions), [15](#)
- GenomicAnnotationsExtract, [13](#), [16](#)
- GenomicAnnotationsExtract, GenomicAnnotations-method (GenomicAnnotationsExtract), [16](#)
- GenomicAnnotationsFilter_neg, [7](#), [13](#), [17](#), [20](#)
- GenomicAnnotationsFilter_neg, DataForPREDA-method (GenomicAnnotationsFilter_neg), [17](#)
- GenomicAnnotationsFilter_neg, GenomicAnnotations-method (GenomicAnnotationsFilter_neg), [17](#)
- GenomicAnnotationsFilter_neg, GenomicAnnotationsForPREDA-method (GenomicAnnotationsFilter_neg), [17](#)
- GenomicAnnotationsFilter_pos, [7](#), [13](#), [17](#), [20](#)
- GenomicAnnotationsFilter_pos, DataForPREDA-method (GenomicAnnotationsFilter_pos), [17](#)
- GenomicAnnotationsFilter_pos, GenomicAnnotations-method (GenomicAnnotationsFilter_pos),

- 17
- GenomicAnnotationsFilter_pos, GenomicAnnotationsForPREDA-method
(GenomicAnnotationsFilter_pos), 17
- GenomicAnnotationsForPREDA, 7, 12, 15, 23, 43, 45, 46
- GenomicAnnotationsForPREDA-class, 18
- GenomicAnnotationsForPREDA2dataframe, 20, 20
- GenomicAnnotationsForPREDA2dataframe, GenomicAnnotationsForPREDA2-method
(GenomicAnnotationsForPREDA2dataframe), 20
- GenomicAnnotationsForPREDA2GenomicAnnotations, 20, 21
- GenomicAnnotationsForPREDA2GenomicAnnotations, GenomicAnnotationsForPREDA-method
(GenomicAnnotationsForPREDA2GenomicAnnotations), 21
- GenomicAnnotationsForPREDA2PREDAResults, 20, 21
- GenomicAnnotationsForPREDA2PREDAResults, GenomicAnnotationsForPREDA-method
(GenomicAnnotationsForPREDA2PREDAResults), 21
- GenomicAnnotationsForPREDAFromfile, 22
- GenomicAnnotationsFromdataframe, 24
- GenomicAnnotationsFromfile, 25
- GenomicAnnotationsFromLibrary, 27
- GenomicAnnotationsSortAndCleanNA, 7, 13, 20, 28, 30, 43, 46
- GenomicAnnotationsSortAndCleanNA, DataForPREDA-method
(GenomicAnnotationsSortAndCleanNA), 28
- GenomicAnnotationsSortAndCleanNA, GenomicAnnotations-method
(GenomicAnnotationsSortAndCleanNA), 28
- GenomicAnnotationsSortAndCleanNA, GenomicAnnotationsForPREDA-method
(GenomicAnnotationsSortAndCleanNA), 28
- GenomicAnnotationsSortAndCleanNA, PREDADDataAndResults-method
(GenomicAnnotationsSortAndCleanNA), 28
- GenomicAnnotationsSortAndCleanNA, PREDAResults-method
(GenomicAnnotationsSortAndCleanNA), 28
- GenomicRegions, 5, 34, 36–39
- GenomicRegions-class, 28
- GenomicRegions2dataframe, 30
- GenomicRegionsAnnotate, 13, 31
- GenomicRegionsAnnotate, GenomicRegions, GenomicAnnotations-method
(GenomicRegionsAnnotate), 31
- GenomicRegionsChrNumber, 32
- GenomicRegionsChrNumber, GenomicRegions-method
(GenomicRegionsChrNumber), 32
- GenomicRegionsComparison, 33, 36
- GenomicRegionsComparison, GenomicRegions, GenomicRegions-
(GenomicRegionsComparison), 33
- GenomicRegionsCreateRegionsIds, 34
- GenomicRegionsCreateRegionsIds, GenomicRegions-method
(GenomicRegionsCreateRegionsIds), 34
- GenomicRegionsFilter_neg, 34
- GenomicRegionsFilter_neg, GenomicRegions-method
(GenomicRegionsFilter_neg), 34
- GenomicRegionsFilter_pos, 35
- GenomicRegionsFilter_pos, GenomicRegions-method
(GenomicRegionsFilter_pos), 35
- GenomicRegionsFindOverlap, 34, 35
- GenomicRegionsFromdataframe, 36
- GenomicRegionsFromfile, 38
- GenomicRegionsNumber, 39
- GenomicRegionsNumber, GenomicRegions-method
(GenomicRegionsNumber), 39
- GenomicRegionsSpan, 39
- GenomicRegionsSpan, GenomicRegions-method
(GenomicRegionsSpan), 39
- GenomicRegionsTotalSpan, 40
- GenomicRegionsTotalSpan, GenomicRegions-method
(GenomicRegionsTotalSpan), 40
- getStatisticByName, 40, 58
- getStatisticByName, StatisticsForPREDA-method
(getStatisticByName), 40
- MergeStatisticAnnotations2DataForPREDA, 41
- PREDADDataAndResults, 12
- PREDADDataAndResults-class, 41
- PREDADDataAndResults2dataframe, 30, 43, 44
- PREDADDataAndResults2dataframe, PREDADDataAndResults-method
(PREDADDataAndResults2dataframe), 44
- PREDAResults, 4, 5, 12, 43
- PREDAResults-class, 44
- PREDAResults2dataframe, 46, 46
- PREDAResults2dataframe, PREDAResults-method
(PREDAResults2dataframe), 46
- PREDAResults2GenomicRegions, 12, 46, 47
- PREDAResults2GenomicRegions, PREDAResults-method
(PREDAResults2GenomicRegions), 47
- PREDAResults2GenomicRegionsSingle, 46, 48
- PREDAResults2GenomicRegionsSingle, PREDAResults-method
(PREDAResults2GenomicRegionsSingle), 48

[48](#)
 PREDAResults2PREDADataAndResults, [46](#),
[49](#)
 PREDAResults2PREDADataAndResults, PREDAResults-method
 (PREDAResults2PREDADataAndResults),
[49](#)
 PREDAResultsGetObservedFlags, [46](#), [49](#)
 PREDAResultsGetObservedFlags, PREDAResults-method
 (PREDAResultsGetObservedFlags),
[49](#)
 preprocessingGE, [51](#), [55](#), [57](#)

 SODEGIR_GEstatistics, [56](#)
 SODEGIR_GEstatistics, ExpressionSet-method
 (SODEGIR_GEstatistics), [56](#)
 SODEGIRpreprocessingGE, [53](#), [57](#)
 StatisticsForPREDA, [4](#), [7](#), [43](#), [61](#), [62](#), [64](#)
 StatisticsForPREDA-class, [57](#)
 StatisticsForPREDA2dataframe, [58](#), [59](#)
 StatisticsForPREDA2dataframe, StatisticsForPREDA-method
 (StatisticsForPREDA2dataframe),
[59](#)
 StatisticsForPREDAFilterColumns_neg, [7](#),
[58](#), [59](#)
 StatisticsForPREDAFilterColumns_neg, DataForPREDA-method
 (StatisticsForPREDAFilterColumns_neg),
[59](#)
 StatisticsForPREDAFilterColumns_neg, StatisticsForPREDA-method
 (StatisticsForPREDAFilterColumns_neg),
[59](#)
 StatisticsForPREDAFilterColumns_pos, [7](#),
[58](#), [60](#)
 StatisticsForPREDAFilterColumns_pos, DataForPREDA-method
 (StatisticsForPREDAFilterColumns_pos),
[60](#)
 StatisticsForPREDAFilterColumns_pos, StatisticsForPREDA-method
 (StatisticsForPREDAFilterColumns_pos),
[60](#)
 StatisticsForPREDAFromdataframe, [60](#)
 statisticsForPREDAfromEset, [61](#)
 statisticsForPREDAfromEset, ExpressionSet-method
 (statisticsForPREDAfromEset),
[61](#)
 StatisticsForPREDAFromfile, [63](#)